



IPC/JEDEC J-STD-035A

Acoustic Microscopy for Non-Hermetic Encapsulated Electronic Devices

A joint standard developed by the J-STD-10a IPC Plastic Chip Carrier Cracking Task Group and the JEDEC JC-14.1 Committee on Reliability Test Methods for Packaged Devices

December 2022

Supersedes:

IPC/JEDEC J-STD-035

April 1999

Users of this standard are encouraged to participate in the development of future revisions.

Contact:

JEDEC

Solid State Technology Association
3103 North 10th Street
Suite 240-South
Arlington, VA 22201-2107
Tel 703 907.0026
Fax 703 907.7501

IPC

3000 Lakeside Drive
Suite 309S
Bannockburn, IL 60015-1249
Tel 847 615.7100
Fax 847 615.7105

NOTICE

JEDEC standards and publications contain material that has been prepared, reviewed, and approved through the JEDEC Board of Directors level and subsequently reviewed and approved by the JEDEC legal counsel.

JEDEC standards and publications are designed to serve the public interest through eliminating misunderstandings between manufacturers and purchasers, facilitating interchangeability and improvement of products, and assisting the purchaser in selecting and obtaining with minimum delay the proper product for use by those other than JEDEC members, whether the standard is to be used either domestically or internationally.

JEDEC standards and publications are adopted without regard to whether or not their adoption may involve patents or articles, materials, or processes. By such action JEDEC does not assume any liability to any patent owner, nor does it assume any obligation whatever to parties adopting the JEDEC standards or publications.

The information included in JEDEC standards and publications represents a sound approach to product specification and application, principally from the solid state device manufacturer viewpoint. Within the JEDEC organization there are procedures whereby a JEDEC standard or publication may be further processed and ultimately become an ANSI standard.

No claims to be in conformance with this standard may be made unless all requirements stated in the standard are met.

Inquiries, comments, and suggestions relative to the content of this JEDEC standard or publication should be addressed to JEDEC at the address below, or refer to www.jedec.org under Standards and Documents for alternative contact information.

Published by
©JEDEC Solid State Technology Association 2022
3103 North 10th Street
Suite 240 South
Arlington, VA 22201-2107

This document may be downloaded free of charge; however JEDEC retains the copyright on this material. By downloading this file the individual agrees not to charge for or resell the resulting material.

PRICE: Contact JEDEC

Printed in the U.S.A.
All rights reserved

PLEASE!

DON'T VIOLATE
THE
LAW!

This document is copyrighted by JEDEC and may not be reproduced without permission.

For information, contact:

JEDEC Solid State Technology Association
3103 North 10th Street
Suite 240 South
Arlington, VA 22201-2107

or refer to www.jedec.org under Standards-Documents/Copyright Information.

Currently in preview, click buy full version

This page intentionally left blank

ACOUSTIC MICROSCOPY FOR NON-HERMETIC ENCAPSULATED ELECTRONIC DEVICES

Contents

		Page
1	Scope	1
2	Definitions	1
3	Apparatus	5
3.1	Reflective Acoustic Microscope System (see Figure 5) Comprised of:.....	5
3.2	Through Transmission Acoustic Microscope System (see Figure 7) Comprised of:	5
3.3	Reference Packages or Standards.....	6
3.4	Sample Holder	6
4	Procedure	6
4.1	Equipment Setup	6
4.1.1	Select the Transducer	6
4.1.2	Verify Setup	6
4.1.3	Place Devices in the Sample Holder	6
4.1.4	Align the Transducer.....	7
4.1.5	Focus.....	7
4.2	Perform Acoustic Scans	7
4.2.1	Inspect for any Anomalies	7
4.2.2	Consider Potential Pitfalls.....	8
4.2.3	Evaluate	8
4.2.4	Record.....	8
4.3	Characterization of AM Reflection Mode System	8
4.3.1	AM System Setup	8
Annex A	Acoustic Microscopy Check Sheet	11
Annex B	Potential Image Pitfalls	14
Annex C	Some Limitations of Acoustic Microscopy	15
Annex D	Reference Procedure for Presenting Applicable Scanned Data	17
 Figures		 Page
Figure 1	— Example of A-mode Display.....	1
Figure 2	— Example of B-mode Display	2
Figure 3	— Example of C-mode Display	2
Figure 4	— Example of Through Transmission Display.....	3
Figure 5	— Relationship of Properties for Focused Transducers	4
Figure 6	— Diagram of a Reflective Acoustic Microscope System.....	4
Figure 7	— Diagram of a Through Transmission Acoustic Microscope System	5
Figure 8	— Example of Maximizing the Focus for the Top Surface, Approximate Middle and Bottom Surface of a Homogeneous Device.....	7
Figure 9	— Example Structure of Reference Bonded Wafer Sample per SEMI 3D17	9
Figure 10	— Layout of the Artificial Voids of Different Sizes and Densities in a Die-sized Array per SEMI 3D-17... ..	9
Figure 11	— Example of a 300mm Diameter Reference Bonded Wafer Sample with the Die Numbering System and Layout for the Die-sized Arrays per SEMI 3D-17.....	10
Figure 12	— Delamination Types from Circuit and Non-Circuit Side Scan.....	11
Figure 13	— Ultrasound Waves Approaching Various Example Surfaces	15
Figure 14	— Ultrasound Reflection from Various Example Surfaces	16
Figure 15	— Edge Effect Causing Reduction in Returned Signal Amplitude Due to Edge.....	16
Figure 16	— Edge Effect Due to Depth in a Sample.....	16

Currently in preview, click buy full version

This page intentionally left blank.

ACOUSTIC MICROSCOPY FOR NON-HERMETIC ENCAPSULATED ELECTRONIC DEVICES

(From JEDEC Board Ballot JCB-22-59, formulated under the cognizance of the JC-14.1 Subcommittee on Reliability Test Methods for Packaged Devices.)

1 Scope

This test method defines the procedures for performing acoustic microscopy on non-hermetic encapsulated electronic devices. This method provides users with an acoustic microscopy process flow for detecting anomalies (delaminations, cracks, mold compound voids, etc.) nondestructively in encapsulated electronic devices while achieving reproducibility.

2 Definitions

A-mode - Acoustic data collected at the smallest X-Y-Z region defined by the limitations of the given reflective acoustic microscope. An A-mode display contains amplitude and phase/polarity information as a function of time of flight at a single point in the X-Y plane. See Figure 1. Example of A-mode Display.




Figure 1 — Example of A-mode Display

B-mode - Acoustic data collected along an X-Z or Y-Z plane versus depth using a reflective acoustic microscope. A B-mode scan contains amplitude and phase/polarity information as a function of time of flight at each point along the scan line. A B-mode scan furnishes a two-dimensional (cross-sectional) description along a scan line (X or Y). See Figure 2.