

JIS

JAPANESE
INDUSTRIAL
STANDARD

Translated and Published by
Japanese Standards Association

JIS B 1856 : 2018

(JBMA/JSA)

**Synchronous belt drives — Imperial pitch
trapezoidal profile system — Belts and
pulleys**

ICS 21.220.10

Reference number : JIS B 1856 : 2018 (E)

PROTECTED BY COPYRIGHT

29 S

B 1856 : 2018

Date of Establishment: 1985-12-01

Date of Revision: 2018-03-20

Date of Public Notice in Official Gazette: 2018-03-20

Investigated by: Japanese Industrial Standards Committee

Standards Board for ISO area

Technical Committee on Machine Elements

JIS B 1856 : 2018, First English edition published in 2018-10

Translated and published by: Japanese Standards Association
Mita MT Building, 3-13-12, Mita, Minato-ku, Tokyo, 108-0073 JAPAN

In the event of any doubts arising as to the contents,
the original JIS is to be the final authority.

© JSA 2018

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Printed in Japan

KK/HN

PROTECTED BY COPYRIGHT

Contents

	Page
Introduction	1
1 Scope	1
2 Normative references	1
3 Terms, symbols, and definitions	2
3.1 Terms related to belt	2
3.2 Terms related to pulley	3
3.3 Names of principal parts related to pulley grooves	3
4 Types of belts	4
5 Shapes and dimensions of belts	4
5.1 Basic dimensions of belts	4
5.2 Belt length and number of belt teeth	5
5.3 Tolerance on belt length	7
5.4 Belt basic width and tolerances	8
6 Test method	9
6.1 Measurement of belt length	9
6.2 Measurement of belt width	12
7 Test report of belt	12
8 Designation of belts	12
8.1 Types MXL, DMXL and XXL with trapezoidal profile	12
8.2 Types XL, DXL, L, DL, H, DH, XH, and XXH with trapezoidal profile	12
9 Marking of belts	13
9.1 Types MXL, DMXL and XXL with trapezoidal profile	13
9.2 Types XL, DXL, L, DL, H, DH, XH, and XXH with trapezoidal profile	13
10 Types of pulley	13
11 Pulley dimensions	13
11.1 Groove profile and dimensions of pulley	13
11.2 Number of teeth, pitch diameter and outside diameter	14
11.3 Pulley width	16
12 Performance of pulleys	17
12.1 Appearance of pulleys	17
12.2 Pitch variation and cumulative pitch deviation	17
12.3 Parallelism of teeth with respect to shaft bore centre line	18
12.4 Axial circular runout	18
12.5 Radial circular runout	19

12.6	Outside diameter difference in tooth width direction	19
12.7	Surface condition of teeth	19
12.8	Balance	19
13	Flange dimensions	20
14	Test method for pulleys	20
14.1	General	20
14.2	Tooth profile of pulley	20
14.3	Pitch variation and cumulative pitch deviation	20
14.4	Parallelism of tooth with respect to the shaft bore centre	21
14.5	Axial circular runout	21
14.6	Radial circular runout	21
14.7	Outside diameter	22
14.8	Outside diameter difference in tooth width direction	22
15	Designation of pulleys	23
16	Marking on pulleys	23
Annex JA (informative)	Guidance on use of synchronous belts	24
Annex JB (normative)	Dimensions and tolerances for ISO pulleys with straight-sided grooves	45
Annex JC (informative)	Comparison table between ISO and corresponding International Standard	46

Foreword

This Japanese Industrial Standard has been revised by the Minister of Economy, Trade and Industry through deliberations at the Japanese Industrial Standards Committee as the result of proposal for revision of Japanese Industrial Standard submitted by The Japan Belting Manufacturers Association (JBMA)/Japanese Standards Association (JSA) with the draft being attached, based on the provision of Article 12 Clause 1 of the Industrial Standardization Law applicable to the case of revision by the provision of Article 14. Consequently **JIS B 1856:1993** is replaced with this Standard. Further, **JIS K 6372:1995** and **JIS K 6373:1995** have been withdrawn and replaced with this Standard.

This **JIS** document is protected by the Copyright Law.

Attention is drawn to the possibility that some parts of this Standard may conflict with patent rights, applications for a patent after opening to the public or utility model rights. The relevant Minister and the Japanese Industrial Standards Committee are not responsible for identifying any of such patent rights, applications for a patent after opening to the public or utility model rights.

Synchronous belt drives — Imperial pitch trapezoidal profile system — Belts and pulleys

Introduction

This Japanese Industrial Standard has been prepared based on ISO 19347:2015, Edition 1, with some modifications of the technical contents.

The vertical lines on both sides and dotted underlines indicate changes from the corresponding International Standard. A list of modifications with the explanations is given in Annex JC.

1 Scope

This Standard provides specifications for the ring-shaped synchronous endless trapezoidal profile belts (hereafter referred to as belts) and machine pulleys (hereafter referred to as pulleys), among other pulleys. It is not applicable to automotive belts and pulleys.

It is recommended that this Standard be also applied to sintered pulleys and taper bushed pulleys.

NOTE 1 Guidance on proper and economical designing of belt drives incorporating synchronous belts is provided in Annex JA.

NOTE 2 The International Standard corresponding to this Standard and the symbol of degree of correspondence are as follows.

ISO 19347 : 2015 *Synchronous belt drives — Imperial pitch trapezoidal profile system — Belts and pulleys* (MOD)

In addition, symbols which denote the degree of correspondence in the contents between the relevant International Standard and JIS are IDT (identical), MOD (modified), and NEQ (not equivalent) according to ISO/IEC Guide 21-1.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this Standard. The most recent editions of the standards (including amendments) indicated below shall be applied.

JIS B 0102-1 *Vocabulary of gear terms — Part 1 : Definitions related to geometry*

JIS B 0601 *Geometrical Product Specifications (GPS) — Surface texture : Profile method — Terms, definitions and surface texture parameters*

JIS B 1757-4 *Evaluation of instruments for the measurement of individual gears — Part 4 : Pitch measurement using sphere artifacts*

JIS B 1859 *Synchronous belt drives — Vocabulary*