

JIS

JAPANESE
INDUSTRIAL
STANDARD

Translated and Published by
Japanese Standards Association

JIS B 8920 : 2014

(JMHA/JSA)

Hand trucks

ICS 53.060

Reference number : **JIS B 8920 : 2014 (E)**

Date of Establishment: 1965-07-01

Date of Revision: 2014-01-20

Date of Public Notice in Official Gazette: 2014-01-20

Investigated by: Japanese Industrial Standards Committee
Standards Board

Technical Committee on Logistics and Distribution
of Goods

JIS B 8920:2014, First English edition published in 2014-10

Translated and published by: Japanese Standards Association
Mita MT Building, 3-13-12, Mita, Minato-ku, Tokyo, 108-0073 JAPAN

In the event of any doubts arising as to the contents,
the original JIS is to be the final authority.

© JSA 2014

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Printed in Japan

HT/AT

Contents

		Page
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Types and symbols	2
5	Maximum loading mass	3
6	Quality	5
6.1	General requirements	5
6.2	Appearance	6
6.3	Joint area	6
6.4	Travelling characteristics	6
6.5	Startability	6
6.6	Load performance	6
6.7	Handrail strength	7
6.8	Assembly accuracy	7
6.9	Parking brake performance	7
7	Structure	7
7.1	Wheels and casters	7
7.2	Parking brake	8
7.3	Appearance	8
8	Dimensions	8
9	Test methods	9
9.1	Travelling characteristics test	9
9.2	Startability test	9
9.3	Load performance test	10
9.4	Handrail strength test	11
9.5	Assembly accuracy test	11
9.6	Parking brake performance test	11
10	Inspection	12
11	Designation of products	12
12	Marking	13
12.1	Marking on the truck body	13
12.2	Marking of prohibitions and precautions	13

Foreword

This translation has been made based on the original Japanese Industrial Standard established by the Minister of Economy, Trade and Industry through deliberations at the Japanese Industrial Standards Committee according to the proposal for establishment of Japanese Industrial Standard submitted by Japan Material Handling Association (JMHA)/Japanese Standards Association (JSA) with the draft being attached, based on the provision of Article 12 Clause 1 of the Industrial Standardization Law.

Consequently **JIS B 8920**:1993 is replaced with this Standard.

This **JIS** document is protected by the Copyright Law.

Attention is drawn to the possibility that some parts of this Standard may conflict with patent rights, applications for a patent after opening to the public or utility model rights. The relevant Minister and the Japanese Industrial Standards Committee are not responsible for identifying any of such patent rights, applications for a patent after opening to the public or utility model rights.

Hand trucks

1 Scope

This Japanese Industrial Standard specifies flatbed hand trucks which are used for carrying goods except humans and animals in plant premises, indoors and the like, mainly by human power, and which are capable of carrying a maximum loading mass not exceeding 1 200 kg.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this Standard. The most recent editions of the standards (including amendments) indicated below shall be applied.

JIS B 8922 *Industrial wheels*

JIS B 8923 *Industrial castors*

JIS K 6302 *Cycles—Tyres*

JIS K 6304 *Inner tubes for bicycle tyres*

3 Terms and definitions

For the purpose of this Standard, the following terms and definitions apply.

3.1 flatbed hand truck

hand truck having three or more wheels and a flat loading platform without any structure on it (see the figure of symbol F in table 1)

3.2 single-handrail hand truck

flatbed hand truck equipped with a handrail on one end of the loading platform (see the figure of symbol S in table 1)

3.3 double-handrail hand truck

flatbed hand truck equipped with a handrail or protective rail on each of the both ends of the loading platform (see the figure of symbol D or P in table 1)

3.4 box-type hand truck

hand truck having a box-type body (see the figure of symbol B in table 1)

NOTE: The box can be mesh or fabric.

3.5 shelf-type hand truck

hand truck having shelf-like multiple loading surfaces (see the figure of symbol R in table 1)