

# JIS

JAPANESE  
INDUSTRIAL  
STANDARD

Translated and Published by  
Japanese Standards Association

---

JIS C 8980 : 2020

**Power conditioner for small photovoltaic  
power generating system**

---

ICS 27.160

Reference number : JIS C 8980 : 2020 (E)

C 8980 : 2020

Date of Establishment: 1997-07-20

Date of Revision: 2020-03-23

Date of Public Notice in Official Gazette: 2020-03-23

Investigated by: Japanese Industrial Standards Committee  
Standards Board for IEC area  
Technical Committee on Electricity

---

JIS C 8980 : 2020, First English edition published in 2022-05

Translated and published by: Japanese Standards Association  
Mita MT Building, 3-13-12, Mita, Minato-ku, Tokyo, 108-0073 JAPAN

---

In the event of any doubts arising as to the contents,  
the original JIS is to be the final authority.

© JSA 2022

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Printed in Japan

KK/HN

PROTECTED BY COPYRIGHT

## Contents

		Page
1	Scope .....	1
2	Normative references .....	1
3	Terms and definitions .....	2
4	Components .....	3
5	Service conditions .....	4
5.1	Standard service conditions .....	4
5.2	Special service conditions .....	4
6	Classification .....	4
7	Performance .....	5
7.1	Insulation resistance .....	5
7.2	Dielectric withstand voltage .....	5
7.3	Lightning impulse withstand voltage .....	5
7.4	Leakage current .....	6
7.5	Equipment capabilities .....	6
7.6	Operating range .....	6
7.7	Steady state characteristics .....	6
7.8	Transient operation .....	7
7.9	Noise .....	8
7.10	Temperature rise .....	9
7.11	Composite temperature/humidity cycle (when installed outdoor) .....	9
7.12	Protective functions .....	9
8	Construction .....	10
9	Conductor arrangement and colour indication .....	11
9.1	Conductors of main circuit .....	11
9.2	Board wiring .....	12
9.3	Grounded circuit .....	13
10	Test conditions .....	13
11	Test circuits .....	13
12	Test equipment .....	16
13	Test methods .....	17
13.1	General matters of test methods .....	17
13.2	Insulation resistance test .....	17
13.3	Dielectric withstand voltage test .....	18
13.4	Lightning impulse withstand voltage test .....	18

13.5	Leakage current test	18
13.6	Equipment capabilities test	26
13.7	Operating range test	27
13.8	Steady state characteristics test	27
13.9	Transient operation test	34
13.10	Noise measurement	40
13.11	Temperature rise test	40
13.12	Composite temperature/humidity cyclic test	40
13.13	Protective function test	41
14	Construction test	47
15	Inspection	48
15.1	Classification of inspection	48
15.2	Test item	45
16	Marking	46
16.1	Marking on specifications or catalogue	46
16.2	Marking items on nameplate	46
16.3	Precaution for handling	47
Annex A (informative)	Relation between rated power factor and rated output	60

## Foreword

This Japanese Industrial Standard has been revised by the Minister of Economy, Trade and Industry, through deliberations at the Japanese Industrial Standards Committee in accordance with the Industrial Standardization Act. This edition replaces the previous edition (**JIS C 8980** : 2009), which has been technically revised, and **JIS C 8962** : 2008, which has been withdrawn.

This **JIS** document is protected by the Copyright Act.

Attention is drawn to the possibility that some parts of this Standard may conflict with patent rights, published patent application or utility model rights. The relevant Minister and the Japanese Industrial Standards Committee are not responsible for identifying any of such patent rights, published patent application or utility model rights.

## Power conditioner for small photovoltaic power generating system

### 1 Scope

This Japanese Industrial Standard specifies the performance evaluation and test methods for stand-alone power conditioners of constant AC output voltage and constant output frequency, stand-alone power conditioners of constant DC output voltage, and the utility-connected power conditioners among the power conditioners for photovoltaic power generating system (hereafter referred to as PCS) complying with a) and b) below. However, AC module is excluded.

- a) Rated output :  $\geq 10$  W,  $< 100$  W
  - 1) DC input and output voltage :  $\geq 30$  V,  $\leq 750$  V
  - 2) AC output voltage :  $\geq 30$  V,  $\leq 600$  V
- b) Rated output :  $\geq 100$  W,  $< 50$  kW
  - 1) DC input and output voltage :  $\leq 750$  V
  - 2) AC output voltage :  $\leq 600$  V

In this Standard, a PCS to which an accumulator device is connected refers only to those which is connected to the accumulator device on the input side. Among the components of utility-connected PCS, the utility interaction protective function and utility interaction protective device such as an islanding operation detection device are excluded. A utility-connected PCS includes those having isolated operation function.

For the component equipment combined with PCSs such as an accumulator device and various interfaces, refer to the respective individual standards.

### 2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this Standard. For standards with the year indication, only the editions of the indicated year shall be applied and the revisions (including amendments) made thereafter shall not be applied. For those without the indication of the year, the most recent editions (including amendments) shall be applied.

JIS C 1302 *Insulation resistance testers*

JIS C 6950-1 *Information technology equipment — Safety — Part 1 : General requirements*

JIS C 8303 *Plugs and receptacles for domestic and similar general use*

JIS C 8905 *General rules for stand-alone photovoltaic power generating system*

JIS C 8960 *Glossary of terms for photovoltaic power generation*