

JIS

JAPANESE
INDUSTRIAL
STANDARD

Translated and Published by
Japanese Standards Association

JIS D 9422 : 2021

(JBPI/JSA)

Tire valves for bicycles

ICS 43.150

Reference number : JIS D 9422 : 2021 (E)

D 9422 : 2021

Date of Establishment: 1961-05-01

Date of Revision: 2021-03-22

Date of Public Notice in Official Gazette: 2021-03-22

Investigated by: Japanese Industrial Standards Committee

Standards Board for ISO area

JIS D 9422 : 2021, First English edition published in 2022-06

Translated and published by: Japanese Standards Association
Mita MT Building, 3-13-12, Mita, Minato-ku, Tokyo, 108-0073 JAPAN

In the event of any doubts arising as to the contents,
the original JIS is to be the final authority.

© JSA 2022

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Printed in Japan

HN

PROTECTED BY COPYRIGHT

Contents

		Page
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Types and symbols	1
5	Configurations of valves	2
6	Performances	7
6.1	Airtightness	7
6.2	Adhesive strength of rubber seat	7
7	Dimensions	7
8	Appearance	7
9	Test methods	8
9.1	Airtightness test	8
9.2	Adhesive strength test of rubber seat	8
10	Designations of products	8
11	Marking	8
	Annex A (normative) Screw threads of tyre valves for bicycles	9
	Annex B (informative) Metal base valves	12

Foreword

This Japanese Industrial Standard has been revised by the Minister of Economy, Trade and Industry through deliberations at the Japanese Industrial Standards Committee as the result of proposal for revision of Japanese Industrial Standard submitted by Japan Bicycle Promotion Institute (JBPI)/Japanese Standards Association (JSA) with a draft being attached, based on the provision of Article 12, paragraph (1) of the Industrial Standardization Act applied mutatis mutandis pursuant to the provision of Article 16 of the said Act. This edition replaces the previous edition (**JIS D 9422** : 2008), which has been technically revised.

This **JIS** document is protected by the Copyright Act.

Attention is drawn to the possibility that some parts of this Standard may conflict with patent rights, published patent application or utility model rights. The relevant Minister and the Japanese Industrial Standards Committee are not responsible for identifying any of such patent rights, published patent application or utility model rights.

Tire valves for bicycles

1 Scope

This Japanese Industrial Standard specifies the requirements for tyre valves used for inner tubes for bicycle tyres specified in **JIS K 6304** (hereafter referred to as valves).

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this Standard. The most recent editions of the standards (including amendments) indicated below shall be applied.

JIS D 4211 *Tyre valve cores for automobiles*

JIS K 6304 *Inner tubes for bicycle tyres*

3 Terms and definitions

No terms and definitions are listed in this Standard.

4 Types and symbols

The valves shall be classified as **a)** and **b)** according to the air seal constructions and the jointing systems with tube. When using symbols to indicate the types, **c)** shall apply.

a) The air seal constructions are classified into three types as shown in Table 1.

Table 1 Types according to air seal constructions

Type	Symbol	Air seal construction
Wood valve	E	Seal by valve rubber
Schneider valve	A	Seal by use of valve packing
Flanta valve	F	Seal by use of shell packing

b) The jointing systems with tube are classified into two types as shown in Table 2.

Table 2 Types according to jointing systems with tube

Type	Symbol	Jointing system with tube
Rubber base valve ^{a)}	R	Adhesion through rubber seat (system in which a valve is adhered to tube through rubber seat)
Metal base valve	M	Metal pressure welding (system in which tube is held between body flange and washer)
Note ^{a)} Including rubber covered valves.		