

# JIS

JAPANESE  
INDUSTRIAL  
STANDARD

Translated and Published by  
Japanese Standards Association

---

---

**JIS G 2403** : 2015

(JAA/JSA)

**Aluminium dross for iron and steel  
making—Sampling and sample  
preparation procedures**

---

ICS 77.040.01;77.120.10

Reference number : **JIS G 2403 : 2015 (E)**

Date of Establishment: 2003-10-20

Date of Revision: 2015-09-24

Date of Public Notice in Official Gazette: 2015-09-24

Investigated by: Japanese Industrial Standards Committee

Standards Board for ISO area

Technical Committee on Metal and Inorganic

Materials

---

JIS G 2403:2015, First English edition published in 2016-02

Translated and published by: Japanese Standards Association  
Mita MT Building, 3-13-12, Mita, Minato-ku, Tokyo, 108-0073 JAPAN

---

In the event of any doubts arising as to the contents,  
the original JIS is to be the final authority.

© JSA 2016

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Printed in Japan

NH/AT

## Contents

		Page
1	Scope.....	1
2	Normative references .....	1
3	Terms and definitions.....	1
4	General requirements .....	2
5	Sampling and sample preparation.....	2
5.1	Outline .....	2
5.2	Treatment of sample .....	3
6	Sampling method.....	4
6.1	Classification of size of quality variation .....	4
6.2	Types of sampling method .....	4
6.3	Increment.....	4
6.4	Method for collecting increments.....	6
6.5	Belt sampling .....	7
6.6	Truck sampling .....	7
6.7	Container sampling.....	8
7	Sample preparation method.....	8
7.1	Outline .....	8
7.2	Pulverization of sample.....	8
7.3	Sample reduction.....	9
7.4	Sample for chemical analysis .....	10
7.5	Moisture content testing sample.....	10
8	Precautions on safety and hygiene, and environment.....	10

## Foreword

This translation has been made based on the original Japanese Industrial Standard revised by the Minister of Economy, Trade and Industry through deliberations at the Japanese Industrial Standards Committee as the result of proposal for revision of Japanese Industrial Standard submitted by Japan Aluminium Association (JAA)/ Japanese Standards Association (JSA) with the draft being attached, based on the provision of Article 12 Clause 1 of the Industrial Standardization Law applicable to the case of revision by the provision of Article 14.

Consequently **JIS G 2403**:2003 is replaced with this Standard.

This **JIS** document is protected by the Copyright Law.

Attention is drawn to the possibility that some parts of this Standard may conflict with patent rights, applications for a patent after opening to the public or utility model rights. The relevant Minister and the Japanese Industrial Standards Committee are not responsible for identifying any of such patent rights, applications for a patent after opening to the public or utility model rights.

# Aluminium dross for iron and steel making—Sampling and sample preparation procedures

## 1 Scope

This Japanese Industrial Standard specifies the procedures for sample preparation including the sampling and the sample reduction methods which are necessary for determining the components and the average value of properties of a lot of aluminium dross for iron and steel making.

## 2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this Standard. The most recent editions of the standards (including amendments) indicated below shall be applied.

JIS G 2402 *Aluminium dross for iron and steel making*

JIS M 8100 *Particulate materials—General rules for methods of sampling*

## 3 Terms and definitions

For the purpose of this Standard, the terms and definitions given in **JIS G 2402**, and the following apply.

### 3.1 lot

an arbitrary mass of aluminium dross for iron and steel making for the determination of the components and the average value of properties

The quantity of aluminium dross for iron and steel making constituting the lot is called the size of lot. When a part or the whole of the combinations of the material sources of aluminium dross for iron and steel making is altered, or when the variation is found in the components of aluminium dross of any material to be combined, it is dealt with as a different lot.

NOTE: For the manufacture of aluminium dross for iron and steel making, it is generally manufactured by combining multiple sources of aluminium dross as the material.

### 3.2 increment

aluminium dross for iron and steel making of the unit amount generally extracted with a sample or the like by one action from a lot

### 3.3 sample reduction

operation wherein a sample for measurement is prepared by gradually reducing the amount from the collected sample, when the sample is prepared from an aggregate