

JIS

JAPANESE
INDUSTRIAL
STANDARD

Translated and Published by
Japanese Standards Association

JIS H 8304 : 2014

(JTSS/JSA)

Ceramic sprayed coatings

ICS 25.220.20

Reference number : **JIS H 8304 : 2014 (E)**

H 8304 : 2014

Date of Establishment: 1980-11-01

Date of Revision: 2014-03-20

Date of Public Notice in Official Gazette: 2014-03-20

Investigated by: Japanese Industrial Standards Committee

Standards Board

Technical Committee on Non-Ferrous Metals

JIS H 8304:2014, First English edition published in 2015-01

Translated and published by: Japanese Standards Association
Mita MT Building, 3-13-12, Mita, Minato-ku, Tokyo, 108-0073 JAPAN

In the event of any doubts arising as to the contents,
the original JIS is to be the final authority.

© JSA 2015

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Printed in Japan

HT/AT

PROTECTED BY COPYRIGHT

Contents

	Page
1 Scope.....	1
2 Normative references	1
3 Terms and definitions	1
4 Classification and symbols	1
5 Application process	2
5.1 General	2
5.2 Structure, shape and surface condition of sprayed product	2
5.3 Pretreatment	2
5.4 Thermal spraying	2
5.5 Post-treatment	2
5.6 Outdoor thermal spraying work	3
6 Quality	3
6.1 General	3
6.2 Common quality	3
6.3 Coating hardness (ceramic sprayed coating for wear resistance)	4
6.4 Thermal shock resistance property (ceramic sprayed coating for heat resistance and ceramic sprayed coating for heat insulation)	4
6.5 Corrosion resistance property (ceramic sprayed coating for corrosion resistance)	4
6.6 Electrical insulation property (ceramic sprayed coating for electrical insulation)	4
7 Test methods	7
7.1 General	7
7.2 Appearance test	7
7.3 Structure test on coating cross-section	7
7.4 Coating thickness test	8
7.5 Adhesive strength test	8
7.6 Coating hardness test	8
7.7 Thermal shock property test	9
7.8 Corrosion resistance property test	10
7.9 Electrical insulation property test	11
8 Inspection	11
9 Marking	12
Annex A (informative) Recommended practice	13
Annex B (informative) Wear resistance test	23

Foreword

This translation has been made based on the original Japanese Industrial Standard revised by the Minister of Economy, Trade and Industry through deliberations at the Japanese Industrial Standards Committee as the result of proposal for revision of Japanese Industrial Standard submitted by Japan Thermal Spray Society (JTSS)/ Japanese Standards Association (JSA) with the draft being attached, based on the provision of Article 12 Clause 1 of the Industrial Standardization Law applicable to the case of revision by the provision of Article 14.

Consequently, **JIS H 8304**:2007 is replaced with this Standard, and **JIS H 9302**:2007 has been withdrawn and replaced with this Standard.

This **JIS** document is protected by the Copyright Law.

Attention is drawn to the possibility that some parts of this Standard may conflict with patent rights, applications for a patent after opening to the public or utility model rights. The relevant Minister and the Japanese Industrial Standards Committee are not responsible for identifying any of such patent rights, applications for a patent after opening to the public or utility model rights.

Ceramic sprayed coatings

1 Scope

This Japanese Industrial Standard specifies ceramic sprayed coatings applied to metallic substrates for the purpose of giving the wear resistance, corrosion resistance, heat resistance, heat insulation, electrical insulation and the like to parts, products, etc.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this Standard. The most recent editions of the standards (including amendments) indicated below shall be applied.

JIS C 2110-2 *Solid electrical insulating materials—Test methods for electric strength—Part 2: Tests using direct voltage*

JIS G 3101 *Rolled steels for general structure*

JIS H 8200 *Thermal spraying terms*

JIS H 8250 *Graphical symbol for thermal spraying*

JIS H 8260 *Powders for thermal spraying*

JIS H 8261 *Wires, rods and cords for flame and air thermal spraying*

JIS H 8302 *Build-up thermal spraying*

JIS H 8401 *Methods of thickness measurement for sprayed coatings*

JIS H 8402 *Test methods of tensile adhesive strength for thermal-sprayed coatings*

JIS H 8451 *Testing methods for thermal cycle and thermal shock resistance of thermal barrier coatings*

JIS Z 2244 *Vickers hardness test—Test method*

JIS Z 2371 *Methods of paint spray testing*

JIS Z 8401 *Guide to the rounding of numbers*

JIS Z 8402-6 *Accuracy (trueness and precision) of measurement methods and results—Part 6: Use in practice of accuracy values*

3 Terms and definitions

For the purposes of this Standard, the terms and definitions given in **JIS H 8200** apply.

4 Classification and symbols

The classification and symbols of sprayed coatings shall be as follows.

- a) The symbols of thermal spraying method, thickness and post-treatment shall be according to **JIS H 8250**.
- b) The symbols for the classification of sprayed coatings shall be as follows.