

JIS

JAPANESE
INDUSTRIAL
STANDARD

Translated and Published by
Japanese Standards Association

JIS K 2235 : 2022

(WIAJ/JSA)

Petroleum waxes

ICS 75.140

Reference number : JIS K 2235 : 2022 (E)

K 2235 : 2022

Date of Establishment: 1957-12-18

Date of Revision: 2022-01-20

Date of Public Notice in Official Gazette: 2022-01-20

Investigated by: Japanese Industrial Standards Committee

Standards Board for ISO area

JIS K 2235 : 2022, First English edition published in 2023-02

Translated and published by: Japanese Standards Association
Mita MT Building, 3-13-12, Mita, Minato-ku, Tokyo, 108-0073 JAPAN

In the event of any doubts arising as to the contents,
the original JIS is to be the final authority.

© JSA 2023

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Printed in Japan

HT/HN

PROTECTED BY COPYRIGHT

Contents

		Page
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Classification	2
5	Quality	3
6	Test methods	4
6.1	Testers general	4
6.2	Sampling methods	4
6.3	Melting point test method	4
6.4	Penetration test method	8
6.5	Reaction test method	14
6.6	Oil content test method	14
6.7	Colour test method	21
6.8	Flash point test method	21
6.9	Kinematic viscosity test method	21
6.10	Consistency test method	21
6.11	Acid value test method	25
7	Packaging	25
8	Designation of products	25
9	Marking	25

Foreword

This Japanese Industrial Standard has been revised by the Minister of Economy, Trade and Industry through deliberations at the Japanese Industrial Standards Committee as the result of proposal for revision of Japanese Industrial Standard submitted by Wax Industry Association of Japan (WIAJ)/Japanese Standards Association (JSA) with a draft being attached, based on the provision of Article 12, paragraph (1) of the Industrial Standardization Act applied mutatis mutandis pursuant to the provision of Article 16 of the said Act.

This edition replaces the previous edition (**JIS K 2235 : 2009**), which has been technically revised.

This **JIS** document is protected by the Copyright Act.

Attention is drawn to the possibility that some parts of this Standard may conflict with patent rights, published patent application or utility model rights. The relevant Minister and the Japanese Industrial Standards Committee are not responsible for identifying any of such patent rights, published patent application or utility model rights.

Petroleum waxes

1 Scope

This Japanese Industrial Standard specifies the requirements for petroleum waxes for industrial use (hereafter referred to as waxes).

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this Standard. The most recent editions of the standards (including amendments) indicated below shall be applied.

- JIS B 0651 *Geometrical Product Specifications (GPS) — Surface texture : Profile method — Nominal characteristics of contact (stylus) instruments*
- JIS B 7410 *Liquid-in-glass thermometers for testing of petroleum product*
- JIS K 2207 *Petroleum asphalts*
- JIS K 2220 *Lubricating grease*
- JIS K 2251 *Crude petroleum and petroleum products — Sampling*
- JIS K 2252 *Petroleum products — Testing method for reaction*
- JIS K 2265-4 *Determination of flash points — Part 4 : Cleveland open cup method*
- JIS K 2283 *Crude petroleum and petroleum products — Determination of kinematic viscosity and calculation of viscosity index from kinematic viscosity*
- JIS K 2501 *Petroleum products and lubricants — Determination of neutralization number*
- JIS K 2580 *Petroleum products — Determination of colour*
- JIS K 8295 *Glycerol (Reagent)*
- JIS K 8900 *2-Butanone (Reagent)*
- JIS T 8000 *Particulate materials — General rules for methods of sampling*
- JIS Z 8401 *Rounding of numbers*

3 Terms and definitions

For the purpose of this Standard, the following terms and definitions apply.

3.1

paraffin wax

solid wax at ordinary temperature, refined by separation from vacuum distillate oil