

Design, Fabrication, and Inspection of Tanks for the Storage of Petroleum Refining Alkylation Unit Spent Sulfuric Acid at Ambient Temperatures

©2021 Association for Materials Protection and Performance (AMPP). All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means (electronic, mechanical, photocopying, recording, or otherwise) without the prior written permission of AMPP.

Design, Fabrication, and Inspection of Tanks for the Storage of Petroleum Refining Alkylation Unit Spent Sulfuric Acid at Ambient Temperatures

This AMPP standard represents a consensus of those individual members who have reviewed this document, its scope, and provisions. Its acceptance does not in any respect preclude anyone, whether he or she has adopted the standard or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not in conformance with this standard. Nothing contained in this AMPP standard is to be construed as granting any right, by implication, or otherwise, to manufacture, sell, or use in connection with any method, apparatus, or product covered by Letters Patent, or as indemnifying or protecting anyone against liability for infringement of Letters Patent. This standard represents minimum requirements and should in no way be interpreted as a restriction on the use of better procedures or materials. Neither is this standard intended to apply in all cases relating to the subject. Unpredictable circumstances may negate the usefulness of this standard in specific instances. AMPP assumes no responsibility for the interpretation or use of this standard by other parties and accepts responsibility for only those official AMPP interpretations issued by AMPP in accordance with its governing procedures and policies which preclude the issuance of interpretations by individual volunteers.

Users of this AMPP standard are responsible for reviewing appropriate health, safety, environmental, and regulatory documents and for determining their applicability in relation to this standard prior to its use. This AMPP standard may not necessarily address all potential health and safety problems or environmental hazards associated with the use of materials, equipment, and/or operations detailed or referred to within this standard. Users of this AMPP standard are also responsible for establishing appropriate health, safety, and environmental protection practices, in consultation with appropriate regulatory authorities, if necessary, to achieve compliance with any existing applicable regulatory requirements prior to the use of this standard.

CAUTIONARY NOTICE: AMPP standards are subject to periodic review and may be revised or withdrawn at any time in accordance with AMPP technical committee procedures. AMPP requires that action be taken to reaffirm, revise, or withdraw this standard no later than five years from the date of initial publication and subsequently from the date of each reaffirmation or revision. The user is cautioned to obtain the latest edition. Purchasers of AMPP standards may receive current information on all standards and other AMPP/NACE/SSPC publications by contacting AMPP Customer Support, 15835 Park Ten Place, Houston, Texas 77040-4-5145 (Tel: +1 281-228-6200, email: customersupport@ampp.org).

Document History

2021-11-08: Reaffirmed by AMPP Standards Committee (SC) 16, Oil and Gas, Downstream.

2015-09-08: Reaffirmed by NACE TG (Task Group) 300,
“Petroleum Refining Spent Sulfuric Acid Storage Tank Requirements: Standard.”

2010-07-29: Reaffirmed by NACE TG 300,
“Petroleum Refining Spent Sulfuric Acid Storage Tank Requirements: Standard.”

2005-10-15: Approved as SP0205 by NACE TG 300,
“Petroleum Refining Spent Sulfuric Acid Storage Tank Requirements: Standard.”

AMPP values your input. To provide feedback on this standard, please contact: standards@ampp.org

NACE SP0205-2021

©2021 Association for Materials Protection and Performance (AMPP). All rights reserved.

Design, Fabrication, and Inspection of Tanks for the Storage of Petroleum Refining Alkylation Unit Spent Sulfuric Acid at Ambient Temperatures

Foreword	4
Section 1	General	5
Section 2	Corrosion Concerns	5
Section 3	Inspection.....	7
Section 4	Design, Construction, and Maintenance	7
References	8
Figure 1	Steel Corrosion by H ₂ SO ₄ ⁶	6

Foreword

Sulfuric acid (H_2SO_4) is the largest volume commodity chemical in use today. It plays some part in the production of nearly all manufactured goods. One large use of concentrated sulfuric acid is used as a catalyst for refinery alkylation units. In these units, C3-C5 olefins such as propylene or butylene are reacted with isobutane to form gasoline-blending components such as isoheptane and isooctane. These gasoline-blending components are used to boost octane for automobile and aviation fuels.

Most refineries have an alkylation unit that uses either hydrofluoric acid (HF) or sulfuric acid as the alkylation catalyst. This standard deals with spent sulfuric acid associated with the sulfuric acid alkylation process only.

Refineries using sulfuric acid alkylation typically require tanks for the storage of fresh (not yet used in the alkylation process) and spent (used in the alkylation process and in need of regeneration) acid. Design, fabrication, and inspection of fresh sulfuric acid tanks are covered in NACE SP0294.¹ This standard covers additions and deviations from SP0294 that apply to spent sulfuric acid storage tanks.

Large, vertical sulfuric acid storage tanks are usually built in accordance with API⁽¹⁾ Standard 650² or API Standard 620,³ and horizontal cylindrical tanks are built in accordance with the ASME⁽²⁾ Boiler and Pressure Vessel Code, Section VIII, Division 1.⁴ Although these codes and standards are sufficient for design strength and toughness considerations, they do not address the peculiarities of corrosion by alkylation unit spent sulfuric acid service. In addition, alkylation unit spent acid may contain dissolved hydrocarbons and hydrogen that release into the vapor space of these tanks and potentially produce an explosive environment. Thus, special care must be taken to deal with vapor leakage from the vapor space of these tanks and air intrusion into the vapor space of these tanks.

Carbon steel corrodes moderately when in contact with alkylation unit spent sulfuric acid. If tanks are properly designed and adequately maintained, use of carbon steel is an economical option for the storage of these acids at ambient temperatures. However, accelerated corrosion can occur in various forms, and a catastrophic failure of a spent acid tank in Delaware City, Delaware, U.S., has focused attention on the hazards associated with corrosion, vapor space leakage, and hot work on or around alkylation spent sulfuric acid tanks. The Chemical Safety Board⁽³⁾ report⁵ provides more details regarding this failure.

In AMPP standards, the terms *shall* and *must* are used to state requirements and are considered mandatory. The term *should* is used to state something that is recommended, but is not considered mandatory. The term *may* is used to state something considered optional.

⁽¹⁾ American Petroleum Institute (API), 1220 L St. NW, Washington, DC 20005-4070.

⁽²⁾ ASME, Two Park Avenue, New York, NY 10016-5990.

⁽³⁾ U.S. Chemical Safety and Hazard Investigation Board (CSB), 2175 K St. NW, Suite 400, Washington, DC 20037-1809.