

Field-Applied, Heat-Shrinkable-Sleeve Coating System for Pipelines: Application, Performance, and Quality Control

This NACE International standard represents a consensus of those individual members who have reviewed this document, its scope, and provisions. Its acceptance does not in any respect preclude anyone, whether he or she has adopted the standard or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not in conformance with this standard. Nothing contained in this NACE standard is to be construed as granting any right, by implication or otherwise, to manufacture, sell, or use in connection with any method, apparatus, or product covered by letters patent, or as indemnifying or protecting anyone against liability for infringement of letters patent. This standard represents minimum requirements and should in no way be interpreted as a restriction on the use of better procedures or materials. Neither is this standard intended to apply in all cases relating to the subject. Unpredictable circumstances may negate the usefulness of this standard in specific instances. NACE assumes no responsibility for the interpretation or use of this standard by other parties and accepts responsibility for only those official NACE interpretations issued by NACE in accordance with its governing procedures and policies which preclude the issuance of interpretations by individual volunteers.

Users of this NACE standard are responsible for reviewing appropriate health, safety, environmental, and regulatory documents and for determining their applicability in relation to this standard prior to its use. This NACE standard may not necessarily address all potential health and safety problems or environmental hazards associated with the use of materials, equipment, and/or operations detailed or referred to within this standard. Users of this NACE standard are also responsible for establishing appropriate health, safety, and environmental protection practices, in consultation with appropriate regulatory authorities if necessary, to achieve compliance with any existing applicable regulatory requirements prior to the use of this standard.

CAUTIONARY NOTICE: NACE standards are subject to periodic review, and may be revised or withdrawn at any time in accordance with NACE technical committee procedures. NACE requires that action be taken to reaffirm, revise, or withdraw this standard no later than five years from the date of initial publication and subsequently from the date of each reaffirmation or revision. The user is cautioned to obtain the latest edition. Purchasers of NACE standards may receive current information on all standards and other NACE publications by contacting the NACE FirstService Department, 15835 Park Ten Place, Houston, TX 77084-5145 (tel: +1 281-228-6200, email: firstservice@nace.org).

ABSTRACT

Revised in 2020, this NACE International standard practice provides current technology and industry practices for the use of field-applied heat-shrinkable-sleeve coating systems. The standard is intended for use by corrosion control personnel, design engineers, project managers, purchasers, and construction engineers and managers. It is applicable to underground steel pipelines in the oil and gas gathering, distribution, and transmission industries.

The standard practice presents guidelines for establishing minimum requirements to ensure proper application and performance of field-applied, heat-shrinkable sleeves to the external surfaces of coated pipe. Included are methods for (1) qualifying and controlling the quality of a heat-shrinkable sleeve, (2) guidelines for proper application, and (3) inspection and repair techniques to ensure its long-term performance. The standard is applicable to coating systems used to prevent corrosion in conjunction with cathodic protection, and heat-shrinkable wraparound- or tubular-type sleeve coating systems, underground steel pipelines.

KEYWORDS

Alyeska shear test, cathodic protection, dry film thickness, external corrosion, field-applied, heat-shrinkable-sleeve coating systems (HSS-CS), hot-melt adhesive layer, Lap shear, mastic-based adhesive layer, oil and gas distribution, polyolefin, SP0169, STG 03, submerged steel pipelines, surface preparation, TG 248, tubular-type heat-shrinkable-sleeve, weld-after-backfill, wraparound-type heat-shrinkable-sleeve

Foreword

This NACE standard practice provides the most current technology and industry practices for the use of two types of field-applied, heat-shrinkable-sleeve coating systems (HSS-CS); one, where the polyolefin backing is coated with a mastics-based adhesive layer, and the other has the polyolefin backing coated with a hot-melt-based adhesive layer. This standard is intended for use by corrosion control personnel, design engineers, project managers, suppliers, purchasers, and construction engineers and managers. It is applicable to underground or submerged steel pipelines in the oil, gas, and water gathering, distribution, and transmission industries.

This standard practice was originally prepared in 2003 and revised in 2020 by Task Group (TG) 248, “Coatings, Heat-Shrink Sleeves for External Repair, Rehabilitations, and Weld Joints on Pipelines.” TG 248 is administered by Specific Technology Group (STG) 03, “Coatings and Linings, Protective—Immersion and Buried Service.” It is also sponsored by STG 04, “Coatings and Linings, Protective—Surface Preparation,” and STG 35, “Pipelines, Tanks, and Well Casings.” This standard is issued by NACE under the auspices of STG 03.

In NACE standards, the terms **shall**, **must**, **should**, and **may** are used in accordance with the definitions of these terms in the NACE Publications Style Manual. The terms **shall** and **must** are used to state a requirement, and are considered mandatory. The term **should** is used to state something good and is recommended, but is not considered mandatory. The term **may** is used to state something considered optional.

Field-Applied, Heat-Shrinkable-Sleeve Coating System for Pipelines: Application, Performance, and Quality Control

1.	General	4
2.	Definitions	4
3.	Coating System	5
4.	Coating Materials	5
5.	Coating Performance	6
6.	Surface Preparation	7
7.	Coating Application	8
8.	Inspection and Repair	9
9.	Backfilling	9
	References	10

TABLE

Table 1: Heat-Shrinkable-Sleeve Coating System Performance Characteristics	6
--	---