

# Screening Tests for Evaluating the Effectiveness of Gypsum Scale Removers

This NACE International standard represents a consensus of those individual members who have reviewed this document, its scope, and provisions. Its acceptance does not in any respect preclude anyone, whether he has adopted the standard or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not in conformance with this standard. Nothing contained in this NACE International standard is to be construed as granting any right, by implication or otherwise, to manufacture, sell, or use in connection with any method, apparatus, or product covered by Letters Patent, or as indemnifying or protecting anyone against liability for infringement of Letters Patent. This standard represents minimum requirements and should in no way be interpreted as a restriction on the use of better procedures or materials. Neither is this standard intended to apply in all cases relating to the subject. Unpredictable circumstances may negate the usefulness of this standard in specific instances. NACE International assumes no responsibility for the interpretation or use of this standard by other parties and accepts responsibility for only those official NACE International interpretations issued by NACE International in accordance with its governing procedures and policies which preclude the issuance of interpretations by individual volunteers.

Users of this NACE International standard are responsible for reviewing appropriate health, safety, environmental, and regulatory documents and for determining their applicability in relation to this standard prior to its use. This NACE International standard may not necessarily address all potential health and safety problems or environmental hazards associated with the use of materials, equipment, and/or operations detailed or referred to within this standard. Users of this NACE International standard are also responsible for establishing appropriate health, safety, and environmental protection practices, in consultation with appropriate regulatory authorities if necessary, to achieve compliance with any existing applicable regulatory requirements prior to the use of this standard.

**CAUTIONARY NOTICE** NACE International standards are subject to periodic review, and may be revised or withdrawn at any time without prior notice. NACE International requires that action be taken to reaffirm, revise, or withdraw this standard no later than five years from the date of initial publication. The user is cautioned to obtain the latest edition. Purchasers of NACE International standards may receive current information on all standards and other NACE International publications by contacting the NACE International FirstService Department, 15835 Park Ten Place, Houston, Texas 77084, telephone +1 (281) 228-6223.

## ABSTRACT

*This standard presents test methods for screening the effectiveness of two types of gypsum scale removers, one for scale dissolvers, and another for scale converters. The test methods described in this standard are static laboratory screening tests designed to measure the ability of chemicals to remove gypsum scale deposits. Test methods for screening both gypsum scale dissolvers and converters are described. This standard is maintained by Task Group 384.*

## KEYWORDS

*Oilfield, test methods, gypsum*

***In NACE standards, the terms “shall,” “must,” “should,” and “may” are used in accordance with the definitions of these terms in the NACE Publications Style Manual. The terms “shall” and “must” are used to state a requirement, and are considered mandatory. The term “should” is used to state something good and is recommended, but is not considered mandatory. The term “may” is used to state something considered optional.***

## Foreword

Hydrocarbon production is often accompanied by the production of brine. Minerals may precipitate from a brine and deposit within the production system. The scale deposits can be located both downhole and in surface equipment. Often, the deposit has an adverse effect on production and must be removed.

Producers and service companies devote considerable effort to developing and marketing effective treating chemicals because of the serious impact that gypsum ( $\text{CaSO}_4 \cdot 2\text{H}_2\text{O}$ ) scale formation can have on hydrocarbon production. The performance of these treating chemicals used for scale removal can be determined most effectively after an actual field trial. However, field testing can be very difficult and time-consuming, especially when many chemicals are being evaluated. Although most laboratory tests cannot exactly duplicate field conditions, the advantage of such tests is to provide the user with a comparison of the performance of one scale remover against that of another under standard laboratory conditions. The industry has not established a standard test method to evaluate gypsum scale removers. Consequently, performance tests on a scale remover or collection of scale removers yield widely differing absolute and relative results depending on the test procedure used.

NACE Unit Committee T-1D formed Task Group T-1D-32 in 1987, in response to an expressed need for a standard test method for the evaluation of chemical-based gypsum scale removers.

The initial task group assignment was to compose and publish a technical committee report. That report was issued in 1991 (NACE Publication 1D191<sup>1</sup>). The subsequent assignment was to develop standard test methods for screening gypsum scale remover chemicals, which are addressed in this standard.

This standard presents test methods for screening the effectiveness of two types of gypsum scale removers, one for scale dissolvers, and another for scale converters. These methods are primarily intended for use by those in the petroleum industry who need to use treating chemicals to remove gypsum scale deposits.

This NACE standard was originally prepared in 1997 by Task Group T-1D-32, a component of former Unit Committee T-1D on Corrosion Monitoring and Control of Corrosion Environments in Petroleum Production Operations. It was reaffirmed in 2002 by Specific Technology Group (STG) 31 on Oil and Gas Production—Corrosion and Scale Inhibition and it was reaffirmed in 2018 by TG 384, Oilfield Scale Removers Evaluation. It is issued by NACE International under the auspices of STG 31.

# Soluble Salt Testing Frequency and Locations on Previously Coated Surfaces

1.	General .....	4
2.	Scale Dissolver Screening Test for Gypsum .....	5
3.	Gypsum Scale Converter Screening Test .....	8
	References.....	11
	Appendix A: Procedure for Making Compressed Gypsum Pellets (Nonmandatory).....	12

## Tables

Table 1:	Screening Test Limits for Na <sub>4</sub> ESTA Reference .....	8
Table 2:	Screening test limits for KC <sub>2</sub> O <sub>3</sub> H <sub>3</sub> reference at ambient conditions .....	11