

NEMA TC 2-2020

Standard for Electrical Polyvinyl Chloride (PVC) Conduit



NEMA Standards Publication TC 2-2020

Electrical Polyvinyl Chloride (PVC) Conduit

Published by:

National Electrical Manufacturers Association

1300 North 17th Street, Suite 900

Rosslyn, Virginia 22209

www.nema.org

© 2020 National Electrical Manufacturers Association. All rights, including translation into other languages, reserved under the Universal Copyright Convention, the Berne Convention for the Protection of Literary and Artistic Works, and the International and Pan American copyright conventions.

NOTICE AND DISCLAIMER

The information in this publication was considered technically sound by a consensus among persons engaged in its development at the time it was approved. Consensus does not necessarily mean there was unanimous agreement among every person participating in the development process.

The National Electrical Manufacturers Association (NEMA) Standards and guideline publications, of which the document herein is one, are developed through a voluntary Standards development process. This process brings together volunteers and/or seeks out the views of persons who have an interest in the topic covered by this publication. Although NEMA administers the process and establishes rules to promote fairness in the development of consensus, it does not write the documents, nor does it independently test, evaluate, or verify the accuracy or completeness of any information or the soundness of any judgments contained in its Standards and guideline publications.

NEMA disclaims liability for any personal injury, property, or other damages of any nature, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, application, or reliance on this document. NEMA disclaims and makes no guaranty or warranty, express or implied, as to the accuracy or completeness of any information published herein, and disclaims and makes no warranty that the information in this document will fulfill any particular purpose(s) or need(s). NEMA does not undertake to guarantee the performance of any individual manufacturer's or seller's products or services by virtue of this Standard or guide.

In publishing and making this document available, NEMA is not undertaking to render professional or other services for or on behalf of any person or entity, nor is NEMA undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstance. Information and other standards on the topic covered by this publication may be available from other sources, which the user may wish to consult for additional views or information not covered by this publication.

NEMA has no power, nor does it undertake to police or enforce compliance with the contents of this document. NEMA does not certify, test, or inspect products, designs, or installations for safety or health purposes. Any certification or other statement of compliance with any health- or safety-related information in this document shall not be attributable to NEMA and is solely the responsibility of the certifier or maker of the statement.

CONTENTS

Section 1 General	1
1.1 Scope	1
1.2 Referenced Standards	1
Section 2 Definitions	3
2.1 Definitions	3
Section 3 General Requirements	4
3.1 Materials	4
3.1.1 Electrical Polyvinyl Chloride (PVC) Conduit (EPC)	4
3.1.2 Solvent Cements	4
3.2 Color	4
3.3 Dimensions and Lengths	4
3.3.1 Average Outside Diameter	4
3.3.2 Out-of-Roundness	4
3.3.3 Wall Thickness	4
3.3.4 Conduit Length	4
3.3.5 Minimum Inside Diameter	4
3.4 Joints	5
3.4.1 Molded Couplings	5
3.4.2 Integral Belled Ends	5
3.5 Inspections	5
Section 4 Performance Requirements	8
4.1 Qualification and Quality Tests	8
4.2 Qualification Test	8
4.2.1 Definition	8
4.2.2 Resistance to Crushing	8
4.2.3 Leakage at Solvent-Cemented Joints	8
4.3 Quality Control Tests	8
4.3.1 Definition	8
4.3.2 Conditioning	8
4.3.3 Dimensions	8
4.3.4 Workmanship	8
4.3.5 Impact Resistance	8
Section 5 Test Methods	10
5.1 Conditioning, Test Conditions, and Sampling	10
5.1.1 Conditioning Test Specimens	10
5.1.2 Test Conditions	10
5.1.3 Sampling	10
5.2 Dimensions	10
5.2.1 Maximum and Minimum Outside Diameter (Out-of-Roundness)	10
5.2.2 Outside Diameter (Average)	10
5.2.3 Wall Thickness	10
5.2.4 Minimum Inside Diameter	10
5.3 Deflection Resistance	10
5.4 Leakage at Solvent Cemented Joints	10
5.5 Impact Resistance	10
Section 6 Markings	12
6.1 Requirements for Markings	12
Annex A Out of Roundness Gauges and Go/No-Go Gauges	13

Tables

	Page
Table 3-1 Sizes and Dimensions Of EPC	6
Table 3-2 Dimensions of Integral Belled Ends.....	7
Table 4-1 Load For Deflection Resistance.....	9
Table A-1 Out of Roundness (Ovality) Gauges for EPC-40 and EPC-80.....	13
Table A-2 Go/No-Go Gauges for EPC-40 and EPC-8.....	14

Currently in preview, click buy full version

Foreword

The purpose of this publication for electrical polyvinyl chloride (PVC) conduit (EPC) for above-ground and below-ground use is:

- a. To list dimensions and other significant requirements.
- b. To set forth some of the properties of these products and to assist in selecting and obtaining the proper product for a particular need.

User needs and safety considerations were considered during the development of these Standards. The NEMA Polymer Raceway Products Section will periodically review this Standard and revise it as necessary. Proposals for revisions can be submitted to:

NEMA Technical Operations Department
National Electrical Manufacturers Association
1300 North 17th Street, Suite 900
Rosslyn, Virginia 22209

NEMA TC 2-2020 revises and supersedes NEMA TC 2-2013. NEMA TC 2 was prepared by a subgroup of the NEMA Polymer Raceway Products Section's Technical Committee. During the preparation phase, the following were active participants:

David Kendall—ABB, Inc.
Ray Horner—Atkore International
Brian Deacy—Atkore International
Andrew Nause—IPEX USA, LLC.

NEMA TC 2 was approved by the NEMA Polymer Raceway Products Section. Approval does not necessarily imply that all Members of the Section voted in its approval. At the time of approval, the Section consisted of the following Members:

ABB, Inc.—www.abb.com—Memphis, TN
Anamet Electrical, Inc.—www.anamet.com—Baltimore, MD
Atkore International—www.atkore.com—Harvey, IL
Champion Fiberglass, Inc.—www.championfiberglass.com—Spring, TX
Electri-Flex Company—www.electriflex.com—Roselle, IL
FRE Composites Group—www.frecomposites.com—St. Andre-d'Argenteuil, QC, Canada
Hubbell Incorporated—www.hubbell.com—Shelton, CT
IPEX USA, LLC.—www.ipexamerica.com—Oakville, ON, Canada
Legrand North America—www.legrand.us—West Hartford, CT
Panduit Corporation—www.panduit.com—Tinley Park, IL
Phoenix Contact—www.phoenixcontact.com—Middletown, PA
Southern Pipe, Inc.—www.southern-pipe.com—New London, NC
Southwire Corporation—www.southwire.com—Carrollton, GA
Underground Devices, Inc.—www.udevices.com—Northbrook, IL
United Fiberglass of America, Inc.—www.unitedfiberglass.com—Springfield, OH

< This page is intentionally left blank >

Currently in preview, click buy full version

Section 1 General

1.1 Scope

NEMA TC 2 covers the following types of Electrical Polyvinyl Chloride (PVC) Conduit (EPC), which can be constructed of a single, solid layer of PVC, or can be constructed of multiple layers of PVC, one of which may be cellular (foamed) PVC. The designations “40” and “80” refer to Schedules 40 and 80 (EPC-40 and EPC-80), respectively, of Iron Pipe Size (IPS) dimensions. Common uses for these designations are:

- a. EPC-40—Electrical conduit designed for normal-duty applications aboveground; concrete-encased applications or direct burial. May be referred to as “heavy wall.”
- b. EPC-80—Electrical conduit designed for heavy-duty (areas of physical damage) applications aboveground; concrete-encased applications or direct burial. May be referred to as “extra heavy wall.”

Note: The values stated in U.S. customary units are to be regarded as the Standard. NEMA TC2 does not fully address elbows and fittings. See NEMA TC 3 latest edition.

1.2 Referenced Standards

In this publication, reference is made to the Standards listed below. Copies are available from the indicated sources. The latest edition of these Standards should be used unless otherwise specified.

American Society for Testing and Materials

100 Barr Harbor Drive
West Conshohocken, PA 19428

D 1600	<i>Standard Terminology for Abbreviated Terms Relating to Plastics</i>
D 2122	<i>Standard Test Method of Determining Dimensions of Thermoplastic Pipe and Fittings</i>
D 2564	<i>Standard Specification for Solvent Cements for Poly (Vinyl Chloride) (PVC) Plastic Piping Systems</i>
D 618	<i>Standard Practice for Conditioning Plastics for Testing</i>
D 883	<i>Standard Terminology Relating to Plastics</i>
F 402	<i>Standard Practice for Safe Handling of Solvent Cements, Primers, and Cleaners Used for Joining Thermoplastic Pipe and Fittings</i>
F 412	<i>Standard Terminology Relating to Plastic Piping Systems</i>
F 656	<i>Standard Specification for Primers for Use in Solvent Cement Joints of Poly (vinyl Chloride) (PVC) Plastic Pipe and Fittings</i>

National Electrical Manufacturers Association

1300 North 17th Street, Suite 900
Rosslyn, Virginia 22209

TC 3	<i>Polyvinyl Chloride (PVC) Fittings for Use with Rigid PVC Conduit and Tubing</i>
------	--

Underwriters Laboratories Inc.

333 Pfingsten Road
Northbrook, IL 60062

UL 514B	<i>Conduit, Tubing, and Cable Fittings</i>
UL 514C	<i>Nonmetallic Outlet Boxes, Flush-Device Boxes and Covers</i>
UL 651	<i>Schedule 40 and 80 Rigid PVC Conduit and Fittings</i>