



PROCESS
INDUSTRY
PRACTICES

COMPLETE REVISION
December 2021

Piping

**PIP PNSMV007
Carbon Steel Butterfly
Valve Descriptions**

Currently in preview, click buy full version

PURPOSE AND USE OF PROCESS INDUSTRY PRACTICES

In an effort to minimize the cost of process industry facilities, this Practice has been prepared from the technical requirements in the existing standards of major industrial users, contractors, or standards organizations. By harmonizing these technical requirements into a single set of Practices, administrative, application, and engineering costs to both the purchaser and the manufacturer should be reduced. While this Practice is expected to incorporate the majority of requirements of most users, individual applications may involve requirements that will be appended to and take precedence over this Practice. Determinations concerning fitness for purpose and particular matters or application of the Practice to particular project or engineering situations should not be made solely on information contained in these materials. The use of trade names from time to time should not be viewed as an expression of preference but rather recognized as normal usage in the trade. Other brands having the same specifications are equally correct and may be substituted for those named. All Practices or guidelines are intended to be consistent with applicable laws and regulations including OSHA requirements. To the extent these Practices or guidelines should conflict with OSHA or other applicable laws or regulations, such laws or regulations must be followed. Consult an appropriate professional before applying or acting on any material contained in or suggested by the Practice.

This Practice is subject to revision at any time.

© Process Industry Practices (PIP), Construction Industry Institute, The University of Texas at Austin, 3925 West Braker Lane (R4500), Austin, Texas 78759. PIP Member Companies and Subscribers may copy this Practice for their internal use. Changes or modifications of any kind are not permitted within any PIP Practice without the express written authorization of PIP. Authorized Users may attach addenda or overlays to clearly indicate modifications or exceptions to specific sections of PIP Practices. Authorized Users may provide their clients, suppliers and contractors with copies of the Practice solely for Authorized Users' purposes. These purposes include but are not limited to the procurement process (e.g., as attachments to requests for quotation/purchase orders or requests for proposals/contracts) and preparation and issue of design engineering deliverables for use on a specific project by Authorized User's client. PIP's copyright notices must be clearly indicated and unequivocally incorporated in documents where an Authorized User desires to provide any third party with copies of the Practice.

PUBLISHING HISTORY

May 2000	Issued	February 2008	Editorial Revision
July 2001	Technical Correction	March 2010	Complete Revision
November 2003	Technical Revision	October 2017	Complete Revision
November 2005	Technical Revision	December 2021	Complete Revision



**PIP PNSMV007
Carbon Steel Butterfly
Valve Descriptions**

Table of Contents

1. Scope	2	4. Notes	2
2. References	2	5. Cross Reference	3
2.1 Process Industry Practices	2	6. Active Valve Descriptions	3
2.2 Industry Codes and Standards	2		
3. Valve Designation System	2		

1. Scope

This Practice provides requirements for suppliers providing carbon steel butterfly valves included in PIP Piping Material Specifications (PMSs).

2. References

Applicable parts of the following Practice and industry codes and standards shall be considered an integral part of this Practice. The edition in effect on the date of contract award shall be used, except as otherwise noted. Short titles will be used herein where appropriate.

2.1 Process Industry Practices (PIP)

- PIP PNCM0004 - *Valve Tag Number Designator System*

2.2 Industry Codes and Standards

- American Petroleum Institute (API)
 - API 6FA - *Specification for Fire Test for Valves*
 - API 607 - *Fire Test for Soft-Seated Quarter-Turn Valve*

3. Valve Designation System

- 3.1 For a full explanation of the format used to structure the valve numbers listed within this Practice, refer to *PIP PNCM0004*.
- 3.2 This Practice provides descriptions for butterfly valves. Therefore, the first two characters in the valve number are BF.
- 3.3 The valves listed in Section 5 and Section 6 of this Practice are sorted by the unique valve number designation in ascending alphanumeric sequence (e.g., BF01CA700, BF01CA701, BF01CB700, BF01CB701, BF03CA700).

4. Notes

- 4.1 Occasionally, valve size ranges listed in this Practice are broader than the size ranges shown for the same valves on a given PMS. While the “most common practice” has been used to specify valve size ranges on PMSs, a purchaser may need to utilize a valve in a size outside this “common practice” choice. Thus, for reference purposes, the full-size range for which a given valve is typically manufactured is shown in this Practice.
- 4.2 Gear operators are specified in some, but not all, butterfly valve descriptions. If not specified in the valve description, the purchaser shall specify that gear operators are needed. One method of specifying this need is by using Field 5 of the valve designation system as described in *PIP PNCM0004*.
- 4.3 Many butterfly valve manufacturers offer numerous handle options (e.g., locking/nonlocking, latching/nonlatching, oval, tee). As a default, valve descriptions within this Practice specify a 10-position ratchet lever with lockout. The purchaser shall specify a different handle option if required.