



PROCESS  
INDUSTRY  
PRACTICES

COMPLETE REVISION  
May 2019

***Piping***

**PIP PNSMV053  
Nickel and Nickel Alloy  
Gate Valve Descriptions**

---

Currently in preview, click buy full version

## PURPOSE AND USE OF PROCESS INDUSTRY PRACTICES

In an effort to minimize the cost of process industry facilities, this Practice has been prepared from the technical requirements in the existing standards of major industrial users, contractors, or standards organizations. By harmonizing these technical requirements into a single set of Practices, administrative, application, and engineering costs to both the purchaser and the manufacturer should be reduced. While this Practice is expected to incorporate the majority of requirements of most users, individual applications may involve requirements that will be appended to and take precedence over this Practice. Determinations concerning fitness for purpose and particular matters or application of the Practice to particular project or engineering situations should not be made solely on information contained in these materials. The use of trade names from time to time should not be viewed as an expression of preference but rather recognized as normal usage in the trade. Other brands having the same specifications are equally correct and may be substituted for those named. All Practices or guidelines are intended to be consistent with applicable laws and regulations including OSHA requirements. To the extent these Practices or guidelines should conflict with OSHA or other applicable laws or regulations, such laws or regulations must be followed. Consult an appropriate professional before applying or acting on any material contained in or suggested by the Practice.

This Practice is subject to revision at any time.

© Process Industry Practices (PIP), Construction Industry Institute, The University of Texas at Austin, 3925 West Braker Lane (R4500), Austin, Texas 78759. PIP Member Companies and Subscribers may copy this Practice for their internal use. Changes or modifications of any kind are not permitted within any PIP Practice without the express written authorization of PIP. Authorized Users may attach addenda or overlays to clearly indicate modifications or exceptions to specific sections of PIP Practices. Authorized Users may provide their clients, suppliers and contractors with copies of the Practice solely for Authorized Users' purposes. These purposes include but are not limited to the procurement process (e.g. as attachments to requests for quotation/ purchase orders or requests for proposals/contracts) and preparation and issue of design engineering deliverables for use on a specific project by Authorized User's client. PIP's copyright notices must be clearly indicated and unequivocally incorporated in documents where an Authorized User desires to provide any third party with copies of the Practice.

### **PRINTING HISTORY**

April 1997	Issued	May 2000	Revision	September 2005	Technical Correction	February 2015	Technical Revision
November 1999	Revision	June 2001	Technical Correction	November 2005	Technical Revision	May 2019	Complete Revision
February 2000	Revision	March 2003	Technical Revision	March 2010	Complete Revision		

Not printed with State funds



## PIP PNSMV053 Nickel and Nickel Alloy Gate Valve Descriptions

---

### Table of Contents

1. Scope .....	2	5. Cross Reference .....	3
2. References .....	2	6. Valve Descriptions.....	4
2.1 Process Industry Practices.....	2		
3. Valve Designation System .....	2		
4. Notes.....	2		

## 1. Scope

---

This Practice provides requirements for suppliers providing nickel and nickel alloy gate valves included in PIP Piping Line Class Material Specifications. This Practice provides the detailed purchase descriptions for nickel and nickel alloy gate valve tag numbers included in PIP Piping Material Specifications and used along with *PIP PNSM0110* for the procurement of valves. This Practice also provides a cross reference for nickel and nickel alloy gate valve tag numbers to applicable PIP Piping Material Specifications.

## 2. References

---

Applicable parts of the following Practice shall be considered an integral part of this Practice. The edition in effect on the date of contract award shall be used, except as otherwise noted. Short titles will be used herein where appropriate.

### 2.1 Process Industry Practices (PIP)

- PIP PNCM0004 - *Valve Commodity Codes Designation System*
- PIP PNC00005 - *Design of ASME B31.3 Metallic Piping Systems*
- PIP PNSM0110 - *Purchasing Requirements for Valves*

## 3. Valve Designation System

---

- 3.1 For a full explanation of the format used to structure the valve numbers listed within this Practice, refer to *PIP PNCM0004*. The first two characters in the valve tag numbers are GA.
- 3.2 The valves listed in Section 5 and Section 6 of this Practice are sorted by the unique valve tag number designation in ascending alphanumeric sequence (e.g., GA01NU500, GA03NU500).

## 4. Notes

---

- 4.1 Occasionally, valve size ranges listed in this Practice are broader than the size ranges shown for the same valves on a PIP Piping Material Specification. While the “most common practice” has been used to specify valve size ranges on Piping Material Specifications, a purchaser may need to utilize a valve in a size outside this “common practice” choice. Thus, for reference purposes, the full size range for which a given valve is typically manufactured is shown in this Practice.
- 4.2 Gear operation may be specified in either of the following ways:
  - a. Select a valve description that includes a gear operator
  - b. Select a valve description that includes a handwheel and use Field 5 (Owner Designation) of the valve tag numbering system described in *PIP PNCM0004*. For guidance, see *PIP PNC00005*, Section 3.5.5.2.