

RTCA, Inc.  
1140 Connecticut Avenue, NW, Suite 1020  
Washington, DC 20036-4001 USA

# **Environmental Conditions and Test Procedures for Airborne Equipment**

**Change 1**

RTCA EDO-160D Change 1  
December 14, 2000

Prepared by: SC-135  
© 2000 RTCA, Inc.

Copies of this document may be obtained from

RTCA, Inc.

Telephone: 202-833-9339

Facsimile: 202-833-9434

Internet: [www.rtca.org](http://www.rtca.org)

Please visit the RTCA Online Store for document pricing and ordering information.

### Change Transmittal

This change forwards revised text for Section 8.0 – Vibration, Section 20.0 – Radio Frequency Susceptibility (Radiated and Conducted) and Appendix C – Change Coordinators.

- Remove Section 8.0 (dated July 29, 1997) from RTCA/DO-160D and replace with the revised Section 8.0.
- Remove Section 20.0 (dated July 29, 1997) from RTCA/DO-160D and replace with the revised Section 20.0.
- Remove Appendix C (dated July 29, 1997) from RTCA/DO-160D and replace with the revised Appendix C.

This page intentionally left blank.

## **Section 8**

### **Vibration**

#### **Important Notice**

Information pertinent to this test procedure is contained in Sections 1, 2 and 3. Further, Appendix A is applicable for identifying the environmental tests performed.

	Page
8.0 VIBRATION.....	8-1
8.1 Purpose of the Tests.....	8-1
8.2 Applicability .....	8-1
8.2.1 Vibration Test Definitions .....	8-1
8.2.1.1 Standard Vibration Test.....	8-1
8.2.1.2 High Level-Short Duration Vibration Test.....	8-1
8.2.1.3 Robust Vibration Test.....	8-1
8.2.2 Category and Test Curve/Level Selection.....	8-1
8.2.2.1 Category Selection.....	8-1
8.2.2.2 Test Curves .....	8-2
8.3 Vibration Test Requirements.....	8-3
8.4 Vibration Test Level Requirements .....	8-4
8.4.1 Control Level Tolerance Requirements .....	8-4
8.4.1.1 Sinusoidal Control Input.....	8-4
8.4.1.2 Random Control Input .....	8-4
8.4.2 Measurement of Acceleration Power Spectral Density .....	8-4
8.4.2.1 Analog Analyzer Requirements.....	8-4
8.4.2.2 Digital Analyzer Requirements .....	8-5
8.5 Standard Vibration Test Procedure-Fixed Wing Aircraft .....	8-5
8.5.1 Sinusoidal Test Procedure.....	8-5
8.5.2 Random Test Procedure .....	8-6
8.6 High Level-Short Duration Vibration Test Procedure .....	8-6
8.7 Robust Vibration Test Procedure-Fixed-Wing Aircraft .....	8-6
8.7.1 Sinusoidal Test Procedure.....	8-6
8.7.2 Random Test Procedure .....	8-7
8.8 Vibration Test for Helicopters .....	8-8
8.8.1 Sine-on-Random Test Procedure – Known Helicopter Frequencies .....	8-8
8.8.1.1 Test Frequencies.....	8-8
8.8.1.2 Sine and Random Test Levels .....	8-8
8.8.1.3 Procedure .....	8-8
8.8.2 Sine on Random Test Procedures for Category U – Unknown Helicopter Frequencies .....	8-9

<u>Figure 8-1</u>	Standard Random Vibration Test Curves for Equipment Installed in Fixed-wing Aircraft with Turbojet or Turbofan Engines.....	8-12
<u>Figure 8-2</u>	Standard and Robust Sinusoidal Vibration Test Curves for Equipment Installed in Applicable Zones in Fixed-Wing Aircraft with Turbojet or Turbofan Engines and Unducted Fan Engines .....	8-13
<u>Figure 8-3</u>	Standard Sinusoidal Vibration Test Curves for Equipment Installed in Fixed-Wing Aircraft with Reciprocating or Turbopropeller Engines.....	8-14
<u>Figure 8-4</u>	Robust Random Vibration Test Curves for Equipment Installed in Fixed-Wing Aircraft with Turbojet or Turbofan Engines.....	8-15
<u>Figure 8-5</u>	High-Level Short Duration Sinusoidal Vibration Test Curves for Equipment Installed on Fixed-Wing Aircraft with Turbojet or Turbofan Engines.....	8-16
<u>Figure 8-6</u>	Sine-On-Random Vibration Test Curve for Helicopters .....	8-17
<u>Table 8-1</u>	Categorization and Vibration Tests by Aircraft Types and Equipment Locations.....	8-10
<u>Table 8-2a</u>	Sine-on-Random Vibration Test Frequencies for Helicopters .....	8-11
<u>Table 8-2b</u>	Sine-on-Random Vibration Test Levels for Helicopters .....	8-11

Currently in preview, click buy full version

This page intentionally left blank.

Currently in preview, click buy full version

## 8.0 VIBRATION

### 8.1 Purpose of the Tests

These tests demonstrate that the equipment complies with the applicable equipment performance standards when subjected to vibration levels specified for the appropriate category.

### 8.2 Applicability

Vibration tests apply to equipment installed on fixed-wing propeller aircraft, fixed-wing turbojet, turbofan, and propfan aircraft and helicopters.

Vibration tests to be performed on any equipment item are selected in this paragraph and are specified by three identifiers: (1) aircraft type, (2) category and (3) aircraft zone location. The test curves to be applied are then specified in paragraph 8.2.2. Requirements and procedures to accomplish these tests are specified in subsequent paragraphs herein.

#### 8.2.1 Vibration Test Definitions

##### 8.2.1.1 Standard Vibration Test

The standard vibration tests demonstrate that equipment will meet its functional performance requirements during normal operating conditions of the aircraft.

##### 8.2.1.2 High Level-Short Duration Vibration Test

High-level short duration transient vibration levels are encountered during abnormal aircraft vibration conditions that occur during blown tires and engine fan blade loss. This test should be applied to equipment in which a functional loss of performance can hazardously affect the aircraft's performance.

**CAUTION:** A full analysis of vibration levels related to some specific engine imbalance conditions has not been evaluated against these limits. Therefore this test alone may not be sufficient for some applications without additional test or analysis.

##### 8.2.1.3 Robust Vibration Test

The robust vibration test demonstrates that equipment will operate satisfactorily while subjected to a performance vibration level and continue to operate satisfactory when being subjected to an endurance vibration level. It combines a demonstration of the equipment functional performance and structural integrity. This test should be performed on all equipment where its resistance to effects of long duration exposure to vibration must be demonstrated. The necessity for conducting this test in lieu of the standard vibration test shall be determined by the relevant equipment specification.

#### 8.2.2 Category and Test Curve/Level Selection

##### 8.2.2.1 Category Selection

The appropriate test category selected for the equipment from the categories defined in Table 8-0 below, should be based upon the level of assurance required for the equipment's demonstration of performance. Categories denoted by the number two (2)