

RTCA, Inc.  
1828 L Street, NW, Suite 805  
Washington, DC 20036-5133 USA

# **Environmental Conditions and Test Procedures for Airborne Equipment**

**Change 3**

RTCA DO-160D Change 3  
January 5, 2002

Prepared by: SC-135  
© 2002 RTCA, Inc.

Copies of this document may be obtained from

RTCA, Inc.

Telephone: 202-633-9539

Facsimile: 202-822-9434

Internet: [www.rtca.org](http://www.rtca.org)

Please visit the RTCA Online Store for document pricing and ordering information.

### Change Transmittal

This change forwards revised text for Section 22.0 – Lightning Induced Transient Susceptibility and Appendix C – Change Coordinators.

- Remove Section 22.0 (dated July 29, 1997) from RTCA/DO-160D and replace with revised Section 22.0.
- Remove Appendix C (dated December 14, 2000) from RTCA/DO-160D and replace with the revised Appendix C.

This page intentionally left blank

## **Section 22**

# **Lightning Induced Transient Susceptibility**

### **Important Notice**

Information pertinent to this test procedure is contained in Sections 1, 2 and 3. Further, Appendix A is applicable for identifying the environmental tests performed.

<b>Table of Contents</b>		<b>Page</b>
22.0	Lightning Induced Transient Susceptibility.....	22-1
22.1	Purpose of Tests.....	22-1
22.2	Definitions.....	22-1
22.3	Categories.....	22-3
22.3.1	Waveform Set Designators (First and Third Characters).....	22-4
22.3.2	Test Level Designators (Second, Fourth and Fifth Characters).....	22-4
22.4	General Test Requirements.....	22-5
22.5	Test Procedures.....	22-8
22.5.1	Pin Injection Tests.....	22-8
22.5.1.1	Procedures - Generator Calibration.....	22-9
22.5.1.2	Procedures - Test Sequence.....	22-9
22.5.2	Cable Bundle Tests.....	22-10
22.5.2.1	Cable Induction Tests.....	22-10
22.5.2.1.1	Procedures - Generator Performance.....	22-10
22.5.2.1.2	Procedures - Test Sequence.....	22-10
22.5.2.2	Ground Injection.....	22-11
22.5.2.2.1	Procedures - Generator Performance Verification.....	22-12
22.5.2.2.2	Procedures - Test Sequence.....	22-12

<b>List of Tables</b>		<b>Page</b>
Table 22-1	Test Requirements.....	22-13
Table 22-2	Test Levels for Pin Injection.....	22-15
Table 22-3	Test Levels for Cable Bundles Single Stroke Tests.....	22-16
Table 22-4	Test Levels for Cable Bundle Multiple Stroke Tests.....	22-17
Table 22-5	Test Levels for Cable Bundle Multiple Burst Tests.....	22-18

<b>List of Figures</b>		<b>Page</b>
Figure 22-1	Installation Configuration - General Case.....	22-19
Figure 22-2	Current Waveform 1.....	22-20
Figure 22-3	Voltage Waveform 2.....	22-20
Figure 22-4	Voltage/Current Waveform 3.....	22-21
Figure 22-5	Voltage Waveform 4.....	22-21
Figure 22-6	Current/Voltage Waveform 5.....	22-22
Figure 22-7	Multiple Stroke Application.....	22-22
Figure 22-8	Multiple Burst Application.....	22-23
Figure 22-9	LISN Input Impedance Characteristic.....	22-24
Figure 22-10	Pin Injection Calibration Setup for Signal Pins.....	22-25
Figure 22-11	Pin Injection Calibration Setup, Power Pins – Cable Induction Method.....	22-26
Figure 22-12	Pin Injection Calibration Setup, Power Pins – Ground Injection Method.....	22-27
Figure 22-13	Pin Injection Test Setup, Signal Pins.....	22-28
Figure 22-14	Pin Injection Test Setup, Power Pins - Cable Induction Method.....	22-29
Figure 22-15	Pin Injection Test Setup, Power Pins - Ground Injection Method.....	22-30
Figure 22-16	Typical Generator Performance Verification Setup for Cable Induction Tests.....	22-31
Figure 22-17	Typical Cable Bundle Test Setup.....	22-32
Figure 22-18	Typical Generator Performance Verification Setup for Ground Injection Tests.....	22-33
Figure 22-19	Typical Ground Injection Test Set-up.....	22-34

## 22.0 Lightning Induced Transient Susceptibility

### 22.1 Purpose of Tests

These test methods and procedures apply idealized waveforms to verify the capability of equipment to withstand effects of lightning induced electrical transients. The criteria for equipment performance in the presence of lightning transients shall be defined in the applicable equipment specification.

Two groups of tests may be used for equipment qualification. The first is a damage tolerance test performed using pin injection as described in paragraph 22.5.1. The second group, as described in paragraph 22.5.2, evaluates the functional upset tolerance of equipment when transients are applied to interconnecting cable bundles. Cable bundle tests include single stroke, multiple stroke, and multiple burst, response tests (hereafter referred to as single stroke, multiple stroke and multiple burst). Cable bundle tests can also provide an indication of damage tolerance. The appropriate test group or groups will be defined in the applicable equipment specifications.

**Note:** These tests may not cover all aspects of lightning induced interaction and effects on equipment, particularly when incorporated into a system. Additional tests such as application of different waveforms, simultaneous cable bundle injection and multiple frequency, may be required to achieve certification of the equipment/system installation, depending upon the functions performed. Tests for the direct effects of lightning on equipment are covered in Section 23.0 of this document.

### 22.2 Definitions

#### Cable Bundle

A group of wires and/or cables bonded or routed together that connect two pieces of equipment.

#### Calibration Loop

A heavy duty, low self-inductance, low resistance, single turn wire loop passed through the injection transformer to form an insulated secondary winding. It should be low enough in impedance to achieve the test level and waveform.

#### Generator

A set of equipment (waveform synthesizer, amplifiers, couplers, etc.) that delivers a voltage or current waveform, via direct or indirect coupling to the equipment under test (EUT).

#### Local Ground

Any ground strap or conductor that is connected to the equipment and the same part of airframe structure to which that equipment is installed. The ground strap or conductor would therefore be bonded to the same ground plane that the equipment is mounted to and, during a lightning strike, would be at the same potential as the equipment.