

RTCA
1828 L Street, NW, Suite 805
Washington, DC 20036

**Minimum Performance Standards – Airborne Ground Proximity Warning
Equipment**

RTCA DO-161A
Revised May 27, 1976

Prepared by:
SC-128

Copies of this document may be obtained from

RTCA, Incorporated
1828 L Street, NW, Suite 805
Washington, D.C. 20036-5133 U.S.A.

Telephone: 202-833-9339

Facsimile: 202-833-9434

Internet: www.rtca.org

Please contact RTCA for price and ordering information.

F O R E W O R D

This Document was prepared by Special Committee 128 of the Radio Technical Commission for Aeronautics (RTCA). It was approved by RTCA on May 27, 1976.

RTCA is an association of aeronautical organizations of the United States from both government and industry. Dedicated to the advancement of aeronautics, RTCA seeks sound technical solutions to problems involving the application of electronics and telecommunications to aeronautical operations. Its objective is the resolution of such problems by mutual agreement of its member organizations.

The findings of RTCA are in the nature of recommendations to all organizations concerned. As RTCA is not an official agency of the Government of the United States, its recommendations may not be regarded as statements of official government policy unless so enunciated by the government organization or agency having statutory jurisdiction over any matters to which the recommendations relate.

THIS PAGE INTENTIONALLY LEFT BLANK

T A B L E O F C O N T E N T S

	<u>Page</u>
FOREWORD	i
INTRODUCTION	vii
1.0 GENERAL STANDARDS	1
1.1 Purpose of Equipment	1
1.2 Operation of Controls	1
1.3 Accessibility of Controls	1
1.4 Effects of Tests	1
1.5 Modes of Operation	1
1.6 Warning and Alert Indications	2
1.6.1 Aural Warning/Alert	2
1.6.2 Visual Warning Characteristics (Modes 1 through 4)	2
1.6.3 Emergency/Planned Abnormal Deactivation .	2
1.7 False Warnings	2
1.8 Failure Monitoring and Self-Test	2
2.0 MINIMUM PERFORMANCE STANDARDS UNDER STANDARD TEST CONDITIONS	3
2.1 Envelopes of Conditions for Warning	3
2.1.1 Excessive Rates of Descent With Respect To Terrain (Mode 1)	3
2.1.2 Excessive Closure Rate To Terrain (Mode 2)	3
2.1.3 Negative Climb Rate (Mode 3A) OR Altitude Loss (Mode 3B) Before Acquiring 700 Feet Terrain Clearance After Take-Off or Missed Approach	3
2.1.4 Flight Into Terrain With Less Than 500 Feet Terrain Clearance and Not in Landing Configuration (Mode 4)	4
2.2 Automatic Mode Selection	5
2.3 Characteristics of Warning Indications (Modes 1 through 4)	5
2.3.1 Aural Warning Characteristics	5

	<u>Page</u>
2.3.1.1 Speaker Output Level	5
2.3.1.2 Headset Output Level	5
2.3.2 Visual Warning	5
2.4 Deactivation Control	5
2.5 Failure Monitor and/or Self-Test	6
2.5.1 Failure Monitor	6
2.5.2 Self-Test	6
2.5.3 Failure Monitor and Self-Test	6
2.6 Glide Slope Deviation Alerting (Mode 5) ...	6
2.6.1 Envelope of Conditions for Alerting	6
2.6.2 Deactivation	7
2.6.3 Reactivation	7
2.6.4 Arming/Disarming	7
2.6.5 Glide Slope Mode Alert	7
3.0 MINIMUM PERFORMANCE STANDARDS UNDER ENVIRONMENTAL TEST CONDITIONS	9
3.1 Temperature and Altitude Test	10
3.1.1 Low Operating Temperature Test	9
3.1.2 High Operating Temperature Tests	9
3.1.3 Altitude Test	10
3.1.4 Decompression Test (When Required) .	10
3.1.5 Overpressure Test (When Required) ..	10
3.2 Temperature Variation Test	10
3.3 Humidity Test	11
3.4 Shock Tests	11
3.5 Vibration Test	11
3.6 Explosion Test (When Required)	12
3.7 Waterproofness (Drip Proof) Test (When Required)	12
3.8 Hydraulic Fluid Test (When Required)	12
3.9 Sand and Dust Test (When Required)	12
3.10 Fungus Resistance Test (When Required)	12
3.11 Salt Spray Test (When Required)	12
3.12 Magnetic Effect Test	12
3.13 Power Input Test	12
3.14 Voltage Spike Conducted Test	13
3.15 Audio-Frequency Conducted Susceptibility Test	14
3.16 Induced Signal Susceptibility Test	14
3.17 Radio-Frequency Susceptibility Test (Radiated and Conducted)	14
3.18 Emission of Radio Frequency Energy Test ...	14

MEMBERSHIP	15
APPENDIX A ENVELOPES OF CONDITIONS FOR WARNING FOR AIRBORNE GROUND PROXIMITY WARNING EQUIPMENT	
Mode 1	Envelope 1, Excessive Rate of Decent With Respect to Terrain 1
	Envelope 2, Excessive Rate of Descent With Respect to Terrain 2
	Envelope 3, Excessive Rate of Descent With Respect to Terrain 3
Mode 2A	Excessive Closure Rate to Terrain (Flaps Not In Landing Configuration) 4
Mode 2B	Excessive Closure Rate to Terrain (Landing Configuration) 5
Mode 3A	Negative Climb (Sink) Rate Acquiring 700 Feet Terrain Clearance After Take-off or Missed Approach 6
Mode 3B	Accumulated Altitude Loss Before Acquiring 700 Feet Terrain Clearance After Take-off or Missed Approach 7
Mode 4	Envelope 1, Flight Into Terrain With Less Than 500 Feet Terrain Clearance and Not in Landing Configuration .. 8
	Envelope 2, Flight Into Terrain With Less Than 500 Feet Terrain Clearance and Not in Landing Configuration .. 9
	Envelope 3, Flight Into Terrain With Less Than 500 Feet Terrain Clearance and Not In Landing Configuration .. 10
Mode 5	Glide Slope Deviation Alerting 11
APPENDIX B TEST PROCEDURES FOR AIRBORNE GROUND PROXIMITY WARNING EQUIPMENT	
PART I	DEFINITIONS OF TERMS AND CONDITIONS OF TEST 1
A	Power Input Voltage - Direct Current 1
B	Power Input Voltage - Alternating Current .. 1
C	Adjustment of Equipment 1
D	Test Instrument Precautions 1
E	Ambient Conditions 2
F	Warm-Up Period 2
G	Connected Loads 2
H	Special Purpose Test Set 2

	<u>Page</u>
<u>FIGURE 1</u> Special Purpose GPW Test Equipment	3
PART II DETAILED TEST PROCEDURES	5
T-1 MODE 1	5
T-2 MODE 2	5
MODE 2A	5
MODE 2B	6
T-3 MODE 3A	6
MODE 3B	7
T-4 MODE 4	7
T-5 Inhibit Altitude Test	8
T-6 Audio Output Test	8
MODES 1-4	9
MODE 5	9
T-7 MODE 5	10

I N T R O D U C T I O N

This Document sets forth Minimum Performance Standards for Airborne Ground Proximity Warning Equipment.

This revision of DO-161 includes Changes 1 and 2 to that Document, and also includes further changes that were suggested by operational experience. The Environmental Tests in this Document have been modified to reflect the requirements of RTCA Document DO-160, "Environmental Conditions and Test Procedures for Airborne Electronic/Electrical Equipment and Instruments".

Compliance with these standards by manufacturers and users is recommended as a means of assuring that the equipment will satisfactorily perform its intended function under all conditions normally encountered in routine aeronautical operations.

In any application of these minimum performance standards, due allowance should be made, where necessary, for equipments in current use which meet the intent of the standards contained herein.

It is recognized that any regulatory application of these standards is the responsibility of governmental agencies.

Inasmuch as the measured values of equipment performance characteristics may be a function of the method of measurement, standard test conditions and methods of test are also recommended in this Document.

The word "equipment" as used herein includes all of the components or units necessary (as determined by the equipment manufacturer) for the equipment to properly perform its intended function. For example, an Airborne Ground Proximity Warning "equipment" may include cockpit controls, an indicator, a computer unit, aural warning generator, a barometric rate computer, a shock mount, etc. In the case of this example, all of the foregoing components or units comprise the "equipment". It should not be inferred from this example, however, that every "equipment" will necessarily include all of the foregoing components. This will depend on the design used by the "equipment" manufacturer. The "equipment" need not include other sensor systems for which separate standards are applicable, e.g. Radio Altimeter.

THIS PAGE INTENTIONALLY LEFT BLANK

1.0 GENERAL STANDARDS

1.1 Purpose of Equipment

Ground Proximity Warning Equipment is an aid to aircrew for determining the imminent occurrence of inadvertent contact with the ground. It is intended to supplement flight instrument data from which this situation may be determined, annunciating the onset of the condition caused by excessive rate of descent, excessive closure rate to terrain, negative climb rate or altitude loss after take-off, flight into terrain when not in landing configuration and excessive downward deviation from an ILS glide slope.

1.2 Operation of Controls

The operation of controls intended for use during flight, in all possible combinations and sequences, shall not result in a condition whose presence or continuation would be detrimental to the continued performance of the equipment.

1.3 Accessibility of Controls

Controls which are not normally adjusted in flight shall not be readily accessible to flight personnel.

1.4 Effects of Tests

Unless otherwise provided, the application of the specified tests shall produce no subsequently discernible condition which would be detrimental to the continued performance of the equipment.

1.5 Modes of Operation

Ground Proximity Warning equipment shall provide indications of imminent inadvertent contact with the ground in the following modes of aircraft operation as further defined by this Minimum Performance Standard:

1. Excessive Rates of Descent
2. Excessive Closure Rate to Terrain
3. Negative Climb Rate or Altitude Loss After Take-Off
4. Flight Into Terrain When Not in Landing Configuration
5. Excessive Downward Deviation From an ILS Glide Slope