

RTCA, Inc.
1828 L Street, NW, Suite 805
Washington, DC 20036-5133 USA

**Minimum Performance Standards-Airborne HF
Radio Communications Transmitting and
Receiving Equipment Operating Within the
Radio-Frequency Range of 1.5 to 30 MHz**

RTCA DO-163
March 19, 1976

Prepared by: SC-131
© RTCA, Inc.

Copies of this document may be obtained from

RTCA, Inc.

Telephone: 202-833-0339

Facsimile: 202-833-9434

Internet: www.rtca.org

Please visit the RTCA Online Store for document pricing and ordering information.

F O R E W O R D

This Document was prepared by Special Committee 131 of the Radio Technical Commission for Aeronautics (RTCA). It was approved by RTCA on March 19, 1976.

RTCA is an association of aeronautical organizations of the United States from both government and industry. Dedicated to the advancement of aeronautics, RTCA seeks sound technical solutions to problems involving the application of electronics and telecommunications to aeronautical operations. Its objective is the resolution of such problems by mutual agreement of its member organizations.

The findings of RTCA are in the nature of recommendations to all organizations concerned. As RTCA is not an official agency of the Government of the United States, its recommendations may not be regarded as statements of official government policy unless so enunciated by the government organization or agency having statutory jurisdiction over any matters to which the recommendations relate.

THIS PAGE INTENTIONALLY LEFT BLANK

T A B L E O F C O N T E N T S

	<u>Page</u>
FOREWORD	i
INTRODUCTION	ix
 <u>SECTION ONE - TRANSMITTERS</u>	
1.0 GENERAL STANDARDS	1
1.1 Operation of Controls	1
1.2 Accessibility of Controls	1
1.3 Effects of Test	1
2.0 MINIMUM PERFORMANCE STANDARDS UNDER STANDARD CONDITIONS	3
2.1 Rated Power Output	3
2.2 Residual Radiation	3
2.3 Spectrum Control	3
2.4 Audio Distortion	4
2.5 Audio Frequency Response	4
2.6 Sidetone	4
2.7 Noise Level	4
2.8 Overmodulation Protection	4
2.9 Carrier Suppression	5
2.10 Frequency Stability	5
2.11 AM Equivalent Mode	5
2.12 Channel Selection Time	5
2.13 Antenna Coupling Circuits and Units	5
3.0 MINIMUM PERFORMANCE STANDARDS UNDER ENVIRON- MENTAL TEST CONDITIONS	7
3.1 Temperature and Altitude Tests (Paragraph 4.0, DO-160)	7
3.1.1 Low Operating Temperature Test	7
3.1.2 High Operating Temperature Tests ..	7
3.1.3 Altitude Test	7
3.1.4 Decompression Test (When Required)..	8
3.1.5 Overpressure Test (When Required)..	8
3.1 Temperature Variation Test (Paragraph 5.0, DO-160).....	8

	<u>Page</u>
3.3 Humidity Test (Paragraph 6.0, DO-160)...	8
3.4 Shock Tests (Paragraph 7.0, DO-160)	8
3.5 Vibration Test (Paragraph 8.0, DO-160) .	9
3.6 Explosion Test (When Required) (Paragraph 9.0, DO-160).....	9
3.7 Waterproofness (Drip Proof) Test (When Required) (Paragraph 10.0, DO-160)	9
3.8 Hydraulic Fluid Test (When Required) Paragraph 11.0, DO-160)	9
3.9 Sand and Dust Test (When Required) (Paragraph 12.0, DO-160)	9
3.10 Fungus Resistance Test (When Required) (Paragraph 13.0, DO-160)	9
3.11 Salt Spray Test (When Required) (Paragraph 14.0, DO-160)	10
3.12 Magnetic Effect Test (Paragraph 15.0, DO-160)	10
3.13 Power Input Tests (Paragraph 16.0, DO-160)	10
3.13.1 Normal Operating Conditions...	10
3.13.2 Abnormal Operating Conditions..	10
3.14 Voltage Spike Conducted Test (Paragraph 17, DO-160)	11
3.15 Audio Frequency Conducted Susceptibility Test (Paragraph 18.0, DO-160).....	11
3.16 Induced Signal Susceptibility Test (Paragraph 19.0, DO-160)	11
3.17 Radio Frequency Susceptibility Test (Radiated and Conducted) (Paragraph 20.0 DO-160)	11
3.18 Emission of Radio Frequency Energy Test (Paragraph 21.0, DO-160)	11

SECTION TWO - RECEIVERS

1.0 GENERAL STANDARDS	1
1.1 Operation of Controls	1
1.2 Accessibility of Controls	1
1.3 Effects of Test	1
2.0 MINIMUM PERFORMANCE STANDARDS UNDER STANDARD CONDITIONS	3
2.1 AGC Characteristics	3
2.1.1 Audio Variation	3
2.1.2 Attack Time	3
2.1.3 Decay Time	3

	<u>Page</u>	
2.2	Gain	3
2.3	Manual Gain Control	3
2.4	Distortion	3
	2.4.1 Intermodulation Distortion	3
	2.4.2 Harmonic Distortion	4
2.5	Hum and Noise Level	4
2.6	Sensitivity	4
2.7	Selectivity	4
	2.7.1 SSB Selectivity.....	4
	2.7.2 AM Selectivity	5
2.8	Spurious Responses	5
2.9	Cross Modulation	5
2.10	Desensitization	5
2.11	Frequency Stability	6
2.12	Channel Selection Time	6
3.0	MINIMUM PERFORMANCE STANDARDS UNDER ENVIRONMENTAL TEST CONDITIONS, HF/SSB RECEIVERS	7
3.1	Temperature and Altitude Tests (Paragraph 4.0, DO-160)	7
	3.1.1 Low Operating Temperature Test .	7
	3.1.2 High Operating Temperature Tests	7
	3.1.3 Altitude Test	7
	3.1.4 Decompression Test (When Required)	8
	3.1.5 Overpressure Test (When Required)	8
3.2	Temperature Variation Test (Paragraph 5.0, DO-160)	8
3.3	Humidity Test (Paragraph 6.0, DO-160)...	8
3.4	Shock Tests (Paragraph 7.0, DO-160)	8
3.5	Vibration Test (Paragraph 8.0, DO-160)..	9
3.6	Explosion Test (When Required) (Paragraph 9.0, DO-160)	9
3.7	Waterproofness (Drip Proof) Test (When Required) (Paragraph 10.0, DO-160).....	9
3.8	Hydraulic Fluid Test (When Required) (Paragraph 12.0, DO-160)	9
3.9	Sand and Dust Test (When Required) (Paragraph 12.0, DO-160)	9
3.10	Fungus Resistance Tests (When Required) (Paragraph 13, DO-160)	9

	<u>Page</u>
3.11 Salt Spray Test (When Required) (Paragraph 14.0, DO-160)	10
3.12 Magnetic Effect Test (Paragraph 15.0, DO-160)	10
3.13 Power Input Tests (Paragraph 16.0, DO-160)	10
3.13.1 Normal Operating Conditions	10
3.13.2 Abnormal Operating Conditions ..	10
3.14 Voltage Spike Conducted Test (Paragraph 17, DO-160)	11
3.15 Audio Frequency Conducted Susceptibility Test (Paragraph 18.0, DO-160)	11
3.16 Induced Signal Susceptibility Test (Paragraph 19.0, DO-160)	11
3.17 Radio Frequency Susceptibility Test (Radiated and Conducted) (Paragraph 20.0, DO-160)	11
3.18 Emission of Radio Frequency Energy Test (Paragraph 21.0, DO-160)	11
MEMBERSHIP	13
 APPENDIX A - TEST PROCEDURES - TRANSMITTERS	
PART I - DEFINITIONS OF TERMS AND CONDITIONS OF TEST	
	1
A. Power Input Voltage	1
B. Power Input Frequency	1
C. Adjustment of Equipment	1
D. Test Equipment Precautions	1
E. Antenna Accessories	2
F. Ambient Conditions	2
G. Warm-Up Period	2
H. Standard Transmitter Load	2
I. Phantom Microphone	2
J. Single Sideband	2
K. Standard Two-Tone Test Signal	3
 PART II - DETAILED TEST PROCEDURES	
T-1 Rated Power Output	5
T-2 Residual Radiation	6
T-3 Spectrum Control	6
T-4 Audio Distortion	7
T-5 Audio Frequency Response	7
T-6 Sidetone	7
T-7 Noise Levels	8

	<u>Page</u>
T-8 Overmodulation	9
T-9 Carrier Suppression	9
T-10 Frequency Stability	9
T-11 AM Equivalent Mode	10
FIGURE 1	11
FIGURE 2	12
FIGURE 3	13
FIGURE 4	14
 APPENDIX B - TEST PROCEDURES - RECEIVERS	
PART I - DEFINITION OF TERMS AND CONDITIONS OF TEST	
	1
A. Power Input Voltage	1
B. Power Input Frequency	1
C. Adjustment of Equipment	1
D. Test Equipment Precautions	1
E. Ambient Conditions	2
F. Warm-Up Period	2
G. Connected Load	2
H. Signal Source	2
I. Standard Test Signals	3
J. Single Sideband	3
K. Center Response Frequency	4
 PART II - DETAILED TEST PROCEDURES	
	5
T-1 AGC Characteristics	5
T-2 Gain	6
T-3 Manual Gain Control	6
T-4 Distortion	6
T-5 Hum and Noise Level	7
T-6 Sensitivity	8
T-7 Selectivity	9
T-8 Spurious Responses	9
T-9 Cross Modulation	10
T-10 Desensitization	11
T-11 Frequency Stability	12

THIS PAGE INTENTIONALLY LEFT BLANK

I N T R O D U C T I O N

This Document sets forth Minimum Performance Standards for airborne radio communications transmitting and receiving equipment operating within the radio-frequency range of 1.5 MHz to 30 MHz.

Compliance with these standards by manufacturers and users is recommended as a means of assuring that the equipment will satisfactorily perform its intended function under all conditions normally encountered in routine aeronautical operations.

In any application of these minimum performance standards, due allowance should be made, where necessary, for equipments in current use which do not fully meet the standards contained herein.

It is recognized that any regulatory application of these standards is the responsibility of governmental agencies.

Inasmuch as the measured values of radio equipment performance characteristics may be a function of the method of measurement, standard test conditions and methods of test are also recommended in this Document.

The word "equipment" as used in this Document includes all of the components or units necessary (as determined by the equipment manufacturer) for the equipment to properly perform its intended function. For example, HF "equipment" may include an antenna and coupler, a transmitter unit, a control box, a power supply, a shock mount, etc. In the case of this example, all of the foregoing components or units comprise the "equipment." It should not be inferred from this example, however, that every HF "equipment" will necessarily include all of the foregoing components. This will depend on the design used by the "equipment" manufacturer.

THIS PAGE INTENTIONALLY LEFT BLANK

S E C T I O N O N E

TRANSMITTERS

THIS PAGE INTENTIONALLY LEFT BLANK

MINIMUM PERFORMANCE STANDARDS -
AIRBORNE HIGH FREQUENCY RADIO COMMUNICATIONS
TRANSMITTING EQUIPMENT OPERATING WITHIN THE
RADIO FREQUENCY RANGE OF 1.5 TO 30 MEGAHERTZ

1.0 GENERAL STANDARDS

1.1 Operation of Controls

The operation of controls intended for use during flight, in all possible combinations and sequences, shall not result in a condition whose presence or continuation would be detrimental to the continued performance of the equipment.

1.2 Accessibility of Controls

Controls which are not normally adjusted in flight shall not be readily accessibly to flight personnel.

1.3 Effects of Test

Unless otherwise provided, the design of the equipment shall be such that, subsequent to the application of the specified tests, no discernible condition exists which would be detrimental to the continued performance of the equipment.