

RTCA, Inc.
1150 18th Street, NW, Suite 910
Washington, DC 20036 USA

**MINIMUM OPERATIONAL PERFORMANCE STANDARDS
FOR AIR TRAFFIC CONTROL RADAR BEACON
SYSTEM/MODE SELECT (ATCRBS/MODE S)
AIRBORNE EQUIPMENT**

RTCA DO-181F
December 17, 2020
DO-181F supersedes DO-181E

Prepared by SC-209
© 2020, RTCA, Inc.

RTCA, Inc.
1150 18th Street, NW, Suite 910
Washington, DC 20036 USA

Telephone: 202-833-9339
Facsimile: 202-833-9434
Internet: <http://www.rca.com>

FOREWORD

RTCA, Incorporated is a not-for-profit corporation formed to advance the art and science of aviation and aviation electronic systems for the benefit of the public. The organization functions as a Standards Development Organization (SDO) and develops consensus based recommendations on contemporary aviation issues. RTCA's objectives include but are not limited to:

- coalescing aviation system user and provider technical requirements in a manner that helps government and industry meet their mutual objectives and responsibilities;
- analyzing and recommending solutions to the system technical issues that aviation faces as it continues to pursue increased safety, system capacity and efficiency;
- developing consensus on the application of pertinent technology to fulfill user and provider requirements, including development of minimum operational performance standards for electronic systems and equipment that support aviation; and
- assisting in developing the appropriate technical material upon which positions for the International Civil Aviation Organization (ICAO), the International Telecommunication Union (ITU) and other appropriate international organizations can be based.

The organization's recommendations are often used as the basis for government and private sector decisions as well as the foundation for many Federal Aviation Administration Technical Standard Orders.

Since RTCA is not an official agency of the United States Government, its recommendations may not be regarded as statements of official government policy unless so enunciated by the U.S. government organization or agency having statutory jurisdiction over any matters to which the recommendations relate.

This Page Intentionally Left Blank.

Currently in preview, click buy full version

TABLE OF CONTENTS

1	PURPOSE AND SCOPE	1
1.1	Introduction	1
1.2	System Overview	2
1.2.1	The Function of Mode S.....	2
1.2.2	Major Operating Characteristics.....	2
1.2.3	System Performance.....	3
1.2.4	Basic System Protocol.....	3
1.2.5	Mode S Message Content.....	4
1.3	Operational Goals.....	5
1.4	Operational Applications.....	5
1.4.1	The ATRBS Environment	5
1.4.2	The Mode S Environment	6
1.4.3	Mode S Transponder Levels.....	6
1.4.4	Additional/Specific Features	9
1.4.5	Minimum Output Power Level Designation	10
1.4.6	Transponder Labeling.....	10
1.4.7	Airborne Equipment	11
1.5	Assumptions	11
1.6	Test Procedures	11
1.6.1	Environmental Tests.....	12
1.6.2	Detailed Test Procedures.....	12
1.6.3	Installed System Tests.....	12
1.7	Definitions of Key Acronyms and Terms	13
1.8	Mode S Specific Services.....	13
1.9	Aircraft Equipment Information Vulnerabilities	13
1.10	Additional Information.....	14
2	MODE S TRANSPONDER EQUIPMENT PERFORMANCE REQUIREMENTS AND TEST PROCEDURES.....	15
2.1	General Requirements for All Equipment.....	15
2.1.1	Airworthiness	15
2.1.2	General Performance.....	15
2.1.3	Communications Regulations.....	15
2.1.4	Fire Protection	15
2.1.5	Operation of Controls.....	15
2.1.6	Accessibility of Controls	16
2.1.7	Flight Crew Control Functions.....	16
2.1.8	Optional Crew Control Functions	16
2.1.9	Effects of Tests.....	16
2.1.10	Equipment Configuration.....	17
2.1.11	Interrogation Signals	17
2.2	Minimum Performance Standards — Standard Conditions and Signals.....	22
2.2.1	Definition of Standard Conditions	22
2.2.2	Receiver Characteristics	22
2.2.3	Transmitter Characteristics.....	24

2.2.4	Reply Pulse Characteristics	27
2.2.5	Side Lobe Suppression Characteristics	33
2.2.6	Pulse Decoder Characteristics	35
2.2.7	Desensitization and Recovery Characteristics.....	36
2.2.8	Response in the Presence of Interference.....	39
2.2.9	Undesired Replies.....	41
2.2.10	Self Test and Monitor(s).....	42
2.2.11	Response to Mutual Suppression Pulses	43
2.2.12	Diversity Operations.....	43
2.2.13	Data Handling and Interfaces	45
2.2.14	Description of the Mode S Signal Format.....	51
2.2.15	Antenna	59
2.2.16	Power Interruption.....	65
2.2.17	Mode S Transponders.....	70
2.2.18	Level 2 Transponder – Surveillance Function.....	71
2.2.19	Level 2 Transponder – Datalink Function.....	83
2.2.20	Level 3 & Level 4 Transponder – Extended Length Message (ELM) Protocol.....	109
2.2.21	Level 5 Transponder – Enhanced Protocols.....	121
2.2.22	CAS-Compatible Mode S Transponder.....	131
2.2.23	Extended Squitter (ES).....	145
2.2.24	Elementary Surveillance Compliant Transponder.....	146
2.2.25	Enhanced Surveillance Compliant Transponders.....	156
2.2.26	Generic Register XX ₁₆ Requirements.....	175
2.2.27	Basic Dataflash.....	177
2.2.28	Phase Overlay.....	184
2.2.29	Air-Air Application Data.....	185
2.3	Equipment Performance – Environmental Conditions.....	187
2.3.1	Environmental Test Conditions.....	187
2.3.2	Detailed Environmental Test Procedures.....	189
2.4	Equipment Test Procedures.....	207
2.4.1	Definitions of Terms and Conditions of Test.....	207
2.4.2	Detailed Test Procedures.....	210
2.5	Test Procedures for the Surveillance and Communications Protocols.....	251
2.5.1	Introduction	251
2.5.2	Required Test Equipment.....	253
2.5.3	Selection and Use of the Test Procedures	254
2.5.4	Test Procedures	255
2.6	Test Procedures for Elementary Surveillance (ELS) Compliant Transponder (§2.2.24).....	353
2.6.1	Ground Initiated Comm-B (§2.2.19.1.12.3).....	353
2.6.2	Surveillance Identifier (“SI”) Code Requirements (§2.2.24.2 and §2.2.24.2.1).....	354
2.6.3	Declaration of Capability in Register 10 ₁₆ – Data Link Capability Report (§2.2.24.3).....	354
2.6.4	Register 17 ₁₆ Common Usage GICB Capability Report (§2.2.24.4).....	356
2.6.5	Register 18 ₁₆ to 1C ₁₆ , Mode S Specific Services Capability Reports (§2.2.24.5).....	357
2.6.6	Baseline Aircraft Identification and Aircraft Registration Testing (§2.2.24.6).....	361
2.7	Test Procedures for Enhanced Surveillance (EHS) Compliant Transponder (§2.2.25).....	396
2.7.1	Register 10 ₁₆ – Data Link Capability Report (§2.2.25.1).....	396
2.7.2	Register 17 ₁₆ ---Common Usage GICB Capability Report (§2.2.25.2).....	398
2.7.3	Register 18 ₁₆ to 1C ₁₆ , Mode S Specific Services Capability Reports (§2.2.25.3).....	401
2.7.4	Register 1D ₁₆ to 1F ₁₆ Mode S Specific Services MSP Capability (§2.2.25.4).....	404
2.7.5	Register 40 ₁₆ – Selected Vertical Intention (§2.2.25.5).....	406
2.7.6	Register 50 ₁₆ – Protocol and Interface (§2.2.25.6).....	437

2.7.7	Register 60 ₁₆ – Protocol and Interface (§2.2.25.8)	463
2.8	Generic Register XX Test Procedures (§2.2.26)	492
2.8.1	Purpose and Definition (§2.2.26.1)	492
2.8.2	Data Requirement (§2.2.26.2)	492
2.8.3	Update Rate (§2.2.26.3)	493
2.8.4	Service Reporting (§2.2.26.4)	493
2.8.5	Register XX ₁₆ – Repeat §2.8.1 through §2.8.4 using Extended Data Source Extraction with “DI” = 3 (§2.2.26)	494
2.9	Test Procedures for Basic Dataflash Compliant Transponder (§2.2.27).....	494
2.9.1	Basic Dataflash Capability (§2.2.27.1).....	495
2.9.2	Basic Dataflash Register in Not Monitored State (§2.2.27.3.a)	495
2.9.3	Basic Dataflash Register Monitored State (§2.2.27.3.b)	499
2.9.4	Basic Dataflash Register First Change of Data (§2.2.27.4.b).....	518
2.9.5	Basic Dataflash Register Next Change of Data (§2.2.27.4.c)	534
2.9.6	Basic Dataflash Register Subsequent Change of Data (§2.2.27.4.b, d and e).....	537
2.9.7	Verification of "Test Timer #2 (§2.2.27.5.a.2).....	540
2.9.8	Return to Not Monitored State (§2.2.27.4.f)	543
3	INSTALLED EQUIPMENT PERFORMANCE.....	547
3.1	Equipment Installation	547
3.1.1	Equipment Accessibility.....	547
3.1.2	Inadvertent Turn Off	547
3.1.3	Displays.....	547
3.1.4	Aircraft Power Source.....	547
3.1.5	Antenna Pattern and Transmission Line(s)	547
3.1.6	Antenna Location	547
3.1.7	Mutual Suppression.....	548
3.2	Conditions of Test	548
3.2.1	Power Input	548
3.2.2	Interference Effects	548
3.2.3	Environment	549
3.2.4	Adjustment of Equipment	549
3.2.5	Warm-up Period.....	549
3.3	Test Procedures for Installed Equipment Performance	549
3.3.1	Conformity Inspection	549
3.3.2	Bench Tests	549
3.3.3	Reply Frequency	549
3.3.4	Framing Pulse Spacing.....	550
3.3.5	Reply Codes	550
3.3.6	Pressure Altitude Transmissions	550
3.3.7	Altitude Reporting Test.....	551
3.3.8	Reply Pulse Width.....	551
3.3.9	Receiver Sensitivity.....	551
3.3.10	Transmitter Power Output	551
3.3.11	Mode S Address	551
3.3.12	Received Reply.....	551
3.3.13	Airspeed Fixed Field	552
3.3.14	Airborne and On-the-Ground Condition	552
3.3.15	Diversity Antenna Installations	552

4	MEMBERSHIP	553
	APPENDIX A ACRONYMS & DEFINITION OF TERMS.....	A-1
A.1	Acronyms	A-1
A.2	Definition of Terms	A-7
	APPENDIX B AIRCRAFT REGISTER FORMATS	B-1
B.1	Introduction	B-1
B.2	Data Formats for Transponder Registers.....	B-1
B.2.1	Register Allocation.....	B-1
B.2.2	General Conventions on Data Formats.....	B-2
B.3	BDS Register Formats.....	B-5-7
B.4	Implementation Guidelines	B-58
B.4.1	Transponder Register 10 ₁₆	B-58
B.4.2	Transponder Registers 18 ₁₆ to 1C ₁₆	B-63
B.4.3	Transponder Register 20 ₁₆	B-63
B.4.4	Transponder Register 40 ₁₆	B-64
B.4.5	Transponder Register 50 ₁₆	B-79
B.4.6	Transponder Register 60 ₁₆	B-81
	APPENDIX C MODE S SPECIFIC SERVICES (MSSS)	C-1
C.1	Introduction	C-1
C.1.1	Purpose	C-1
C.1.2	Scope	C-1
C.1.3	Mode S Application Entity (AE) / Transponder Interface Management.....	C-1
C.2	Design Requirements	C-1
C.2.1	Basic Operations.....	C-1
C.2.2	Mode S Specific Services Entity (SSE) Interface Requirements	C-2
C.3	Mode S Specific Services Test Procedures	C-14
C.3.1	General Characteristics.....	C-14
C.3.2	Detailed Test Procedures.....	C-15
	APPENDIX D FOR THE POTENTIAL ADDITION OF HIJACK MODE OPERATIONS	
	D-1	
D.1	Potential Changes from DO-181D	D-1
	APPENDIX E BASIC DATAFLASH OPERATION.....	E-1
E.1	Introduction	E-1
E.2	Explanation of Basic Dataflash Operation	E-1
E.3	Example of Basic Dataflash Operation	E-2
E.4	Timing Associated With Basic Dataflash.....	E-4
	APPENDIX F INTERROGATION/REPLY MONITOR (IRM) APPLICATION.....	F-1
F.1	Purpose	F-1
F.2	Design Requirements	F-2

F.2.1	Register 66 ₁₆ – IRM Interrogation Rate Monitor Message	F-2
F.2.2	Register 67 ₁₆ – IRM Reply Rate Monitor Message.....	F-8
F.2.3	IRM Phase Overlay Interrogation Rate Monitor Message Data Requirements	F-15
F.2.4	IRM Phase Overlay Reply Rate Monitor Message Data Requirements.....	F-19
F.2.5	Maximum Update Interval of Register 66 ₁₆ and Register 67 ₁₆	F-22
F.2.6	Phase Overlay Message Data Timeout.....	F-23
F.2.7	Extended Squitter Type.....	F-23
F.3	Test Procedures	F-23
F.3.1	Register 66 ₁₆ – IRM Interrogation Rate Monitor Message	F-24
F.3.2	Register 67 ₁₆ – IRM Reply Rate Monitor Message.....	F-26
F.3.3	IRM Phase Overlay Interrogation Rate Monitor Message Data Requirements	F-30
F.3.4	IRM Phase Overlay Reply Rate Monitor Message Data Requirements.....	F-31
F.3.5	Squitter Rates (§F.2.5).....	F-32
F.3.6	Update Rate (§F.2.5)	F-33

APPENDIX G COMMITMENT TO LICENSE PHASE OVERLAY TECHNOLOGY G-1

List of Figures

Figure 2-1: General Pulse Patterns for PAM Interrogations	19
Figure 2-2: General Pulse Pattern for DPSK Interrogations	20
Figure 2-3: Unwanted Output Power	25
Figure 2-4: Mode S Reply Waveform	29
Figure 2-5: Spectrum Limits for Mode S Transponder Transmitter.....	30
Figure 2-6: PPM Data Interval	32
Figure 2-7: Overview of Mode S Interrogation Formats.....	52
Figure 2-8: Overview of Mode S Reply Formats	53
Figure 2-9: Field Index.....	55
Figure 2-10: Level 2 Transponder: Surveillance Function Uplink Formats.....	61
Figure 2-11: Level 2 Transponder: Surveillance Function Downlink Formats.....	71
Figure 2-12: Functional Diagram of Uplink Coding	74
Figure 2-13: Functional Diagram of Downlink Coding	75
Figure 2-14: The Level 2 Transponder: Surveillance Interrogation Acceptance	76
Figure 2-15: All Transponders: Lockout Initiation	79
Figure 2-16: All Level 2 Transponders: Formats	88
Figure 2-17: Level 2 Transponders: Interrogation Acceptance.....	89
Figure 2-18: All Level 2 Transponders: Coordination	90
Figure 2-19: All Transponders: FS and VS Protocol	91
Figure 2-20: All Transponders: Reply Content	92
Figure 2-21: All Level 2 Transponders: UM Protocol	93
Figure 2-22: All Data Link Transponders: B-Protocol.....	94
Figure 2-23: Comm-C Reservation and Closeout	112
Figure 2-24: Comm-C Message Handling	113
Figure 2-25: Comm-D Reservation and Closeout.....	116
Figure 2-26: Comm-D Message Handling	117
Figure 2-27: Enhanced Comm-B Protocol.....	124
Figure 2-28: Enhanced Comm-B Protocol (Continued).....	125
Figure 2-29: Enhanced Comm-C Reservation and Closeout.....	126
Figure 2-30: Enhanced Comm-C Message Handling.....	127
Figure 2-31: Enhanced Comm-D Reservation and Closeout	129
Figure 2-32: Enhanced Comm-D Message Handling.....	130
Figure 2-33: Register 20 ₁₆ Data Processing.....	153
Figure 2-34: Basic Data Link Process Flow.....	178
Figure 2-35: Phase Overlay Transmitter Test Setup	191
Figure 2-36: Test Equipment Connection	192
Figure 2-37: Test Equipment Connection	196
Figure 2-38: Test Equipment Connection	197
Figure 2-39: Test Equipment Connection	210
Figure 2-40: Test Equipment Connection	213
Figure 2-41: Test Equipment Connection	215
Figure 2-42: Test Equipment Connection	217
Figure 2-43: Phase Overlay Transmitter Test Setup	220
Figure 2-44: Test Equipment Connection	237
Figure 2-45: Test Equipment Connection	239
Figure B-4-1: Aircraft Flight Path.....	B-65
Figure B-4-2: General Example for the Loading of Data in Register 40 ₁₆	B-75
Figure C-2-1: Mode S Specific Services Architecture	C-3

Figure C-2-2: The SD Field Structure	C-9
Figure C-3-1: Mode S Specific Services Test Configuration.....	C-15
Figure E-1: Basic Dataflash standalone change – single extraction.....	E-5
Figure E-2: Basic Dataflash combined changes – single extraction.....	E-6
Figure E-3: Basic Dataflash multiple changes – multiple extraction	E-7
Figure E-4: Basic Dataflash combined changes – multiple extraction.....	E-8

List of Tables

Table 1-1: Transponder Optional Additional Features.....	10
Table 2-1: Timer Characteristics.....	76
Table 2-2: Level 2 Transponder Compliance Matrix.....	85
Table 2-3: Mode S Subnetwork Version Number Encoding.....	97
Table 2-4: Uplink ELM Average Throughput Capability Encoding.....	98
Table 2-5: Downlink ELM Throughput Capability Encoding.....	98
Table 2-6: CAS Versions.....	131
Table 2-7: Status of MCP/FCU Mode Bits (Bit 48) Encoding.....	167
Table 2-8: Vertical Navigation Mode (Bit 49) Encoding.....	167
Table 2-9: Altitude Hold Mode (Bit 50) Encoding.....	168
Table 2-10: Approach Mode (Bit 51) Encoding.....	168
Table 2-11: Status of Target Altitude Source Bits (Bit 54) Encoding.....	168
Table 2-12: Target Altitude Source (Bit 55, 56) Encoding.....	169
Table 2-13: PO Message Subtype.....	185
Table 2-14: Environmental Test Groups.....	188
Table 2-15: Performance Test Requirements During Environmental Tests.....	189
Table 2-16: Barometric Altitude Data Inputs.....	282
Table B-2-1: GICB Register Number Assignments.....	B-1
Table B-2-2: 6-Bit Subset of International Alphabet Number (IA-5) for Character Coding.....	B-7
Table B-3-16a: BDS Code 1,0 – Data Link Capability Report (§2.2.19.1.12.6).....	B-10
Table B-3-16b: BDS Code 1,0 – Default Phase Overlay Data-Block.....	B-12
Table B-3-17: BDS Code 1,1 – Data Link Capability Report (extension).....	B-14
Table B-3-23: BDS Code 1,7 – Common Usage GICB Capability Report.....	B-15
Table B-3-24: BDS Code 1,8 – MSSS GICB Capability Report (1 of 5).....	B-16
Table B-3-25: BDS Code 1,9 – MSSS GICB Capability Report (2 of 5).....	B-17
Table B-3-26: BDS Code 1,A – MSSS GICB Capability Report (3 of 5).....	B-18
Table B-3-27: BDS Code 1,B – MSSS GICB Capability Report (4 of 5).....	B-19
Table B-3-28: BDS Code 1,C – MSSS GICB Capability Report (5 of 5).....	B-20
Table B-3-29: BDS Code 1,D – MSSS MSP Capability Report (1 of 3).....	B-21
Table B-3-30: BDS Code 1,E – MSSS MSP Capability Report (2 of 3).....	B-22
Table B-3-31: BDS Code 1,F – MSSS MSP Capability Report (3 of 3).....	B-23
Table B-3-32: BDS Code 2,0 – Aircraft Identification (§2.2.19.1.13).....	B-24
Table B-3-33: BDS Code 2,1 – Aircraft and Airline Registration Markings.....	B-25
Table B-3-37: BDS Code 2,5 – Aircraft Type.....	B-26
Table B-3-48a: BDS Code 3,0 – CAS Active Resolution Advisory.....	B-27
Table B-3-48b: BDS Code 3,0 – Default Phase Overlay Data-Block.....	B-28
Table B-3-49: BDS Code 3,1 – CAS Active Resolution Advisory (Part 2).....	B-30
Table B-3-51 to B-3-55: BDS Codes 3,3 to 3,7 – ACAS X Operational Coordination Message. B-31	
Table B-3-64a: BDS Code 4,0 – Selected Vertical Intention.....	B-32
Table B-3-64b: BDS Code 4,0 – Default Phase Overlay Data-Block.....	B-33
Table B-3-65: BDS Code 4,1 – Next Waypoint Details.....	B-35
Table B-3-66: BDS Code 4,2 – Next Waypoint Details.....	B-36
Table B-3-67: BDS Code 4,3 – Next Waypoint Details.....	B-37
Table B-3-72: BDS Code 4,8 – VHF Channel Report.....	B-38
Table B-3-80a: BDS Code 5,0 – Track and Turn Report.....	B-39
Table B-3-80b: BDS Code 5,0 – Default Phase Overlay Data-Block.....	B-40
Table B-3-81: BDS Code 5,1 – Position Report Coarse.....	B-42

Table B-3-82: BDS Code 5,2 – Position Report Fine	B-43
Table B-3-83: BDS Code 5,3 – Air-Referenced State Vector.....	B-44
Table B-3-84 to B-3-86: BDS Codes 5,4 to 5,6 – Waypoints 1, 2 and 3	B-45
Table B-3-96a: BDS Code 6,0 – Heading and Speed Report.....	B-46
Table B-3-96b: BDS Code 6,0 – Default Phase Overlay Data-Block.....	B-47
Table B-3-102: BDS Code 6,6 – IRM - Interrogation Rate Monitor Message	B-49
Table B-3-103: BDS Code 6,7 – IRM - Reply Rate Monitor Message.....	B-50
Table B-3-113: BDS Code 7,1 – Interval Management Report	B-51
Table B-3-227: BDS Code E,3 – Transponder Type / Part Number	B-52
Table B-3-228: BDS Code E,4 – Transponder Software Revision Number	B-53
Table B-3-229: BDS Code E,5 –CAS Unit Part Number.....	B-54
Table B-3-230: BDS Code E,6 –CAS Unit Software Revision	B-55
Table B-3-231: BDS Code E,7 – Transponder Status and Diagnostics	B-56
Table B-3-234: BDS Code E,A – Vendor Specific Status and Diagnostics.....	B-57
Table B-4-1: Register 40 ₁₆ Parameters.....	B-66
Table C-2-1: MSP Channel Number Assignments.....	C-6
Table C-2-2: Broadcast Identifier Number Assignments	C-6
Table C-2-3: LAS Subfield Coding.....	C-10
Table C-2-4: LBS Subfield Coding.....	C-12
Table C-2-5: AE Mode S Subnetwork Timers	C-14
Table F-1: IRM Interrogation Rate Reports	F-1
Table F-2: IRM Reply Rate Reports	F-2
Table F-3: “ATCRBS Suppression Rate” Encoding	F-3
Table F-4: “ATCRBS-Only All-Call Interrogation Rate” Encoding	F-4
Table F-5: “Short Air-Air Surveillance Interrogation Rate” Encoding.....	F-4
Table F-6: “Long Air-Air Surveillance Interrogation Rate” Encoding.....	F-5
Table F-7: “Identity and Altitude Surveillance and Comm-A Interrogation Rate” Encoding	F-6
Table F-8: “Mode S-Only All-Call Interrogation Rate” Encoding	F-7
Table F-9: “Other Uplink Formats Interrogation Rate” Encoding	F-8
Table F-10: “ATCRBS Reply Reporting Capability Bit” Encoding.....	F-9
Table F-11: “Mode A/ATCRBS Reply Rate” Encoding - Mode A Only	F-9
Table F-12: “Mode A/ATCRBS Reply Rate” Encoding - Mode A and Mode C.....	F-10
Table F-13: “Mode C Reply Rate” Encoding.....	F-10
Table F-14: “Short Air-Air Surveillance Reply Rate” Encoding	F-11
Table F-15: “Long Air-Air Surveillance Reply Rate” Encoding	F-12
Table F-16: “Identity and Altitude Surveillance Reply Rate” Encoding	F-13
Table F-17: “Identity and Altitude Comm-B Reply Rate” Encoding.....	F-14
Table F-18: “All-Call Reply Rate (DF=11)” Encoding.....	F-15

This Page Intentionally Left Blank

1 PURPOSE AND SCOPE

1.1 Introduction

This document sets forth minimum operational performance standards for Mode Select (Mode S)¹ airborne equipment. Incorporated within these standards are system characteristics that will be useful to users of the system as well as designers, manufacturers and installers.

Compliance with these standards is recommended as a means of assuring that the equipment will perform its intended function(s) satisfactorily under all conditions normally encountered in routine operations.

It is recognized that any regulatory application of these standards is the responsibility of appropriate government agencies.

Because the measured values of equipment performance characteristics may be a function of the measurement method, standard test conditions and methods of test are included in this document.

This document considers an equipment configuration consisting of: transponder, control panel, antenna and interconnecting cables. It should not be inferred that all Mode S airborne equipment will necessarily include all of the foregoing components as separate units; this will depend on the design configuration chosen by the manufacturer. Additional functions and components that may refer to expanded equipment capabilities are identified as additional capabilities. Equipment features that are beyond the scope of this document may be developed in future RTCA activities.

If the equipment implementation includes a computer software package, the guidelines contained in the most current issue of RTCA DO-178, *Software Considerations in Airborne Systems and Equipment Certification*, should be considered. If the equipment implementation includes design considerations for use in conjunction with TCAS functionality, the guidelines contained in the most current issue of RTCA DO-185, *Minimum Operational Performance Standards for Traffic Alert and Collision Avoidance System (TCAS) Airborne Equipment*, should be considered. If the equipment implementation includes design considerations for use in conjunction with ACAS Xa functionality, the guidelines contained in the most current issue of RTCA DO-385, *Minimum Operational Performance Standards for Airborne Collision Avoidance System X (ACAS X) (ACAS Xa and ACAS Xo)*, should be considered. If the equipment implementation includes design considerations for use in conjunction with ACAS-Xu functionality, the guidelines contained in the most current issue of RTCA DO-386, *Minimum Operational Performance Standards for Airborne Collision Avoidance System Xu (ACAS Xu)*, should be considered.

Throughout this document, the term CAS is used to mean a generic collision avoidance system, applicable to any of the existing airborne collision avoidance implementations. The specific terms TCAS, ACAS Xa (or RTCA DO-385) and ACAS Xu (or RTCA DO-386) are used when the associated text applies only to a particular implementation. The full descriptor ACAS Xa/Xo is shortened to ACAS Xa, and TCAS II is shortened to

¹ For the purpose of this document, the term "Mode S" implies a combined ATCRBS/Mode S capability.