

RTCA, Inc.
1140 Connecticut Avenue, NW, Suite 1020
Washington, DC 20036 USA

**Minimum Operational Performance Standards
(MOPS) for an Active Traffic Alert and Collision
Avoidance System I
(Active TCAS I)**

RTCA DO-197A
September 12, 1994

Prepared by: SC-147
© 1994 RTCA, Inc.

Copies of this document may be obtained from

RTCA, Inc.

Telephone: 202-333-9439

Facsimile: 202-333-4434

Internet: www.rtca.org

Please visit the RTCA Online Store for document pricing and ordering information.

FOREWORD

This report was prepared by RTCA Special Committee 147 (SC-147) and approved by the RTCA Technical Management Committee (TMC) on September 12, 1994.

RTCA, Incorporated is a not-for-profit corporation formed to advance the art and science of aviation and aviation electronic systems for the benefit of the public. The organization functions as a Federal Advisory Committee and develops consensus based recommendations on contemporary aviation issues. RTCA's objectives include but are not limited to:

- coalescing aviation system user and provider technical requirements in a manner that helps government and industry meet their mutual objectives and responsibilities;
- analyzing and recommending solutions to the system technical issues that aviation faces as it continues to pursue increased safety, system capacity and efficiency;
- developing consensus on the application of pertinent technology to fulfill user and provider requirements, including development of minimum operational performance standards for electronic systems and equipment that support aviation; and
- assisting in developing the appropriate technical material upon which positions for the International Civil Aviation Organization and the International Telecommunication Union and other appropriate international organizations can be based.

The organization's recommendations are often used as the basis for government and private sector decisions as well as the foundation for many Federal Aviation Administration Technical Standard Orders.

Since RTCA is not an official agency of the United States Government, its recommendations may not be regarded as statements of official government policy unless so enunciated by the U. S. government organization or agency having statutory jurisdiction over any matters to which the recommendations relate.

This Page Intentionally Left Blank

EXECUTIVE SUMMARY

This document provides Minimum Operational Performance Standards (MOPS) for Active Traffic Alert and Collision Avoidance System I (Active TCAS I) on aircraft up to thirty passenger seats as prescribed by the Federal Aviation Administration (FAA) TCAS rules.

Active TCAS I is an air-to-air interrogation device that provides traffic advice to the flight crew by alerting them to the presence of a nearby transponder-equipped aircraft and advising the crew where to look for the aircraft so that it can be visually acquired and avoided if necessary. Unlike TCAS II and TCAS III, Active TCAS I does not provide conflict resolution advisories.

The following summarizes the operational goals to be met by a minimum performance Active TCAS I system for revenue passenger operations:

- a. The system is capable of providing reliable and timely advice to the pilot by using an audible and visual advisory of the proximity of an intruder aircraft.
- b. The system will detect and then timely report the range, altitude (if reported) and relative bearing of the proximate aircraft with high reliability.
- c. The probability of displaying false targets will be as low as possible.
- d. The system should not increase the traffic on the Secondary Surveillance Radar (SSR) radio frequencies in a manner that degrades the ATC system.

Section 1.0 of this document is intended to provide information needed to understand the rationale for the equipment characteristics and requirements stated in the remaining sections.

Section 2.0 contains the minimum performance standards for the equipment. These standards define the required performance under standard operating conditions and stressed physical environments. Section 2.0 also details the recommended bench test procedures necessary to demonstrate compliance with system performance requirements.

Section 3.0 describes the performance required of the installed equipment. Tests for installed equipment are included to ensure that its performance is acceptable when performance cannot be adequately determined through bench testing.

This Page Intentionally Left Blank

TABLE OF CONTENTS

	<u>Page</u>
FOREWORD	i
EXECUTIVE SUMMARY	iii
TABLE OF CONTENTS	v
1.0 Purpose and Scope	1
1.1 Introduction	1
1.2 Useful Range of a PWI-Operational Environment	1
1.3 Need for Cooperative Equipment	1
1.4 Contents of This Document	2
1.5 Operational Goals	2
1.5.1 Minimum Performance Active TCAS I System	2
1.5.2 Operational Enhancements to a Minimum Performance Active TCAS I	3
1.6 Assumptions and Limitations	4
1.6.1 Disadvantages of Providing a Longer Range Active TCAS I Capability	4
1.6.2 Transponder Population	4
1.7 Test Procedures	5
1.7.1 Environmental Tests	5
1.7.2 Bench Tests	5
2.0 ACTIVE TCAS I EQUIPMENT REQUIREMENTS AND TEST PROCEDURES	7
2.1 General Requirements	7
2.1.1 Airworthiness	7
2.1.2 General Performance	7
2.1.3 Federal Communications Commission Rules	7
2.1.4 Controls	7
2.1.4.1 Operation of Controls	7
2.1.5 Pilot Advisory Functions	7
2.1.6 Equipment Configuration	7
2.1.7 Active TCAS I Combined With Other Aircraft Systems	8
2.1.8 Effects of Test	8
2.2 Minimum Performance Standards - Standard Conditions and Signals	8
2.2.1 Definition of Standard Conditions	8
2.2.1.1 Measurement Conventions	8
2.2.1.2 Performance Compatibility With Own-Aircraft's Transponder	8
2.2.2 Receiver Characteristics	9
2.2.2.1 In-Band Acceptance	9
2.2.2.2 Out-of-Band Rejection	9
2.2.3 Active TCAS I Transmitter Characteristics	10
2.2.3.1 Transmission Frequency	10
2.2.3.2 Transmitter RF Power Output	10
2.2.3.2.1 Interrogations Spectrum	10
2.2.3.2.2 Unwanted Output Power	10
2.2.3.3 Interrogation Interval Jitter	11

	2.2.3.4	Interrogation Rate	11
2.2.4		Signal Reception	13
	2.2.4.1	Mode C Reply Reception	13
	2.2.4.2	Mode S Broadcast Reception	15
2.2.5		Reduction of Multipath Interference	15
	2.2.5.1	Interrogation Link Interference	15
	2.2.5.2	Reply Link Interference	15
2.2.6		Interference Limiting	16
2.2.7		Control of Synchronous Interference	17
2.2.8		Surveillance Track Requirements	18
	2.2.8.1	Surveillance Range	18
	2.2.8.2	Surveillance Target Capacity	18
	2.2.8.3	Surveillance Track Acquisition	18
	2.2.8.4	Surveillance Track Coast Period	18
	2.2.8.5	Surveillance of Non-Altitude-Reporting (NAR) Targets	18
2.2.9		Bearing Estimation	18
	2.2.9.1	General Requirements	21
	2.2.9.2	Bearing Accuracy With Standard Ground Plane	21
	2.2.9.2.1	Bearing Accuracy, -10 to +10 Degrees Elevation ...	21
	2.2.9.2.2	Bearing Accuracy, +10 to +20 Degrees Elevation ..	21
2.2.10		Active TCAS I Antenna System	21
	2.2.10.1	Polarization	21
	2.2.10.2	Radiation Pattern	21
2.2.11		Aircraft Suppression Bus	21
2.2.12		Active TCAS I Pilot Interface	22
2.2.13		Computer Performance Validation	22
2.2.14		Traffic Advisory Criteria	22
2.2.15		Aural Alert	24
2.2.16		Display of Intruders on the Ground	24
2.2.17		Display Overload	25
2.3		Equipment Performance - Environmental Conditions	25
	2.3.1	Environmental Test Conditions	26
	2.3.2	Detailed Environmental Test Procedures	26
2.4		Equipment Test Procedures	29
	2.4.1	Definitions of Terms and Conditions of Test	29
	2.4.1.1	Standard Test Signals	30
	2.4.1.2	Test Equipment Capabilities	31
	2.4.2	Detailed Test Procedures	34
	2.4.2.1	Transmitter Characteristics	34
	2.4.2.1.1	Transmission Frequency (2.2.3.1)	34
	2.4.2.1.2	RF Peak Output Power (2.2.3.2)	34
	2.4.2.1.3	Active TCAS I Transmitter Pulse Characteristics (2.2.3.5)	36
	2.4.2.1.4	Interrogation Spectrum (2.2.3.2.1)	36
	2.4.2.1.5	Unwanted Output Power (2.2.3.2.2)	39
	2.4.2.1.6	Aircraft Suppression Bus (2.2.11)	39
	2.4.2.1.7	Interrogation Repetition Interval (2.2.3.4) and Jitter (2.2.3.3)	42

2.4.2.2	Active TCAS I Receiver Characteristics (2.2.2)	45
2.4.2.2.1	In-Band Acceptance (2.2.2.1)	45
2.4.2.2.2	Out-of Band Rejection (2.2.2.2)	45
2.4.2.3	Signal Reception (2.2.4)	46
2.4.2.3.1	Detection and Decoding of Garbled Mode C Replies (2.2.4.1)	46
2.4.2.4	Reduction of Multipath Interference (2.2.5)	48
2.4.2.4.1	Interrogation Link Interference (2.2.5.1)	48
2.4.2.4.2	Reply Link Interference (2.2.5.2)	49
2.4.2.5	Interference Limiting (2.2.6)	51
2.4.2.6	Control of Synchronous Interference (2.2.7)	52
2.4.2.7	Surveillance Track Requirements (2.2.8)	53
2.4.2.7.1	Surveillance Track Range, Acquisition and Coast (2.2.8.1, 2.2.8.3 and 2.2.8.4)	53
2.4.2.7.2	Surveillance of NAR Targets (2.2.8.5)	55
2.4.2.7.3	Surveillance Target Capacity (2.2.8.2)	55
2.4.2.7.4	Display Overload (2.2.17)	57
2.4.2.7.5	Aural Alert Annunciation (2.2.15)	60
2.4.2.7.6	Intruder on the Ground Logic (2.2.16)	61
2.4.2.8	Performance Compatibility with Own-Aircraft's Transponder	61
2.4.2.8.1	Active TCAS I to Transponder Interference (2.2.1.2)	62
2.4.2.8.2	Transponder to Active TCAS I Interference (2.2.1.2)	62
2.4.2.9	Bearing Estimation	62
2.4.2.9.1	Bearing Accuracy with Standard Ground Plane (2.2.9.2)	62
2.4.2.10	Active TCAS I Antenna System (2.2.10)	64
2.4.2.11	Computer Performance Validation (2.2.13)	65
2.4.2.11.1	Memory Pattern Tests	65
2.4.2.11.2	CPU Instruction Test	65
2.4.2.11.3	Program Memory Tests	65
2.4.2.11.4	CPU Input/Output Tests	65
2.4.2.11.5	CPU Timing Tests	65
2.4.2.11.6	Target Reporting Timing (2.2.12)	65
2.4.2.12	Traffic Advisory Criteria (2.2.14)	65
2.4.2.12.1	Sensitivity Level Selection	65
2.4.2.12.2	Traffic Advisory Criteria for SLA	67
2.4.2.12.3	Traffic Advisory Criteria for SLB	70
3.0	INSTALLED EQUIPMENT PERFORMANCE	73
3.1	Test Conditions	73
3.1.1	Power Input	73
3.1.2	Associated Equipment	73
3.1.3	Environment	73
3.1.4	Adjustment of Equipment	73
3.2	Equipment Installation	73
3.2.1	Equipment Accessibility	73

	<u>Page</u>	
3.2.2	Display Visibility	73
3.2.3	Interference	73
3.2.4	Physical Installation	74
3.2.5	Aircraft Power Source	74
3.2.6	Transmission Lines	74
3.2.7	Altimetry	74
3.3	Minimum Installed Equipment Performance Requirements	74
3.4	Test Procedures for Installed Equipment Performance	74
3.4.1	Conformity Inspection	74
3.4.2	General Test Procedures	75
3.4.2.1	Equipment Function	75
3.4.2.2	Interference Effects (Ground Test)	75
3.4.2.3	Accessibility	75
3.4.3.1	Displayed Data Readability	75
3.4.3.2	Interference Effects	75
3.4.3.3	Surveillance	76
Membership	77
Table 2-1	Environmental Test Groups	27
Table 2-2	Performance Requirements	28
Figure 2-1	Mode C Interrogation Pulse Sequence for TCAS I	12
Figure 2-2	ATCRBS Reply	14
Figure 2-3	Example Whisper-Shout Sequence	19
Figure 2-4	Example Interference Limiting States Appropriate for Whisper-Shout Sequence of Figure 2-3	20
Figure 2-5	Frequency Test Setup	35
Figure 2-6	Peak Power Test Setup	37
Figure 2-7	Transmission Test Setup	38
Figure 2-8	RF Spectrum Test Setup	40
Figure 2.9	Unwanted Output Power Test Setup	41
Figure 2-10	Suppression Pulse Reception Test Setup	43
Figure 2-11	Interrogation Rate Jitter Test Setup	44

1.0 Purpose and Scope

1.1 Introduction

This document sets forth minimum operational performance standards for an Active Traffic Alert and Collision Avoidance System (Active TCAS I) to provide the Proximity Warning Indicator (PWI) function on aircraft with up to 30 passenger seats as required by the Federal Aviation Administration's TCAS Rule.

Active TCAS I is an air-to-air interrogation device that provides traffic advice to the flight crew by alerting them to the presence of a nearby transponder-equipped aircraft and advising the crew where to look for the aircraft so that it can be visually acquired and avoided, if necessary. The pilot must be alerted in time to: a) visually look for the intruding aircraft; b) locate it; c) determine if an avoiding maneuver is necessary; and d) accomplish the avoiding maneuver, if necessary (see Appendix A). Unlike Active TCAS II and Active TCAS III, Active TCAS I does not provide conflict resolution advisories.

A significant amount of data demonstrates that a pilot will visually locate an intruder aircraft more rapidly, under normal as well as poor visibility conditions, when intruder range, relative bearing and altitude information are provided.

For the purpose of this document, "own aircraft" refers to the aircraft equipped with Active TCAS I; "other aircraft" refers to another aircraft that the Active TCAS I aircraft is interacting with.

1.2 Useful Range of a PWI-Operational Environment

Three or four nautical miles is a nominal range at which aircraft can reliably be detected in visual flight conditions with normal in-flight visibility. The maximum range that a pilot can visually detect another aircraft varies as a function of relative motion and the contrast of the other aircraft against the background as seen by the pilot. Most near misses and mid-air collisions occur in the airspace below 10,000 feet MSL.

It is expected that there will continue to be a mix of controlled and uncontrolled aircraft using the same airspace and operating in visual meteorological conditions. Thus, a system that can be installed on an aircraft that enhances the pilot's capability of visually locating other aircraft will be operationally useful.

1.3 Need for Cooperative Equipment

It would be best if the system did not require special cooperative equipment to permit an airborne collision avoidance system to perform its function in a suitable manner. However, numerous studies show that some type of cooperative device is necessary to permit the intruding aircraft to be detected in an operationally useful manner. The preferable cooperative device is the ATCRBS or Mode S transponder, with altitude reporting capability, so the pilot of the Active TCAS I equipped aircraft can be told when and where