

RTCA, Inc.  
1425 K Street, NW, Suite 500  
Washington, DC 20005 USA

**Potential Interference to Aircraft Electronic  
Equipment from Devices Carried Aboard**

**Volume I**

RTCA DO-199  
September 16, 1988  
Supersedes: RTCA DO-119

Prepared by: SC-156  
© RTCA, Inc.

Copies of this document may be obtained from

RTCA, Inc.

Telephone: 202-833-9339

Facsimile: 202-833-9434

Internet: [www.rtca.org](http://www.rtca.org)

Please visit the RTCA Online Store for document pricing and ordering information.

## F O R E W O R D

This document was prepared by Special Committee 156 of the Radio Technical Commission for Aeronautics. It was approved by RTCA on September 16, 1988, and supersedes RTCA/DO-119, "Interference to Aircraft Electronic Equipment from Devices Carried Aboard," April 12, 1963.

RTCA is an association of aeronautical organizations of the United States from both government and industry. Dedicated to the advancement of aeronautics, RTCA seeks sound technical solutions to problems involving the application of electronics and telecommunications to aeronautical operations. Its objective is the resolution of such problems by mutual agreement of its member organizations. The findings of RTCA are in the nature of recommendations to all organizations concerned. Since RTCA is not an official agency of the United States Government, its recommendations may not be regarded as statements of official government policy unless so enunciated by the U. S. government organization or agency having statutory jurisdiction over any matters to which the recommendations relate.

THIS PAGE INTENTIONALLY LEFT BLANK

# TABLE OF CONTENTS

	<u>Page</u>
FOREWORD .....	i
TABLE OF CONTENTS .....	iii
1.0 EXECUTIVE SUMMARY .....	1
2.0 INTRODUCTION .....	3
2.1 Media Interest .....	3
2.2 Establishment of SC-156 -- Terms of Reference .....	3
2.3 Statement of the Problem .....	4
2.4 Scope of Investigation .....	5
2.4.1 Type of Aircraft .....	5
2.4.2 Type of Portable Equipment .....	5
2.5 Glossary of Terms .....	6
3.0 BACKGROUND .....	7
3.1 Incident Reports .....	7
3.2 Summary of Electromagnetic Interference (EMI) Control for Aircraft Communications, Navigation Systems .....	7
3.2.1 Between Installed Systems .....	7
3.2.2 Interference from Ground-Based Sources .....	11
3.2.2.1 Description of Sources and Interference Mechanisms .....	11
3.2.2.2 Interference Prevention/Mitigation Techniques .....	11
3.2.3 Interference from Devices Carried On Board .....	12
3.2.3.1 Operator Survey .....	13
3.2.4 Cumulative Interference Effects .....	13
3.2.5 Vulnerable Frequencies and Functions .....	16
3.3 Federal Aviation Regulations (FAR) .....	18
3.4 Existing Industry Standards .....	18
3.4.1 FCC Controls, Limits, and Effectiveness .....	18
3.4.2 Other Industry Standards .....	22
3.4.2.1 VERBAND DEUTSCHER ELEKTROTECHNIKER (VDE) .....	22
3.4.2.2 International Special Committee on Radio Interference (C.I.S.P.R.) .....	23

	<u>Page</u>
3.4.2.3 Radio Technical Commission for Aeronautics RTCA/DO-160B .....	23
3.4.3 Summary of Existing Standards .....	23
3.4.4 Need for New Standards .....	23
4.0 DATA COLLECTION .....	27
4.1 Aircraft Equipment Susceptibility .....	27
4.1.1 List of Aeronautical Systems and Frequencies to be Tested. ....	27
4.1.2 Standards for Tests Adopted .....	27
4.1.3 Test Procedures .....	27
4.1.3.1 Omega/VLF .....	27
4.1.3.2 Loran-C .....	31
4.1.3.3 ADF Receiver .....	33
4.1.3.4 HF Communications .....	34
4.1.3.5 75 MHz Marker Beacon Receiver .....	34
4.1.3.6 VOR .....	35
4.1.3.7 ILS Localizer .....	36
4.1.3.8 VHF Communications - Voice Modulation .....	37
4.1.3.9 VHF Communications - Data Link .....	38
4.1.3.10 ILS Glide Slope .....	38
4.1.3.11 Systems Not Tested .....	39
4.2 Path Loss .....	41
4.2.1 Path Loss Measurements .....	41
4.2.1.1 On-Aircraft Testing .....	41
4.2.1.2 Definitions of Path Loss and Path Loss Factor (PLF) .....	41
4.2.1.3 Characterization of Portable Devices .....	42
5.0 DATA ANALYSIS .....	45
5.1 Incident Reports .....	45
5.2 Aircraft Equipment Susceptibility .....	46
5.2.1 Test Procedures Employed .....	46
5.2.2 Test Results .....	46
5.2.2.1 Further Analysis of Possibility of Interfering with VOR Receivers .....	46
5.2.2.2 Analysis of VOR and Interfering Signal Stabilities .....	59
5.2.2.3 Probability .....	63
5.3 Path Loss .....	68

	<u>Page</u>
5.3.1	Determination of "Portable Device" Test Limits Using PLF . . . . . 66
5.3.2	Determination of "Portable Device" Test Limits for Low Frequency Aircraft Systems . . . . . 70
5.3.3	Electromagnetic Shielding of Aircraft Windows . . . . . 71
5.4	Portable Device Radiation Levels . . . . . 72
5.5	Comparison of Test Methods . . . . . 77
5.6	Summary . . . . . 82
6.0	CONCLUSIONS AND RECOMMENDATIONS . . . . . 89
6.1	Multiple Conditions Required for Receiver Disruption to Occur . . . . . 89
6.2	Limits of Radiation, Test Methods . . . . . 91
6.2.1	Radiated Magnetic Field (H-Field) Measurements . . . . . 91
6.2.2	Radiated Electric Field (E-Field) Measurements . . . . . 93
6.2.3	Radiated Electric Field Above 1,000 MHz . . . . . 93
6.3	Recommendations to FCC . . . . . 93
6.4	Recommended Changes to Federal Aviation Regulations (FAR) . . . . . 95
6.4.1	Proposed Revision of FAR 91.19 . . . . . 95
6.4.2	Recommended Regulatory Compliance Information . . . . . 97
6.5	Procedures for Reporting Suspected Interference . . . . . 98
6.5.1	Recommended Precautions and Procedures . . . . . 98
6.5.1.1	Procedures to Assist Control of Device Use By Aircraft Crews . . . . . 99
6.5.2	Recommended Report . . . . . 99
<hr/>	
MEMBERSHIP	. . . . . 101
APPENDIX A	PATH LOSS FACTOR (PLF) TEST DATA
APPENDIX B	CONVERTING FIELD STRENGTH IN SPACE TO VOLTAGE LEVEL AT RECEIVER
APPENDIX C	INCIDENT REPORTS
APPENDIX D	DEMONSTRATION OF CUMULATIVE INTERFERENCE EFFECTS
APPENDIX E	COMPARISON OF DO-160B WITH FCC AND VDE STANDARDS
APPENDIX F	COMPENDIUM OF REFERENCES CONCERNING HARMFUL INTERFERENCE FROM GROUND EMITTERS TO AIRCRAFT RADIO NAVIGATION AND RADIO COMMUNICATION SYSTEMS DURING THE APPROACH, LANDING, AND TAKEOFF PHASES OF FLIGHT
APPENDIX G	RADIO FREQUENCY INTERFERENCE TO NAVIGATION SYSTEMS FROM PORTABLE ELECTRONIC DEVICES

THIS PAGE INTENTIONALLY LEFT BLANK

---

## 1.0 EXECUTIVE SUMMARY

In response to an airline request, RTCA Special Committee 156 was formed in 1983 to investigate and quantify, if possible, the potential interference from portable electronic devices carried aboard aircraft by passengers to installed communication, navigation and other systems on the aircraft. While a fairly comprehensive list of incidents of such interference reports was in the record, no demonstration of such interference from a portable electronic device had ever been repeated under controlled conditions in the air or on the ground.

With strong support from the Federal Aviation Administration (FAA), supplemented by data provided by Hewlett Packard and IBM, a reasonable collection of data on the frequency and level of emissions from a variety of portable electronic devices was obtained. Included were lap-top computers, portable televisions, AM and FM radios, scanning monitors, medical devices and battery operated games. Particular attention was paid to RF emissions in seven frequency bands of interest to aviation from Omega navigation at 10 kHz - 14 kHz to DME at 960 MHz - 1.215 GHz.

Susceptibility of installed systems to RF interference was expected to be equal to or better than the limits set in RTCA DO-160B, which provides standards for undesired RF interference radiated by equipment designed for installation in the aircraft. Since these limits were very different from those established in Federal Communications Commission (FCC) Rules and Regulations Part 15, tests were performed in screen rooms on representative navigation and communication avionics system elements to correlate the portable device emission with installed system susceptibility.

The most elusive factor in the equation was labeled Path Loss Factor (PLF). PLF approximates the attenuation of a signal emitted by a portable device as it passes through a window, bounces off a wing or tail section, reaches an appropriate aircraft antenna, and is measured at the receiver end of the antenna cable.

It was further determined that interference would be more complex in the presence of one or more high-level external interfering signals such as FM broadcast. Such intermodulation products were also measured.

The results of the data collection and analysis were reviewed and have resulted in recommendations to the FCC, FAA, airlines and other operators of aircraft.

At the time of publication of this report, the FCC is considering changes to the FCC regulations contained in the Code of Federal Regulations, CFR 47, Part 15. It would be impossible to anticipate the final form of these changes should they be implemented. It is anticipated that changes to CFR 47, Part 15, would affect Subsections 3.4.1; 3.4.2; 6.2 and 6.3 of this report.

This document is published in two volumes.

- Volume I is the report itself that includes the background, data collection, data analysis, conclusion and recommendations.