

RTCA, Inc.
1828 L Street, NW, Suite 805
Washington, DC 20036-5133 USA

**Minimum Operational Performance Standards
(MOPS) for Airborne Weather Radar with
Forward-Looking Windshear Capability**

RTCA DO-220
September 21, 1993

Prepared by: SC-173
© RTCA, Inc.

Copies of this document may be obtained from

RTCA, Inc.

Telephone: 202-333-9439

Facsimile: 202-333-4434

Internet: www.rtca.org

Please visit the RTCA Online Store for document pricing and ordering information.

FOREWORD

This document was prepared by Special Committee 173 (SC-173). It was approved by RTCA Technical Management Committee on September 21, 1993.

RTCA, Incorporated is a not-for-profit corporation formed to advance the art and science of aviation and aviation electronic systems for the benefit of the public. The organization functions as a Federal Advisory Committee and develops consensus based recommendations on contemporary aviation issues. RTCA's objectives include but are not limited to:

- coalescing aviation system user and provider technical requirements in a manner that helps government and industry meet their mutual objectives and responsibilities;
- analyzing and recommending solutions to the system technical issues that aviation faces as it continues to pursue increased safety, system capacity and efficiency;
- developing consensus on the application of pertinent technology to fulfill user and provider requirements, including development of minimum operational performance standards for electronic systems and equipment that support aviation, and
- assisting in developing the appropriate technical material upon which positions for the International Civil Aviation Organization and the International Telecommunication Union and other appropriate international organizations can be based.

The organization's recommendations are often used as the basis for government and private sector decisions as well as the foundation for many Federal Aviation Administration Technical Standard Orders.

Since RTCA is not an official agency of the United States Government, its recommendations may not be regarded as statements of official government policy unless so enunciated by the U. S. government organization or agency having statutory jurisdiction over any matters to which the recommendations relate.

THIS PAGE INTENTIONALLY LEFT BLANK

TABLE OF CONTENTS

	<u>Page</u>
FOREWORD	i
TABLE OF CONTENTS	iii
1.0 PURPOSE AND SCOPE	1
1.1 Introduction	1
1.2 Operational Goals	1
1.2.1 Windshear Detection	1
1.2.2 Weather Detection	2
1.2.3 Ground Mapping	2
1.3 Operational Applications	2
1.4 Test Procedures	3
1.4.1 Bench Tests	3
1.4.2 Environmental Tests	3
1.4.3 Installed Tests	3
1.4.4 Operational Tests	4
1.5 Assumptions	4
1.6 Radome Design	4
1.7 Definition of F Factor	5
2.0 REQUIREMENTS	7
2.1 General Requirements	7
2.1.1 Airworthiness	7
2.1.2 Intended Function	7
2.1.3 Federal Communications Commission Rules	7
2.1.4 Operation of Controls	7
2.1.5 Effects of Test	7
2.1.6 Fire Protection	7
2.2 Equipment Performance — Standard Conditions	7
2.2.1 General Equipment Characteristics	8
2.2.1.1 Area Scanned	8
2.2.1.2 Display	8
2.2.1.3 Indicator Range Scale	8
2.2.1.4 Range Markers	8

	<u>Page</u>
2.2.1.5 Receiver Gain Control	8
2.2.1.5.1 Weather Avoidance Mode	8
2.2.1.5.2 Windshear Detection Mode	8
2.2.2 Airborne Weather and Ground Mapping Radar Equipment and Windshear Detection Performance	8
2.2.2.1 Antenna Beam Characteristics	9
2.2.2.2 Beam Tilting	9
2.2.2.3 Antenna Stabilization	9
2.2.2.4 Frequency of Antenna Scan	9
2.2.2.5 Pulse Duration	9
2.2.2.6 Sensitivity Time Control (STC) Weather Avoidance and Ground Mapping	10
2.2.2.7 Performance	10
2.2.2.7.1 Weather Performance Index	10
2.2.2.7.2 Windshear Performance	12
2.2.2.8 Display Bearing Accuracy	14
2.2.2.9 Indicated Distance Error	14
2.2.2.10 Minimum Displayed Target Range	14
2.2.2.11 Receiver Selectivity	14
2.2.2.12 Radio Frequency at Maximum Emission	14
2.2.2.13 Windshear Alert Outputs	14
2.2.2.14 Windshear System Fault Detection Indication	15
2.2.2.15 Mutual Interference	15
2.3 Equipment Performance — Environmental Conditions	15
2.3.1 Temperature and Altitude Tests	16
2.3.1.1 Ground Survival Low Temperature and Operating Low Temperature Test	16
2.3.1.2 Ground Survival High Temperature Test and Short-Time Operating High Temperature Test	17
2.3.1.3 Operating High Temperature Test	17
2.3.1.4 Altitude Test	17
2.3.1.5 Decompression Test	18
2.3.1.6 Overpressure Test	18
2.3.2 Temperature Variation Test	18
2.3.3 Humidity Tests	18
2.3.3.1 Fifteen-Minute Test	19
2.3.3.2 Four-Hour Test	19

	<u>Page</u>
2.3.4 Shock Tests	19
2.3.4.1 Operational Tests	19
2.3.4.2 Crash Safety Shocks	19
2.3.5 Vibration Tests	20
2.3.6 Explosion Test	20
2.3.7 Waterproofness Test	20
2.3.7.1 Dripproof Test	20
2.3.7.2 Spray Proof Test	20
2.3.7.3 Continuous Streamproof Test	21
2.3.8 Fluids Susceptibility Tests (When Required)	21
2.3.8.1 Spray Test	21
2.3.8.2 Immersion Test	22
2.3.9 Sand and Dust Test	22
2.3.10 Fungus Resistance Test	22
2.3.11 Salt Spray Test	23
2.3.12 Magnetic Effects Test	23
2.3.13 Power Input Tests	23
2.3.13.1 Normal Operating Conditions	23
2.3.13.2 Abnormal Operating Conditions	23
2.3.14 Voltage Spike Conducted Test	24
2.3.14.1 Category A Requirements	24
2.3.14.2 Category B Requirements	24
2.3.14.2.1 Intermittent Transients	24
2.3.14.2.2 Repetitive Transients	25
2.3.15 Audio Frequency Conducted Susceptibility Test	25
2.3.16 Induced Signal Susceptibility Test	25
2.3.17 Radio Frequency Susceptibility Test (Radiated and Conducted) ...	25
2.3.18 Emission of Radio Frequency Energy Test	26
2.3.18.1 Interference Levels	26
2.3.18.2 Spurious Emissions	26
2.3.19 Lightning Induced Transient Susceptibility (When Required)	26
2.3.20 Lightning Direct Effects (When Required)	26
2.3.21 Icing	27

	<u>Page</u>
3.2.3 Interference Effects	46
3.3 Minimum Installed Equipment Performance Requirements	46
3.3.1 General Radar Equipment Performance Requirements	46
3.3.1.1 Range Performance	46
3.3.1.2 Range Accuracy	46
3.3.1.3 Stabilization Performance	47
3.3.1.4 Bearing Accuracy	47
3.3.1.5 Aperture Blockage	47
3.4 Test Procedures for Installed Equipment Performance	47
3.4.1 Conformity Inspection	47
3.4.2 Ground Test Procedures	47
3.4.2.1 Equipment Function	47
3.4.2.2 Interference Effects	47
3.4.2.3 Bearing Alignment Tests	48
3.4.2.4 Power Supply Fluctuation	48
3.4.2.5 Equipment accessibility	48
3.4.3 Flight Test Procedures	48
3.4.3.1 Display Visibility	48
3.4.3.2 Interference Effects	48
3.4.3.3 Range Performance	48
3.4.3.4 Stabilization Performance	49
3.4.3.5 Clutter Rejection	49
3.4.3.6 Windshear Mode Activation	49
3.4.3.7 Windshear and Weather Detection	49
4.0 OPERATIONAL CHARACTERISTICS	51
4.1 Required Operational Characteristics	51
4.1.1 Power Input	51
4.1.2 Antenna Tilt and Stabilization	51
4.1.3 Display Range Scales	51
4.1.4 Equipment Operating Modes	51
4.2 Test Procedures for Operational Characteristics	51
4.2.1 Power Input	51
4.2.2 Antenna Tilt and Stabilization	52
4.2.3 Display Range Scales	52

	<u>Page</u>
4.2.4 Equipment Operating Modes	52
4.2.4.1 Clutter/Interference Rejection	52
4.2.4.2 Windshear Detection Mode Activation	52
4.2.4.3 Weather Detection	52
4.2.4.4 Alerts	53
Membership	53

FIGURES

FIGURE 2-1 MEASUREMENT OF ANTENNA GAIN 36
FIGURE 2-2 WINDSHEAR TEST CONFIGURATION 39

TABLES

TABLE 2-1 MINIMUM PERFORMANCE INDEX VS MAXIMUM SYSTEM RANGE 13
TABLE 2-2 WINDSHEAR SIMULATION DATA SETS 40
TABLE 2-3 TESTING MATRIX 41

APPENDIX A

WINDSHEAR DATABASE FOR FORWARD-LOOKING SYSTEMS CERTIFICATION

APPENDIX B

ANALYTICAL TECHNIQUE FOR EVALUATION OF MISSED EVENTS AND NUISANCE ALERTS

APPENDIX C

CONSIDERATIONS ASSOCIATED WITH THE USE OF THE WINDSHEAR TEST SET-UP

THIS PAGE INTENTIONALLY LEFT BLANK

1.0 PURPOSE AND SCOPE

1.1 Introduction

This document sets forth Minimum Operational Performance Standards (MOPS) for Airborne Doppler Weather Radar with Forward-Looking Windshear Detection capability. In addition to updating and expanding the scope of RTCA/DO-173 *Minimum Operational Performance Standards for Airborne Weather and Ground Mapping Pulsed Radars*, it incorporates new radar technology and serves as a standard for both air carrier and general aviation aircraft. It considers those requirements and technologies pertinent to general aviation, where limitations on space and/or weight may apply.

Compliance with these standards by manufacturers, installers and users is recommended as one means of assuring the equipment will perform its intended function under conditions normally encountered in routine aeronautical operations. It is recognized that any regulatory application of these standards is the responsibility of appropriate governmental agencies.

The word "equipment" as used herein includes all components or units necessary (as determined by the manufacturer or installer) for the equipment to properly perform its function. For example, the airborne radar "equipment" may include a radome, an antenna, antenna mounting, transmission line, a receiver/transmitter unit, a control/display unit, shock mounts, etc. In this illustrative example, all these components or units comprise the "equipment." It should not be inferred from this example that every equipment configuration will necessarily include (or be limited to) all these components or units. This will depend on the design chosen by the equipment manufacturer and the techniques of the installer.

Some system designs may not include a dedicated radar display unit. They may instead share the display medium with TCAS and/or ACARS. They may also share a multipurpose display such as an EFIS (Electronic Flight Instrument System). For airborne radar systems with this architecture, the shared display device, when used for displaying radar information, must meet the display requirements as set forth in this document.

1.2 Operational Goals

There are three primary operational goals that must be satisfied by the equipment described in this document. These are forward-looking windshear detection, weather detection and ground mapping.

1.2.1 Windshear Detection

For windshear detection, the airborne radar equipment must detect areas containing windshear activity. It will be capable of correlating and generating appropriate