

RTCA, Inc.
1828 L Street, NW, Suite 805
Washington, DC 20036-5133 USA

**Minimum Operational Performance Standards
(MOPS) for GPS Local Area Augmentation
System (LAAS) Airborne Equipment**

RTCA DO-253B
June 26, 2007

Prepared by: SC-159
© 2007 RTCA, Inc.

Copies of this document may be obtained from

RTCA, Inc.

Telephone: 202-333-9439

Facsimile: 202-333-4434

Internet: www.rtca.org

Please visit the RTCA Online Store for document pricing and ordering information.

Foreword

This document was prepared by RTCA Special Committee 159 (SC-159) and approved by the RTCA Program Management Committee (PMC) on June 26, 2007.

RTCA, Incorporated is a not-for-profit corporation formed to advance the art and science of aviation and aviation electronic systems for the benefit of the public. The organization functions as a Federal Advisory Committee and develops consensus-based recommendations on contemporary aviation issues. RTCA's objectives include but are not limited to:

- Coalescing aviation system user and provider technical requirements in a manner that helps government and industry meet their mutual objectives and responsibilities;
- Analyzing and recommending solutions to the system technical issues that aviation faces as it continues to pursue increased safety, system capacity, and efficiency;
- Developing consensus on the application of pertinent technology to fulfill user and provider requirements, including development of Minimum Operation Performance Standards (MOPS) for electronic systems and equipment that support aviation; and
- Assisting in developing the appropriate technical material upon which positions for the International Civil Aviation Organization (ICAO) and the International Telecommunication Union (ITU) and other appropriate international organizations can be based.

The recommendations of RTCA are often used as the basis for government and private sector decisions as well as the foundation for many Federal Aviation Administration Technical Standard Orders (TSO).

Since RTCA is not an official agency of the United States Government, its recommendations may not be regarded as statements of official government policy unless so enunciated by the U.S. government organization or agency having statutory jurisdiction over any matters to which the recommendations relate.

Currently in preview, click buy full version

This page is intentionally left blank

Table of Contents

1	PURPOSE AND SCOPE	1
1.1	Introduction	1
1.2	System Overview	2
1.3	Operational Goals.....	4
1.4	LAAS Airborne Equipment Functions.....	4
1.5	Assumptions.....	6
1.5.1	GPS Signal-in-Space	6
1.5.2	SBAS Signal-in-Space.....	6
1.5.3	LAAS Signal-in-Space	6
1.5.4	GPS/LAAS Applications.....	6
1.5.5	Applicability	6
1.5.6	LAAS Ground Subsystem	7
1.5.7	Interoperability	7
1.5.8	RF Interference.....	7
1.6	Test Considerations.....	7
1.6.1	Environmental Tests	7
1.6.2	Bench Tests	8
1.6.3	Installed Tests.....	8
1.7	Applicable Standards and Regulatory Documents.....	8
2	EQUIPMENT PERFORMANCE REQUIREMENTS AND TEST PROCEDURES.....	11
2.1	General GPS/LAAS Airborne Requirements	11
2.1.1	Airworthiness	12
2.1.2	Intended Function.....	12
2.1.3	Fire Protection	12
2.1.4	General Human Factors Requirements and Applicable Documents.....	12
2.1.4.1	Operation of Controls	13
2.1.4.2	Accessibility of Controls	13
2.1.4.3	Control Labels	13
2.1.4.4	Equipment Operating Procedures	14
2.1.4.5	Minimum Workload Functions.....	14
2.1.4.6	Displays.....	14
2.1.4.6.1	Discriminability.....	15
2.1.4.6.2	Brightness, Contrast, and Color	15
2.1.4.6.3	Angle of Regard	15
2.1.4.6.4	Symbology	15
2.1.4.6.5	Alphanumerics	15
2.1.4.7	Annunciations.....	16
2.1.4.7.1	Annunciators	16
2.1.4.7.2	Pilot Indications.....	16
2.1.5	Effects of Test.....	16
2.2	VHF Data Broadcast (VDB) Receiver Subsystem	17
2.2.1	General Requirements	17

2.2.1.1	Design Assurance	17
2.2.1.1.1	Hardware	17
2.2.1.1.2	Software	18
2.2.2	Tuning.....	18
2.2.2.1	Frequency Range	18
2.2.2.2	Frequency Selection	18
2.2.2.3	Response Time	18
2.2.3	Data Latency.....	19
2.2.4	Data Format Decoding.....	19
2.2.5	Message Failure Rate.....	19
2.2.6	VDB Signal Tracking Requirements	19
2.2.6.1	Carrier Frequency Capture Range	20
2.2.6.2	Carrier Frequency Slew Rate.....	20
2.2.6.3	Symbol Rate Tolerance.....	20
2.2.7	Co-Channel Rejection.....	20
2.2.7.1	VDB as the Undesired Signal	20
2.2.7.2	VOR as the Undesired Signal	20
2.2.7.3	ILS Localizer as the Undesired Signal.....	20
2.2.8	Adjacent Channel Rejection	21
2.2.8.1	1 st Adjacent 25 kHz Channels (± 25 kHz)	21
2.2.8.2	2 nd Adjacent 25 kHz Channels (± 50 kHz)	21
2.2.8.3	3 rd Adjacent 25 kHz Channels (± 75 kHz) and Beyond.....	21
2.2.9	Out-of-Band Rejection.....	22
2.2.9.1	VDB Interference Immunity.....	22
2.2.9.2	FM Immunity.....	22
2.2.9.2.1	Desensitization	22
2.2.9.2.2	Intermodulation Rejection.....	23
2.2.9.3	Burn Out Protection.....	24
2.2.10	Receiver-to-Antenna Interface.....	24
2.2.10.1	Receiver Voltage Standing Wave Ratio (VSWR)	24
2.2.10.2	Antenna Characteristics	25
2.2.10.2.1	Horizontally Polarized Antenna Characteristics.....	25
2.2.10.2.1.1	Horizontal Antenna Gain	25
2.2.10.2.1.2	Horizontal Antenna VSWR	25
2.2.10.2.2	Vertically Polarized Antenna Characteristics.....	25
2.2.10.2.2.1	Vertical Antenna Gain	26
2.2.10.2.2.2	Vertical Antenna VSWR.....	26
2.3	Position and Navigation (PAN) Subsystem	26
2.3.1	General	26
2.3.2	Design Assurance	26
2.3.2.1	Hardware	27
2.3.2.2	Software.....	27
2.3.3	Interference and Dynamics Environment	27
2.3.4	Approach and Reference Station Selection.....	27
2.3.5	Reference Data Selectors and Frequency Mapping	28
2.3.6	GNSS Receiver Function.....	29
2.3.6.1	Ranging Sources	29
2.3.6.2	Sensitivity and Dynamic Range.....	29
2.3.6.3	Equipment Burnout Protection	31
2.3.6.4	GPS Signal Processing	31
2.3.6.4.1	GPS Tracking Constraints	32
2.3.6.4.2	Correlation Peak Validation	36
2.3.6.4.3	GPS Satellite Acquisition Time.....	36
2.3.6.4.4	GPS Satellite Reacquisition Time	36
2.3.6.5	SBAS Signal Processing.....	36

2.3.6.6	Smoothing.....	38
2.3.6.7	Measurement Quality Monitoring.....	39
2.3.6.8	Accuracy.....	39
2.3.6.8.1	GPS Satellites.....	40
2.3.6.8.2	SBAS Satellites.....	40
2.3.6.9	Integrity in the Presence of Interference.....	41
2.3.6.10	Integrity in the Presence of Abnormal Dynamics.....	41
2.3.7	Message Processing Function.....	42
2.3.7.1	VDB Message Validity Check.....	42
2.3.7.2	VDB Message Block Identifier Check.....	42
2.3.8	Corrected Pseudorange.....	42
2.3.8.1	Conditions for Use of Differential Corrections.....	42
2.3.8.1.1	Ephemeris CRC Conditions.....	42
2.3.8.1.2	Reference Time Conditions.....	42
2.3.8.1.3	Other Ranging Source Conditions.....	43
2.3.8.2	Application of Differential Corrections.....	44
2.3.8.3	Tropospheric Correction.....	44
2.3.9	LAAS Differential Positioning Requirements.....	45
2.3.10	Position, Velocity, and Time (PVT) Outputs.....	47
2.3.10.1	Message Processing -- GBAS ID Selection.....	47
2.3.10.2	Horizontal & Vertical Protection Levels, Ephemeris Error Position & Figures of Merit.....	47
2.3.10.3	Figures of Merit Outputs.....	51
2.3.10.4	PVT Output Latency.....	51
2.3.11	Precision Approach Guidance Outputs.....	51
2.3.11.1	Message Processing.....	51
2.3.11.1.1	FAS Data Block Selection and Confirmation.....	51
2.3.11.1.2	GBAS ID Selection.....	52
2.3.11.2	Precision Approach Region.....	52
2.3.11.3	Approach Status Verification.....	53
2.3.11.4	Ground Continuity Integrity Designator (GCID) Conditions.....	53
2.3.11.5	Outputs.....	53
2.3.11.5.1	Deviations.....	53
2.3.11.5.1.1	Lateral Deviations for the Approach Segment.....	55
2.3.11.5.1.1.1	Proportional Lateral Deviation.....	55
2.3.11.5.1.1.2	Rectilinear Lateral Deviation.....	56
2.3.11.5.1.2	Vertical Deviations for the Approach Segment.....	56
2.3.11.5.1.2.1	Proportional Vertical Deviation.....	57
2.3.11.5.1.2.2	Rectilinear Vertical Deviation.....	58
2.3.11.5.1.3	Deviation Output Rate and Latency.....	58
2.3.11.5.1.4	Missed Approach Guidance.....	59
2.3.11.5.2	Alerts.....	59
2.3.11.5.2.1	Loss of Approach Guidance.....	59
2.3.11.5.2.1.1	Alert Limits.....	60
2.3.11.5.2.1.1.1	Lateral Alert Limits.....	60
2.3.11.5.2.1.1.2	Vertical Alert Limits.....	60
2.3.11.5.2.1.2	Lateral and Vertical Protection Levels.....	61
2.3.11.5.2.1.3	Vertical and Lateral Ephemeris Error Position Bounds.....	63
2.3.11.5.2.2	Bias Approach Monitor (BAM).....	64
2.3.11.5.3	Distance to Threshold.....	65
2.3.11.5.3.1	Distance to Threshold Output.....	65
2.3.11.5.3.2	Distance to Threshold Output Latency.....	65
2.3.12	Error Models.....	65
2.3.12.1	Model of Airborne Pseudorange Performance.....	65
2.3.12.2	Model of Tropospheric Residual Uncertainty.....	67
2.3.12.3	Model of Ionospheric Residual Uncertainty.....	67

2.4	Equipment Performance Environmental Conditions.....	68
2.4.1	Environmental Tests	69
2.4.1.1	VDB Required Performance.....	69
2.4.1.1.1	Antenna Test	74
2.4.1.1.2	System Accuracy.....	74
2.4.1.2	PAN Required Performance	74
2.4.1.2.1	Accuracy	76
2.4.1.2.2	Sensitivity and Dynamic Range	76
2.4.1.2.3	System Operating	76
2.4.1.3	Clarification of Environmental Tests.....	76
2.4.1.3.1	Power Input Tests.....	77
2.4.1.3.2	Icing Tests	77
2.4.1.3.3	RF Susceptibility Tests.....	77
2.4.1.3.4	Lightning Induced Transient Susceptibility Tests	77
2.4.1.3.5	Lightning Direct Effects Tests.....	78
2.4.1.3.6	Crash Safety Shock	78
2.5	Equipment Test Procedures	78
2.5.1	Definition of General Test Terms and Conditions.....	78
2.5.1.1	Power Input Voltage.....	78
2.5.1.2	Power Input Frequency.....	79
2.5.1.3	RF Signal Levels	79
2.5.1.4	Adjustment of Equipment.....	79
2.5.1.5	Test Instrument Precautions	79
2.5.1.6	Ambient Conditions.....	79
2.5.1.7	Warm-Up.....	79
2.5.1.8	Connected Loads	79
2.5.1.9	EMI Testing.....	79
2.5.1.10	Analysis	80
2.5.1.11	Demonstration	80
2.5.1.12	Inspection	80
2.5.1.13	Test	80
2.5.1.14	Test Cross Reference Matrix.....	80
2.5.2	VDB Receiver Subsystem Test Procedures.....	106
2.5.2.1	Definition of VDB Test Terms and Conditions.....	106
2.5.2.1.1	Standard Test Signal.....	106
2.5.2.1.2	Test Message Format.....	107
2.5.2.1.3	Statistical Sample Size and Pass/Fail Criteria	107
2.5.2.1.4	Standard Output.....	108
2.5.2.2	Detailed Test Procedures	108
2.5.2.2.1	General Requirements	108
2.5.2.2.2	Minimum	108
2.5.2.2.2.1	Frequency Range	108
2.5.2.2.2.2	Frequency Selection.....	108
2.5.2.2.2.3	Response Time.....	108
2.5.2.2.3	Data Latency	110
2.5.2.2.4	Data Format Decoding	111
2.5.2.2.5	Message Failure Rate	112
2.5.2.2.5.1	Sensitivity and Dynamic Range.....	112
2.5.2.2.5.2	Frame-to-Frame Variations for a Given Slot	113
2.5.2.2.5.3	Slot-to-Slot Variations Within a Given Frame.....	115
2.5.2.2.5.4	Training Sequence and Message Failure Rate Test.....	117
2.5.2.2.6	VDB Signal Tracking Requirements.....	119
2.5.2.2.6.1	Carrier Frequency Capture Range.....	119
2.5.2.2.6.2	Carrier Frequency Slew Rate	121
2.5.2.2.6.3	Symbol Rate Tolerance.....	122

2.5.2.2.7	Co-Channel Rejection	123
2.5.2.2.7.1	VDB as the Undesired Signal	123
2.5.2.2.7.2	VOR as the Undesired Signal	125
2.5.2.2.7.3	ILS Localizer as the Undesired Signal	127
2.5.2.2.8	Adjacent Channel Rejection	128
2.5.2.2.9	Out-of-Band Rejection	134
2.5.2.2.9.1	VDB Interference Immunity	134
2.5.2.2.9.2	FM Immunity	136
2.5.2.2.9.2.1	Desensitization	136
2.5.2.2.9.2.2	Intermodulation Rejection	138
2.5.2.2.10	Receiver-to-Antenna Interface	141
2.5.2.2.10.1	Receiver Voltage Standing Wave Ratio (VSWR)	141
2.5.2.2.10.2	Antenna Characteristics	141
2.5.2.2.10.2.1	Horizontal Polarized Antenna	141
2.5.2.2.10.2.1.1	Horizontal Antenna Gain	141
2.5.2.2.10.2.1.2	Horizontal Antenna VSWR	143
2.5.2.2.10.2.2	Vertical Polarized Antenna Characteristics	144
2.5.2.2.10.2.2.1	Vertical Antenna Gain	144
2.5.2.2.10.2.2.2	Vertical Antenna VSWR	146
2.5.3	Precision Approach Navigator Tests	146
2.5.3.1	Definition of PAN Test Terms and Conditions	146
2.5.3.1.1	Standard Test Signals and Simulator Requirements	146
2.5.3.2	Accuracy	148
2.5.3.2.1	Simulator and Interference Conditions	149
2.5.3.2.2	Test Procedure	151
2.5.3.2.3	SBAS Tracking Bias	154
2.5.3.3	Interference Rejection	155
2.5.3.3.1	Simulator and Interference Conditions	155
2.5.3.3.2	Test Procedures	155
2.5.3.3.3	Pass/Fail Determination	156
3	INSTALLED EQUIPMENT PERFORMANCE REQUIREMENTS	157
3.1	General Performance Requirements	157
3.2	Interference Effects	157
3.3	Inadvertent Turnoff	157
3.4	Test Environment	157
3.5	Associated Equipment or Systems	157
3.6	Environmental Conditions	157
3.7	Adjustment of Equipment	158
3.8	Warm-Up Period	158
3.9	GPS Antenna and Installation Requirements	158
3.10	VDB Aircraft Implementation Factor	158
3.11	GNSS Electromagnetic Compatibility	158

3.12	VDB Electromagnetic Compatibility	159
3.13	Equipment Interfaces.....	159
4	OPERATIONAL PERFORMANCE REQUIREMENTS.....	161
4.1	Alert Presentation.....	161
4.2	Guidance Reference Point	161
4.3	Missed Approach Guidance.....	161
5	MEMBERSHIP	163

Appendices

Appendix A	Acronyms, Abbreviations, and Definitions
Appendix B	Requirements Changes Between Versions
Appendix C	Final Approach Segment and Deviation Example
Appendix D	Standard GPS Interference Environment
Appendix E	(Reserved)
Appendix F	Determination of GPS/LAAS Velocity and Time Accuracy
Appendix G	Precision Approach Requirements for Rotorcraft
Appendix H	Test Considerations

Table of Figures

Figure 1-1	GPS/LAAS System	3
Figure 1-2	LAAS Airborne Equipment Functions	5
Figure 1-3	VDB Receiver Functional Block Diagram	6
Figure 2-1	Maximum Tolerable Equal-Level FM Broadcast Signals	24
Figure 2-2	Antenna with Preamplifier Configuration	31
Figure 2-3	Receiver Bandwidth vs. Average Correlator Spacing	35
Figure 2-4	Pseudorange Processing	44
Figure 2-5	Precision Approach Region	52
Figure 2-6	Final Approach Segment Definition	54
Figure 2-7	Full-Scale Deflection for Proportional Lateral Deviation	56
Figure 2-8	Full-Scale Deflection for Proportional Vertical Deviation	58
Figure 2-9	Typical Simulated FM Broadcast Spectrum	107
Figure 2-10	Response Time Test Equipment Connection	110
Figure 2-11	Data Latency Test Equipment Connection	111
Figure 2-12	Data Format Decoding Test Equipment Connection	112
Figure 2-13	Sensitivity and Dynamic Range in an AWGN Channel Test Equipment Connection	113
Figure 2-14	Frame-to-Frame Timing Diagram 1	115
Figure 2-15	Frame-to-Frame Timing Diagram 2	115
Figure 2-16	Slot-to-Slot (and Frame-to-Frame) Variation Test Equipment Connection	117
Figure 2-17	Slot-to-Slot Timing Diagram	117
Figure 2-18	Carrier Frequency Capture Range (and Slew Rate) Test Equipment Connection	121
Figure 2-19	Symbol Rate Tolerance Test Equipment Connection	123
Figure 2-20	VDB/VDB Co-Channel (and Adjacent Channel) Rejection Test Equipment Connection ..	124
Figure 2-21	VOR (ILS) as the Undesired Signal Test Equipment Connection	127
Figure 2-22	Interference Immunity Test Equipment Connection	136
Figure 2-23	Desensitization Test Equipment Connection	138
Figure 2-24	FM Broadcast Intermodulation Rejection Test Equipment Connection	140
Figure 2-25	Horizontal (Standard Dipole) Antenna Gain Test Configuration	143
Figure 2-26	Horizontal (VDB) Antenna Gain Test Configuration	143
Figure 2-27	Vertical (Standard Dipole) Antenna Gain Test Configuration	145
Figure 2-28	Vertical (VDB) Antenna Gain Test Configuration	146
<u>Figure C-1</u>	Final Approach Segment Definition	C-2
<u>Figure C-2</u>	Lateral Deviations	C-4
<u>Figure C-3</u>	GLS Elevation Reference Point Definition	C-5
<u>Figure C-4</u>	GLS Vertical Deviation Definition	C-6
<u>Figure D-1</u>	Interference Levels at the Antenna Port	D-2
<u>Figure D-2</u>	In-Band and Near-Band Interference Environments	D-2
<u>Figure D-3</u>	Frequency Selectivity	D-6
<u>Figure G-1</u>	Lateral Display Scaling	G-2
<u>Figure G-2</u>	Vertical Display Scaling	G-3
<u>Figure H-1</u>	Pseudorange Accuracy Test Pass Criteria	H-2
<u>Figure H-2</u>	Pseudorange Accuracy Test Pass Probability	H-3
<u>Figure H-3</u>	Example Test Set-up	H-3

Table of Tables

Table 2-1	GPS/LAAS Airborne Equipment Output Requirements	11
Table 2-2	Frequency and Power of Undesired Signals.....	22
Table 2-3	Desensitization Frequency and Power Requirements That Apply for VDB Frequencies 108.000 to 111.975 MHz.....	23
Table 2-4	Desensitization Frequency and Power Requirements That Apply for VDB Frequencies 112.000 to 117.950 MHz.....	23
Table 2-5	Normal Maneuvers Maximum Values	27
Table 2-6	GPS Tracking Constraints for E-L DLL Discriminators.....	32
Table 2-7	GPS Tracking Constraints for DD DLL Discriminators	33
Table 2-8	SBAS Ranging Source Requirements	37
Table 2-9	SBAS Ranging Function Tracking Constraints.....	37
Table 2-10	Abnormal Maneuvers.....	41
Table 2-11	Non-Numeric Electrical Output Requirements	55
Table 2-12	Lateral Alert Limit	60
Table 2-13	Vertical Alert Limit.....	61
Table 2-14	VDB Environmental Performance Requirements	70
Table 2-15	VDB Antenna Performance Requirements	72
Table 2-16	PAN Environmental Performance Requirements.....	75
Table 2-17	Test Cross-Reference Matrix.....	82
Table 2-18	Test Conditions for Sensitivity and Dynamic Range Tests.....	113
Table 2-19	Test Conditions for Frame-to-Frame Variation Tests	114
Table 2-20	Test Frequencies for Slot-to-Slot Variation Tests	116
Table 2-21	Embedded Synchronization and Ambiguity Resolution Sequence Test Message.....	118
Table 2-22	Test Conditions for Same Slot Co-Channel VDB Rejection Tests	124
Table 2-23	Test Frequencies for Adjacent Slot Co-Channel VDB Rejection Tests	125
Table 2-24	Test Conditions for Co-Channel VOR Rejection Tests.....	126
Table 2-25	Test Conditions for Co-Channel Localizer Rejection Tests	128
Table 2-26	Test Conditions for 1 st Adjacent Channel VDB Rejection Tests.....	129
Table 2-27	Test Conditions for 2 nd Adjacent Channel VDB Rejection Tests.....	129
Table 2-28	Test Conditions for 3 rd Adjacent Channel VDB Rejection Tests	130
Table 2-29	Test Conditions for 1 st Adjacent Channel VOR Rejection Tests.....	130
Table 2-30	Test Conditions for 2 nd Adjacent Channel VOR Rejection Tests.....	131
Table 2-31	Test Conditions for 3 rd Adjacent Channel VOR Rejection Tests	131
Table 2-32	Test Conditions for 1 st Adjacent Channel Localizer Rejection Tests.....	132
Table 2-33	Test Conditions for 2 nd Adjacent Channel Localizer Rejection Tests	132
Table 2-34	Test Conditions for 3 rd Adjacent Channel Localizer Rejection Tests.....	133
Table 2-35	Test Conditions for Rejection Tests with No On-Channel VDB Signal	133
Table 2-36	Test Frequencies for VDB Interference Immunity Tests	136
Table 2-37	Test Conditions for Desensitization Tests.....	138
Table 2-38	Test Conditions for Intermodulation Rejection Tests.....	140
Table 2-39	Test Frequencies for Receiver VSWR Tests	141
Table 2-40	Test Frequencies for Horizontal Antenna Gain Tests	142
Table 2-41	Test Frequencies for Vertical Antenna Gain Tests.....	145
Table 2-42	Steady-State Accuracy Test CWI Values.....	151
Table 2-43	Satellite Equivalent Power Spectral Density	151
Table 2-44	Pass Threshold Table	154
Table B-1	LAAS Requirements Changes Between DO-253 and DO-253A.....	B-1
Table B-2	LAAS Requirements Changes Between DO-253A and DO-253B.....	B-4
Table C-1	The FAS Definition Parameters.....	C-1
Table D-1	Out-of-Band Pulse Interference	D-3
Table D-2	In-Band and Near-Band Interference Bandwidth Definitions.....	D-4
Table D-3	In-Band And Near-Band Pulse Interference	D-4
Table D-4	Effective Noise Density for all GNSS Sources.....	D-5

Table D-5	Frequency Selectivity	D-5
Table F-1	Example of NUC_r Determination Including Sensor Integration Time.....	F-2

This page is intentionally left blank.

1 PURPOSE AND SCOPE

1.1 Introduction

This document contains minimum operational performance standards (MOPS) for airborne navigation equipment using the Global Positioning System (GPS) augmented by the Local Area Augmentation System (LAAS). These standards are derived from the requirements specified in RTCA DO-245(), *Minimum Aviation System Performance Standards (MASPS) for the Local Area Augmentation System (LAAS)*. Throughout this document, the term “LAAS” is used as a generic reference to ground-based augmentation systems (GBAS) as defined by the International Civil Aviation Organization (ICAO), as the requirements in this standard are intended to comply with the ICAO Standards and Recommended Practices (SARPs) for the GBAS aircraft element.

The standards in this document define minimum performance requirements, functions and features for LAAS airborne equipment to support Category I (CAT I) precision approach operations. This standard also covers the computation and output of position, velocity, and time (PVT) to support area navigation and other applications.

Note: The requirements for area navigation systems continue to evolve. Applicable standards include RTCA/DO-236(), RTCA/DO-229(), RTCA/DO-187() [as amended by TSO-C115()] and RTCA/DO-208() [as amended by TSO-C129()].

Compliance with these standards by manufacturers, installers and users is recommended as a means of assuring that the equipment will satisfactorily perform its intended functions under conditions encountered in routine aeronautical operations.

The regulatory application of these standards is the responsibility of appropriate government agencies. In the United States, the Federal Aviation Administration (FAA) has published two Technical Standard Orders (TSO) for GPS/LAAS equipment, one for the LAAS VHF Data Broadcast (VDB) receiver function (TSO-C162) and another for the LAAS Position And Navigation (PAN) function (TSO-C161). The FAA plans to update these TSOs.

The word "equipment", as used in this document, includes all components or units necessary (as determined by the equipment manufacturer or installer) to properly perform its intended function.

In this document, the term “shall” is used to indicate requirements. An approved design would comply with every requirement, which can be assured by inspection, test, analysis, or demonstration. The term “must” is used to identify items which are important but are either duplicated somewhere else in the document as a “shall”, or are considered to be outside the scope of this document. The term “should” is used to denote a recommendation that would improve the LAAS equipment, but does not constitute a minimum requirement.

This document facilitates traceability by identifying each specific requirement with a requirement designator. The notation “[LAAS-xxx]”, where xxx is a three-digit number, identifies each specific requirement for traceability purposes.