

RTCA, Inc.  
1828 L Street, NW, Suite 805  
Washington, DC 20036-5133 USA

**Minimum Operational Performance Standards  
(MOPS) for GPS Local Area Augmentation  
System (LAAS) Airborne Equipment**

RTCA DO-253C  
December 16, 2008

Prepared by: SC-159  
© 2008 RTCA, Inc.

Copies of this document may be obtained from

RTCA, Inc.

Telephone: 202-333-9439

Facsimile: 202-333-4434

Internet: [www.rtca.org](http://www.rtca.org)

Please visit the RTCA Online Store for document pricing and ordering information.

## Foreword

This document was prepared by RTCA Special Committee 159 (SC-159) and approved by the RTCA Program Management Committee (PMC) on December 16, 2008.

RTCA, Incorporated is a not-for-profit corporation formed to advance the art and science of aviation and aviation electronic systems for the benefit of the public. The organization functions as a Federal Advisory Committee and develops consensus-based recommendations on contemporary aviation issues. RTCA's objectives include but are not limited to:

- Coalescing aviation system user and provider technical requirements in a manner that help government and industry meet their mutual objectives and responsibilities;
- Analyzing and recommending solutions to the system technical issues that aviation faces as it continues to pursue increased safety, system capacity, and efficiency;
- Developing consensus on the application of pertinent technology to fulfill user and provider requirements, including development of Minimum Operation Performance Standards (MOPS) for electronic systems and equipment that support aviation and
- Assisting in developing the appropriate technical material upon which positions for the International Civil Aviation Organization (ICAO) and the International Telecommunication Union (ITU) and other appropriate international organizations can be based.

The recommendations of RTCA are often used as the basis for government and private sector decisions as well as the foundation for many Federal Aviation Administration Technical Standard Orders (TSO).

Since RTCA is not an official agency of the United States Government, its recommendations may not be regarded as statements of official government policy unless so enunciated by the U.S. government organization or agency having statutory jurisdiction over any matters to which the recommendations relate.

Currently in preview, click buy full version

This page is intentionally left blank

## Table of Contents

<b>1</b>	<b>PURPOSE AND SCOPE .....</b>	<b>1</b>
1.1	Introduction .....	1
1.2	System Overview .....	3
1.3	Operational Goals.....	4
1.3.1	GBAS Approach Service Types .....	4
1.3.2	Notable Changes from Previous Version.....	4
1.4	LAAS Airborne Equipment Functions.....	7
1.5	Assumptions.....	7
1.5.1	GPS Signal-in-Space .....	7
1.5.2	SBAS Signal-in-Space.....	7
1.5.3	LAAS Signal-in-Space .....	7
1.5.4	GPS/LAAS Applications .....	7
1.5.5	Applicability .....	7
1.5.6	LAAS Ground Subsystem .....	8
1.5.7	Interoperability .....	8
1.5.8	RF Interference.....	8
1.6	Test Considerations.....	8
1.6.1	Environmental Tests .....	9
1.6.2	Bench Tests .....	9
1.6.3	Installed Tests.....	9
1.7	Applicable Standards and Regulatory Documents.....	9
<b>2</b>	<b>EQUIPMENT PERFORMANCE REQUIREMENTS AND TEST PROCEDURES.....</b>	<b>13</b>
2.1	General GPS/LAAS Airborne Requirements .....	13
2.1.1	Airworthiness .....	14
2.1.2	Intended Function.....	14
2.1.3	Fire Protection .....	14
2.1.4	General Human Factors Requirements and Applicable Documents.....	14
2.1.4.1	Operation of Controls .....	15
2.1.4.2	Accessibility of Controls .....	15
2.1.4.3	Control Labels .....	15
2.1.4.4	Equipment Operating Procedures .....	16
2.1.4.5	Minimum Workload Functions.....	16
2.1.4.6	Displays.....	16
2.1.4.6.1	Discriminability.....	16
2.1.4.6.2	Brightness, Contrast, and Color .....	17
2.1.4.6.3	Angle of Regard .....	17
2.1.4.6.4	Symbology .....	17
2.1.4.6.5	Alphanumerics .....	17
2.1.4.7	Annunciations.....	18
2.1.4.7.1	Annunciators .....	18
2.1.4.7.2	Pilot Indications.....	18
2.1.5	Effects of Test.....	18

<b>2.2</b>	<b>VHF Data Broadcast (VDB) Receiver Subsystem .....</b>	<b>18</b>
2.2.1	General Requirements .....	18
2.2.1.1	Design Assurance .....	19
2.2.1.1.1	Hardware .....	19
2.2.1.1.2	Software .....	19
2.2.2	Tuning .....	20
2.2.2.1	Frequency Range .....	20
2.2.2.2	Frequency Selection .....	20
2.2.2.3	Response Time .....	20
2.2.3	Data Latency .....	20
2.2.4	Data Format Decoding .....	21
2.2.5	Message Failure Rate .....	21
2.2.6	VDB Signal Tracking Requirements .....	21
2.2.6.1	Carrier Frequency Capture Range .....	21
2.2.6.2	Carrier Frequency Slew Rate .....	22
2.2.6.3	Symbol Rate Tolerance .....	22
2.2.7	Co-Channel Rejection .....	22
2.2.7.1	VDB as the Undesired Signal .....	22
2.2.7.2	VOR as the Undesired Signal .....	22
2.2.7.3	ILS Localizer as the Undesired Signal .....	22
2.2.8	Adjacent Channel Rejection .....	22
2.2.8.1	1 <sup>st</sup> Adjacent 25 kHz Channels ( $\pm 25$ kHz) .....	22
2.2.8.2	2 <sup>nd</sup> Adjacent 25 kHz Channels ( $\pm 50$ kHz) .....	23
2.2.8.3	3 <sup>rd</sup> Adjacent 25 kHz Channels ( $\pm 75$ kHz) and Beyond .....	23
2.2.9	Out-of-Band Rejection .....	23
2.2.9.1	VDB Interference Immunity .....	23
2.2.9.2	FM Immunity .....	24
2.2.9.2.1	Desensitization .....	24
2.2.9.2.2	Intermodulation Rejection .....	25
2.2.9.3	Burn Out Protection .....	26
2.2.10	Receiver-to-Antenna Interface .....	26
2.2.10.1	Receiver Voltage Standing Wave Ratio (VSWR) .....	26
2.2.10.2	Antenna Characteristics .....	26
2.2.10.2.1	Horizontally Polarized Antenna Characteristics .....	27
2.2.10.2.1.1	Horizontal Antenna Gain .....	27
2.2.10.2.1.2	Horizontal Antenna VSWR .....	27
2.2.10.2.2	Vertically Polarized Antenna Characteristics .....	27
2.2.10.2.2.1	Vertical Antenna Gain .....	27
2.2.10.2.2.2	Vertical Antenna VSWR .....	28
<b>2.3</b>	<b>Position and Navigation (PAN) Subsystem .....</b>	<b>28</b>
2.3.1	General .....	28
2.3.2	Design Assurance .....	28
2.3.2.1	Hardware .....	28
2.3.2.2	Software .....	29
2.3.3	Interference and Dynamics Environment .....	29
2.3.4	Approach and Reference Station Selection .....	29
2.3.5	Reference Data Selectors and Frequency Mapping .....	30
2.3.6	GNSS Receiver Function .....	30
2.3.6.1	Ranging Sources .....	30
2.3.6.2	Sensitivity and Dynamic Range .....	31
2.3.6.3	Equipment Burnout Protection .....	33
2.3.6.4	GPS Signal Processing .....	33
2.3.6.4.1	GPS Tracking Constraints .....	34
2.3.6.4.2	Correlation Peak Validation .....	38
2.3.6.4.3	GPS Satellite Acquisition Time .....	38

2.3.6.4.4	GPS Satellite Reacquisition Time .....	38
2.3.6.4.5	GPS Satellite Initial Acquisition Time .....	38
2.3.6.5	SBAS Signal Processing.....	39
2.3.6.6	Smoothing.....	40
2.3.6.6.1	GAST D Smoothing Requirement.....	41
2.3.6.7	Measurement Quality Monitoring .....	41
2.3.6.8	Accuracy.....	42
2.3.6.8.1	GPS Satellites.....	42
2.3.6.8.1.1	Equipment Class Specific Accuracy Requirements .....	43
2.3.6.8.2	SBAS Satellites .....	43
2.3.6.9	Integrity in the Presence of Interference.....	44
2.3.6.10	Integrity in the Presence of Abnormal Dynamics .....	44
2.3.6.11	Airborne Code Carrier Divergence Filtering .....	45
2.3.7	Message Processing Function.....	46
2.3.7.1	VDB Message Validity Check.....	46
2.3.7.2	VDB Message Block Identifier Check .....	46
2.3.7.3	VDB Message Authentication Protocols .....	46
2.3.7.4	Message Processing Requirements for Forward Compatibility.....	47
2.3.8	Corrected Pseudorange.....	48
2.3.8.1	Conditions for Use of Differential Corrections.....	48
2.3.8.1.1	Ephemeris CRC Conditions .....	48
2.3.8.1.2	Reference Time Conditions.....	48
2.3.8.1.3	Other Ranging Source Conditions.....	49
2.3.8.1.3.1	Ranging Source Conditions for AEC D equipment .....	50
2.3.8.2	Application of Differential Corrections.....	50
2.3.8.2.1	Application of Differential Corrections for 100 Second Smoothed Pseudoranges .....	51
2.3.8.2.2	Application of Differential Corrections for 50 Second Smoothed Pseudoranges .....	52
2.3.8.3	Tropospheric Correction.....	52
2.3.9	LAAS Differential Position Requirements .....	52
2.3.9.1	Differential Position Solution – One Acceptable Means .....	53
2.3.9.2	Service Type Specific Differential Position Solution Requirements.....	55
2.3.9.2.1	Differential Position Solution for the GBAS Positioning Service.....	55
2.3.9.2.2	Differential Position Solution for Approach Service GAST C.....	55
2.3.9.2.3	Differential Position Solution for Approach Service GAST D .....	56
2.3.9.3	Dual Solution Ionospheric Gradient Monitoring .....	56
2.3.9.4	Satellite Geometry Screening .....	56
2.3.9.5	Differential Correction Magnitude Check .....	57
2.3.9.6	Fault Detection .....	58
2.3.9.6.1	Fault Detection for Satellite Addition .....	58
2.3.10	Position, Velocity, and Time (PVT) Outputs.....	59
2.3.10.1	Message Processing -- GBAS ID Selection.....	59
2.3.10.2	Protective Level, Ephemeris Error Bound, & Figures of Merit.....	59
2.3.10.3	Figures of Merit Outputs .....	62
2.3.10.4	PVT Output Latency.....	63
2.3.10.5	Velocity Accuracy .....	63
2.3.11	Precision Approach Guidance Outputs.....	63
2.3.11.1	Message Processing.....	63
2.3.11.1.1	FAS Data Block Selection and Confirmation.....	64
2.3.11.1.2	GBAS ID Selection .....	64
2.3.11.1.3	Approach Service Type (AST) Selection .....	64
2.3.11.1.3.1	AST Selection for Single Approach Service Type Capable Equipment .....	64
2.3.11.1.3.2	AST Selection for Multiple Approach Service Type Capable Airborne Equipment.....	64
2.3.11.1.3.3	Approach Service Type Output.....	65
2.3.11.2	Precision Approach Region .....	65
2.3.11.3	Approach Status Verification.....	66
2.3.11.4	Ground Continuity Integrity Designator (GCID) Conditions .....	66

2.3.11.5	Outputs .....	66
2.3.11.5.1	Deviations .....	66
2.3.11.5.1.1	Lateral Deviations for the Approach Segment .....	68
2.3.11.5.1.1.1	Proportional Lateral Deviation .....	68
2.3.11.5.1.1.2	Rectilinear Lateral Deviation .....	69
2.3.11.5.1.2	Vertical Deviations for the Approach Segment .....	69
2.3.11.5.1.2.1	Proportional Vertical Deviation .....	70
2.3.11.5.1.2.2	Rectilinear Vertical Deviation .....	71
2.3.11.5.1.3	Deviation Output Rate and Latency .....	71
2.3.11.5.1.4	Missed Approach Guidance .....	72
2.3.11.5.2	Alerts .....	72
2.3.11.5.2.1	Loss of Approach Guidance .....	72
2.3.11.5.2.1.1	Loss of Approach Guidance – GAST C .....	72
2.3.11.5.2.1.2	Loss of Approach Guidance – GAST D .....	72
2.3.11.5.2.1.3	Alert Limits .....	74
2.3.11.5.2.1.3.1	Lateral Alert Limits .....	74
2.3.11.5.2.1.3.2	Vertical Alert Limits .....	75
2.3.11.5.2.1.4	Lateral and Vertical Protection Levels .....	75
2.3.11.5.2.1.5	Vertical and Lateral Ephemeris Error Position Bounds .....	78
2.3.11.5.2.2	Bias Approach Monitor (BAM) .....	80
2.3.11.5.2.3	Reference Receiver Fault Monitor (RRFM) .....	80
2.3.11.5.2.4	Protection Levels - Service Type Specific Requirements .....	81
2.3.11.5.3	Distance to Threshold .....	82
2.3.11.5.3.1	Distance to Threshold Output .....	82
2.3.11.5.3.2	Distance to Threshold Output Latency .....	82
2.3.12	Error Models .....	82
2.3.12.1	Model of Airborne Pseudorange Performance .....	82
2.3.12.2	Model of Tropospheric Residual Uncertainty .....	84
2.3.12.3	Model of Ionospheric Residual Uncertainty .....	84
<b>2.4</b>	<b>Equipment Performance Environmental Conditions .....</b>	<b>85</b>
2.4.1	Environmental Tests .....	86
2.4.1.1	VDB Required Performance .....	86
2.4.1.1.1	Antenna Test .....	91
2.4.1.1.2	System Accuracy .....	91
2.4.1.2	PAN Required Performance .....	91
2.4.1.2.1	Accuracy .....	93
2.4.1.2.2	Sensitivity and Dynamic Range .....	93
2.4.1.2.3	System Coverage .....	93
2.4.1.3	Clarification of Environmental Tests .....	94
2.4.1.3.1	Power Output Tests .....	94
2.4.1.3.2	Temperature Tests .....	94
2.4.1.3.3	RF Susceptibility Tests .....	94
2.4.1.3.4	Lightning Induced Transient Susceptibility Tests .....	95
2.4.1.3.5	Lightning Direct Effects Tests .....	95
2.4.1.3.6	Crash Safety Shock .....	95
<b>2.5</b>	<b>Equipment Test Procedures .....</b>	<b>95</b>
2.5.1	Definition of General Test Terms and Conditions .....	95
2.5.1.1	Power Input Voltage .....	95
2.5.1.2	Power Input Frequency .....	96
2.5.1.3	RF Signal Levels .....	96
2.5.1.4	Adjustment of Equipment .....	96
2.5.1.5	Test Instrument Precautions .....	96
2.5.1.6	Ambient Conditions .....	96
2.5.1.7	Warm-Up .....	96

2.5.1.8	Connected Loads .....	96
2.5.1.9	EMI Testing.....	97
2.5.1.10	Analysis .....	97
2.5.1.11	Demonstration .....	97
2.5.1.12	Inspection .....	97
2.5.1.13	Test .....	97
2.5.1.14	Test Cross Reference Matrix .....	97
2.5.2	VDB Receiver Subsystem Test Procedures.....	130
2.5.2.1	Definition of VDB Test Terms and Conditions.....	130
2.5.2.1.1	Standard Test Signals .....	130
2.5.2.1.2	Test Message Format.....	131
2.5.2.1.3	Statistical Sample Size and Pass/Fail Criteria .....	131
2.5.2.1.4	Standard Output.....	132
2.5.2.2	Detailed Test Procedures.....	132
2.5.2.2.1	General Requirements .....	132
2.5.2.2.2	Tuning .....	132
2.5.2.2.2.1	Frequency Range .....	132
2.5.2.2.2.2	Frequency Selection.....	132
2.5.2.2.2.3	Response Time.....	132
2.5.2.2.3	Data Latency .....	134
2.5.2.2.4	Data Format Decoding .....	135
2.5.2.2.5	Message Failure Rate .....	136
2.5.2.2.5.1	Sensitivity and Dynamic Range.....	136
2.5.2.2.5.2	Frame-to-Frame Variations for a Given Slot .....	137
2.5.2.2.5.3	Slot-to-Slot Variations Within a Given Frame .....	139
2.5.2.2.5.4	Training Sequence and Message Failure Rate Test.....	141
2.5.2.2.6	VDB Signal Tracking Requirements.....	143
2.5.2.2.6.1	Carrier Frequency Capture Range.....	143
2.5.2.2.6.2	Carrier Frequency Slew Rate .....	145
2.5.2.2.6.3	Symbol Rate Tolerance.....	146
2.5.2.2.7	Co-Channel Rejection .....	147
2.5.2.2.7.1	VDB as the Undesired Signal.....	147
2.5.2.2.7.2	VOR as the Undesired Signal.....	150
2.5.2.2.7.3	ILS Localizer as the Undesired Signal.....	151
2.5.2.2.8	Adjacent Channel Rejection.....	152
2.5.2.2.9	Out-of-Band Rejection.....	158
2.5.2.2.9.1	VDB Interference Immunity.....	158
2.5.2.2.9.2	FM Immunity.....	160
2.5.2.2.9.2.1	Desensitization.....	160
2.5.2.2.9.2.2	Intermodulation Rejection.....	162
2.5.2.2.10	Receiver-to-Antenna Interface.....	165
2.5.2.2.10.1	Receiver Voltage Standing Wave Ratio (VSWR).....	165
2.5.2.2.10.2	Antenna Characteristics .....	165
2.5.2.2.10.2.1	Horizontal Polarized Antenna.....	165
2.5.2.2.10.2.1.1	Horizontal Antenna Gain .....	165
2.5.2.2.10.2.1.2	Horizontal Antenna VSWR.....	167
2.5.2.2.10.2.2	Vertical Polarized Antenna Characteristics.....	168
2.5.2.2.10.2.2.1	Vertical Antenna Gain .....	168
2.5.2.2.10.2.2.2	Vertical Antenna VSWR.....	170
2.5.3	Precision Approach Navigator Tests .....	170
2.5.3.1	Definition of PAN Test Terms and Conditions.....	170
2.5.3.1.1	Standard Test Signals and Simulator Requirements.....	170
2.5.3.2	Accuracy.....	172
2.5.3.2.1	Simulator and Interference Conditions.....	173
2.5.3.2.2	Test Procedure.....	175
2.5.3.2.3	SBAS Tracking Bias .....	178

2.5.3.3	Interference Rejection.....	178
2.5.3.3.1	Simulator and Interference Conditions.....	178
2.5.3.3.2	Test Procedures.....	179
2.5.3.3.3	Pass/Fail Determination.....	179
2.5.3.4	Velocity Accuracy and Velocity Figure of Merit Tests.....	180
2.5.3.4.1	Horizontal Velocity Accuracy Test Conditions.....	180
2.5.3.4.1.1	Horizontal Velocity Accuracy Pass/Fail determination.....	182
2.5.3.4.1.2	Horizontal Velocity Figure of Merit Pass/Fail Determination.....	182
2.5.3.4.2	Vertical Velocity Accuracy Test Conditions.....	182
2.5.3.4.2.1	Vertical Velocity Accuracy Pass/Fail determination.....	185
2.5.3.4.2.2	Vertical Velocity Figure of Merit Pass/Fail Determination.....	185
2.5.3.4.3	Optional Additional Tests To Demonstrate an Improved Level of Accuracy.....	186
<b>3</b>	<b>INSTALLED EQUIPMENT PERFORMANCE REQUIREMENTS.....</b>	<b>87</b>
3.1	General Performance Requirement.....	187
3.2	Interference Effects.....	187
3.3	Inadvertent Turnoff.....	187
3.4	Test Environment.....	187
3.5	Associated Equipment or Systems.....	187
3.6	Environmental Conditions.....	187
3.7	Adjustment of Equipment.....	188
3.8	Warm-Up Period.....	188
3.9	GPS Antenna and Installation Requirements.....	188
3.10	VDB Aircraft Implementation Factor.....	188
3.11	GNSS Electromagnetic Compatibility.....	188
3.12	VDB Electromagnetic Compatibility.....	189
3.13	Equipment Interfaces.....	189
<b>4</b>	<b>OPERATIONAL PERFORMANCE REQUIREMENTS.....</b>	<b>191</b>
4.1	Alert Presentation.....	191
4.2	Guidance Reference Point.....	191
4.3	Missed Approach Guidance.....	191
<b>5</b>	<b>MEMBERSHIP.....</b>	<b>193</b>

**Appendices**

Appendix A	Acronyms, Abbreviations, and Definitions
Appendix B	Requirements Changes Between Versions
Appendix C	Final Approach Segment and Deviation Example
Appendix D	Standard GPS Interference Environment
Appendix E	(Reserved)
Appendix F	(Reserved)
Appendix G	Rotorcraft Point-in-Space (PinS) Approach Operations to Heliports
Appendix H	Test Considerations
Appendix I	Service Types, Facility Classifications and Airborne Equipment Classifications
Appendix J	Example Derivation of Airborne Receiver Geometry Screening Requirements

## Table of Figures

Figure 1-1	GPS/LAAS System .....	3
Figure 1-2	LAAS Airborne Equipment Functions .....	6
Figure 1-3	VDB Receiver Functional Block Diagram .....	7
Figure 2-1	Maximum Tolerable Equal-Level FM Broadcast Signals .....	26
Figure 2-2	Antenna with Preamplifier Configuration .....	33
Figure 2-3	Receiver Bandwidth vs. Average Correlator Spacing .....	37
Figure 2-4	Pseudorange Processing .....	51
Figure 2-5	Precision Approach Region .....	65
Figure 2-6	Final Approach Segment Definition .....	67
Figure 2-7	Full-Scale Deflection for Proportional Lateral Deviation .....	69
Figure 2-8	Full-Scale Deflection for Proportional Vertical Deviation .....	71
Figure 2-9	Typical Simulated FM Broadcast Spectrum .....	131
Figure 2-10	Response Time Test Equipment Connection .....	134
Figure 2-11	Data Latency Test Equipment Connection .....	135
Figure 2-12	Data Format Decoding Test Equipment Connection .....	136
Figure 2-13	Sensitivity and Dynamic Range in an AWGN Channel Test Equipment Connection .....	137
Figure 2-14	Frame-to-Frame Timing Diagram 1 .....	139
Figure 2-15	Frame-to-Frame Timing Diagram 2 .....	139
Figure 2-16	Slot-to-Slot (and Frame-to-Frame) Variation Test Equipment Connection .....	141
Figure 2-17	Slot-to-Slot Timing Diagram .....	141
Figure 2-18	Carrier Frequency Capture Range (and Slew Rate) Test Equipment Connection .....	145
Figure 2-19	Symbol Rate Tolerance Test Equipment Connection .....	147
Figure 2-20	VDB/VDB Co-Channel (and Adjacent Channel) Rejection Test Equipment Connection ..	149
Figure 2-21	VOR (ILS) as the Undesired Signal Test Equipment Connection .....	151
Figure 2-22	Interference Immunity Test Equipment Connection .....	160
Figure 2-23	Desensitization Test Equipment Connection .....	162
Figure 2-24	FM Broadcast Intermodulation Rejection Test Equipment Connection .....	164
Figure 2-25	Horizontal (Standard Dipole) Antenna Gain Test Configuration .....	167
Figure 2-26	Horizontal (VDB) Antenna Gain Test Configuration .....	167
Figure 2-27	Vertical (Standard Dipole) Antenna Gain Test Configuration .....	169
Figure 2-28	Vertical (VDB) Antenna Gain Test Configuration .....	170
Figure C-1	Final Approach Segment Definition .....	C-2
Figure C-2	Lateral Deviations .....	C-4
Figure C-3	GLS Elevation Reference Point Definition .....	C-5
Figure C-4	GLS Vertical Deviation Definition .....	C-6
Figure D-1	Interference Levels at the Antenna Port .....	D-2
Figure D-2	In-Band and Near-Band Interference Environments .....	D-2
Figure D-3	Frequency Selectivity .....	D-6
Figure G-1	Lateral Display Scaling and Orientation of the FTP to the Heliport .....	G-1
Figure G-2	Vertical Display Scaling .....	G-2
Figure H-1	Pseudorange Accuracy Test Pass Criteria .....	H-2
Figure H-2	Pseudorange Accuracy Test Pass Probability .....	H-3
Figure H-3	Example Test Set-up .....	H-3
Figure I-1	Service Types, Facility Classifications and Airborne Equipment Classes .....	I-1
Figure I-2	Relationship between GBAS Facility Classification and Approach Facility Designation ..	I-5
Figure J-1	Limit on the Probability that a Range Error Due to a Fault with Magnitude $ E_R $ Goes Undetected by Ground Reference Station Monitoring .....	J-2
Figure J-2	Notional Examples of Unsuccessful Landing Probability .....	J-7

## Table of Tables

Table 2-1	GPS/LAAS Airborne Equipment Output Requirements .....	13
Table 2-2	Frequency and Power of Undesired Signals.....	24
Table 2-3	Desensitization Frequency and Power Requirements That Apply for VDB Frequencies 108.000 to 111.975 MHz.....	24
Table 2-4	Desensitization Frequency and Power Requirements That Apply for VDB Frequencies 112.000 to 117.950 MHz.....	25
Table 2-5	Normal Maneuvers Maximum Values .....	29
Table 2-6	GPS Tracking Constraints for E-L DLL Discriminators.....	34
Table 2-7	GPS Tracking Constraints for DD DLL Discriminators .....	35
Table 2-8	SBAS Ranging Source Requirements .....	39
Table 2-9	SBAS Ranging Function Tracking Constraints.....	40
Table 2-10	Abnormal Maneuvers.....	44
Table 2-11	RPI First Character Mapping to SSID.....	47
Table 2-12	Summary of Service Type Specific Requirements for Weighting Computations .....	54
Table 2-13	Non-Numeric Electrical Output Requirements .....	68
Table 2-14	Lateral Alert Limit .....	74
Table 2-15	Vertical Alert Limit.....	75
Table 2-16	Fault-free Missed Detection Multiplier ( $K_{ffmd}$ ) .....	76
Table 2-17	Missed Detection Multiplier ( $K_{md}$ ) .....	78
Table 2-18	Service Type Dependent Parameters Used in Protection Level Calculations .....	82
Table 2-19	VDB Environmental Performance Requirements .....	87
Table 2-20	VDB Antenna Performance Requirements .....	89
Table 2-21	PAN Environmental Performance Requirements.....	92
Table 2-22	Test Cross-Reference Matrix.....	99
Table 2-23	Test Conditions for Sensitivity and Dynamic Range Tests .....	137
Table 2-24	Test Conditions for Frame-to-Frame Variation Tests .....	139
Table 2-25	Test Frequencies for Slot-to-Slot Variation Tests .....	140
Table 2-26	Embedded Synchronization and Ambiguity Resolution Sequence Test Message.....	142
Table 2-27	Test Conditions for Same Slot Co-Channel VDB Rejection Tests .....	148
Table 2-28	Test Frequencies for Adjacent Slot Co-Channel VDB Rejection Tests .....	150
Table 2-29	Test Conditions for Co-Channel VOR Rejection Tests.....	151
Table 2-30	Test Conditions for Co-Channel Localizer Rejection Tests .....	152
Table 2-31	Test Conditions for 1 <sup>st</sup> Adjacent Channel VDB Rejection Tests.....	153
Table 2-32	Test Conditions for 2 <sup>nd</sup> Adjacent Channel VDB Rejection Tests.....	154
Table 2-33	Test Conditions for 3 <sup>rd</sup> Adjacent Channel VDB Rejection Tests .....	154
Table 2-34	Test Conditions for 1 <sup>st</sup> Adjacent Channel VOR Rejection Tests.....	155
Table 2-35	Test Conditions for 2 <sup>nd</sup> Adjacent Channel VOR Rejection Tests.....	155
Table 2-36	Test Conditions for 3 <sup>rd</sup> Adjacent Channel VOR Rejection Tests .....	155
Table 2-37	Test Conditions for 1 <sup>st</sup> Adjacent Channel Localizer Rejection Tests.....	156
Table 2-38	Test Conditions for 2 <sup>nd</sup> Adjacent Channel Localizer Rejection Tests.....	156
Table 2-39	Test Conditions for 3 <sup>rd</sup> Adjacent Channel Localizer Rejection Tests.....	157
Table 2-40	Test Conditions for Rejection Tests with No On-Channel VDB Signal .....	157
Table 2-41	Test Frequencies for VDB Interference Immunity Tests .....	160
Table 2-42	Test Conditions for Desensitization Tests.....	162
Table 2-43	Test Conditions for Intermodulation Rejection Tests.....	164
Table 2-44	Test Frequencies for Receiver VSWR Tests .....	165
Table 2-45	Test Frequencies for Horizontal Antenna Gain Tests .....	166
Table 2-46	Test Frequencies for Vertical Antenna Gain Tests.....	169
Table 2-47	Steady-State Accuracy Test CWI Values.....	174
Table 2-48	Satellite Equivalent Power Spectral Density.....	175
Table 2-49	Pass Threshold Table .....	177
Table 2-50	Platform Dynamics For Horizontal Velocity Accuracy Test .....	181
Table 2-51	Platform Dynamics For Vertical Velocity Accuracy Test.....	184

Table B-1	LAAS Requirements Changes Between DO-253 and DO-253A.....	B-1
Table B-2	LAAS Requirements Changes Between DO-253A and DO-253B.....	B-4
Table B-3	LAAS Requirements Changes Between DO-253B and DO-253C.....	B-5
Table C-1	The FAS Definition Parameters.....	C-1
Table D-1	Out-of-Band Pulse Interference.....	D-3
Table D-2	In-Band and Near-Band Interference Bandwidth Definitions.....	D-4
Table D-3	In-Band And Near-Band Pulse Interference.....	D-4
Table D-4	Effective Noise Density for all GNSS Sources.....	D-5
Table D-5	Frequency Selectivity.....	D-5

# 1 PURPOSE AND SCOPE

## 1.1 Introduction

This document contains minimum operational performance standards (MOPS) for airborne navigation equipment using the Global Positioning System (GPS) augmented by the Local Area Augmentation System (LAAS). These standards are partially derived from the requirements specified in RTCA DO-245(), *Minimum Aviation System Performance Standards (MASPS) for the Local Area Augmentation System (LAAS)*. Additional requirements have been derived by analysis of operational intent and direct allocation of performance requirements between airborne and ground systems. Throughout this document, the term "LAAS" is used as a generic reference to ground-based augmentation systems (GBAS) as defined by the International Civil Aviation Organization (ICAO), as the requirements in this standard are intended to comply with the ICAO Standards and Recommended Practices (SARPs) for the GBAS aircraft element.

*Note: At the time of this writing, the ICAO SARPs (through Amendment 82) have not been updated to include requirements for GBAS to support a type of service appropriate for conducting CAT II/III operations. Consequently, some requirements in this MOPS are beyond the requirements in the SARPs.*

The standards in this document define minimum performance requirements, functions and features for LAAS airborne equipment to support multiple types of service that are intended to support precision approach operations for all weather minimums. This standard also covers the computation and output of position, velocity, and time (PVT) to support area navigation and other applications.

*Note: The requirements for area navigation systems continue to evolve. Applicable standards include RTCA/DO-236(), RTCA/DO-229(), RTCA/DO-187() [as amended by TSO-C115()] and RTCA/DO-208() [as amended by TSO-C129()].*

Compliance with these standards by manufacturers, installers and users is recommended as a means of assuring that the equipment will satisfactorily perform its intended functions under conditions encountered in routine aeronautical operations.

The regulatory application of these standards is the responsibility of appropriate government agencies. In the United States, the Federal Aviation Administration (FAA) has published two Technical Standard Orders (TSO) for GPS/LAAS equipment, one for the LAAS VHF Data Broadcast (VDB) receiver function (TSO-C162) and another for the LAAS Position And Navigation (PAN) function (TSO-C161). The FAA plans to update these TSOs. These updated TSOs will continue to reflect the requirements in this MOPS consistent with supporting Category I approaches and the positioning service only. Requirements for Airborne Equipment Class D will be addressed by a subsequent TSO revision or an additional TSO after validation of these requirements.

The word "equipment", as used in this document, includes all components or units necessary (as determined by the equipment manufacturer or installer) to properly perform its intended function.