

RTCA, Inc.
1828 L Street, NW, Suite 805
Washington, DC 20036-5133 USA

**Minimum Aviation System Performance
Standards (MASPS) for Flight Information
Services-Broadcast (FIS-B) Data Link**

Revision A

RTCA DO-267A
April 29, 2004

Prepared by: SC-195
© 2004 RTCA, Inc.

Copies of this document may be obtained from

RTCA, Inc.

Telephone: 202-835-9333

Facsimile: 202-835-9434

Internet: www.rtca.org

Please visit the RTCA Online Store for document pricing and ordering information.

FOREWORD

The original report (DO-267) was prepared by Special Committee 195 (SC-195) and approved by the RTCA Program Management Committee (PMC) on March 27, 2001. Revision A of DO-267 was prepared by SC-195 and approved by the PMC on April 29, 2004. Appendices D, F and I are normative appendices.

RTCA, Incorporated is a not-for-profit corporation formed to advance the art and science of aviation and aviation electronic systems for the benefit of the public. The organization functions as a Federal Advisory Committee and develops consensus-based recommendations on contemporary aviation issues. RTCA's objectives include but are not limited to:

- a. coalescing aviation system user and provider technical requirements in a manner that helps government and industry meet their mutual objectives and responsibilities;
- b. analyzing and recommending solutions to the system technical issues that aviation faces as it continues to pursue increased safety, system capacity and efficiency;
- c. developing consensus on the application of pertinent technology to fulfill user and provider requirements, including development of minimum operational performance standards for electronic systems and equipment that support aviation; and
- d. assisting in developing the appropriate technical material upon which positions for the International Civil Aviation Organization and the International Telecommunication Union and other appropriate international organizations can be based.

The organization's recommendations are often used as a basis for government and private sector decisions as well as the foundation for many Federal Aviation Administration Technical Standard Orders.

Since RTCA is not an official agency of the United States Government, its recommendations may not be regarded as statements of official government policy unless so enunciated by the U.S. government organization or agency have statutory jurisdiction over any matters to which the recommendations relate.

This page intentionally left blank.

Currently in preview, click buy full version

EXECUTIVE SUMMARY

This document contains Minimum Aviation System Performance Standards (MASPS) for Flight Information Services-Broadcast (FIS-B), an automated, digital data link system. The FIS-B system will provide timely access to data link updates of non-control, advisory information needed by pilots to operate safely and efficiently in the National Airspace System and in international airspace.

The format of this document generally follows that of an RTCA Minimum Operational Performance Specification (MOPS). However, a traditional MOPS is not appropriate for FIS-B since this document establishes system performance rather than requirements for specific equipment. This MASPS supports interoperability between providers of ground and airborne FIS processing systems by defining a broadcast protocol that may be used in any broadcast medium (i.e., VHF, satellite). The MASPS also provides design guidelines and recommended standards for airborne processing and display of FIS products.

The FIS-B broadcast network organization described in the MASPS consists of a physical layer, an International Standards Organization (ISO) standard-based Data Link Services (DLS) layer, a Network layer, an FIS-B Application Service Element (ASE), and an FIS-B Application. The physical layer is supplied by the manufacture with all the other layers and/or elements defined in the MASPS.

The FIS-B Application Service Element (ASE), noted above, provides connectionless unacknowledged protocol services to include support for the segmentation (and reassembly) of large data files into Application Protocol Data Units (APDUs). Segmenting large application data files into smaller APDUs reduces the amount of data lost due to any data link impairments. The MASPS also establishes a publicly accessible FIS-B Product Registry that facilitates coordination and publication of specifications for APDU Payload encoding of new FIS products.

The MASPS guidance for airborne processing and display of FIS products is applicable to any display of FIS information in the flight deck (or cockpit). It is anticipated that most avionics that process and display FIS products will be approved using existing type certification or supplemental type certification processes such as TSO C113, Airborne Multipurpose Electronic Displays. Consequently, this document only contains guidance that is unique to FIS-B and independent of other functions that are governed by other directives such as terrain and obstacles, and traffic.

As the National Airspace System (NAS) evolves and the concepts of Free Flight are implemented, the requirement for use of FIS products and services may change from being advisory in nature to being required for safety of flight. Any such required use will require a revised definition of the operating environment outlined in the MASPS to include the associated application of Required Communications Performance (RCP) criteria. The introduction of such RCP criteria will require changes to this MASPS, especially to Section 3.0, System Performance Specifications, and Section 4.0, Procedures for Performance Requirement Verification.

This page intentionally left blank.

TABLE OF CONTENTS

1	PURPOSE AND SCOPE	1
1.1	Introduction	1
1.2	System Overview	2
1.3	Operational Applications	4
1.4	Future Applications.....	5
1.5	Scope and Objectives	5
1.6	Assumptions.....	7
1.7	Verification Procedures.....	7
1.8	Definition of Terms.....	8
2	SYSTEM PERFORMANCE SPECIFICATION	9
2.1	Airborne Equipment General Requirements	9
2.1.1	Equipment Compliance	9
2.1.2	Priority Service.....	9
2.1.3	Interoperability	9
2.1.4	Abstract Syntax Notation (ASN) Reference.....	9
2.2	FIS-B Functional Requirements.....	10
2.2.1	Lossless Compression	10
2.2.2	Lossless Display of the Most Intense or Severe Condition	10
2.2.3	Verification of Data Link Integrity.....	10
2.2.4	Positive Indication of Missing Data	10
2.2.5	Indication Associated with the Loss of Data Link	10
2.2.6	Product Type Indication	10
2.2.7	Product Age Indication.....	11
2.2.8	Product Validity Indication	11
2.2.9	Standard Display Scheme for Weather Data.....	11
2.2.10	Product Geographic Location.....	11
2.2.11	FIS-B Content.....	11
2.2.11.1	Composite/Mosaic Products	11
2.2.11.2	Product Discard	11
2.2.11.2.1	Weather Product Discard	12
2.2.12	Application Service Element.....	12
2.2.13	Application Protocol Data Unit (APDU) Header	12
3	SUBSYSTEM/FUNCTION PERFORMANCE REQUIREMENTS.....	13
3.1	FIS-B Network Interface.....	13
3.2	FIS-B Broadcast Network Organization	13
3.3	Physical Layer	13
3.4	Data Link Services Layer (DLS).....	13
3.4.1	General Requirements	14
3.4.2	Flag Field.....	14
3.4.3	Data Transparency Processing	14
3.4.3.1	Synchronous Transparency Processing	14
3.4.3.2	Asynchronous Transparency Processing	14

3.4.4	Address Field.....	15
3.4.4.1	Minimum Addressing.....	15
3.4.5	Link Control Field.....	16
3.4.6	Information Field.....	16
3.4.7	Frame Check Sequence (FCS).....	16
3.5	Network Layer.....	16
3.6	Application Service Element.....	16
3.6.1	Application Protocol Data Unit (APDU).....	17
3.6.1.1	APDU Header.....	18
3.6.2	Segmentation into APDUs and Reassembly.....	18
3.6.2.1	APDU Length.....	18
3.6.2.2	Segmentation of Product File into Linked APDUs.....	18
3.6.2.3	Reassembly of Linked APDUs to Form an FIS-B Product File.....	19
3.6.3	Application File Selection and Conversion.....	21
3.7	FIS-B Application Layer.....	21
3.8	Design Guidelines & Recommended Standards for Airborne Processing & Display of FIS Products.....	21
3.8.1	Airborne Processing and Display.....	22
3.8.1.1	Product Title.....	23
3.8.1.2	Product Age.....	23
3.8.1.2.1	Weather Product Age.....	23
3.8.1.3	Product Legend.....	24
3.8.1.4	Missing Data.....	25
3.8.1.5	Product Mapping or Location.....	25
3.8.1.6	Text Product Format Criteria.....	25
3.8.1.7	Text Product Display Features.....	26
3.8.1.8	Data Blocks.....	27
3.8.1.9	Symbols.....	27
3.8.1.10	Combined Graphical and Textual Displays.....	27
3.8.1.11	Multiple Page Displays.....	27
3.8.1.12	General Display Features.....	27
3.8.2	Use of Color, Textures and Symbols.....	28
3.8.2.1	Color Philosophy in FIS Graphics.....	28
3.8.2.1.1	FIS Graphics - Weather.....	28
3.8.2.1.2	FIS Graphics - Airspace.....	29
3.8.2.2	Color & Symbol Characterization Chart.....	29
3.8.3	Integrated Display Formats Combining Layers of FIS Graphics and Text.....	30
4	PROCEDURES FOR PERFORMANCE REQUIREMENT VERIFICATION.....	33
4.1	Assumptions.....	33
4.2	Verification.....	33
4.2.1	Equipment Configuration.....	35
4.2.2	Sequence of Verification.....	35
4.2.3	Standard Test Data.....	35
4.3	FIS-B Frame and APDU Header Processing.....	36
4.3.1	Conditions of Test/Test Objectives.....	37
4.3.2	Detailed Test and Demonstration Procedures.....	38
4.3.2.1	Lossless Process, Lossless Compression Test Procedures.....	38
4.3.2.2	FIS-B Frame and APDU Header Processing Test Procedures.....	38
4.4	FIS-B Display Conformance.....	39

4.4.1	Conditions of Test Procedures/Test Objectives.....	40
4.4.2	Detailed Test Procedures.....	41
4.4.2.1	Faithful Display of Data Test Procedures.....	41
MEMBERSHIP.....		43
APPENDIX A	ACRONYMS AND ABBREVIATIONS	A-1
APPENDIX B	GLOSSARY OF TERMS	B-1
APPENDIX C	LIST OF REFERENCES	C-1
APPENDIX D	APDU FORMAT (NORMATIVE).....	D-1
D.1	Subnetwork Access Protocol Identification.....	D-1
D.2	Product Descriptor Fields.....	D-2
D.2.1	Product Identifier.....	D-3
D.2.2	Compression Method	D-3
D.2.2.1	Run Length Encoding Compression Method 1.....	D-4
D.2.2.2	Run Length Encoding Compression Method 2.....	D-5
D.2.2.3	DEFLATE Compression Method.....	D-6
D.2.2.4	Weather-Huffman (WH) Method of Data Compression of Weather Images	D-6
D.2.2.5	PNG and MNG Image Formats	D-7
D.2.3	Geographic Reference Method or File Format.....	D-7
D.2.3.1	Cylindrical Equidistant.....	D-8
D.2.3.2	Lambertian.....	D-9
D.2.3.3	Polar Stereographic.....	D-9
D.2.3.4	GeoTIFF File Format.....	D-12
D.2.3.5	Global Block Representation.....	D-13
D.2.3.5.1	The Use of “Bins” and “Blocks”.....	D-13
D.2.3.5.2	Global Block Numbering Plan.....	D-13
D.2.3.5.2.1	Grid Layout.....	D-13
D.2.3.5.2.2	The Block Reference Indicator.....	D-14
D.2.3.5.3	Run Length Encoding of Cells within the Block	D-15
D.2.3.5.4	The “Empty” Element.....	D-17
D.2.3.5.4.1	Length and Bitmap Bytes	D-17
D.2.3.5.4.2	Mapping Bits to Blocks	D-18
D.2.3.5.4.3	Prime Meridian Case	D-19
D.2.3.5.5	APDU Payload Format for Graphical Image	D-19
D.2.4	Geographic Location.....	D-20
D.3	Segmentation Fields.....	D-20
D.4	APDU Header Time.....	D-20
D.4.1	Time Options.....	D-20
D.4.2	Month of Year & Day of Month (optional).....	D-21
D.4.3	Time Hours.....	D-21
D.4.4	Time Minutes	D-21
D.4.5	Time Seconds (optional).....	D-21
D.5	Segmentation Data Block.....	D-21
D.5.1	Product File Length Field.....	D-21
D.5.2	APDU Number Field.....	D-21
D.6	Zero Padding.....	D-21
D.7	APDU Payload.....	D-22
D.7.1	Report.....	D-22
D.7.2	Record	D-22

D.7.3	Field.....	D-22
APPENDIX E	FIS-B PRODUCT REGISTRY.....	E-1
E.1	FIS-B Product Registry Control.....	E-1
E.2	FIS-B Product Identifier.....	E-1
E.3	APDU Payload.....	E-2
E.3.1	Operational Products.....	E-2
E.3.2	Developmental Products.....	E-3
E.4	FIS-B Product Registry Application.....	E-3
E.4.1	User Registration.....	E-3
E.4.2	FIS-B Data Link Network Registration.....	E-3
E.4.3	FIS-B Product File Registration.....	E-3
E.4.3.1	Operational Products.....	E-3
E.4.3.2	Developmental Products.....	E-4
APPENDIX F	EXCEPTIONS TO STRICT COMPLIANCE WITH ISO 3309 (NORMATIVE).....	F-1
F.1	VDL Mode 2 Unnumbered Information Link Layer Frame Format.....	F-1
F.1.1	Flag.....	F-1
F.1.2	Destination Address Field.....	F-1
F.1.2.1	Aircraft Specific Address.....	F-2
F.1.2.2	Address Type.....	F-2
F.1.2.3	A/G Transmitter.....	F-2
F.1.3	Source Address Field.....	F-2
F.1.3.1	Broadcast Source Address.....	F-2
F.1.3.2	Address Type.....	F-2
F.1.3.3	C/R Bit.....	F-2
F.1.4	Link Control Field.....	F-2
F.1.5	Information Field.....	F-3
F.1.6	Frame Check Sequence.....	F-3
F.2	Universal Access Transceiver (UAT) Data Link Services.....	F-3
F.2.1	RF Segment.....	F-3
F.2.1.1	Data Transparency.....	F-3
F.2.1.2	Addressing.....	F-3
F.2.1.3	Integrity of Frame Data.....	F-4
F.2.2	Local Segment.....	F-4
APPENDIX G	TEST DATA SET DESCRIPTION.....	G-1
G.1	Text Data Set.....	G-1
G.1.1	Unaltered Data Set.....	G-1
G.1.2	Altered Data Set.....	G-1
G.2	Graphical Text Pattern.....	G-1
G.2.1	Unaltered Image.....	G-2
G.2.2	Missing Data.....	G-2
G.2.3	Altered Data Set.....	G-2
APPENDIX H	RADAR COLOR CONSISTENCY.....	H-1
H.1	Color Consistency Between Ground-based and Airborne Weather Radars.....	H-1
H.2	Radar Basics.....	H-1
H.3	Range-normalization.....	H-2
H.4	Spectrum.....	H-2

H.5	Backscatter.....	H-3
H.6	Losses Due to Attenuation.....	H-3
H.7	What is a dBZ?.....	H-5
H.8	What is the Relationship Between dBZ and Rainfall Rate?.....	H-5
H.9	Current Quantization Standards.....	H-6
H.10	Observed Data.....	H-8
H.11	Operational Considerations.....	H-9
H.12	Conclusions & Recommendations.....	H-9
APPENDIX I	DISPLAY OF LAYERED GRAPHICS AND TEXT (NORMATIVE).....	I-1
APPENDIX J	NATIONAL CONVECTIVE WEATHER FORECAST (NCWF).....	J-1
APPENDIX K	DATA LINK APPLICATIONS CODING (DLAC) 6-BIT ALPHABET.....	K-1

TABLE OF FIGURES

Figure 1-1	FIS-B Data Link System.....	3
Figure 3-1	Connectionless Unacknowledged Broadcast Organizations.....	13
Figure 3-2	Frame Layer Format.....	14
Figure 3-3	FIS-B Unnumbered Format of Link Control Field Bits.....	16
Figure 3-4	Overview of FIS-B System Data Flow.....	17
Figure 3-5	State Transition Diagram for Reassembly of Product File from Linked APDUs.....	20
Figure 4-1	Overview of FIS-B System Verification Methods.....	34
Figure D-1	Run Length Encoding Block.....	D-13
Figure D-2	Global Block Numbering Plan.....	D-14
Figure D-3	Block Reference Indicator Format.....	D-15
Figure D-4	Encoding a "Run" of Similar Bins.....	D-16
Figure D-5	Block Containing 12 Runs.....	D-16
Figure D-6	Format of the Run Length Encoded Element.....	D-17
Figure D-7	Format of the Empty Element.....	D-17
Figure D-8	Bitmap Bytes.....	D-18
Figure D-9	APDU Header Layouts.....	D-23
Figure H-1	Radar Attenuation.....	H-4

TABLE OF TABLES

Table 3-1 FIS Data Display Time Indication Requirements.....	24
Table 3-2 Color & Symbol Characterization Chart for Selected Weather Products.....	30
Table 4-1 FIS-B Frame and APDU Header Processing Verification Items.....	37
Table 4-2 Avionics Display Performance Verification Items.....	39
Table D-1 FIS-B APDU Header Format.....	D-1
Table D-2 Format of the FIS-B Product Descriptor.....	D-3
Table D-3 Compression Methods	D-4
Table D-4 Example of Run Length Compression Method 1 Encoding	D-5
Table D-5 Format of Raster Data Packet	D-5
Table D-6 Descriptions of Contents of Raster Data Packet.....	D-6
Table D-7 Geographic Reference Methods	D-8
Table D-8 ASN.1 Representation of Cylindrical Equidistant.....	D-10
Table D-9 ASN.1 Representation of Lambertian.....	D-11
Table D-10 ASN.1 Representation of Polar Stereographic Grid	D-12
Table D-11 Run Encoding for Example Block.....	D-16
Table D-12 Bit-Mapped Blocks	D-19
Table D-13 Options for APDU Header Time Fields	D-20
Table D-14 ASN.1 Representation of the APDU	D-24
Table F-1 Link Layer Frame Format	F-1
Table H-1 Airborne WXR Standards.....	H-6
Table H-2 ASR-9 Intensity Levels.....	H-7
Table H-3 WSR-88D Reflectivity-Rainfall Rate Relationships	H-7
Table H-4 Comparison of Weather Radar Intensity Levels and Display Colors.....	H-8
Table H-5 Recommended Weather Radar Intensity Levels and Display Colors.....	H-10
Table J-1 Approximate VIL-VIP Correlations	J-1
Table K-1 Data Link Applications Coding (DLAC) 6-Bit Alphabet.....	K-1

1 PURPOSE AND SCOPE

1.1 Introduction

This document contains Minimum Aviation System Performance Standards (MASPS) for Flight Information Services-Broadcast (FIS-B), an automated, digital data link system. The FIS-B system will provide timely access to data link updates of non-control, advisory information needed by pilots to operate safely and efficiently in the National Airspace System and in international airspace. FIS-B services will provide FIS information to pilots such as weather graphics and text, Special Use Airspace (SUA) information, and Notices to Airmen (NOTAMs). This document provides a broadcast protocol for use in any broadcast medium.

These specific system performance standards and equipment characteristics should be useful to designers, manufacturers, installers, and users of FIS-B data link systems. Functional specifications are used where possible so that implementers may have flexibility in developing FIS-B data link systems. Designing to these standards is one means of assuring that the system and equipment will perform their intended functions satisfactorily under all conditions normally encountered in routine aeronautical operations. Any regulatory application of this document is the sole responsibility of appropriate governmental agencies.

The format of this document generally follows that of an RTCA Minimum Operational Performance Specification (MOPS). However, a traditional MOPS is not appropriate for FIS-B, since this document establishes system performance rather than requirements for specific equipment. This MASPS defines a broadcast protocol that supports interoperability between providers of ground and airborne FIS processing systems and provides design guidelines and recommended standards for airborne processing and display of FIS products.

Section 1 of this document provides information on purpose and scope needed to understand the rationale for system and equipment characteristics, standards, and performance requirements stated in the remaining sections. It describes typical system applications and operational goals, and establishes the basis for the standards and performance requirements stated in Sections 1 and 3, and Appendices D and F.

Section 2 contains the minimum system performance standards for FIS-B data link systems.

Section 3 contains the minimum performance standards for each subsystem/function that is a required element of the minimum system performance in Section 1. Section 3.1 defines the FIS-B network interface and Section 3.8 provides guidelines and recommended standards for airborne processing and display of FIS products.

Section 4 describes a set of minimum system test procedures to verify system performance compliance (e.g., end-to-end performance verification) and that subsystem performance meets the minimum performance requirements in Sections 1 and 3, and normative Appendices D, F and I.

Appendix A contains a list of acronyms and abbreviations.

Appendix B contains a glossary of terms.

Appendix C contains a list of references.