

RTCA, Inc.
1828 L Street, NW, Suite 805
Washington, DC 20036 USA

Change No. 1
-to-
RTCA DO-270

**Minimum Aviation System Performance Standards
for the Aeronautical Mobile-Satellite (Route) Service (AMSR(S))
as Used in Aeronautical Data Links**

System Specific Attachment for Medium Satellite

© 2009 RTCA, Inc.
RTCA Paper No. 103-09/PMC-718
April 14, 2009

Copies of this document may be obtained from

RTCA, Inc.
1828 L Street, NW, Suite 805
Washington, DC 20036 USA

Telephone: 202-833-9339
Fax: 202-833-9434
Internet: www.rtca.org

Please call RTCA for price and ordering information.

Currently in preview, click buy full version

TABLE OF CONTENTS

RTCA DO-270.....	i
Minimum Aviation System Performance Standards	i
System Specific Attachment for Iridium Satellite	i
Table of Contents	i
1 INTRODUCTION	1
1.1 Objective.....	1
1.2 Scope.....	1
1.3 Iridium Satellite Network.....	2
1.3.1 Overview.....	2
1.3.2 System Architecture.....	2
1.3.3 Space Segment	3
1.3.3.1 Terrestrial Segment	5
1.3.4 Channel Classifications	5
1.3.4.1 Overhead Channels.....	6
1.3.4.2 Bearer Service Channels.....	7
1.3.5 Channel Multiplexing	7
1.3.5.1 TDMA Frame Structure	7
1.3.5.2 FDMA Frequency Plan	8
1.3.5.3 Duplex Channel Band	8
1.3.5.4 Simplex Channel Band.....	10
1.3.6 L-Band (1616-1626.5 MHz) Transmission Characteristics.....	10
1.3.6.1 Signal Format	10
1.3.6.2 Power Control	12
1.3.7 Call Processing	12
1.3.7.1 Acquisition.....	12
1.3.7.1.1 Acquisition Control	13
1.3.7.2 Access.....	14
1.3.7.3 Registration and Auto-Registration	14
1.3.7.4 Telephony.....	14
1.3.7.5 Handoff	16
1.3.8 Voice and Data Traffic Channel	17
1.3.9 Iridium Data Services – RUDICS and SBD.....	17
1.3.9.1 Iridium RUDICS Service.....	17
1.3.9.2 Iridium SBD Service.....	19
1.4 Iridium AMSS System.....	21
1.4.1 System Overview	23
1.4.2 Aircraft Earth Station (AES)	23
1.4.3 Space Segment	24
1.4.4 Ground Earth Station.....	24
2 SYSTEM NETWORK PERFORMANCE REQUIREMENTS	25
2.1 General Requirements	25
2.2 Specific Requirements.....	25
2.2.1 Standard Operating Conditions.....	25
2.2.2 Spectrum Requirements	26
2.2.2.1 Emission Designators.....	26
2.2.2.2 Interference.....	29
2.2.2.2.1 Emissions.....	29
2.2.2.2.2 Susceptibility	29

2.2.3	Coverage Volume	29
2.2.4	Priority, Precedence and Preemption	30
2.2.4.1	Priority Levels	31
2.2.4.2	Precedence	31
2.2.4.3	Preemption	31
2.2.5	Subnetwork Installed Communications Performance (ICP)	31
2.2.5.1	Transfer Delay	31
2.2.5.1.1	Traffic Model	32
2.2.5.1.2	Subnetwork Model	33
2.2.5.1.3	Transfer Delay Performance	33
2.2.5.1.4	Transfer Delay Characterization	33
2.2.5.2	Integrity	34
2.2.5.3	Service Availability Criteria	35
2.2.5.3.1	Service Outages	35
2.2.5.3.2	Availability Ratio	36
2.2.5.3.3	Multi-User Availability	36
2.2.5.3.4	Single-User Availability	36
2.2.5.4	Continuity of Service Criteria	37
2.2.5.4.1	Continuity of Service Event	37
2.2.5.4.2	Continuity of Service	37
2.2.5.4.3	Multi-User Continuity of Service	37
2.2.5.4.4	Single-User Continuity of Service	38
2.2.6	Service Monitoring	38
2.2.7	Subnetwork Interoperability	38
2.2.7.1	Subnetwork Communications Protocols	39
2.2.7.2	Transparency to User Data	39
2.2.7.3	Interactions with External Elements	39
2.2.7.3.1	Connection Establishment Delay	39
2.2.7.3.2	Connectivity Events	39
2.2.7.3.3	System Control Interactions	39
3	SUBSYSTEM REQUIREMENTS	41
3.1	Performance Partitioning Methodologies	41
3.1.1	RF Performance	42
3.1.2	Transfer Delay Partitioning Methodology	42
3.1.2.1	Latency Transfer Delay Component	42
3.1.2.2	Mean Transfer Delay	42
3.1.2.3	95th Percentile Transfer Delay	42
3.1.3	Integrity Methodology	43
3.1.4	Availability Methodology	43
3.1.4.1	Methodology for Computing Multi-User Availability	43
3.1.4.2	Methodology for Computing Single User Availability	44
3.1.5	Continuity Methodology	44
3.1.5.1	Methodology for Computing Multi-User Continuity of Service	44
3.1.5.2	Methodology for Computing Single User Continuity of Service	45
3.2	AES Subsystem Requirements	46
3.3	Satellite Network Infrastructure (SNI) Requirements	46
3.3.1	SNI Performance Requirements	46
3.3.1.1	RF Link Performance Requirements	46
3.3.1.2	Mitigation of Harmful Interference	46
3.3.1.2.1	Intrasystem Interference	46
3.3.1.2.2	Intersystem Interference	47
3.3.1.3	Network Coordination and Control Function	47

3.3.1.3.1	Intrasystem Coordination.....	47
3.3.1.3.2	Intersystem Coordination: Same Frequency Band, Same Protocols.....	48
3.3.1.3.3	Intersystem Coordination: Different Frequency Bands.....	48
3.3.1.3.4	Intersystem Coordination: Same Frequency Band, Different Protocols.....	48
3.3.2	SNI Functional Requirements	48
4	SUBNETWORK PERFORMANCE VERIFICATION PROCEDURES	49
4.1	Verification Techniques.....	49
4.2	Verification of Specific Requirements	50
4.2.1	Standard Operating Conditions.....	50
4.2.2	Spectrum Requirements	50
4.2.2.1	Emissions Designators	50
4.2.2.2	Interference.....	51
4.2.2.2.1	Emissions.....	51
4.2.2.2.2	Susceptibility	51
4.2.3	Coverage Volume	52
4.2.4	Priority, Precedence and Preemption.....	52
4.2.4.1	Priority Levels	53
4.2.4.2	Precedence.....	54
4.2.4.3	Preemption.....	54
4.2.5	Subnetwork Installed Communications Performance	54
Transfer Delay.....		54
4.2.5.1.1	Traffic Model.....	55
4.2.5.1.2	Subnetwork Model	55
4.2.5.1.3	Transfer Delay Performance.....	55
4.2.5.1.4	Transfer Delay Characterization.....	56
4.2.5.2	Integrity.....	57
4.2.5.3	Service Availability Criteria.....	58
4.2.5.3.1	Service Outages	58
4.2.5.3.2	Availability Ratio	58
4.2.5.3.3	Multi-User Availability	59
4.2.5.3.4	Single-User Availability	59
4.2.5.4	Continuity of Service Criteria.....	60
4.2.5.4.1	Continuity of Service Event	60
4.2.5.4.2	Continuity of Service	60
4.2.5.4.3	Multi-User Continuity of Service.....	60
4.2.5.4.4	Single-User Continuity of Service	61
4.2.6	Service Monitoring.....	62
4.2.7	Subnetwork Interoperability.....	62
4.2.7.1	Subnetwork Communications Protocols.....	62
4.2.7.2	Transparency to User Data.....	63
4.2.7.3	Interactions with External Elements	63
4.2.7.3.1	Connection Establishment Delay.....	63
4.2.7.3.2	Connectivity Events.....	64
4.2.7.3.3	System Control Interactions	64
4.3	Verification of Section 3 Requirements.....	64

TABLE OF FIGURES

1-1	Key Elements of the Iridium AMS(R)S	3
1-2	Iridium 66-Satellite Constellation	4
1-3	Iridium Spot-Beam Configuration	5
1-4	Iridium Channel Structure Hierarchy	6
1-5	Iridium TDMA Structure	7
1-6	FDMA Frequency Plan	11
1-7	Protocol Partitions	15
1-8	Iridium RUDICS Mobile Originated Data Call Setup	18
1-9	System Architecture of Iridium SBD Service	19
1-10	Setting Up a MO SBD Call (a) Registration (b) Message Delivery	20
1-11	Iridium Aviation Safety Services Air-to-Ground Voice (End-to-End Model)	22
1-12	Iridium Aviation Safety Services Air-to-Air Voice (End-to-End Model)	22
1-13	Iridium Aviation Safety Services Air-to-Ground Data (End-to-End Model)	23
1-14	Iridium Aviation Safety Services Air-to-Air Data (End-to-End Model)	23
1-15	Generic Block Diagram of Aircraft Earth Station	24
2-1	AMS(R)S Subnetwork and Performance Reference Points	26
4-1	Harmonic Bandwidths for Interference Analysis	51
4-2	Example of To-Aircraft-Direction Transfer Delay Measurement System	57

TABLE OF TABLES

1-1	Sub-Band Frequency Allocation	9
1-2	Reuse Unit Frequency Accesses	10
1-3	Simplex Frequency Allocation	10
2-1	<i>Pro Forma</i> for Iridium Satellite System Characteristic Declaration	27
2-2	<i>Pro Forma</i> Table for Transfer Delay Characteristics	34

GLOSSARY

AAC	Aeronautical Administrative Communications
AC	Acquisition Class
ACCHL	Associated Control Channel, L-Band
AES	Aircraft Earth Station
AOC	Aircraft Operational Communication
APC	Aeronautical Public Correspondence
ATC	Air Traffic Communications (Command)
BPSK	Binary Phase Shift Keying
CC	Call Control
CMU	Communications Management Unit
COCR	Communications Operating Concept and Requirements
CSP	Communications Service Provider
DCE	Data Communications Equipment
DFOA	Differential Frequency of Arrival
DSP	Datalink Service Provider
DTE	Data Terminal Equipment
DTOA	Differential Time of Arrival
FDMA	Frequency Domain Multiple Access
FEC	Forward Error Correction
GES	Ground-Earth Station (Gateway)
GSM	Global System for Mobile Communications
ICAO	International Civil Aviation Organization
ISLLC	Iridium Satellite Limited Liability Corporation
IP	Internet Protocol
LAI	Location Area Identity
LBP	L-Band Physical
LBT	L-Band Transceiver
LL	L-Band Link
MLPPP	Multi-Link Point to Point Protocol
MM	Mobility Management
MO	Mobile Originated
MOPS	Minimum Operation Performance Standards
MT	Mobile Terminated
NGSS	Next Generation Satellite System
OSN	Operational Support Network
PPP	Point to Point Protocol
PSDN	Public Switched Data Network
PSTN	Public Switched Telephone Network
QPSK	Quadrature Phase Shift Keying modulation
RUDICS	Router-Based Unrestricted Digital Interworking Connectivity

	Solution
SBD	Short Burst Data
SDU	Satellite Data Unit
SIM	Subscriber Identity Module card
SNOC	Satellite Network Operations Centre
SV	Space Vehicle (Satellite)
TCP	Transport Control Protocol
TDMA	Time Domain Multiple Access
TE	Terminal Equipment
TMSI	Temporary Mobile Subscriber Identification
TTAC	Telemetry, Tracking, and Control facility
UTC	Universal Coordinated Time

1 INTRODUCTION

1.1 Objective

This document has been prepared in accordance with *DO-270 Minimum Aviation System Performance Standards (MASPS) for the Aeronautical Mobile-Satellite (R) Service (AMS(R)S) as Used in Aeronautical Data Links* as a system specific attachment for the Iridium Satellite System. It contains minimum aviation system performance standards for communications utilizing the Iridium Satellite network for the air-ground communications subnetwork in an Aeronautical Telecommunications Network (ATN). This attachment reflects the Standards and Recommended Practices defined in ICAO Annex 10, Part I, Volume III, Chapter 4 (Chapter 4 SARPS), as revised in 2007.

Compliance with these standards is recommended as one means of assuring that the Iridium Satellite system and its subsystems will perform its intended function(s) satisfactorily under conditions normally encountered in routine aeronautical operations for the environment intended. Any regulatory application of this document is the sole responsibility of appropriate governmental agencies.

The technical characteristics specific to the Iridium Satellite system will be prepared in accordance with this System Specific Attachment. The system specific performance declared in accordance with this attachment will provide one means of assessing whether Iridium Satellite AMS(R)S is appropriate for a specific operational environment. Iridium's system specific performance declaration will not require RTCA publication or approval.

A companion document, the *Iridium Satellite Nominate Appendix to the DO-262A Minimum Operational Performance standards (MOPS) for Avionics Supporting Next Generation Satellite Systems (NGSS)*, should be consulted for operational requirements at the air/ground system level, and for details of specific systems providing Iridium AMS(R)S. RTCA documents DO-215A and DO-231 provide overall guidance on data and voice performance.

1.2 Scope

This system specific attachment contains a description of the Iridium Satellite communication system configuration including Ground Subnetworks; Iridium Satellite Subnetworks, of which the Aircraft Earth Station (AES) is a part; and Aircraft Subnetworks. However, the *minimum system performance standards* in this document address only the Satellite Subnetwork.

Section 1 of this attachment provides an informative description of the Iridium Satellite network, focusing on those aspects particular to AMS(R)S. Section 1 provides information needed to understand the rationale for Iridium system characteristics and requirements stated within this document. Definitions and assumptions essential to proper understanding of the Iridium System are provided in this Section, while a more extensive generic glossary can be found in Appendix A of DO-270. Section 1 is intended to be informative in nature and contains no requirements applicable to the Iridium Satellite System.

Section 2 defines the general requirements of an Iridium Satellite AMS(R)S subnetwork, specific requirements for its interfaces, and specific minimum Installed Communications Performance (ICP) requirements when viewed as an air/ground subnetwork of an end-to-end data network. The ICP