

RTCA, Inc.
1150 18th Street NW, Suite 910
Washington, DC 20036

**Minimum Operational Performance
Standards (MOPS) for Aircraft VDL Mode 2
Physical Link and Network Layer**

RTCA DO-281B
March 21, 2012
Supersedes DO-281A

Prepared by: SC-214
© 2012 RTCA, Inc.

Copies of this document may be obtained from

RTCA, Inc.

Telephone: 202-833-9339

Facsimile: 202-833-9434

Internet: www.rtca.org

Please visit the RTCA Online Store for document pricing and ordering information.

FOREWORD

This document was originally prepared by RTCA Special Committee 214 (SC-214), and approved by the RTCA Program Management Committee (PMC) on March 21, 2012.

RTCA, Incorporated is a not-for-profit corporation formed to advance the art and science of aviation and aviation electronic systems for the benefit of the public. The organization functions as a Federal advisory committee, and develops consensus-based recommendations on contemporary aviation issues. RTCA's objectives include but are not limited to:

- coalescing aviation system user and provider technical requirements in a manner that helps government and industry meet their mutual objectives and responsibilities;
- analyzing and recommending solutions to the system technical issues that aviation faces as it continues to pursue increased safety, system capacity and efficiency;
- developing consensus on the application of pertinent technology to fulfill user and provider requirements, including development of minimum operational performance standards for electronic systems and equipment that support aviation; and
- assisting in developing the appropriate technical material upon which positions for the International Civil Aviation Organization and the International Telecommunication Union and other appropriate international organizations can be based.

The organization's recommendations are often used as the basis for government and private sector decisions as well as the foundation for many Federal Aviation Administration Technical Standard Orders and several advisory circulars.

Since RTCA is not an official agency of the United States Government, its recommendations may not be regarded as statements of official government policy unless so enunciated by the U.S. government organization or agency having statutory jurisdiction over any matters to which the recommendations relate.

This Page Intentionally Left Blank

EXECUTIVE SUMMARY

This document has been structured with guidelines according to the RTCA MOPS Drafting Guide dated September 21, 2001.

The material in this document highlights the minimum procedures for the physical link and network layer of the VDL Mode 2 subnetwork.

The test procedures used in this document have been coordinated with EUROCAE Working Group 92 during the preparation of EUROCAE Document ED92B.

This document includes four appendices. Appendix B should be considered a normative appendix.

This Page Intentionally Left Blank

TABLE OF CONTENTS

1.	PURPOSE AND SCOPE	1
1.1	Introduction	1
1.2	System Overview.....	2
1.3	Possible Configuration of Aircraft Equipment	3
1.3.1	Separated Equipment.....	3
1.3.2	Integrated Equipment	4
1.4	Operational Applications	5
1.5	Operational Goals.....	5
1.6	Equipment Performance Verification	5
1.6.1	Bench Tests	5
1.6.2	Environmental Tests.....	5
1.6.3	Installed Equipment Tests	6
1.6.4	Operational Tests.....	6
1.7	Definitions of Terms.....	6
1.7.1	Adjacent Channel	6
1.7.2	Adjacent Channel Power	6
1.7.3	Adjacent Channel Rejection (ACR)	6
1.7.4	Bit Error Rate (BER).....	6
1.7.5	Co-channel Interference (CCI).....	7
1.7.6	Error Vector Magnitude (EVM).....	7
1.7.7	Reference Signal Level	7
1.7.8	Undesired VDL Mode 2 Test Signal	7
1.7.9	Reference Bit Sequence.....	7
1.8	Reference Documents	8
1.9	Assumptions	8
2.	MINIMUM PERFORMANCE STANDARDS	9
2.1	General Design Requirements	9
2.1.1	Airworthiness	9
2.1.2	Intended Function.....	9
2.1.3	ITU and FCC Rules and Regulations	9
2.1.4	Fire Protection	9
2.1.5	Operation of Controls.....	9
2.1.6	Accessibility of Controls	9
2.1.7	Effects of Test	9
2.1.8	Equipment Classes	10
2.1.8.1	Receivers.....	10

2.1.8.2	Transmitters.....	10
2.1.9	VDL Mode 2 Avionics Architecture Classes	10
2.1.9.1	ISO 8208-compliant Equipment Classes.....	10
2.1.9.1.1	Class X.....	10
2.1.9.1.2	Class Y.....	10
2.1.9.1.3	Class Z.....	11
2.1.9.2	Non-ISO 8208 Equipment Classes.....	11
2.1.9.2.1	Class V.....	11
2.1.9.2.2	Class W.....	11
2.1.10	Software Management.....	12
2.2	Minimum Performance Requirements - Standard Conditions.....	12
2.2.1	VDL Mode 2 Physical Layer Requirements	12
2.2.1.1	Transceiver Requirements.....	12
2.2.1.1.1	Tuning Range and Channel Increments	12
2.2.1.1.2	Modulation.....	12
2.2.1.1.3	Tuning Time.....	12
2.2.1.1.4	Receive to Transmit Switching Time.....	12
2.2.1.1.5	Transmit to Receive Switching Time.....	13
2.2.1.1.6	Channel Sensing.....	13
2.2.1.2	Receiver Requirements.....	13
2.2.1.2.1	Sensitivity	14
2.2.1.2.2	Adjacent Channel Rejection	14
2.2.1.2.3	Receiver Performance in the Presence of Strong Signals Within the VHF Aeronautical Band.....	14
2.2.1.2.4	Receiver Performance in the Presence of Strong Signals Outside the VHF Aeronautical Band	14
2.2.1.2.5	Desired Signal Dynamic Range	15
2.2.1.2.6	Symbol Rate Capture Range.....	15
2.2.1.2.7	Frequency Capture Range.....	15
2.2.1.2.8	Phase Acceleration.....	16
2.2.1.2.9	Co-channel Interference (CCI).....	16
2.2.1.2.10	Conducted Spurious Emission.....	16
2.2.1.2.11	FM Broadcast Intermodulation.....	16
2.2.1.2.12	In-band Intermodulation	16
2.2.1.3	Transmitter Requirements.....	17
2.2.1.3.1	Channel Bandwidth.....	17
2.2.1.3.2	RF Output Power.....	17
2.2.1.3.3	RF Power Rise Time.....	17
2.2.1.3.4	RF Power Release Time.....	18
2.2.1.3.5	Symbol Constellation Error	18
2.2.1.3.6	Spurious Emissions.....	18
2.2.1.3.7	Adjacent Channel Power.....	19
2.2.1.3.8	(Reserved).....	20
2.2.1.3.9	Load VSWR Capability	20
2.2.1.3.10	Frequency Tolerance.....	20
2.2.2	VDL Mode 2 Link Layer Requirements	20
2.2.3	VDL Mode 2 Network Layer 8208 Requirements	20
2.2.4	VDL Mode 2 Network Layer Mobile SndCF Requirements.....	21

2.2.5	Non-ISO 8208 Use of VDL Mode 2	21
2.2.6	Data/Management Interface	21
2.3	Minimum Performance Requirements - Environmental Conditions	21
2.3.1	Introduction	21
2.3.2	Receiver.....	22
2.3.3	Transmitter	22
2.4	Equipment Test Procedures	29
2.4.1	Definition of Terms and Conditions of Tests	29
2.4.1.1	Warm-up and Stabilization of Test Equipment/Equipment Under Test.....	29
2.4.1.2	Alignment, Adjustment and Calibration for Equipment Under Test.....	29
2.4.1.3	Equipment Termination	29
2.4.1.4	Test Equipment Calibration and Replacement	29
2.4.1.5	Failure of the Equipment Under Test.....	29
2.4.1.6	Measurement Error Due to Test Equipment and Test Setup.....	29
2.4.1.7	Default RF Signal Level for Avionics High Level Protocol Testing.....	30
2.4.2	Special Test Mode and Test Equipment for Physical Layer Tests	30
2.4.2.1	Frame Error Rate Testing.....	30
2.4.2.1.1	FER Test	30
2.4.2.1.2	FER Test Setup	31
2.4.2.2	Bit Error Rate Testing.....	32
2.4.2.2.1	External BER Test Fixture.....	32
2.4.2.2.2	Test Payload.....	32
2.4.2.2.3	BER Test Setup.....	32
2.4.2.3	Desired VDL Mode 2 Signal Source.....	33
2.4.2.3.1	VDL Mode 2 Data Generator.....	33
2.4.2.3.2	VHF Signal Generator	33
2.4.2.4	Undesired VDL Mode 2 Signal Source.....	33
2.4.3	VDL Mode 2 Test Set Definitions	33
2.4.3.1	Upper Tester (UT).....	34
2.4.3.1.1	Aircraft Test Tool / Protocol Analyzer (ATT).....	35
2.4.3.1.2	Upper Data/Management Interface Test Tool (UDMITT)	36
2.4.3.2	Lower Tester (LT).....	36
2.4.3.2.1	Ground Station Emulator (GSE).....	37
2.4.3.2.2	VDL Mode 2 Lower Data/Management Interface Test Tool (LDMITT).....	38
2.4.3.2.3	Air/Ground Router.....	38
2.4.3.2.4	Standard LT Configurations	38
2.4.3.2.4.1	LT Configuration 1.....	38
2.4.3.2.4.2	LT Configuration 2.....	39
2.4.3.2.4.3	LT Configuration 3.....	39
2.4.3.2.4.4	LT Configuration 4.....	39
2.4.3.2.4.5	LT Configuration 5.....	40
2.4.4	Physical Layer Test Procedures	40
2.4.4.1	Receiver Test Procedures	41
2.4.4.1.1	Sensitivity	41
2.4.4.1.2	Adjacent Channel Rejection	41
2.4.4.1.3	Rejection of Signals Within the VHF Aeronautical Band	42
2.4.4.1.4	Rejection of Signals Outside the VHF Aeronautical Band.....	43
2.4.4.1.5	Desired Signal Dynamic Range	44

2.4.4.1.6	Symbol Rate Capture Range	45
2.4.4.1.7	Frequency Capture Range	45
2.4.4.1.8	Phase Acceleration	46
2.4.4.1.9	Co-Channel Interference	47
2.4.4.1.10	Conducted Spurious Emission	47
2.4.4.1.11	FM Broadcast Intermodulation	48
2.4.4.1.12	In-Band Intermodulation/Desensitization	49
2.4.4.2	Transmitter Test Procedures	50
2.4.4.2.1	Bit Rate	50
2.4.4.2.2	RF Output Power	51
2.4.4.2.3	RF Power Rise Time	51
2.4.4.2.4	RF Power Release Time	53
2.4.4.2.5	Symbol Constellation Error	54
2.4.4.2.6	Spurious Emissions	54
2.4.4.2.7	Adjacent Channel Power	55
2.4.4.2.8	(Reserved)	60
2.4.4.2.9	Load VSWR Capability	60
2.4.4.2.10	Frequency Tolerance	61
2.4.4.3	Physical Layer System Level Test Procedures	61
2.4.4.3.1	Receive to Transmit Switching Time	61
2.4.4.3.2	Transmit to Receive Switching Time	63
2.4.4.3.3	Channel Sensing	64
2.4.4.3.4	Tuning Time	68
2.4.5	VDL Mode 2 Link Layer Test Procedures	68
2.4.5.1	Test Procedure Structure	68
2.4.5.1.1	Overview of Test Cases	69
2.4.5.1.2	Declarations Part	69
2.4.5.1.3	Constraints Part	69
2.4.5.1.4	Detailed Test Cases	69
2.4.5.1.5	Test Case Description	69
2.4.5.1.5.1	Procedure description	69
2.4.5.1.5.2	Message Sequence Chart	69
2.4.5.1.6	Test Cases Macro	70
2.4.5.1.6.1	Establish a link layer connection (SET _{AVLC})	71
2.4.5.1.6.2	Establish (explicit) a network layer connection (SET ₈₂₀₈)	72
2.4.5.1.6.3	Establish (expedited) a network layer connection	72
2.4.5.1.6.4	Check link is established	72
2.4.5.1.6.5	Check network link is established	73
2.4.5.1.6.6	Close a link layer connection	73
2.4.5.1.6.7	Close network layer connection	73
2.4.5.2	(Reserved)	73
2.4.5.3	MAC Sublayer	73
2.4.5.3.1	MAC services	73
2.4.5.3.1.1	Multiple Access	73
2.4.5.3.1.2	Channel Occupancy	74
2.4.5.3.1.3	Channel Congestion	74
2.4.5.3.2	MAC System Parameters	74
2.4.5.3.2.1	Timer TM1 (inter-access delay timer)	74
2.4.5.3.2.2	Parameter p (persistence)	77
2.4.5.3.2.3	Counter M1 (maximum access attempts)	79

2.4.5.3.3	Description of MAC Layer Procedures	79
2.4.5.3.3.1	Channel Sensing	79
2.4.5.3.3.2	Access Attempt	79
2.4.5.3.3.3	Signal Quality Parameter	80
2.4.5.3.3.3.1	Original SQP	80
2.4.5.3.3.3.2	Supplement 4 SQP (Optional)	80
2.4.5.4	Data Link Service Sublayer	81
2.4.5.4.1	Services	82
2.4.5.4.1.1	Frame Sequencing	82
2.4.5.4.1.2	Error Detection	83
2.4.5.4.1.3	Station Identification	84
2.4.5.4.1.4	Broadcast Addressing	84
2.4.5.4.1.5	Data Transfer	85
2.4.5.4.2	AVLC Data Link Protocol	85
2.4.5.4.2.1	Frame Format	85
2.4.5.4.2.2	Address Structure	86
2.4.5.4.2.3	Address Fields	86
2.4.5.4.2.4	Broadcast Address	87
2.4.5.4.2.5	Link Control Field	88
2.4.5.4.2.6	Information Field	88
2.4.5.4.3	Data Link Service System Parameters	89
2.4.5.4.3.1	Timer T1 (delay before retransmission)	90
2.4.5.4.3.2	Timer T2 (delay before acknowledgement)	91
2.4.5.4.3.3	Timer T3 (link initialization time)	92
2.4.5.4.3.4	Timer T4 (maximum delay between transmissions)	93
2.4.5.4.3.5	Parameter N1 (maximum number of bits in frame)	95
2.4.5.4.3.6	Counter N2 (maximum number of transmissions)	96
2.4.5.4.3.7	Parameter k (window size)	97
2.4.5.4.4	Modes of Operation	98
2.4.5.4.4.1	Operational Mode	98
2.4.5.4.4.2	Non-Operational Mode	98
2.4.5.4.4.2.1	DISC Frame	99
2.4.5.4.4.2.2	DM Frame	100
2.4.5.4.4.2.3	Frame Reject Mode	101
2.4.5.4.4.2.4	Selective Reject Mode	102
2.4.5.4.5	Use of the P/F bit	102
2.4.5.4.5.1	General	102
2.4.5.4.5.2	INFO frames	103
2.4.5.4.5.3	Unnumbered Frames	104
2.4.5.4.6	Unnumbered Command Frames Collisions	104
2.4.5.4.6.1	DLE Procedures	104
2.4.5.4.6.2	LME Procedures	106
2.4.5.4.7	XID Frame	109
2.4.5.4.8	Broadcast	110
2.4.5.4.9	Information Transfer	110
2.4.5.4.9.1	Transmit Queue Management	111
2.4.5.4.9.1.1	Eliminate Redundant Frames	111
2.4.5.4.9.1.2	Procedures for Transmission	111
2.4.5.4.9.2	SREJ Frame	114
2.4.5.4.9.3	FRMR Frame	115
2.4.5.4.9.4	UA Frame	116

2.4.5.4.9.5	UI Frame	117
2.4.5.4.9.6	TEST Frame.....	118
2.4.5.5	Link Management Entity	118
2.4.5.5.1	Services.....	119
2.4.5.5.1.1	Link Provision.....	119
2.4.5.5.1.2	Link Change Notification	119
2.4.5.5.2	Exchange Identity (XID) Formats.....	120
2.4.5.5.2.1	Encoding	120
2.4.5.5.2.2	Public Parameters.....	120
2.4.5.5.2.3	Private Parameters	121
2.4.5.5.2.4	General Purpose Private Parameters	121
2.4.5.5.2.5	Aircraft Initiated Private Parameters	121
2.4.5.5.2.6	Ground Initiated Modification Private Parameters	122
2.4.5.5.2.7	Ground Initiated Private Parameters	122
2.4.5.5.3	LME Service System Parameters.....	123
2.4.5.5.3.1	Timer TG1 (frequency dwell time).....	123
2.4.5.5.3.2	Timer TG2 (maximum idle activity time).....	124
2.4.5.5.3.3	Timer TG3 (maximum time between transmissions)	125
2.4.5.5.3.4	Timer TG4 (maximum time between GSIFs).....	125
2.4.5.5.3.5	Timer TG5 (maximum link overlap time)	126
2.4.5.5.4	Description of LME Procedures.....	126
2.4.5.5.4.1	Frequency Management.....	126
2.4.5.5.4.2	Link Connectivity	135
2.4.5.5.4.3	Ground Station Identification	135
2.4.5.5.4.4	Link Establishment	136
2.4.5.5.4.5	Link Parameter Modification	143
2.4.5.5.4.6	Aircraft Initiated Handoff	144
2.4.5.5.4.7	(Reserved).....	151
2.4.5.5.4.8	Ground Initiated Handoff.....	152
2.4.5.5.4.9	Ground Requested Aircraft Initiated Handoff	161
2.4.5.5.4.10	Ground Requested Broadcast Handoff (optional).....	177
2.4.5.5.4.11	Ground Requested Autotune.....	182
2.4.5.5.4.12	Expedited Subnetwork Connection Management (optional)	186
2.4.5.5.4.13	Frequency Support List.....	187
2.4.6	VDL Mode 2 Network Layer Test Procedures.....	212
2.4.6.1	Architecture.....	212
2.4.6.1.1	Access Points.....	213
2.4.6.2	Services.....	213
2.4.6.2.1	Subnetwork Connection Management	213
2.4.6.2.2	Packet Fragmentation and Reassembly	217
2.4.6.2.3	Error Recovery.....	218
2.4.6.2.4	Connection Flow Control.....	218
2.4.6.3	Packet Format	220
2.4.6.3.1	General Format Identifier	221
2.4.6.3.2	Calling and Called DTE Addresses.....	221
2.4.6.3.2.1	Encoding	221
2.4.6.3.2.2	Aircraft DTE Address	221
2.4.6.3.2.3	Ground DTE Address	222
2.4.6.3.2.4	Ground Network DTE Address	223
2.4.6.3.3	Call User Data Field.....	223

2.4.6.3.4	Packet Types	223
2.4.6.4	Subnetwork Layer System Parameters	225
2.4.6.4.1	Packet Size	226
2.4.6.4.2	Parameter W (transmit window size)	226
2.4.6.4.3	Parameter A (acknowledgement window size)	227
2.4.6.5	Description of Procedures	227
2.4.6.5.1	Supported Facilities	227
2.4.6.5.1.1	Nonstandard Default Packet Sizes	228
2.4.6.5.1.2	Nonstandard Default Window Sizes	228
2.4.6.5.1.3	Flow Control Parameter Negotiation	228
2.4.6.5.1.4	Fast Select	228
2.4.6.5.1.5	Fast Select Acceptance	228
2.4.6.5.1.6	Called Line Address Modified Notification	229
2.4.6.5.1.7	Called Address Extension	229
2.4.6.5.2	Unsupported Facilities	229
2.4.6.5.3	Subnetwork Establishment and Connection Management	229
2.4.6.5.3.1	Subnetwork Entity Initialization	229
2.4.6.5.3.2	Subnetwork Connection Establishment	229
2.4.6.5.3.2.1	Explicit Subnetwork Connection Establishment	230
2.4.6.5.3.2.2	Expedited Subnetwork Connection Establishment (optional)	230
2.4.6.5.4	Subnetwork Connection Maintenance	230
2.4.6.5.4.1	Explicit Subnetwork Connection Maintenance	230
2.4.6.5.4.2	Expedited Subnetwork Connection Maintenance (optional)	230
2.4.6.5.4.3	Broadcast Subnetwork Connection Maintenance	230
2.4.6.5.4.4	Call Redirection for X.121-based Networks	231
2.4.6.5.5	Error Handling	231
2.4.6.5.6	Acknowledgements	231
2.4.7	VDL Mode 2 Mobile SNDCF Test Procedures	231
2.4.7.1	(Reserved)	231
2.4.7.2	Call User Data Encoding	231
2.4.7.2.1	ISH PDU	232
2.4.7.2.2	Maintained/Initialized Status Bit	233
2.4.7.2.3	CALL REQUEST	234
2.4.7.2.4	CALL ACCEPTED	234
2.4.8	Non-ISO 8208 Use of VDL Mode 2	234
2.4.9	Data/Management Interface	234

3. INSTALLED EQUIPMENT TESTS..... 235

3.1	Equipment Installation.....	235
3.1.1	Accessibility	235
3.1.2	Aircraft Environment	235
3.1.3	Display Visibility	235
3.1.4	Dynamic response	235
3.1.5	Failure Protection	235
3.1.6	Inadvertent Turnoff	235
3.1.7	Aircraft Power Source	235
3.2	Installed Equipment Performance Requirements	236
3.2.1	Dynamic Response	236

3.2.2	Interference Effects	236
3.3	Conditions of Test	237
3.3.1	Power Input	237
3.3.2	Associated Equipment or Systems	237
3.3.3	Environment	237
3.4	Test Procedures for Installed Equipment Performance	239
3.4.1	Conformity Inspection.....	239
3.4.2	Equipment Function	239
3.4.3	Equipment Accessibility.....	239
3.4.4	Interference Effects	239
3.4.5	Power Supply Fluctuations.....	239
3.4.6	Reception.....	239
3.4.7	Transmission	240
4.	EQUIPMENT OPERATIONAL PERFORMANCE CHARACTERISTICS ..	241
4.1	Required Operational Performance Requirements	241
4.1.1	Power Inputs.....	241
4.1.2	Displays.....	241
4.1.3	Communications Controls.....	241
4.1.4	Equipment Operating Functions.....	241
4.1.5	System Operational Indication	241
4.1.6	Equipment Operating Limitations	241
4.2	Test Procedures for Operational Performance Requirements.....	241
4.2.1	Power Input	241
4.2.2	Communications Displays.....	242
4.2.3	Communications Controls.....	242
4.2.4	Functional Operating Tests	242
4.2.5	System Operational Indication	242
4.2.6	Equipment Operating Limitations	242
	MEMBERSHIP.....	243
	APPENDIX A: ACRONYMS AND GLOSSARY.....	A-1
	APPENDIX B: REQUIREMENTS CROSS REFERENCE MATRICES – VERIFICATION TESTING AND EQUIPMENT ARCHITECTURE CLASS (NORMATIVE)	B-1
	APPENDIX C: ANALYSIS OF BER VS. BLOCK FAILURE RATE	C-1
	APPENDIX D: ASSUMED FUNCTIONAL CAPABILITIES OF THE DATA/MANAGEMENT INTERFACE.....	D-1

TABLE OF TABLES

Table 2-1: Receiver Environmental Test Conditions Matrix.....	23
Table 2-2: Transmitter Environmental Test Conditions Matrix.....	25
Table 2-3: <i>Pro Forma</i> Test Description Table.....	71
Table 2-4: Default Values for GSIF Parameters.....	90
Table 2-5: Minimum and Maximum Values of T1 for Testing.....	91
Table 2-6: Minimum and Maximum Values of T3 for Testing.....	93
Table 3-1: Example of Interference Protection for GNSS and AMSS.....	238

TABLE OF FIGURES

Figure 1-1: VDL Mode 2 Protocol Layers Using ATN/OSI Nomenclature.....	3
Figure 1-2: VDL Functions for Combination Class Y/Z Equipment.....	4
Figure 1-3: Integrated Class X VDL Mode 2 Architecture.....	5
Figure 1-4: Receive to Transmit Turnaround Time.....	13
Figure 1-5: Accept/Reject/Continue Regions for Sequential FER Test.....	31
Figure 1-6: Frame Error Rate Test Set Up.....	31
Figure 1-7: Bit Error Rate Test Setup.....	33
Figure 1-8: ISO 9646 Test Configuration.....	34
Figure 1-9: Upper Tester for Class X or Class Z Equipment.....	35
Figure 1-10: Upper Tester for Class Y Equipment.....	35
Figure 1-11: Lower Tester for Class X or Class Y Equipment.....	36
Figure 1-12: Lower Tester for Class Z Equipment.....	37
Figure 1-13: Lower Tester Configuration 1.....	39
Figure 1-14: Lower Tester Configuration 2.....	39
Figure 1-15: Lower Tester Configuration 3.....	39
Figure 1-16: Lower Tester Configuration 4.....	40
Figure 1-17: Lower Tester Configuration 5.....	40
Figure 1-18: Frequency Modulated VDL Mode 2 Source.....	46
Figure 1-19: Intermodulation Measurement (BER).....	49
Figure 1-20: Intermodulation Measurement (FER).....	49
Figure 1-21: Output Power Measurement.....	51
Figure 1-22: RF Power Rise and Release Time Measurement.....	52
Figure 1-23: Ramp Up and Beginning of VDL Mode 2 Synchronization Sequence.....	53
Figure 1-24: Spurious Emissions Measurement.....	55
Figure 1-25: First Adjacent Channel Power Measurement.....	56
Figure 1-26: Second, Third and Fourth Adjacent Channel Power Measurement.....	57
Figure 1-27: Measurement beyond 4 th Adjacent Channel.....	60
Figure 1-28: Load VSWR Capability.....	61
Figure 1-29: Receive to Transmit Turn-Around Time Measurement.....	63
Figure 1-30: Transmit to Receive Turn-Around Time Measurement.....	64
Figure 1-31: Channel Sensing Test Configuration.....	67
Figure 1-32: PIN Attenuator Control Signals for Channel Sense Test.....	68
Figure 1-33: Error Detection.....	84
Figure 1-34: Station Identification.....	84
Figure 1-35: Timer T1 (delay before retransmission).....	91
Figure 1-36: Timer T2 (delay before acknowledgement).....	92
Figure 1-37: Timer T3 (link initialization time).....	93
Figure 1-38: Parameter N1 (maximum number of bits in frame).....	95
Figure 1-39: Counter N2 (maximum number of transmissions).....	96
Figure 1-40: Parameter k (window size).....	97

Figure 1-41: Operational Mode.....	98
Figure 1-42: Non-Operational Mode	99
Figure 1-43: Frame Reject Mode	102
Figure 1-44: INFO frames	104
Figure 1-45: DLE Procedures	105
Figure 1-46: XID Frame	110
Figure 1-47: Procedures for Transmission.....	113
Figure 1-48: SREJ Frame.....	114
Figure 1-49: TEST Frame	118
Figure 1-50: Timer TG2.....	125
Figure 1-51: Link Establishment.....	136
Figure 1-52: Ground Requested Broadcast Handoff (a) (partial)	179
Figure 1-53: (RESERVED)	217
Figure 1-54: Packet Fragmentation and Reassembly.....	217
Figure 1-55: Error Recovery	218
Figure 1-56: Connection Flow Control.....	220
Figure C-57: Upper Bound on FER vs. BER for VDL Mode 2 Reed-Solomon Decoding	C-3

1. PURPOSE AND SCOPE

1.1 Introduction

This document contains the Minimum Operational Performance Standards (MOPS) and test procedures for aircraft Very High Frequency (VHF) Digital Link (VDL) Mode 2 physical, link and network layer protocol components which comprise an avionics transmitter/receiver (transceiver) function intended to be used for air-ground (A/G) data communications. This document is designed so that equipment certified to it will be compatible with the relevant Minimum Aviation System Performance Standards (MASPS) in RTCA DO-224C and with International Civil Aviation Organization (ICAO) Doc 9776, *Manual on VHF Digital Link (VDL) Mode 2*, which is also known as the VDL Mode 2 Technical Manual. Additional information on VDL Mode 2 is contained in ARINC Specification 631 and ARINC Characteristics 750 and 758.

Compliance with this MOPS is one means of assuring that the VDL Mode 2 equipment will function satisfactorily under all conditions normally encountered in air traffic services communications and that data formats will be compatible with the Aeronautical Telecommunication Network (ATN). These standards specify characteristics useful to designers, manufacturers, installers, and users of the VDL Mode 2 A/G communications system equipment. This document is organized with the following order and format:

- Section 1 describes the purpose and scope.
- Section 2 describes the minimum operational performance standards for:
 - general design requirements
 - standard conditions
 - environmental conditions
 - equipment test procedures
- Section 3 describes the installed equipment tests.
- Section 4 describes the operational tests.

Appendix A contains a list of acronyms used in this document.

Appendix B provides a correlation matrix between the test procedures of Section 2.4 and the VDL Mode 2 system level requirements given in RTCA DO-224C, and the equipment architecture classes defined in Section 1.3. This appendix is normative in the sense that it specifically identifies which requirements make up the minimum set for the standard classes of equipment.

Appendix C provides the analysis that establishes the equivalency between the Frame Error Rate and the bit error rate. This appendix provides the basis for the use of either bit error rate or frame error rate in the verification procedures of Section 2.4.

Appendix D defines the minimum functionality of the Data/Management Interface for Class Y and Class Z architectures. This functionality is described at a high level. No protocol details (i.e., bit definition, data rate, physical layer details, etc.) for the Data/Management Interface are given in this document. Such a standardized interface is the AVLC Simple Interface Protocol (ASIP) described in Attachment 10 to ARINC Characteristic 750.