

RTCA, Inc.
1150 18th Street, NW, Suite 910
Washington, DC 20036, USA

Minimum Operational Performance Standards (MOPS) for Universal Access Transceiver (UAT) Automatic Dependent Surveillance - Broadcast (ADS-B)

(Corrigendum Appendix T, integrated and highlighted)

RTCA DO-282B
December 2, 2009
Supersedes RTCA DO-282A, including Change 1
Corrigendum 1 (Included)
December 13, 2011

Prepared by: SC-186
© 2011 RTCA, Inc.

Copies of this document may be obtained from

RTCA, Inc

Telephone: 202-335-9339

Facsimile: 202-335-4344

Internet: www.rtca.org

Please visit the RTCA Online Store for document pricing and ordering information.

FOREWORD

This report was prepared by Special Committee 186 (SC-186) and approved by the RTCA Program Management Committee (PMC) on December 13, 2011.

RTCA, Incorporated is a not-for-profit corporation formed to advance the art and science of aviation and aviation electronic systems for the benefit of the public. The organization functions as a Federal Advisory Committee and develops consensus based recommendations on contemporary aviation issues. RTCA's objectives include but are not limited to:

- coalescing aviation system user and provider technical requirements in a manner that helps government and industry meet their mutual objectives and responsibilities;
- analyzing and recommending solutions to the system technical issues that aviation faces as it continues to pursue increased safety, system capacity and efficiency;
- developing consensus on the application of pertinent technology to fulfill user and provider requirements, including development of minimum operational performance standards for electronic systems and equipment that support aviation; and
- assisting in developing the appropriate technical material upon which positions for the International Civil Aviation Organization and the International Telecommunications Union and other appropriate international organizations can be based.

The organization's recommendations are often used as the basis for government and private sector decisions as well as the foundation for many Federal Aviation Administration Technical Standard Orders.

Since RTCA is not an official agency of the United States Government, its recommendations may not be regarded as statements of official government policy unless so enunciated by the U.S. government organization or agency having statutory jurisdiction over any matters to which the recommendations relate.

This Page Intentionally Left Blank

TABLE OF CONTENTS

1	PURPOSE AND SCOPE	1
1.1	INTRODUCTION.....	1
1.2	ADS-B SYSTEM OVERVIEW	4
1.3	UAT SYSTEM OVERVIEW.....	5
1.3.1	UAT MEDIUM ACCESS FOR ADS-B AND GROUND UPLINK SEGMENTS	5
1.3.2	GROUND UPLINK MESSAGE TRANSMISSIONS	6
1.3.3	ADS-B MESSAGE TRANSMISSIONS	7
1.3.4	TRAFFIC INFORMATION SERVICE - BROADCAST (TIS-B) TRANSMISSION	7
1.3.5	UAT ADS-B MESSAGE STRUCTURE AND SCHEDULING	8
1.4	OPERATIONAL GOALS AND APPLICATIONS.....	9
1.4.1	APPLICATIONS INVOLVING COCKPIT DISPLAY OF TRAFFIC INFORMATION (CDTI)	10
1.4.1.1	Aid to Visual Acquisition.....	10
1.4.1.2	Enhanced Traffic Situational Awareness.....	10
1.4.1.3	Station Keeping and Maintenance of Established Separation	10
1.4.1.4	CDTI-Based Electronic Flight Rules (CEFR).....	11
1.4.2	APPLICATIONS INVOLVING AIRBORNE CONFLICT MANAGEMENT AND FUTURE COLLISION AVOIDANCE	11
1.4.2.1	Future Airborne Collision Avoidance.....	11
1.4.2.2	Airborne Conflict Management.....	11
1.4.3	AIRPORT SURFACE APPLICATIONS	11
1.4.4	SUPPORT OF GROUND-BASED SURVEILLANCE APPLICATIONS	12
1.4.5	OTHER APPLICATIONS.....	12
1.5	ASSUMPTIONS AND RATIONALE.....	12
1.6	TEST PROCEDURES.....	12
2	EQUIPMENT PERFORMANCE REQUIREMENTS AND TEST PROCEDURES.....	15
2.1	GENERAL REQUIREMENTS.....	15
2.1.1	AIRWORTHINESS	15
2.1.2	INTENDED FUNCTION	15
2.1.3	FEDERAL COMMUNICATIONS COMMISSION RULES	15
2.1.4	FIRE PROTECTION	15
2.1.5	OPERATION OF CONTROLS	15
2.1.6	ACCESSIBILITY OF CONTROLS.....	15
2.1.7	EQUIPMENT INTERFACES.....	15
2.1.8	EFFECTS OF TEST	16
2.1.9	INTEGRATION WITH OTHER AVIONICS EQUIPMENT	16
2.1.10	DESIGN ASSURANCE	16
2.1.11	EQUIPAGE CLASSES	16
2.1.12	TRANSMITTING SUBSYSTEM	18
2.1.13	RECEIVING SUBSYSTEM	19
2.1.14	ANTENNA SUBSYSTEM.....	19
2.2	EQUIPMENT PERFORMANCE – STANDARD CONDITIONS.....	19
2.2.1	DEFINITION OF STANDARD CONDITIONS	19
2.2.1.1	Signal Levels	19

2.2.1.2	Desired Signals	19
2.2.1.3	Data Quantization	19
2.2.2	ADS-B TRANSMITTER CHARACTERISTICS	20
2.2.2.1	Transmission Frequency	20
2.2.2.2	Modulation Rate.....	20
2.2.2.3	Modulation Type.....	20
2.2.2.4	Modulation Distortion.....	21
2.2.2.5	Transmitter Power Output	21
2.2.2.6	In Band Transmission Spectrum.....	22
2.2.2.7	Out-of-Band Emissions	23
2.2.3	BROADCAST MESSAGE CHARACTERISTICS	23
2.2.3.1	ADS-B Message Format	24
2.2.3.1.1	Synchronization	24
2.2.3.1.2	Payload	24
2.2.3.1.3	FEC Parity	24
2.2.3.1.3.1	Code Type.....	24
2.2.3.1.3.2	Generation and Transmission Order of FEC Parity.....	25
2.2.3.2	Ground Uplink Message Format	25
2.2.3.2.1	Synchronization	26
2.2.3.2.2	Payload (Before Interleaving and After De-interleaving)	26
2.2.3.2.2.1	UAT-Specific Header.....	27
2.2.3.2.2.1.1	“GROUND STATION LATITUDE” Field Encoding	27
2.2.3.2.2.1.2	“GROUND STATION LONGITUDE” Field Encoding	27
2.2.3.2.2.1.3	“POSITION VALID” Field Encoding	28
2.2.3.2.2.1.4	“UTC COUPLED” Field Encoding	28
2.2.3.2.2.1.5	Reserved Bit.....	28
2.2.3.2.2.1.6	“APPLICATION DATA VALID” Field Encoding.....	28
2.2.3.2.2.1.7	“SLOT ID” Field Encoding.....	28
2.2.3.2.2.1.8	“TIS-B SITE ID” Field Encoding.....	28
2.2.3.2.2.1.9	Reserved Bits	29
2.2.3.2.2.2	Ground Uplink Application Data.....	29
2.2.3.2.2.2.1	The Length Subfield Encoding.....	29
2.2.3.2.2.2.2	The Reserved Subfield Encoding.....	29
2.2.3.2.2.2.3	The Frame Type Subfield Encoding.....	30
2.2.3.2.2.2.4	The Frame Data Content	30
2.2.3.2.2.2.4.1	FIS-B APDU.....	30
2.2.3.2.2.2.4.2	TIS-B/ADS-R Service Status	30
2.2.3.2.2.2.4.3	Other Potential Future Frame Data Content.....	30
2.2.3.2.3	FEC Parity (Before Interleaving and After De-interleaving).....	31
2.2.3.2.3.1	Code Type	31
2.2.3.2.3.2	Generation and Transmission Order of FEC Parity.....	31
2.2.3.2.4	Interleaved Payload and FEC Parity.....	31
2.2.4	THE ADDRESS MESSAGE PAYLOAD	32
2.2.4.1	Payload Type	32
2.2.4.2	Payload Elements.....	32
2.2.4.3	ADS-B Payload Composition by Payload Type Code	33
2.2.4.4	Payload Transmission Order	33
2.2.4.5	Payload Contents	34
2.2.4.5.1	HEADER Element	34
2.2.4.5.1.1	“PAYLOAD TYPE CODE” Field Encoding.....	34
2.2.4.5.1.2	“ADDRESS QUALIFIER” Field Encoding	34
2.2.4.5.1.3	“ADDRESS” Field Encoding.....	35
2.2.4.5.1.3.1	ICAO 24-bit Aircraft Address of Transmitting Aircraft.....	35

2.2.4.5.1.3.2	Self-Assigned Temporary Address of Transmitting Aircraft.....	35
2.2.4.5.1.3.3	ICAO 24-bit Aircraft Address of TIS-B or ADS-R Target Aircraft	36
2.2.4.5.1.3.4	TIS-B Track File Identifier.....	36
2.2.4.5.1.3.5	Surface Vehicle Address	36
2.2.4.5.1.3.6	Fixed ADS-B Beacon Address	36
2.2.4.5.1.3.7	ADS-R Target with Non-ICAO Address	36
2.2.4.5.2	STATE VECTOR Element	37
2.2.4.5.2.1	“LATITUDE” and “LONGITUDE” Field Encoding.....	37
2.2.4.5.2.2	“ALTITUDE TYPE” Field Encoding.....	40
2.2.4.5.2.3	“ALTITUDE” Field Encoding	40
2.2.4.5.2.4	“NIC” Field Encoding.....	41
2.2.4.5.2.5	“A/G STATE” Field Encoding.....	43
2.2.4.5.2.5.1	Determination of Vertical Status	44
2.2.4.5.2.5.2	Validation of Vertical Status	46
2.2.4.5.2.6	“HORIZONTAL VELOCITY” Subfields	47
2.2.4.5.2.6.1	Encoding as “North Velocity” Form.....	47
2.2.4.5.2.6.2	Encoding as “Ground Speed” Form.....	48
2.2.4.5.2.6.3	Encoding as “East Velocity” Form.....	49
2.2.4.5.2.6.4	Encoding as “Track Angle/Heading” Form	50
2.2.4.5.2.7	“VERTICAL VELOCITY or A/V SIZE” Field.....	51
2.2.4.5.2.7.1	Encoding as “Vertical Velocity” Form	51
2.2.4.5.2.7.1.1	“VV Src” Subfield Encoding.....	51
2.2.4.5.2.7.1.2	“VV Sign” Subfield Encoding.....	52
2.2.4.5.2.7.1.3	“Vertical Rate” Subfield Encoding.....	52
2.2.4.5.2.7.2	Encoding as “A/V Size” Form.....	53
2.2.4.5.2.8	“UTC” Field Encoding.....	55
2.2.4.5.2.9	Uplink Feedback Encoding	55
2.2.4.5.2.10	Reserved Byte 18 of Payload Type Zero	57
2.2.4.5.3	STATE VECTOR Element (For TIS-B or ADS-R).....	57
2.2.4.5.3.1	“TIS-B SITE ID” Field Encoding.....	58
2.2.4.5.3.2	Encoding for All Other Fields	58
2.2.4.5.4	MODE STATUS Element.....	59
2.2.4.5.4.1	“EMITTER CATEGORY” Field	59
2.2.4.5.4.2	“CALL SIGN/FLIGHT PLAN ID” Field	60
2.2.4.5.4.3	Compressed Format Encoding for “EMITTER CATEGORY” and “CALL SIGN /FLIGHT PLAN ID”.....	62
2.2.4.5.4.3.1	Bytes 18 and 19	62
2.2.4.5.4.3.2	Bytes 20 and 21.....	62
2.2.4.5.4.3.3	Bytes 22 and 23.....	62
2.2.4.5.4.4	“EMERGENCY/PRIORITY STATUS” Field Encoding.....	63
2.2.4.5.4.5	“UAT MOPS VERSION” Field Encoding	63
2.2.4.5.4.6	“SD” Field Encoding.....	64
2.2.4.5.4.7	“TRANSMIT MSO” Field Encoding	65
2.2.4.5.4.8	“System Design Assurance” (SDA) Field Encoding.....	65
2.2.4.5.4.9	“NAC _P ” Field Encoding.....	65
2.2.4.5.4.10	“NAC _V ” Field Encoding	66
2.2.4.5.4.11	“NIC _{BARO} ” Field Encoding.....	67
2.2.4.5.4.12	“CAPABILITY CODES” Field Encoding.....	68
2.2.4.5.4.12.1	“UAT IN Capability” Subfield Encoding	68
2.2.4.5.4.12.2	“1090ES IN Capability” Subfield Encoding	69
2.2.4.5.4.12.3	“TCAS/ACAS Operational” Subfield Encoding.....	69
2.2.4.5.4.13	“OPERATIONAL MODES” Field Encoding	69
2.2.4.5.4.13.1	“TCAS/ACAS Resolution Advisory” Flag.....	70

2.2.4.5.4.13.2	“IDENT Switch Active” Flag	70
2.2.4.5.4.13.3	“Reserved for Receiving ATC Services” Flag	70
2.2.4.5.4.14	Call Sign Identification (CSID) Flag	71
2.2.4.5.4.15	CSID Logic Configuration Item	71
2.2.4.5.4.16	Source Integrity Level (SIL) Supplement (SIL _{SUPP}) Flag Encoding	71
2.2.4.5.4.17	“Geometric Vertical Accuracy” (GVA) Field Encoding	72
2.2.4.5.4.18	“Single Antenna” Flag Encoding	72
2.2.4.5.4.19	Navigational Integrity Category (NIC) Supplement (NIC _{SUPP}) Flag	73
2.2.4.5.4.20	Reserved Bits	73
2.2.4.5.5	AUXILIARY STATE VECTOR Element	73
2.2.4.5.5.1	“SECONDARY ALTITUDE” Field Encoding	73
2.2.4.5.5.2	Reserved Bits	74
2.2.4.5.6	TARGET STATE Element (Payload Type Codes “3” and “4”)	74
2.2.4.5.6.1	“Selected Altitude Type (SAT)” Field Encoding	74
2.2.4.5.6.2	“Selected Altitude” Field Encoding	75
2.2.4.5.6.3	“Barometric Pressure Setting” (Minus 800 millibars) Field Encoding	75
2.2.4.5.6.4	“Selected Heading” Field Encoding	76
2.2.4.5.6.5	“Status of MCP/FCU Mode Bits” (ST) Field Encoding	77
2.2.4.5.6.6	“Mode Indicators: Autopilot Engaged” (AP) Field Encoding	77
2.2.4.5.6.7	“Mode Indicators: VNAV Mode Engaged” (VNAV) Field Encoding	78
2.2.4.5.6.8	“Mode Indicators: Altitude Hold Mode” (ALT) Field Encoding	78
2.2.4.5.6.9	“Mode Indicators: Approach Mode” (APP) Field Encoding	78
2.2.4.5.6.10	“Mode Indicators: LNAV Mode Engaged” (LNAV) Field Encoding	78
2.2.4.5.6.11	Reserved Bits	78
2.2.4.5.7	TARGET STATE Element (Payload Type Code “5”)	78
2.2.4.5.8	TRAJECTORY CHANGE Element	79
2.2.5	PROCEDURES FOR PROCESSING OF TIME DATA	79
2.2.5.1	UTC Coupled Condition	79
2.2.5.2	Non-UTC Coupled Condition	81
2.2.6	PROCEDURES FOR ADS-B MESSAGE TRANSMISSION	82
2.2.6.1	Scheduling of ADS-B Message Type	82
2.2.6.1.1	Payload Selection Cycle	82
2.2.6.1.2	ADS-B Payload Type Allocation	83
2.2.6.1.2.1	Event-Driven ADS-B Payload Allocation	83
2.2.6.1.3	Message Transmission Cycle	84
2.2.6.2	ADS-B Message Transmit Timing	84
2.2.6.2.1	The Message Start Opportunity (MSO)	84
2.2.6.2.2	Relationship of the MSO to the Modulated Data	85
2.2.6.3	Report Assembly on Transmission of Ownship ADS-B Message	86
2.2.7	UAT TRANSMITTER MESSAGE DATA CHARACTERISTICS	86
2.2.7.1	UAT Transmitter Input Requirements	86
2.2.7.2	Time Registration and Latency	88
2.2.7.2.1	Requirements When in Non-Precision Condition and UTC Coupled	88
2.2.7.2.2	Requirements When in Precision Condition and UTC Coupled	89
2.2.7.2.3	Requirements When Non-UTC Coupled	89
2.2.7.2.4	Total Latency of Position Measurements	89
2.2.7.2.5	Data Timeout	89
2.2.8	RECEIVER CHARACTERISTICS	90
2.2.8.1	Receiving Diversity	90
2.2.8.2	Receiver Performance	91
2.2.8.2.1	Receiver Sensitivity	91
2.2.8.2.1.1	Long ADS-B Message As Desired Signal	91
2.2.8.2.1.2	Basic ADS-B Message As Desired Signal	91

2.2.8.2.1.3	Ground Uplink Message As Desired Signal	92
2.2.8.2.2	Receiver Desired Signal Dynamic Range	92
2.2.8.2.3	Receiver Selectivity	92
2.2.8.2.4	Receiver Tolerance to Pulsed Interference	93
2.2.8.2.5	Receiver Tolerance to Overlapping ADS-B Messages (Self Interference)	94
2.2.8.2.6	Rate of False “Trigger”	94
2.2.8.2.7	Trigger Processing Rate	95
2.2.8.3	Receiver Message Processing.....	95
2.2.8.3.1	Criteria for Successful Message Reception.....	95
2.2.8.3.1.1	ADS-B Messages	95
2.2.8.3.1.2	Ground Uplink Messages	95
2.2.8.3.2	Receiver Discrimination Between ADS-B and Ground Uplink Message Types	96
2.2.8.3.3	Receiver Processing of ADS-B Synchronization “Trigger”	96
2.2.8.3.4	Receiver Processing of Ground Uplink Synchronization “Trigger”	97
2.2.8.3.5	Receiver Time of Message Receipt	97
2.2.9	REPORT ASSEMBLY REQUIREMENTS	98
2.2.9.1	Report Assembly on Receipt of ADS-B Message.....	98
2.2.9.2	Report Assembly on Receipt of Ground Uplink Message.....	98
2.2.10	RECEIVER SUBSYSTEM CAPACITY AND THROUGHPUT REQUIREMENTS	99
2.2.10.1	Fundamental Principals of Report Assembly	99
2.2.10.2	Capacity for Successful Message Reception.....	100
2.2.10.3	Applicable Messages.....	100
2.2.10.4	Message Reception-to-Report Completion Time	101
2.2.11	SPECIAL REQUIREMENTS FOR TRANSCEIVER IMPLEMENTATION	101
2.2.11.1	Transmit-Receive Turnaround Time	101
2.2.11.2	Receive-Transmit Turnaround Time	102
2.2.12	MUTUAL SUPPRESSION PULSES.....	102
2.2.13	SELF TEST AND MONITORS	102
2.2.13.1	Self Test.....	102
2.2.13.2	Broadcast Monitoring.....	103
2.2.13.3	Address Verification	103
2.2.13.4	Receiver Self-Test Capability.....	103
2.2.13.5	Failure Annunciation.....	103
2.2.13.5.1	UAT Transmitting Subsystem and ADS-B Function Failure Annunciations	103
2.2.13.5.2	UAT Receiving Subsystem Failure Annunciation	103
2.2.13.5.3	Co-Located UAT Transmitting and Receiving Device Failure Annunciation	104
2.2.14	ANTENNA SYSTEM	104
2.2.14.1	Polarization	104
2.2.14.2	Antenna Voltage Standing Wave Ratio (VSWR)	104
2.2.14.3	Requirements for Optional Passive Diplexer	104
2.2.14.3.1	Diplexer RF Requirements	105
2.2.14.3.1.1	The UAT Channel	105
2.2.14.3.1.2	The Transponder Channel	105
2.2.14.3.1.3	Channel to Channel Isolation	105
2.2.15	UAT INTERFACES	106
2.2.15.1	UAT Transmitting Subsystem Interfaces.....	106
2.2.15.1.1	UAT Transmitting Subsystem Input Interfaces.....	106
2.2.15.1.1.1	Discrete Input Interfaces	106
2.2.15.1.1.2	Digital Communication Input Interfaces.....	106
2.2.15.1.1.3	Processing Efficiency	106
2.2.15.1.2	UAT Transmitting Subsystem Output Interfaces	106
2.2.15.1.2.1	Discrete Output Interfaces	106
2.2.15.1.2.2	Digital Communication Output Interfaces	106

2.2.15.2	UAT Receiving Subsystem Interfaces	107
2.2.15.2.1	UAT Receiving Subsystem Input Interfaces	107
2.2.15.2.1.1	Discrete Input Interfaces	107
2.2.15.2.1.2	Digital Communication Input Interfaces	107
2.2.15.2.1.3	Processing Efficiency	107
2.2.15.2.2	UAT Receiving Subsystem Output Interfaces	107
2.2.15.2.2.1	Discrete Output Interfaces	107
2.2.15.2.2.2	Digital Communication Output Interfaces	107
2.2.16	POWER INTERRUPTION	107
2.2.17	COMPATIBILITY WITH OTHER SYSTEMS	108
2.2.17.1	EMI Compatibility	108
2.2.17.2	Compatibility with GPS Receivers	108
2.2.17.3	Compatibility with Other Navigation Receivers and ATC Transponders	108
2.3	EQUIPMENT PERFORMANCE – ENVIRONMENTAL CONDITIONS	108
2.3.1	ENVIRONMENTAL TEST CONDITIONS	109
2.3.2	DETAILED ENVIRONMENTAL TEST PROCEDURES	111
2.3.2.1	Transmission Frequency (§2.2.2.1)	112
2.3.2.2	Modulation Type (§2.2.2.3)	112
2.3.2.3	Modulation Rate and Distortion (§2.2.2.2 and §2.2.2.4)	112
2.3.2.4	Transmitter Power Output (§2.2.2.5)	112
2.3.2.5	In-Band Transmission Spectrum (§2.2.2.6)	112
2.3.2.6	Message Transmission Cycle (Transmitter Diversity) (§2.2.6.1.3)	112
2.3.2.7	Message Start Opportunity (MSO) (§2.2.6.2.1)	112
2.3.2.8	Relationship of the MSO to the Modulated Data (§2.2.6.2.2)	112
2.3.2.9	Report Assembly on Transmission of Ownship ADS-B Message (§2.2.6.3 and §2.2.7.1)	112
2.3.2.10	Receiving Diversity (§2.2.8.1)	114
2.3.2.10.1	Full Diversity (§2.2.8.1.a and §2.2.8.1.b)	114
2.3.2.10.2	Antenna Switching (§2.2.8.1.c)	114
2.3.2.11	Long ADS-B Message As Desired Signal (§2.2.8.2.1.1)	115
2.3.2.12	Basic ADS-B Message As Desired Signal (§2.2.8.2.1.2)	115
2.3.2.13	Ground Uplink Message As Desired Signal (§2.2.8.2.1.3)	115
2.3.2.14	Receiver Desired Signal Dynamic Range (§2.2.8.2.2)	115
2.3.2.15	Receiver Selectivity (§2.2.8.2.3)	115
2.3.2.16	Report Assembly on Receipt of ADS-B Message (§2.2.9.1)	115
2.3.2.17	Report Assembly on Receipt of Ground Uplink Message (§2.2.9.2)	115
2.3.2.18	Address Verification (§2.2.13.3)	115
2.3.2.19	Receiver Self Test Capability (§2.2.13.4)	115
2.3.2.20	Transmission Device Failure Annunciation (§2.2.13.5.1)	115
2.3.2.21	Requirements for Optional Passive Diplexer (§2.2.14.3)	115
2.3.2.22	Power Interruption (§2.2.16)	116
2.3.2.22.1	Power Interruption for ADS-B Transmitting Subsystems (§2.2.16)	116
2.3.2.22.2	Power Interruption for ADS-B Receiving Subsystems (§2.2.16)	116
2.4	EQUIPMENT TEST PROCEDURES	116
2.4.1	DEFINITION OF STANDARD CONDITIONS OF TEST	116
2.4.1.1	Verification of Signal Levels (§2.2.1.1)	117
2.4.1.2	Verification of Desired Signals (§2.2.1.2)	117
2.4.1.3	Verification of Data Quantization (§2.2.1.3)	117
2.4.2	VERIFICATION OF ADS-B TRANSMITTER CHARACTERISTICS (§2.2.2)	117
2.4.2.1	Verification of Transmission Frequency (§2.2.2.1)	118
2.4.2.2	Verification of Modulation Rate (§2.2.2.2)	121
2.4.2.3	Verification of Modulation Type (§2.2.2.3)	121
2.4.2.4	Verification of Modulation Distortion (§2.2.2.4)	122
2.4.2.5	Verification of Transmitter Power Output (§2.2.2.5)	123

2.4.2.6	Verification of In Band Transmission Spectrum (§2.2.2.6).....	126
2.4.2.7	Verification of Out-of-Band Emissions (§2.2.2.7).....	127
2.4.3	VERIFICATION OF BROADCAST MESSAGE CHARACTERISTICS (§2.2.3).....	127
2.4.3.1	Verification of ADS-B Message Format (§2.2.3.1).....	127
2.4.3.1.1	Verification of Synchronization (§2.2.3.1.1).....	128
2.4.3.1.2	Verification of Payload (§2.2.3.1.2).....	128
2.4.3.1.3	Verification of FEC Parity (§2.2.3.1.3).....	128
2.4.3.1.3.1	Verification of Code Type (§2.2.3.1.3.1).....	128
2.4.3.1.3.2	Verification of Generation and Transmission Order of FEC Parity (§2.2.3.1.3.2).....	134
2.4.3.2	Verification of Ground Uplink Message Format (§2.2.3.2).....	134
2.4.3.2.1	Verification of Synchronization (§2.2.3.2.1).....	134
2.4.3.2.2	Verification of Payload (Before Interleaving and After De-interleaving) (§2.2.3.2.2).....	134
2.4.3.2.2.1	Verification of UAT-Specific Header (§2.2.3.2.2.1).....	134
2.4.3.2.2.1.1	Verification of “GROUND STATION LATITUDE” Field Encoding (§2.2.3.2.2.1.1)....	134
2.4.3.2.2.1.2	Verification of “GROUND STATION LONGITUDE” Field Encoding (§2.2.3.2.2.1.2)	134
2.4.3.2.2.1.3	Verification of “POSITION VALID” Field Encoding (§2.2.3.2.2.1.3).....	134
2.4.3.2.2.1.4	Verification of “UTC Coupled” Field Encoding (§2.2.3.2.2.1.4).....	134
2.4.3.2.2.1.5	Verification of Reserved Bits (§2.2.3.2.2.1.5).....	134
2.4.3.2.2.1.6	Verification of “APPLICATION DATA VALID” Field Encoding (§2.2.3.2.2.1.6).....	134
2.4.3.2.2.1.7	Verification of “SLOT ID” Field Encoding (§2.2.3.2.2.1.7).....	134
2.4.3.2.2.1.8	Verification of “TIS-B SITE ID” Field Encoding (§2.2.3.2.2.1.8).....	135
2.4.3.2.2.1.9	Verification of Reserved Bits (§2.2.3.2.2.1.9).....	135
2.4.3.2.2.2	Verification of Ground Uplink Application Data (§2.2.3.2.2.2).....	135
2.4.3.2.2.2.1	Verification of The Length Subfield Encoding (§2.2.3.2.2.2.1).....	135
2.4.3.2.2.2.2	Verification of The Reserved Subfield Encoding (§2.2.3.2.2.2.2).....	135
2.4.3.2.2.2.3	Verification of The Frame Type Subfield Encoding (§2.2.3.2.2.2.3).....	135
2.4.3.2.2.2.4	Verification of The Frame Data Content (§2.2.3.2.2.2.4).....	135
2.4.3.2.2.2.4.1	Verification of FIS-B APDU (§2.2.3.2.2.2.4.1).....	135
2.4.3.2.2.2.4.2	Verification of Other Potential Future Frame Data Content (§2.2.3.2.2.2.4.2).....	135
2.4.3.2.3	Verification of FEC Parity (Before Interleaving and After De-interleaving) (§2.2.3.2.3).....	135
2.4.3.2.3.1	Verification of Code Type (§2.2.3.2.3.1).....	135
2.4.3.2.3.2	Verification of Generation and Transmission Order of FEC Parity (§2.2.3.2.3.2).....	135
2.4.3.2.4	Verification of Interleaved Payload and FEC Parity (§2.2.3.2.4).....	135
2.4.4	VERIFICATION OF THE ADS-B MESSAGE PAYLOAD (§2.2.4).....	136
2.4.4.1	Verification of Payload Type (§2.2.4.1).....	136
2.4.4.2	Verification of Payload Elements (§2.2.4.2).....	136
2.4.4.3	Verification of ADS-B Payload Composition by Payload Type Code (§2.2.4.3).....	136
2.4.4.4	Verification of Payload Transmission Order (§2.2.4.4).....	136
2.4.4.5	Verification of Payload Contents (§2.2.4.5).....	136
2.4.4.5.1	Verification of HEADER Element (§2.2.4.5.1).....	136
2.4.4.5.1.1	Verification of “PAYLOAD TYPE CODE” Field Encoding (§2.2.4.5.1.1).....	136
2.4.4.5.1.2	Verification of “ADDRESS QUALIFIER” Field Encoding (§2.2.4.5.1.2).....	137
2.4.4.5.1.3	Verification of “ADDRESS” Field Encoding (§2.2.4.5.1.3).....	137
2.4.4.5.1.3.1	Verification of ICAO 24-bit Aircraft Address of Transmitting Aircraft (§2.2.4.5.1.3.1).	138
2.4.4.5.1.3.2	Verification of Self-Assigned Temporary Address of Transmitting Aircraft (§2.2.4.5.1.3.2).....	139
2.4.4.5.1.3.3	Verification of ICAO 24-bit Aircraft Address of TIS-B or ADS-R Target Aircraft (§2.2.4.5.1.3.3).....	141
2.4.4.5.1.3.4	Verification of TIS-B Track File Identifier (§2.2.4.5.1.3.4).....	142
2.4.4.5.1.3.5	Verification of Surface Vehicle Address (§2.2.4.5.1.3.5).....	142
2.4.4.5.1.3.6	Verification of Fixed ADS-D Beacon Address (§2.2.4.5.1.3.6).....	142
2.4.4.5.1.3.7	Verification of ADS-R Target with Non-ICAO Address (§2.2.4.5.1.3.7).....	142
2.4.4.5.2	Verification of STATE VECTOR Element (§2.2.4.5.2).....	142

2.4.4.5.2.1	Verification of “LATITUDE” and “LONGITUDE” Field Encoding (§2.2.4.5.2.1).....	143
2.4.4.5.2.1.1	Verification of Latitude and Longitude for $NAC_p < 10$ (§2.2.4.5.2.1 and §2.2.7.2.1)	144
2.4.4.5.2.1.2	Verification of Latitude and Longitude for $NAC_p \geq 10$ (§2.2.4.5.2.1 and §2.2.7.2.2)	149
2.4.4.5.2.2	Verification of “ALTITUDE TYPE” Field Encoding (§2.2.4.5.2.2).....	149
2.4.4.5.2.3	Verification of “ALTITUDE” Field Encoding (§2.2.4.5.2.3).....	151
2.4.4.5.2.4	Verification of “NIC” Field Encoding (§2.2.4.5.2.4).....	154
2.4.4.5.2.5	Verification of “A/G STATE” Field Encoding (§2.2.4.5.2.5).....	156
2.4.4.5.2.5.1	Verification of Determination of Vertical Status (§2.2.4.5.2.5.1).....	158
2.4.4.5.2.5.2	Verification of the Validation of Vertical Status (§2.2.4.5.2.5.2).....	159
2.4.4.5.2.6	Verification of “HORIZONTAL VELOCITY” Subfields (§2.2.4.5.2.6).....	162
2.4.4.5.2.6.1	Verification of Encoding as “North Velocity” Form (§2.2.4.5.2.6.1).....	162
2.4.4.5.2.6.1.1	Verification of the “North/South Velocity” Sign Flag (§2.2.4.5.2.6.1.a).....	162
2.4.4.5.2.6.1.2	Verification of the “North Velocity Magnitude” Subfield - Subsonic (§2.2.4.5.2.6.1.b).....	163
2.4.4.5.2.6.1.3	Verification of the “North Velocity Magnitude” Subfield - Supersonic (§2.2.4.5.2.6.1.b).....	166
2.4.4.5.2.6.2	Verification of Encoding as “Ground Speed” Form (§2.2.4.5.2.6.2).....	168
2.4.4.5.2.6.2.1	Verification of Reserved Bit (§2.2.4.5.2.6.2.a).....	169
2.4.4.5.2.6.2.2	Verification of the Encoding of the Ground Speed Magnitude – Subsonic (§2.2.4.5.2.6.2.b).....	169
2.4.4.5.2.6.3	Verification of Encoding as “East Velocity” Form (§2.2.4.5.2.6.3).....	171
2.4.4.5.2.6.3.1	Verification of the “East/West Velocity” Sign Flag (§2.2.4.5.2.6.3.a).....	171
2.4.4.5.2.6.3.2	Verification of the “East Velocity Magnitude” Subfield - Subsonic (§2.2.4.5.2.6.3.b).....	173
2.4.4.5.2.6.3.3	Verification of the “East Velocity Magnitude” Subfield - Supersonic (§2.2.4.5.2.6.3.b).....	175
2.4.4.5.2.6.4	Verification of Encoding as “Track Angle/Heading” Form (§2.2.4.5.2.6.4).....	178
2.4.4.5.2.6.4.1	Verification of “Track Angle/Heading Type” Flag Subfield (§2.2.4.5.2.6.4.a).....	178
2.4.4.5.2.6.4.2	Verification of the “Track Angle/Heading” Data Subfield (§2.2.4.5.2.6.4.b).....	179
2.4.4.5.2.7	Verification of “VERTICAL VELOCITY or A/V SIZE” Field (§2.2.4.5.2.7).....	180
2.4.4.5.2.7.1	Verification of Encoding as “Vertical Velocity” Form (§2.2.4.5.2.7.1).....	181
2.4.4.5.2.7.1.1	Verification of “VV Src” Subfield Encoding (§2.2.4.5.2.7.1.1).....	181
2.4.4.5.2.7.1.2	Verification of “VV Sign” Subfield Encoding (§2.2.4.5.2.7.1.2).....	181
2.4.4.5.2.7.1.3	Verification of “Vertical Rate” Subfield Encoding (§2.2.4.5.2.7.1.3).....	183
2.4.4.5.2.7.2	Verification of Encoding as “A/V Size” Form (§2.2.4.5.2.7.2).....	185
2.4.4.5.2.8	Verification of “UTC” Field Encoding (§2.2.4.5.2.8).....	186
2.4.4.5.2.9	Verification of Uplink Feedback Encoding (§2.2.4.5.2.9).....	187
2.4.4.5.2.10	Verification of Reserved Byte 18, Payload Type Zero (§2.2.4.5.2.10).....	188
2.4.4.5.3	Verification of STATE VECTOR Element (For TIS-B) (§2.2.4.5.3).....	189
2.4.4.5.3.1	Verification of “TIS-B SITE ID” Field Encoding (§2.2.4.5.3.1).....	189
2.4.4.5.3.2	Verification of Encoding for All Other Fields (§2.2.4.5.3.2).....	189
2.4.4.5.4	Verification of MODE STATUS Element (§2.2.4.5.4).....	189
2.4.4.5.4.1	Verification of “EMITTER CATEGORY” Field (§2.2.4.5.4.1).....	189
2.4.4.5.4.2	Verification of “CALL SIGN/FLIGHT PLAN ID” Field (§2.2.4.5.4.2).....	190
2.4.4.5.4.3	Verification of Compressed Format Encoding for “EMITTER CATEGORY” and “CALL SIGN/FLIGHT PLAN ID” (§2.2.4.5.4.3).....	190
2.4.4.5.4.3.1	Verification of Bytes #18 and #19 (§2.2.4.5.4.3.1).....	190
2.4.4.5.4.3.2	Verification of Bytes #20 and #21 (§2.2.4.5.4.3.2).....	191
2.4.4.5.4.3.3	Verification of Bytes #22 and 23 (§2.2.4.5.4.3.3).....	193
2.4.4.5.4.3.4	Verification of Unavailable “CALL SIGN/FLIGHT PLAN ID” Field (§2.2.4.5.4.2).....	194
2.4.4.5.4.4	Verification of “EMERGENCY/PRIORITY STATUS” Field Encoding (§2.2.4.5.4.4).....	195
2.4.4.5.4.5	Verification of “UAT MOPS VERSION” Field Encoding (§2.2.4.5.4.5).....	196
2.4.4.5.4.6	Verification of “SIL” Field Encoding (§2.2.4.5.4.6).....	196
2.4.4.5.4.7	Verification of “TRANSMIT MSO” Field Encoding (§2.2.4.5.4.7).....	197
2.4.4.5.4.8	Verification of System Design Assurance (SDA) Field Encoding (§2.2.4.5.4.8).....	197

2.4.4.5.4.9	Verification of “NAC _P ” Field Encoding (§2.2.4.5.4.9).....	198
2.4.4.5.4.10	Verification of “NAC _V ” Field Encoding (§2.2.4.5.4.10)	199
2.4.4.5.4.11	Verification of “NIC _{BARO} ” Field Encoding (§2.2.4.5.4.11).....	200
2.4.4.5.4.12	Verification of “CAPABILITY CODES” Field Encoding (§2.2.4.5.4.12).....	201
2.4.4.5.4.12.1	Verification of “UAT IN Capability” Subfield (§2.2.4.5.4.12.1).....	201
2.4.4.5.4.12.2	Verification of “1090ES IN Capability Subfield Encoding (§2.2.4.5.4.12.2).....	201
2.4.4.5.4.12.3	Verification of “TCAS/ACAS Operational” Subfield (§2.2.4.5.4.12.3).....	202
2.4.4.5.4.13	Verification of “OPERATIONAL MODES” Field Encoding (§2.2.4.5.4.13).....	203
2.4.4.5.4.13.1	Verification of “TCAS/ACAS Resolution Advisory” Flag (§2.2.4.5.4.13.1)	203
2.4.4.5.4.13.2	Verification of “IDENT Switch Active” Flag (§2.2.4.5.4.13.2)	204
2.4.4.5.4.13.3	Verification of “Reserved for Receiving ATC Services” Flag (§2.2.4.5.4.13.3)	205
2.4.4.5.4.14	Verification of Call Sign Identification (CSID) Flag (§2.2.4.5.4.14)	205
2.4.4.5.4.15	Verification of CSID Logic Configuration Item (§2.2.4.5.4.15)	206
2.4.4.5.4.16	Verification of “SIL Supplement (SIL _{SUPP}) (§2.2.4.5.4.16).....	206
2.4.4.5.4.17	Verification of “Geometric Vertical Accuracy (GVA) (§2.2.4.5.4.17).....	207
2.4.4.5.4.18	Verification of “Single Antenna (SA) Flag (§2.2.4.5.4.18).....	208
2.4.4.5.4.19	Verification of “NIC Supplement” (NIC _{SUPP}) Flag (§2.2.4.5.4.19).....	209
2.4.4.5.4.20	Verification of Reserved Bits (§2.2.4.5.4.20)	209
2.4.4.5.5	Verification of AUXILIARY STATE VECTOR Element (§2.2.4.5.5).....	209
2.4.4.5.5.1	Verification of “SECONDARY ALTITUDE” Field Encoding (§2.2.4.5.5.1).....	209
2.4.4.5.5.2	Verification of Reserved Bits (§2.2.4.5.5.2)	212
2.4.4.5.6	Verification of TARGET STATE Element (Payload Type Codes “3” and “4”) (§2.2.4.5.6).....	213
2.4.4.5.6.1	Verification of “SELECTED ALTITUDE TYPE (SAT)” Field Encoding (§2.2.4.5.6.1).....	213
2.4.4.5.6.2	Verification of “Selected Altitude” Field Encoding (§2.2.4.5.6.2).....	213
2.4.4.5.6.3	Verification of “Barometric Pressure Setting” (Minus 800 millibars) Field Encoding (§2.2.4.5.6.3).....	214
2.4.4.5.6.4	Verification of “Selected Heading” Field Encoding (§2.2.4.5.6.4)	215
2.4.4.5.6.5	Verification of “Status of MCP/FCU Mode Bits” (ST) Field Encoding (§2.2.4.5.6.5).....	217
2.4.4.5.6.6	Verification of “Mode Indicators: Autopilot Engaged” (AP) Field Encoding (§2.2.4.5.6.6).....	217
2.4.4.5.6.7	Verification of “Mode Indicators: VNAV Mode Engaged” (VNAV) Field Encoding (§2.2.4.5.6.7).....	218
2.4.4.5.6.8	Verification of “Mode Indicators: Altitude Hold Mode” (ALT) Field Encoding (§2.2.4.5.6.8).....	218
2.4.4.5.6.9	Verification of “Mode Indicators: Approach Mode” (APP) Field Encoding (§2.2.4.5.6.9).....	219
2.4.4.5.6.10	Verification of “Mode Indicators: LNAV Mode Engaged” (LNAV) Field Encoding (§2.2.4.5.6.10).....	220
2.4.4.5.7	Verification of TARGET STATE Element (Payload Type Code “6”) (§2.2.4.5.7).....	220
2.4.4.5.8	Verification of TRAJECTORY CHANGE Element (§2.2.4.5.8).....	220
2.4.5	VERIFICATION OF PROCEDURES FOR PROCESSING OF TIME DATA (§2.2.5).....	221
2.4.5.1	Verification of UTC Coupled Condition (§2.2.5.1)	221
2.4.5.2	Verification of Non-UTC Coupled Condition (§2.2.5.2)	222
2.4.6	VERIFICATION OF PROCEDURES FOR ADS-B MESSAGE TRANSMISSION (§2.2.6).....	224
2.4.6.1	Verification of Scheduling of ADS-B Message Types (§2.2.6.1)	224
2.4.6.1.1	Verification of Payload Selection Cycle (§2.2.6.1.1).....	224
2.4.6.1.2	Verification of ADS-B Payload Type Allocation (§2.2.6.1.2)	224
2.4.6.1.3	Verification of Message Transmission Cycle (§2.2.6.1.3)	225
2.4.6.2	Verification of ADS-B Message Transmit Timing (§2.2.6.2).....	227
2.4.6.2.1	Verification of The Message Start Opportunity (MSO) (§2.2.6.2.1).....	227
2.4.6.2.2	Verification of Relationship of the MSO to the Modulated Data (§2.2.6.2.2).....	231
2.4.6.3	Verification of Report Assembly on Transmission of Ownship ADS-B Message (§2.2.6.3).....	232
2.4.7	VERIFICATION OF UAT TRANSMITTER MESSAGE DATA CHARACTERISTICS (§2.2.7)	233
2.4.7.1	Verification of UAT Transmitter Input Requirements (§2.2.7.1).....	233

2.4.7.2	Verification of Time Registration and Latency (§2.2.7.2)	235
2.4.7.2.1	Verification of Requirements When in Non-Precision Condition and UTC Coupled (§2.2.7.2.1)	235
2.4.7.2.1.1	Verification of Latitude and Longitude Requirements When in Non-Precision Condition and UTC Coupled (§2.2.7.2.1.a, §2.2.4.5.2.1, §2.2.4.5.2.6)	235
2.4.7.2.1.2	Verification of Requirements for Other ADS-B Message Fields When in Non-Precision Condition and UTC Coupled (§2.2.7.2.1.b)	237
2.4.7.2.2	Verification of Requirements When in Precision Condition and UTC Coupled (§2.2.7.2.2)	239
2.4.7.2.2.1	Verification of Latitude and Longitude Requirements When in Precision Condition and UTC Coupled (§2.2.7.2.2.a, §2.2.4.5.2.1, §2.2.4.5.2.6)	239
2.4.7.2.2.2	Verification of Requirements for Other ADS-B Message Fields When in Precision Condition and UTC Coupled (§2.2.7.2.2.b)	241
2.4.7.2.3	Verification of Requirements When Non-UTC Coupled (§2.2.7.2.3)	242
2.4.7.2.4	Verification of Total Latency of Position Measurements (§2.2.7.2.4)	243
2.4.7.2.5	Verification of Data Timeout (§2.2.7.2.5)	244
2.4.8	VERIFICATION OF RECEIVER CHARACTERISTICS (§2.2.8)	244
2.4.8.1	Verification of Receiving Diversity (§2.2.8.1)	244
2.4.8.1.1	Verification of Full Receiving Diversity (§2.2.8.1.a and §2.2.8.1.b)	244
2.4.8.1.2	Verification of Switching Receiving Diversity (§2.2.8.1.c)	245
2.4.8.2	Verification of Receiver Performance (§2.2.8.2)	248
2.4.8.2.1	Verification of Receiver Sensitivity (§2.2.8.2.1)	248
2.4.8.2.1.1	Verification of Long ADS-B Message As Desired Signal (§2.2.8.2.1.1)	248
2.4.8.2.1.2	Verification of Basic ADS-B Message As Desired Signal (§2.2.8.2.1.2)	249
2.4.8.2.1.3	Verification of Ground Uplink Message As Desired Signal (§2.2.8.2.1.3)	251
2.4.8.2.2	Verification of Receiver Desired Signal Dynamic Range (§2.2.8.2.2)	252
2.4.8.2.3	Verification of Receiver Selectivity (§2.2.8.2.3)	253
2.4.8.2.4	Verification of Receiver Tolerance to Pulsed Interference (§2.2.8.2.4)	258
2.4.8.2.5	Verification of Receiver Tolerance to Overlapping ADS-B Messages (Self Interference) (§2.2.8.2.5)	263
2.4.8.2.6	Verification of Rate of False “Trigger” (§2.2.8.2.6)	264
2.4.8.2.7	Verification of Trigger Processing Rate (§2.2.8.2.7)	265
2.4.8.3	Verification of Receiver Message Processing (§2.2.8.3)	266
2.4.8.3.1	Verification of Criteria for Successful Message Reception (§2.2.8.3.1)	267
2.4.8.3.1.1	Verification of ADS-B Messages (§2.2.8.3.1.1)	267
2.4.8.3.1.2	Verification of Ground Uplink Messages (§2.2.8.3.1.2)	275
2.4.8.3.2	Verification of Receiver Discrimination Between ADS-B and Ground Uplink Message Types (§2.2.8.3.2)	286
2.4.8.3.3	Verification of Receiver Processing of ADS-B Synchronization “Trigger” (§2.2.8.3.3)	286
2.4.8.3.4	Verification of Receiver Processing of Ground Uplink Synchronization “Trigger” (§2.2.8.3.4)	292
2.4.8.3.5	Verification of Receiver Time of Message Receipt (§2.2.8.3.5)	294
2.4.9	VERIFICATION OF REPORT ASSEMBLY REQUIREMENTS (§2.2.9)	295
2.4.9.1	Verification of Report Assembly on Receipt of ADS-B Message (§2.2.9.1)	295
2.4.9.2	Verification of Report Assembly on Receipt of Ground Uplink Message (§2.2.9.2)	296
2.4.10	VERIFICATION OF RECEIVER SUBSYSTEM CAPACITY AND THROUGHPUT REQUIREMENTS (§2.2.10)	297
2.4.10.1	Verification of Fundamental Principals of Report Assembly (§2.2.10.1)	297
2.4.10.2	Verification of Capacity for Successful Message Reception (§2.2.10.2)	297
2.4.10.3	Verification of Applicable Messages (§2.2.10.3)	298
2.4.10.4	Verification of Message Reception-to-Report Completion Time (§2.2.10.4)	300
2.4.11	VERIFICATION OF SPECIAL REQUIREMENTS FOR TRANSCIVER IMPLEMENTATIONS (§2.2.11)	300
2.4.11.1	Verification of Transmit-Receive Turnaround Time (§2.2.11.1)	301
2.4.11.2	Verification of Receive-Transmit Turnaround Time (§2.2.11.2)	302

2.4.12	VERIFICATION OF MUTUAL SUPPRESSION PULSES (§2.2.12)	302
2.4.13	VERIFICATION OF SELF TEST AND MONITORS (§2.2.13)	302
2.4.13.1	Verification of Self Test (§2.2.13.1)	303
2.4.13.2	Verification of Broadcast Monitoring (§2.2.13.2)	303
2.4.13.3	Verification of Address Verification (§2.2.13.3)	304
2.4.13.4	Verification of Receiver Self-Test Capability (§2.2.13.4)	304
2.4.13.5	Verification of Failure Annunciation (§2.2.13.5)	305
2.4.13.5.1	Verification of UAT Transmitting Device Failure Annunciation (§2.2.13.5.1)	305
2.4.13.5.2	Verification of UAT Receiving Subsystem Failure Annunciation (§2.2.13.5.2)	306
2.4.13.5.3	Verification of Co-Located UAT Transmitting and Receiving Device Failure Annunciation (§2.2.13.5.3)	306
2.4.14	VERIFICATION OF ANTENNA SYSTEM (§2.2.14)	306
2.4.14.1	Verification of Polarization (§2.2.14.1)	306
2.4.14.2	Verification of Antenna Voltage Standing Wave Ratio (VSWR) (§2.2.14.2)	306
2.4.14.3	Verification of Requirements for Optional Passive Diplexer (§2.2.14.3)	307
2.4.14.3.1	Verification of Diplexer RF Requirements (§2.2.14.3.1)	307
2.4.14.3.1.1	Verification of The UAT Channel (§2.2.14.3.1.1)	307
2.4.14.3.1.2	Verification of The Transponder Channel (§2.2.14.3.1.2)	309
2.4.14.3.1.3	Verification of Channel to Channel Isolation (§2.2.14.3.1.3)	311
2.4.15	VERIFICATION OF INTERFACES (§2.2.15)	312
2.4.15.1	Verification of UAT Transmitting Subsystem Interfaces (§2.2.15.1)	312
2.4.15.1.1	Verification of UAT Transmitting Subsystem Input Interfaces (§2.2.15.1.1)	312
2.4.15.1.1.1	Verification of Discrete Input Interfaces (§2.2.15.1.1.1)	312
2.4.15.1.1.2	Verification of Digital Communication Input Interfaces (§2.2.15.1.1.2)	312
2.4.15.1.1.3	Verification of Processing Efficiency (§2.2.15.1.1.3)	313
2.4.15.1.2	Verification of UAT Transmitting Subsystem Output Interfaces (§2.2.15.1.2)	313
2.4.15.1.2.1	Verification of Discrete Output Interfaces (§2.2.15.1.2.1)	313
2.4.15.1.2.2	Verification of Digital Communication Output Interfaces (§2.2.15.1.2.2)	314
2.4.15.2	Verification of UAT Receiving Subsystem Interfaces (§2.2.15.2)	314
2.4.15.2.1	Verification of UAT Receiving Subsystem Input Interfaces (§2.2.15.2.1)	314
2.4.15.2.1.1	Verification of Discrete Input Interfaces (§2.2.15.2.1.1)	314
2.4.15.2.1.2	Verification of Digital Communication Input Interfaces (§2.2.15.2.1.2)	315
2.4.15.2.1.3	Verification of Processing Efficiency (§2.2.15.2.1.3)	315
2.4.15.2.2	Verification of UAT Receiving Subsystem Output Interfaces (§2.2.15.2.2)	315
2.4.15.2.2.1	Verification of Discrete Output Interfaces (§2.2.15.2.2.1)	315
2.4.15.2.2.2	Verification of Digital Communication Output Interfaces (§2.2.15.2.2.2)	316
2.4.16	VERIFICATION OF POWER INTERRUPTION (§2.2.16)	316
2.4.16.1	Verification of Power Interruption to UAT Transmitting Functions (§2.2.16)	316
2.4.16.2	Verification of Power Interruption to UAT Receiving Functions (§2.2.16)	317
2.4.17	VERIFICATION OF COMPATIBILITY WITH OTHER SYSTEMS (§2.2.17)	318
2.4.17.1	Verification of EMI Compatibility (§2.2.17.1)	318
2.4.17.2	Verification of Compatibility with GPS Receivers (§2.2.17.2)	318
2.4.17.3	Verification of Compatibility with Other Navigation Receivers and ATC Transponders (§2.2.17.3)	318

3 EQUIPMENT PERFORMANCE CHARACTERISTICS.....321

3.1	EQUIPMENT INSTALLATION	321
3.1.1	INSTALLED EQUIPMENT CONSIDERATIONS	321
3.1.1.1	Data Sources	321
3.1.1.2	ADS-B Transmitter	321
3.1.1.3	ADS-B Receiver	322

3.1.1.4	Report Assembly.....	322
3.1.1.5	Applications.....	322
3.1.2	AIRCRAFT ENVIRONMENT.....	322
3.1.3	AIRCRAFT POWER SOURCE.....	322
3.1.3.1	Power Fluctuation.....	322
3.1.4	ACCESSIBILITY.....	322
3.1.5	DISPLAY VISIBILITY.....	323
3.1.6	INDICATORS.....	323
3.1.7	ALERTS.....	323
3.1.8	FAILURE PROTECTION.....	323
3.1.9	FAILURE INDICATION.....	323
3.1.10	INTERFERENCE EFFECTS.....	323
3.1.11	MUTUAL SUPPRESSION.....	324
3.2	INSTALLED EQUIPMENT PERFORMANCE REQUIREMENTS.....	324
3.2.1	ANTENNA INSTALLATION.....	324
3.2.1.1	General Considerations.....	324
3.2.1.2	Transmission Lines.....	324
3.2.1.3	Antenna Polarization.....	324
3.2.1.4	Antenna Location.....	325
3.2.1.5	Minimum Distance from Other Antennas.....	325
3.2.1.6	Minimum Reception Range.....	325
3.2.1.7	Transmit Pattern Gain.....	326
3.2.1.8	Receive Pattern Gain.....	326
3.2.1.9	Dynamic Response.....	326
3.2.1.10	Antenna Diplexer.....	326
3.2.2	MUTUAL SUPPRESSION BUS.....	327
3.3	CONDITIONS OF TEST.....	327
3.3.1	SAFETY PRECAUTIONS.....	327
3.3.2	POWER INPUT.....	327
3.3.3	ENVIRONMENT.....	327
3.3.4	ADJUSTMENT OF EQUIPMENT.....	327
3.3.5	WARM-UP PERIOD.....	328
3.4	TEST PROCEDURES FOR INSTALLED EQUIPMENT PERFORMANCE.....	328
3.4.1	VERIFICATION OF ANTENNA INSTALLATION (§3.2.1).....	328
3.4.1.1	Verification of General Considerations (§3.2.1.1).....	328
3.4.1.2	Verification of Transmission Lines (§3.2.1.2).....	328
3.4.1.3	Verification of Antenna Polarization (§3.2.1.3).....	329
3.4.1.4	Verification of Antenna Location (§3.2.1.4).....	329
3.4.1.5	Verification of Minimum Distance from Other Antennas (§3.2.1.5).....	329
3.4.1.6	Verification of Minimum Reception Range (§3.2.1.6).....	329
3.4.1.7	Verification of Transmit Pattern Gain (§3.2.1.7).....	329
3.4.1.7.1	Background Material on Gain Performance Verification.....	329
3.4.1.7.1.1	Full Scale Anechoic Antenna Range Measurements of Gain.....	330
3.4.1.7.1.2	Scaled Model Measurements of Gain.....	330
3.4.1.7.1.3	Model Tests.....	331
3.4.1.7.1.4	Theoretical Calculations of Antenna Gain.....	331
3.4.1.7.1.4.1	Validation of Theoretical Calculations.....	331
3.4.1.7.1.5	Distance Area Calculations.....	331
3.4.1.7.2	Success Criteria.....	332
3.4.1.7.3	Verification Procedure for Transmit Pattern Gain.....	332
3.4.1.8	Verification of Receive Pattern Gain (§3.2.1.8).....	339
3.4.1.9	Verification of Dynamic Response (§3.2.1.9).....	341
3.5	FLIGHT ENVIRONMENT DATA SOURCES.....	341

3.5.1	NAVIGATION INTEGRITY CATEGORY (NIC)	341
3.5.2	NAVIGATION ACCURACY CATEGORY – POSITION (NAC _P).....	341
3.5.3	ALTITUDE	342
3.5.3.1	Altitude Reporting Source.....	342
3.5.4	ON-GROUND / AIRBORNE STATUS.....	342
3.5.5	SHORT-TERM INTENT SOURCES	342
3.5.6	IDENT SOURCE	342
3.6	AIRCRAFT / VEHICLE DATA	342
3.6.1	FIXED DATA.....	343
3.6.2	VARIABLE DATA	343
3.6.3	ON-CONDITION AND STATUS SENSORS	343
3.7	FLIGHT TEST PROCEDURES	343
3.7.1	DISPLAYED DATA RELIABILITY	343
3.7.2	INTERFERENCE EFFECTS	344
3.7.3	ADS-B PERFORMANCE TESTING.....	344
4	<u>EQUIPMENT OPERATIONAL PERFORMANCE CHARACTERISTICS.....</u>	<u>345</u>
4.1	REQUIRED OPERATIONAL PERFORMANCE CHARACTERISTICS	345
4.1.1	POWER INPUT AND CONTROL.....	345
4.1.1.1	Power On/Off (Optional)	345
4.1.2	EQUIPMENT OPERATING MODES	345
4.1.2.1	Transmission Modes	345
4.1.2.1.1	ON-GROUND Condition.....	346
4.1.2.1.2	AIRBORNE Condition	346
4.1.2.2	Receive Subsystem	346
4.1.2.2.1	Receive Function	346
4.1.2.2.2	Report Assembly Function.....	346
4.1.3	UAT LINK CONTROL (OPTIONAL).....	347
4.1.4	STANDBY	347
4.1.5	MODE STATUS MESSAGE CONTROL.....	347
4.1.6	BAROMETRIC ALTITUDE	347
4.1.7	BROADCAST MONITOR.....	347
4.1.8	ADDRESS MONITOR	347
4.1.9	FAILURE INDICATION	347
4.2	CERTIFICATION TEST PROCEDURES FOR OPERATIONAL PERFORMANCE REQUIREMENTS	348
4.2.1	POWER INPUT.....	348
4.2.1.1	Ground Power Unit (GPU).....	348
4.2.1.2	Auxiliary Power Unit (APU).....	348
4.2.1.3	Engine Generator(s)	348
4.2.1.4	Power On/Off (Optional)	348
4.2.2	UAT TRANSMITTING SUBSYSTEM OPERATING MODES	348
4.2.2.1	ON-GROUND Condition.....	349
4.2.2.2	AIRBORNE Condition	349
4.2.2.3	Automatic Operation.....	349
4.2.3	CONTROLS AND INDICATORS	349
4.2.3.1	Standby Mode.....	349
4.2.3.2	UAT Link Control (Optional)	349
4.2.3.3	Barometric Altitude.....	349
4.2.3.4	Failure Indication.....	349
MEMBERSHIP	351

<u>A.</u>	<u>ACRONYMS & DEFINITION OF TERMS</u>	A-3
A.1	ACRONYMS	A-3
A.2	DEFINITION OF TERMS	A-10
<u>B.</u>	<u>MASPS COMPLIANCE MATRIX</u>	B-3
B.1	INTRODUCTION	B-3
B.2	ADS-B MASPS COMPLIANCE MATRIX	B-3
B.3	FIS-B MASPS COMPLIANCE	B-3
<u>C.</u>	<u>EXAMPLE ADS-B MESSAGE ENCODING</u>	C-3
C.1	REED SOLOMON ENCODING OF MESSAGE PAYLOAD.....	C-3
C.2	REED SOLOMON ENCODING OF BASIC TYPE 0 ADS-B MESSAGE PAYLOAD.....	C-4
C.3	REED SOLOMON ENCODING OF LONG TYPE 1 ADS-B MESSAGE PAYLOAD	C-5
C.4	REED SOLOMON ENCODING OF GROUND UPLINK MESSAGE PAYLOAD	C-8
<u>D.</u>	<u>UAT GROUND INFRASTRUCTURE</u>	D-3
D.1	GENERAL DESCRIPTION.....	D-3
D.1.1	UPLINK: BROADCAST.....	D-3
D.1.1.1	Geometric Coverage	D-3
D.1.1.1.1	Radio Coverage.....	D-3
D.1.1.1.2	FIS-B Product Coverage	D-4
D.1.1.1.3	TIS-B Product Coverage	D-5
D.1.1.2	Data Source For Ground Broadcast	D-5
D.1.2	DOWNLINK: SURVEILLANCE	D-5
D.1.3	SUMMARY OF INFRASTRUCTURE AND IMPLICATIONS	D-6
D.2	GROUND STATION DEPLOYMENT	D-7
D.2.1	TIME SLOTS	D-7
D.2.2	SLOT ROTATION.....	D-8
D.2.3	ANTENNA CONSIDERATIONS FOR UPLINK	D-8
D.2.4	TIS-B SITE ID	D-10
D.2.5	SECTORIZED CELLS AND CO-SITE TRANSMISSION ISOLATION	D-12
D.3	RF INTERFERENCE	D-13
D.3.1	JTIDS INTERFERENCE.....	D-13
D.3.2	DME INTERFERENCE	D-13
D.4	MULTIPLE ADS-B LINKS	D-14
<u>E.</u>	<u>AIRCRAFT ANTENNA CHARACTERISTICS</u>	E-3
E.1	ANTENNA CHARACTERISTICS	E-3
E.1.1	GENERAL CHARACTERISTICS	E-3
E.1.2	RADIATION PATTERNS	E-3
E.1.3	DIRECTIONAL GAIN RADIATION PATTERNS	E-3
E.2	TYPICAL VSWR MEASUREMENTS OF EXISTING TRANSPONDER / DME ANTENNAS	E-5
E.2.1	SENSOR SYSTEMS L BAND BLADE ANTENNA P/N S65-5366-7L	E-7
E.2.2	AEROANTENNA P/N AT-130-1	E-7

E.2.3	¼ WAVE WHIP ANTENNA	E-7
E.3	PASSIVE ANTENNA DIPLEXER CHARACTERISTICS	E-8
E.3.1	ANTENNA DIPLEXER TESTING.....	E-9
E.3.1.1	SSR Transponder Testing.....	E-9
E.3.1.2	UAT Diplexer Testing.....	E-12
E.3.1.3	Prototype Diplexer Performance	E-13
E.3.2	TYPICAL INSTALLATION DIAGRAM	E-16
F.	<u>TRANSMITTER AND RECEIVER POWER REQUIREMENTS.....</u>	F-3
G.	<u>STANDARD INTERFERENCE ENVIRONMENT.....</u>	G-3
G.1	BACKGROUND.....	G-3
G.2	OPERATIONAL ENVIRONMENTS.....	G-3
G.3	CO-SITE ENVIRONMENT	G-6
G.4	SCENARIO ASSESSMENTS	G-7
H.	<u>UAT SYNCHRONIZATION ISSUES</u>	H-3
H.1	INTRODUCTION.....	H-3
H.2	SYNCHRONIZATION PROCESS DESCRIPTION.....	H-3
H.3	SYNCHRONIZATION PERFORMANCE	H-5
H.4	FALSE ALARM RATE (NOISE).....	H-10
H.5	FALSE ALARM RATE (EMBEDDED SYNCHRONIZATION SEQUENCE)	H-12
H.6	UP LINK MESSAGE CONSIDERATIONS	H-13
H.7	REQUIRED MEMORY SIZE	H-14
H.8	SUMMARY	H-15
I.	<u>UAT TIMING REQUIREMENTS.....</u>	I-3
I.1	BACKGROUND.....	I-3
I.2	PURPOSE	I-3
I.3	INSTALLED END-END TIMING PERFORMANCE.....	I-3
I.4	MOPS TIMING REQUIREMENTS	I-5
I.5	CONSIDERATIONS FOR ADS-B VALIDATION APPLICATIONS	I-6
J.	<u>REFERENCE UPPER-LAYER EXTERNAL INTERFACE FORMAT.....</u>	J-3
J.1	BACKGROUND.....	J-3
J.2	SCOPE	J-3
J.3	SERIAL DATA FORMAT DESCRIPTION	J-3
K.	<u>UAT SYSTEM PERFORMANCE SIMULATION RESULTS</u>	K-3
K.1	INTRODUCTION.....	K-3
K.1.1	ORGANIZATION	K-3
K.1.2	BACKGROUND.....	K-3

K.1.3	GENERAL ASSUMPTIONS	K-4
K.1.4	UAT DETAILED SIMULATION DESCRIPTION AND LIMITATIONS	K-4
K.2	TLAT ANTENNA MODEL	K-6
K.3	RECEIVER PERFORMANCE MODEL	K-8
K.3.1	MEASURED DATA	K-8
K.3.2	RECEIVER MODEL ASSUMPTIONS.....	K-12
K.3.3	RECEIVER MODEL ACCURACY.....	K-15
K.4	MULTI-AIRCRAFT SIMULATION (MAUS) RESULTS	K-19
K.4.1	LOS ANGELES BASIN 2020 (LA2020).....	K-19
K.4.2	CORE EUROPE SCENARIOS	K-35
K.4.2.1	Current Core Europe	K-37
K.4.2.2	Core Europe 2015	K-60
K.4.3	LOW DENSITY SCENARIO	K-74
K.4.4	ACQUISITION PERFORMANCE	K-76
K.4.5	SURFACE PERFORMANCE	K-79
K.4.6	AN A0 ON THE SURFACE RECEIVING AN AIRCRAFT THAT IS ON APPROACH	K-88
K.5	MODEL VALIDATION.....	K-90
K.6	UAT AIS PERFORMANCE ANALYSIS	K-92
<u>L.</u>	<u>PROPOSED SUPPORT OF THE TRAJECTORY CHANGE REPORT</u>	<u>L-3</u>
<u>M.</u>	<u>UAT ERROR DETECTION AND CORRECTION PERFORMANCE.....</u>	<u>M-3</u>
<u>N.</u>	<u>SETUP FILES FOR TEST PROCEDURES</u>	<u>N-3</u>
<u>O.</u>	<u>DME OPERATION IN THE PRESENCE OF UAT SIGNALS.....</u>	<u>O-3</u>
<u>P.</u>	<u>UAT MESSAGE OVERLAP STATISTICS.....</u>	<u>P-3</u>
P.1	INTRODUCTION.....	P-3
P.2	STATISTICAL MODEL RESULTS	P-4
P.2.1	DISCUSSION	P-11
P.2.2	EFFECT OF UPLINK MESSAGE.....	P-13
P.3	MAUS RESULTS	P-13
P.4	SUMMARY	P-16
<u>Q</u>	<u>DETERMINING THE NAVIGATION ACCURACY CATEGORY FOR VELOCITY</u>	
	<u>(NAC_v).....</u>	<u>Q-3</u>
Q.1	PURPOSE AND SCOPE.....	Q-3
Q.2	BACKGROUND.....	Q-3
Q.3	TESTS TO DETERMINE VELOCITY ACCURACY FOR SUPPORT SETTING NAC_v = 1 OR 2.....	Q-4
Q.3.1	HORIZONTAL VELOCITY ACCURACY TEST CONDITIONS COMMENSURATE WITH NAC _v = 1	Q-4
Q.3.1.1	Pass/Fail Determination	Q-5

Q.3.1.2	Vertical Velocity Accuracy Test Conditions Commensurate with $NAC_v = 1$	Q-6
Q.3.1.3	Pass/Fail Determination	Q-8
Q.3.2	ADDITIONAL TESTS TO DEMONSTRATE ACCURACY COMMENSURATE WITH $NAC_v = 2$	Q-8
Q.4	EXPECTED GNSS VELOCITY ACCURACY IN STABLE FLIGHT	Q-9

R PROPOSED DO-282B PROVISIONS FOR BACKWARD COMPATIBILITY WITH DO-282A MESSAGE FORMATSR-3

R.1	BACKGROUND.....	R-3
R.2	VERSION 1 SIL FIELD DEFINITION	R-3

S PROVISIONING FOR POTENTIAL WAKE VORTEX AND ARRIVAL MANAGEMENT ADS-B APPLICATIONS S-3

S.1	INTRODUCTION.....	S-3
S.1.1	PROPOSED WAKE TURBULENCE APPLICATIONS	S-4
S.1.2	ADDITIONAL CAPABILITIES.....	S-7
S.1.2.1	Improved Arrival Management Scheduling and Aircraft Trajectory Synthesis.....	S-7
S.1.2.2	Increased Wind Field Prediction Accuracy.....	S-8
S.1.2.3	Better Situational Awareness of Current Weather	S-8
S.1.3	BROADCAST SYSTEM ARCHITECTURE.....	S-8
S.2	DATA REQUIREMENTS FOR WAKE AND ARRIVAL MANAGEMENT APPLICATIONS	S-9
S.3	MESSAGE FORMATS AND TRANSMISSION RATES.....	S-15
S.3.1	WIND TRIANGLE AND DERIVATION OF WIND VECTOR FROM GROUND VECTOR AND ARV DATA.....	S-15
S.3.2	DERIVATION OF WIND VECTOR FROM GROUND VECTOR AND LOW RATE ARV BROADCASTS	S-17
S.3.3	PROPOSED UPDATE RATES FOR WIND VECTOR AND ARV BROADCASTS.....	S-18
S.3.4	DATA COASTING FOR CONTINUITY OF ARV DATA DURING GAPS IN ARV RECEPTION	S-19
S.4	PROVISIONING OF MET AND ARV DATA	S-20
S.5	REFERENCES.....	S-26
S.6	ADDENDUM ON CAS, MACH, AND TAS RELATIONSHIPS	S-26

T	CORRIGENDUM-1 FOR RTCA DO-282B	T-1
---	--------------------------------	-----

LIST OF FIGURES

Figure 1-1: UAT Frame	6
Figure 1-2: UAT ADS-B Message Structures	9
Figure 2-1: Time/Amplitude Profile of ADS-B Message Transmission Interval	22
Figure 2-2: UAT Transmit Spectrum	23
Figure 2-3: ADS-B Message Format.....	24
Figure 2-4: Ground Uplink Message Format.....	25
Figure 2-5: Ground Uplink Information Frame	27
Figure 2-6: Angular Weighted Binary Encoding of Latitude and Longitude	39
Figure 2-7: GPS/GNSS Time Mark Pulse.....	81
Figure 2-8: Transmitter Antenna Use for Diversity Installations.....	84
Figure 2-9: ADS-B Receiving Architectures.....	91
Figure 2-10: ADS-B Message and Report General Data Flow	99
Figure 2-11: Digital Demodulation Mode – Trace A: Ch1 2FSK Meas Time	120
Figure 2-12: Digital Demodulation Mode – Trace C: “Eye Diagram”	123
Figure 2-13: MSO Timing Measurement Configuration	230
Figure 2-14: ADS-B Long Message Envelope & Spectrum – No Interference.....	256
Figure 2-15: ADS-B Long Message Envelope & Spectrum – With CW	257
Figure 2-16: ADS-B Long Message Envelope & Spectrum – With DME/TACAN.....	260
Figure 3-1: Antenna Test Configuration - 1	333
Figure 3-2: Antenna Test Configuration - 2	340
<u>Figure A-1: Ideal eye diagram</u>	<u>A-14</u>
<u>Figure A-2: Distorted eye diagram.....</u>	<u>A-14</u>
<u>Figure D-1: Example Coverage Cell Layout</u>	<u>D-4</u>
<u>Figure D-2: General Form of Ground Infrastructure</u>	<u>D-7</u>
<u>Figure D-3: 7-Cell Re-Use Pattern.....</u>	<u>D-8</u>
<u>Figure D-4: Self-Interference with Low-Gain Antenna.....</u>	<u>D-9</u>
<u>Figure D-5: Self-Interference with DME-Type Antenna.....</u>	<u>D-10</u>
<u>Figure D-6: Example of TIS-B Site ID and Channel.....</u>	<u>D-11</u>
<u>Figure D-7: Sectorized Antenna Pattern (3 sectors)</u>	<u>D-13</u>
<u>Figure D-8: Possible antenna locations</u>	<u>D-13</u>
<u>Figure E-1: L-Band Passive Gain Antenna</u>	<u>E-4</u>
<u>Figure E-2: Gain Array Antenna Azimuth Pattern</u>	<u>E-5</u>
<u>Figure E-3: Jet Transport Antenna</u>	<u>E-7</u>
<u>Figure E-4: Capstone Antenna</u>	<u>E-7</u>
<u>Figure E-5: ¼ Wave Whip Antenna.....</u>	<u>E-8</u>
<u>Figure E-6: Sensitivity Variation with Frequency, All 1’s Interrogation, Transponder MS-1</u>	<u>E-12</u>
<u>Figure E-7: Diplexer UAT Port.....</u>	<u>E-13</u>
<u>Figure E-8: Diplexer Transponder Port.....</u>	<u>E-14</u>
<u>Figure E-9: Diplexer UAT-to-Transponder Port Isolation.....</u>	<u>E-15</u>
<u>Figure E-10: Diplexer Installation.....</u>	<u>E-16</u>
<u>Figure G-1: Sample Scenario</u>	<u>G-5</u>
<u>Figure G-2: Normalized DME Pattern</u>	<u>G-5</u>
<u>Figure G-3: Normalized TACAN Pattern</u>	<u>G-6</u>
<u>Figure G-4: Targets of Interest for Computing Update Interval</u>	<u>G-10</u>
<u>Figure H-1: UAT Receiver Processing.....</u>	<u>H-4</u>
<u>Figure H-2: Baseband Transmit Filter. Truncated Raised-Cosine Nyquist Filter With Roll-Off Factor = 0.5</u>	<u>H-6</u>
<u>Figure H-3: ADS-B Synchronization Sequence</u>	<u>H-7</u>
<u>Figure H-4: A Portion of the ADS-B Synchronization Sequence</u>	<u>H-8</u>
<u>Figure H-5: Performance of the Three Sample per Bit Scheme.....</u>	<u>H-9</u>

<u>Figure H-6: Performance of the One Sample per Bit Scheme</u>	H-10
<u>Figure H-7: False Alarm Rate versus Threshold</u>	H-12
<u>Figure H-8: Memory Length Determination (Memory Size in bits)</u>	H-14
<u>Figure K-1: TLAT Antenna Model Elevation Gain.....</u>	K-7
<u>Figure K-2: TLAT Random Azimuth Gain.....</u>	K-8
<u>Figure K-3: Test Setup for measuring BER</u>	K-9
<u>Figure K-4: BER Due to DME interference.....</u>	K-11
<u>Figure K-5: BER Due to DME Interference.....</u>	K-11
<u>Figure K-6: Link 16 Interference</u>	K-12
<u>Figure K-7: Assumed Piecewise Linear IIBER Vs. SINR Curve (Typical)</u>	K-13
<u>Figure K-8: BER Vs. SINR Curve Corresponding to Figure K-7.....</u>	K-13
<u>Figure K-9: Gaussian Noise + Single UAT, 1.2 MHz Receiver</u>	K-16
<u>Figure K-10: Gaussian Noise + Two Equal UATs, 1.2 MHz Receiver.....</u>	K-16
<u>Figure K-11: Two Unequal UATs, INR \gg 0 dB, 0.8 MHz Receiver.....</u>	K-17
<u>Figure K-12: N Equal UATs, INR \gg 0, 0.8 MHz Receiver</u>	K-17
<u>Figure K-13 Model Errors for All Data, 1.2 MHz Receiver</u>	K-18
<u>Figure K-14: Model Errors for All Data, 0.8 MHz Receiver.....</u>	K-18
<u>Figure K-15: A3 Receiver in LA2020 at High Altitude Receiving A3 Transmissions.....</u>	K-21
<u>Figure K-16: A3 Receiver in LA2020 at High Altitude Receiving A2 Transmissions.....</u>	K-21
<u>Figure K-17: A3 Receiver in LA2020 at High Altitude Receiving A1H Transmissions.....</u>	K-22
<u>Figure K-18: A3 Receiver in LA2020 at FL 150 Receiving A3 Transmissions.....</u>	K-22
<u>Figure K-19: A3 Receiver in LA2020 at FL 150 Receiving A2 Transmissions.....</u>	K-23
<u>Figure K-20: A3 Receiver in LA2020 at FL 150 Receiving A1 and A0 Transmissions.....</u>	K-23
<u>Figure K-21: A2 Receiver in LA2020 at High Altitude Receiving A3 Transmissions.....</u>	K-24
<u>Figure K-22: A2 Receiver in LA2020 at High Altitude Receiving A2 Transmissions.....</u>	K-24
<u>Figure K-23: A2 Receiver in LA2020 at High Altitude Receiving A1H Transmissions.....</u>	K-25
<u>Figure K-24: A2 Receiver in LA2020 at FL 150 Receiving A3 Transmissions.....</u>	K-25
<u>Figure K-25: A2 Receiver in LA2020 at FL 150 Receiving A2 Transmissions.....</u>	K-26
<u>Figure K-26: A2 Receiver in LA2020 at FL 150 Receiving A1 and A0 Transmissions.....</u>	K-26
<u>Figure K-27: A1H Receiver in LA2020 at High Altitude Receiving A3 Transmissions.....</u>	K-27
<u>Figure K-28: A1H Receiver in LA2020 at High Altitude Receiving A2 Transmissions.....</u>	K-27
<u>Figure K-29: A1H Receiver in LA2020 at High Altitude Receiving A1H Transmissions</u>	K-28
<u>Figure K-30: A1 Receiver in LA2020 at FL 150 Receiving A3 Transmissions.....</u>	K-28
<u>Figure K-31: A1 Receiver in LA2020 at FL 150 Receiving A2 Transmissions.....</u>	K-29
<u>Figure K-32: A1 Receiver in LA2020 at FL 150 Receiving A1 and A0 Transmissions.....</u>	K-29
<u>Figure K-33: A0 Receiver in LA2020 at FL 150 Receiving A3 Transmissions.....</u>	K-30
<u>Figure K-34: A0 Receiver in LA2020 at FL 150 Receiving A2 Transmissions.....</u>	K-30
<u>Figure K-35: A0 Receiver in LA2020 at FL 150 Receiving A1 and A0 Transmissions.....</u>	K-31
<u>Figure K-36: Ground Receiver in LA2020 Receiving A3 Transmissions.....</u>	K-31
<u>Figure K-37: Ground Receiver in LA2020 Receiving A2 Transmissions.....</u>	K-32
<u>Figure K-38: Ground Receiver in LA2020 Receiving A1 and A0 Transmissions.....</u>	K-32
<u>Figure K-39: Ground Receiver in LA with Sectorized Antenna with a 10 kW TACAN at 980 MHz located 1000' away.....</u>	K-33
<u>Figure K-40: Standard Ground Receiver in LA with TACAN that delivers -90 dBm at 980 MHz to the UAT Ground Antenna.....</u>	K-33
<u>Figure K-41: State Vector Updates from Ground Vehicle Transmitters for all Types of Receivers at 2000 feet Altitude</u>	K-34
<u>Figure K-42: A3 Receiver at High Altitude in Current Europe Receiving A3 Transmissions.....</u>	K-38
<u>Figure K-43: A3 Receiver at High Altitude in Current Europe Receiving A2 Transmissions.....</u>	K-38
<u>Figure K-44: A3 Receiver at High Altitude in Current Europe Receiving A1H Transmissions.....</u>	K-39
<u>Figure K-45: A3 Receiver at FL 150 in Current Europe Receiving A3 Transmissions.....</u>	K-39
<u>Figure K-46: A3 Receiver at FL 150 in Current Europe Receiving A2 Transmissions.....</u>	K-40
<u>Figure K-47: A3 Receiver at FL 150 in Current Europe Receiving A1 and A0 Transmissions.....</u>	K-40

<u>Figure K-48:</u> A2 Receiver at High Altitude in Current Europe Receiving A3 Transmissions.....	K-41
<u>Figure K-49:</u> A2 Receiver at High Altitude in Current Europe Receiving A2 Transmissions.....	K-41
<u>Figure K-50:</u> A2 Receiver at High Altitude in Current Europe Receiving A1H Transmissions.....	K-42
<u>Figure K-51:</u> A2 Receiver at FL 150 in Current Europe Receiving A3 Transmissions.....	K-42
<u>Figure K-52:</u> A2 Receiver at FL 150 in Current Europe Receiving A2 Transmissions.....	K-43
<u>Figure K-53:</u> A2 Receiver at FL 150 in Current Europe Receiving A1 and A0 Transmissions.....	K-43
<u>Figure K-54:</u> A1H Receiver at High Altitude in Current Europe Receiving A3 Transmissions.....	K-44
<u>Figure K-55:</u> A1H Receiver at High Altitude in Current Europe Receiving A2 Transmissions.....	K-44
<u>Figure K-56:</u> A1H Receiver at High Altitude in Current Europe Receiving A1H Transmissions.....	K-45
<u>Figure K-57:</u> A1 Receiver at FL 150 in Current Europe Receiving A3 Transmissions.....	K-45
<u>Figure K-58:</u> A1 Receiver at FL 150 in Current Europe Receiving A2 Transmissions.....	K-46
<u>Figure K-59:</u> A1 Receiver at FL 150 in Current Europe Receiving A1 and A0 Transmissions.....	K-46
<u>Figure K-60:</u> A0 Receiver at FL 150 in Current Europe Receiving A3 Transmissions.....	K-47
<u>Figure K-61:</u> A0 Receiver at FL 150 in Current Europe Receiving A2 Transmissions.....	K-47
<u>Figure K-62:</u> A0 Receiver at FL 150 in Current Europe Receiving A1 and A0 Transmissions.....	K-48
<u>Figure K-63:</u> A3 Receivers in the Worst-Case Current DME Position (154 equipped aircraft) at High Altitude Receiving A3 Transmissions.....	K-49
<u>Figure K-64:</u> A3 Receivers in the Worst-Case Current DME Position (154 equipped aircraft) at High Altitude Receiving A2 Transmissions.....	K-50
<u>Figure K-65:</u> A3 Receivers in the Worst-Case Current DME Position (154 equipped aircraft) at High Altitude Receiving A1H Transmissions.....	K-50
<u>Figure K-66:</u> A3 Receiver at FL 150 in the Worst-Case Current DME Position (154 equipped aircraft) Receiving A3 Transmissions.....	K-51
<u>Figure K-67:</u> A3 Receiver at FL 150 in the Worst-Case Current DME Position (154 equipped aircraft) Receiving A2 Transmissions.....	K-51
<u>Figure K-68:</u> A3 Receiver at FL 150 in the Worst-Case Current DME Position (154 equipped aircraft) Receiving A1 and A0 Transmissions.....	K-52
<u>Figure K-69:</u> A2 Receiver at High Altitude in the Worst-Case Current DME Position (154 equipped aircraft) Receiving A3 Transmissions.....	K-52
<u>Figure K-70:</u> A2 Receiver at High Altitude in the Current Worst-Case DME Position (154 equipped aircraft) Receiving A2 Transmissions.....	K-53
<u>Figure K-71:</u> A2 Receiver at High Altitude in the Worst-Case Current DME Position (154 equipped aircraft) Receiving A1H Transmissions.....	K-53
<u>Figure K-72:</u> A2 Receiver at FL 150 in the Worst-Case Current DME Position (154 equipped aircraft) Receiving A3 Transmissions.....	K-54
<u>Figure K-73:</u> A2 Receiver at FL 150 in the Worst-Case Current DME Position (154 equipped aircraft) Receiving A2 Transmissions.....	K-54
<u>Figure K-74:</u> A2 Receiver at FL 150 in the Worst-Case Current DME Position (154 equipped aircraft) Receiving A1 and A0 Transmissions.....	K-55
<u>Figure K-75:</u> A1H Receiver at High Altitude in the Worst-Case Current DME Position (154 equipped aircraft) Receiving A3 Transmissions.....	K-55
<u>Figure K-76:</u> A1H Receiver at High Altitude in the Worst-Case Current DME Position (154 equipped aircraft) Receiving A2 Transmissions.....	K-56
<u>Figure K-77:</u> A1H Receiver at High Altitude in the Worst-Case Current DME Position (154 equipped aircraft) Receiving A1H Transmissions.....	K-56
<u>Figure K-78:</u> A1 Receiver at FL 150 in the Worst-Case Current DME Position (154 equipped aircraft) Receiving A3 Transmissions.....	K-57
<u>Figure K-79:</u> A1 Receiver at FL 150 in the Worst-Case Current DME Position (154 equipped aircraft) Receiving A2 Transmissions.....	K-57
<u>Figure K-80:</u> A1 Receiver at FL 150 in the Worst-Case Current DME Position (154 equipped aircraft) Receiving A1 and A0 Transmissions.....	K-58
<u>Figure K-81:</u> A0 Receiver at FL 150 in the Worst-Case Current DME Position (154 equipped aircraft) Receiving A3 Transmissions.....	K-58

<u>Figure K-82: A0 Receiver at FL 150 in the Worst-Case Current DME Position (154 equipped aircraft) Receiving A2 Transmissions.....</u>	K-59
<u>Figure K-83: A0 Receiver at FL 150 in the Worst-Case Current DME Position (154 equipped aircraft) Receiving A1 and A0 Transmissions</u>	K-59
<u>Figure K-84: A3 Receiver in CE2015 at High Altitude Receiving A3 Transmissions</u>	K-61
<u>Figure K-85: A3 Receiver in CE2015 at High Altitude Receiving A2 Transmissions</u>	K-62
<u>Figure K-86: A3 Receiver in CE2015 at High Altitude Receiving A1H Transmissions</u>	K-62
<u>Figure K-87: A3 Receiver in CE2015 at FL 150 Receiving A3 Transmissions</u>	K-63
<u>Figure K-88: A3 Receiver in CE2015 at FL 150 Receiving A2 Transmissions</u>	K-63
<u>Figure K-89: A3 Receiver in CE2015 at FL 150 Receiving A1 and A0 Transmissions.....</u>	K-64
<u>Figure K-90: A2 Receiver in CE2015 at High Altitude Receiving A3 Transmissions</u>	K-64
<u>Figure K-91: A2 Receiver in CE2015 at High Altitude Receiving A2 Transmissions</u>	K-65
<u>Figure K-92: A2 Receiver in CE2015 at High Altitude Receiving A1 and A0 Transmissions.....</u>	K-65
<u>Figure K-93: A2 Receiver in CE2015 at FL 150 Receiving A3 Transmissions</u>	K-66
<u>Figure K-94: A2 Receiver in CE2015 at FL 150 Receiving A2 Transmissions</u>	K-66
<u>Figure K-95: A2 Receiver in CE2015 at FL 150 Receiving A1 and A0 Transmissions.....</u>	K-67
<u>Figure K-96: A1H Receiver in CE2015 at High Altitude Receiving A3 Transmissions</u>	K-67
<u>Figure K-97: A1H Receiver in CE2015 at High Altitude Receiving A2 Transmissions</u>	K-68
<u>Figure K-98: A1H Receiver in CE2015 at High Altitude Receiving A1H Transmissions</u>	K-68
<u>Figure K-99: A1 Receiver in CE2015 at FL 150 Receiving A3 Transmissions</u>	K-69
<u>Figure K-100: A1 Receiver in CE2015 at FL 150 Receiving A2 Transmissions</u>	K-69
<u>Figure K-101: A1 Receiver in CE2015 at FL 150 Receiving A1 and A0 Transmissions.....</u>	K-70
<u>Figure K-102: A0 Receiver in CE2015 at FL 150 Receiving A3 Transmissions</u>	K-70
<u>Figure K-103: A0 Receiver in CE2015 at FL 150 Receiving A2 Transmissions</u>	K-71
<u>Figure K-104: A0 Receiver in CE2015 at FL 150 Receiving A1 and A0 Transmissions.....</u>	K-71
<u>Figure K-105: Ground Receiver in CE2015 with 3-Sector Antenna in Brussels Receiving all Equipage Transmissions</u>	K-72
<u>Figure K-106: Ground Receiver in CE2015 with 3-Sector Antenna in Brussels, co-located with a 979 MHz TACAN delivering –50 dBm power to antenna, Receiving All Equipage Transmissions....</u>	K-73
<u>Figure K-107: Receptions of Ground Vehicle Transmissions by All Equipage Classes on Approach (at constant 2000 foot altitude) in CE2015 with 10 kW 979 MHz TACAN at Airport.....</u>	K-73
<u>Figure K-108: A3 Receiver in Low Density Scenario Receiving A3 Transmissions</u>	K-75
<u>Figure K-109: Receptions of A3 Transmissions by a Standard Ground Receiver in a Low Density Scenario co-located with a TACAN at 979 MHz with –30 dBm Power at the UAT Antenna.....</u>	K-76
<u>Figure K-110: A3 Receiver on the Surface in LA2020 Scenario Receiving A3 Transmissions</u>	K-80
<u>Figure K-111: A3 Receiver on the Surface in LA2020 Scenario Receiving A2 Transmissions</u>	K-80
<u>Figure K-112: A3 Receiver on the Surface in LA2020 Scenario Receiving A1 Transmissions</u>	K-81
<u>Figure K-113: A3 Receiver on the Surface in LA2020 Scenario Receiving A0 Transmissions</u>	K-81
<u>Figure K-114: A2 Receiver on the Surface in LA2020 Scenario Receiving A3 Transmissions</u>	K-82
<u>Figure K-115: A2 Receiver on the Surface in LA2020 Scenario Receiving A2 Transmissions</u>	K-82
<u>Figure K-116: A2 Receiver on the Surface in LA2020 Scenario Receiving A1 Transmissions</u>	K-83
<u>Figure K-117: A2 Receiver on the Surface in LA2020 Scenario Receiving A0 Transmissions</u>	K-83
<u>Figure K-118: A1 Receiver on the Surface in LA2020 Scenario Receiving A3 Transmissions</u>	K-84
<u>Figure K-119: A1 Receiver on the Surface in LA2020 Scenario Receiving A2 Transmissions</u>	K-84
<u>Figure K-120: A1 Receiver on the Surface in LA2020 Scenario Receiving A1 Transmissions</u>	K-85
<u>Figure K-121: A1 Receiver on the Surface in LA2020 Scenario Receiving A0 Transmissions</u>	K-85
<u>Figure K-122: A0 Receiver on the Surface in LA2020 Scenario Receiving A3 Transmissions</u>	K-86
<u>Figure K-123: A0 Receiver on the Surface in LA2020 Scenario Receiving A2 Transmissions</u>	K-86
<u>Figure K-124: A0 Receiver on the Surface in LA2020 Scenario Receiving A1 Transmissions</u>	K-87
<u>Figure K-125: A0 Receiver on the Surface in LA2020 Scenario Receiving A0 Transmissions</u>	K-87
<u>Figure K-126: A0 Receivers on the Ground in LA2020 Receiving All Aircraft on Approach at an Altitude of 2000 feet.....</u>	K-89

<u>Figure K-127: A0 Receivers on the Ground in CE2015 Receiving All Aircraft on Approach at an Altitude of 2000 ft to Brussels co-located with a 10 kW 979 MHz TACAN</u>	K-89
<u>Figure K-128: Comparison of Bench Test Measurements of MOPS-Compliant UAT Reception in LA2020 Self-Interference with Predictions by MAUS</u>	K-91
<u>Figure K-129: Bench Test Measurements of UAT Performance in Core Europe UAT Self-Interference, Combined with DME/TACAN and Link 16 Interference</u>	K-91
<u>Figure K-130: Bench Test Measurements of UAT Performance in the LA2020 UAT Self-Interference, Combined with DME/TACAN and Link 16 Interference</u>	K-92
<u>Figure K-131: Typical Result for Scenario 3 for Update Interval as a Function of Bank Angle</u>	K-95
<u>Figure M-1: Short ADS-B Message Performance</u>	M-4
<u>Figure M-2: Long ADS-B Message Performance</u>	M-4
<u>Figure M-3: Ground Up Link Message Performance</u>	M-5
<u>Figure M-4: Ground Up Link Message Undetected Message Error Rate</u>	M-6
<u>Figure M-5: Ground Up Link Message Total Message Error Rate</u>	M-6
<u>Figure M-6: Logical Flow of ADS-B Reception</u>	M-7
<u>Figure O-1: Bendix King KD-7000 Frequency Offset Test</u>	O-4
<u>Figure O-2: Bendix King KD-7000 Reply Efficiency Test</u>	O-5
<u>Figure O-3: Bendix King KD-7000 CW testing: DME level -83 dBm</u>	O-6
<u>Figure O-4: Narco DME-890 Frequency Offset Test</u>	O-7
<u>Figure O-5: Narco DME-890 Reply Efficiency Test</u>	O-8
<u>Figure O-6: Narco DME-890 CW testing: DME level -75 dBm</u>	O-8
<u>Figure O-7: Honeywell KDM-706A Frequency Offset Test</u>	O-9
<u>Figure O-8: Honeywell KDM-706A Reply Efficiency Test</u>	O-10
<u>Figure O-9: Honeywell KDM-706A CW testing: DME level -83 dBm</u>	O-11
<u>Figure O-10: Rockwell-Collins DME-900 Frequency Offset Test</u>	O-11
<u>Figure O-11: Rockwell-Collins DME-900 Reply Efficiency Test</u>	O-12
<u>Figure O-12: Rockwell-Collins DME-900 CW testing: DME level -83 dBm</u>	O-12
<u>Figure O-13: Comparison of all DME Frequency Offset Tests</u>	O-13
<u>Figure O-14: Comparison of all DME Reply Efficiency Tests</u>	O-14
<u>Figure O-15: Comparison of all DME CW Interference Tests</u>	O-14
<u>Figure O-16: JTIDS and UAT Combined Interference Analysis</u>	O-16
<u>Figure P-1: Possible UAT Receiver Architecture</u>	P-3
<u>Figure P-2: UAT Received Power Distribution (for 2200 users)</u>	P-5
<u>Figure P-3: Message Overlap Possibilities</u>	P-6
<u>Figure P-4: Simulation Results for 200 Aircraft</u>	P-8
<u>Figure P-5: Simulation Results for 600 Aircraft</u>	P-8
<u>Figure P-6: Simulation Results for 1000 Aircraft</u>	P-9
<u>Figure P-7: Simulation Results for 1400 Aircraft</u>	P-9
<u>Figure P-8: Simulation Results for 1800 Aircraft</u>	P-10
<u>Figure P-9: Simulation Results for 2200 Aircraft</u>	P-10
<u>Figure P-10: Simulation Results for 2600 Aircraft</u>	P-11
<u>Figure P-11: Simulation Results for 3000 Aircraft</u>	P-11
<u>Figure P-12: Overall Synchronization Performance</u>	P-12
<u>Figure P-13: Fraction of Rejected Messages (Parameter is the Number of Registers)</u>	P-13
<u>Figure P-14a: Percentage of Successful Overlapping Synch Sequences for Messages Received > -94 dBm for an A2 at 40,000 ft. in CE 2015 for the Bottom Antenna</u>	P-15
<u>Figure P-14b: Percentage of Successful Overlapping Synch Sequences for Messages Received > -94 dBm for an A2 at 40,000 ft. in CE 2015 for the Top Antenna</u>	P-15
<u>Figure S-1: System Diagram for Initial and Mid-Term Ground-Based Wake Applications Using ADS-B</u>	S-6
<u>Figure S-2: Wind Triangle for Modeling Aircraft Velocity Relationships</u>	S-16
<u>Figure S-3: Derivation of Wind Vector from Received ARV and State Vector Data</u>	S-18

LIST OF TABLES

Table 2-1: UAT Installed Equipment Classes	17
Table 2-2: Transmitter Power Requirements.....	18
Table 2-3: UAT Transmit Spectrum	22
Table 2-4: Format of the Ground Uplink Message Payload.....	26
Table 2-5: Encoding of TIS-B SITE ID	29
Table 2-6: The Information Frame.....	29
Table 2-7: Frame Types.....	30
Table 2-8: Ground Uplink Interleaver Matrix	32
Table 2-9: ADS-B Payload Elements.....	32
Table 2-10: Composition of ADS-B Payload.....	33
Table 2-11: Encoding of HEADER Element into ADS-B Payload.....	34
Table 2-12: “ADDRESS QUALIFIER” Encoding.....	34
Table 2-13: Format of STATE VECTOR Element	37
Table 2-14: Angular Weighted Binary Encoding of Latitude and Longitude.....	38
Table 2-15: “ALTITUDE TYPE” Encoding	40
Table 2-16: “ALTITUDE” Encoding.....	41
Table 2-17: “NIC” Encoding	42
Table 2-18: “A/G STATE” Field Encoding	44
Table 2-19: “North Velocity” Format	47
Table 2-20: “North/South Sign” Encoding.....	47
Table 2-21: “North Velocity Magnitude” Encoding.....	48
Table 2-22: “Ground Speed” Format	48
Table 2-23: “Ground Speed” Encoding.....	49
Table 2-24: “East Velocity” Format.....	49
Table 2-25: “East/West Sign” Encoding	49
Table 2-26: “East Velocity Magnitude” Encoding	50
Table 2-27: “Track Angle/Heading” Format	50
Table 2-28: “Track Angle/Heading Type” Encoding	50
Table 2-29: “Track Angle/Heading” Encoding	51
Table 2-30: “Vertical Velocity” Format.....	51
Table 2-31: “Vertical Velocity Source” Encoding	51
Table 2-32: “Sign Bit for Vertical Rate” Encoding.....	52
Table 2-33: “Vertical Rate” Encoding	52
Table 2-34: “A/V Size” Format	53
Table 2-35: “Aircraft Length and Width” Encoding.....	53
Table 2-36: Lateral Axis GPS Antenna Offset Encoding	54
Table 2-37: Longitudinal Axis GPS Antenna Offset Encoding	55
Table 2-38: “UTC” Encoding.....	55
Table 2-39: “Uplink Feedback” Encoding	57
Table 2-40: Format of STATE VECTOR Element (For TIS-B or ADS-R).....	58
Table 2-41: Format of MODE STATUS Element	59
Table 2-42: “EMITTER CATEGORY” Encoding	60
Table 2-43: “Call Sign” Character Encoding	61
Table 2-44: “EMERGENCY/PRIORITY STATUS” Encoding	63
Table 2-45: UAT MOPS Version Number.....	63
Table 2-46: “SIL” Encoding	64
Table 2-47: System Design Assurance (SDA) Field Encoding.....	65
Table 2-48: “NAC _P ” Encoding.....	66
Table 2-49: “NAC _V ” Encoding.....	67

Table 2-50: “NIC _{BARO} ” Encoding	68
Table 2-51: “CAPABILITY CODES” Encoding	68
Table 2-52: “OPERATIONAL MODES” Encoding	70
Table 2-53: SIL Supplement (SIL _{SUPP}) Flag Encoding.....	71
Table 2-54: Geometric Vertical Accuracy (GVA) Field Encoding.....	72
Table 2-55: Format of AUXILIARY STATE VECTOR Element.....	73
Table 2-56: Format of TARGET STATE Element (Payload Type Codes “3” and “4”).....	74
Table 2-57: “Selected Altitude Type” Field.....	74
Table 2-58: “Selected Altitude” Format.....	75
Table 2-59: “Barometric Pressure Setting (Minus 800 millibars) Field Encoding.....	76
Table 2-60: “Selected Heading” Magnitude Subfield Encoding.....	77
Table 2-61: Format of TARGET STATE Element.....	79
Table 2-62: Payload Type Code Allocation	83
Table 2-63: UAT ADS-B Transmitter Input Requirements	87
Table 2-64: Selectivity Rejection Ratios.....	93
Table 2-65: Message-to-Completed Report Assembly Throughput Requirements	100
Table 2-66: Range Criteria for ADS-B Messages	101
Table 2-67: Range Criteria for Ground Uplink Messages	101
Table 2-68: Environmental Test Group Applicability	110
Table 2-69: Performance Test Requirements During Environmental Testing.....	111
Table 2-70: Digital Demodulation Mode Configuration.....	119
Table 2-71: FEC Parity Encoding for Basic ADS-B Messages	131
Table 2-72: FEC Parity Encoding for Long ADS-B Messages.....	132
Table 2-73: ICAO 24-bit Aircraft Address Encoding.....	138
Table 2-74: Temporary Addresses with ICAO 24-bit Address.....	141
Table 2-75: Temporary Addresses without ICAO 24-bit Address.....	141
Table 2-76: Latitude Encoding Values.....	147
Table 2-77: Longitude Encoding Values.....	148
Table 2-78: Latitude and Longitude Encoding Values for Data Unavailable and Data Equals ZERO Cases	149
Table 2-79: Altitude Field Encoding.....	152
Table 2-80: Vertical Status Determination when no Automatic AIRBORNE/ON-GROUND Indication is Available	159
Table 2-81: ON-GROUND Override Verification	161
Table 2-82: Discrete Values for Subsonic North/South Velocity	164
Table 2-83: Discrete Values for Supersonic North/South Velocity	167
Table 2-84: Discrete Values for Subsonic Ground Speed.....	170
Table 2-85: Discrete Values for Subsonic East/West Velocity.....	174
Table 2-86: Discrete Values for Supersonic East/West Velocity.....	177
Table 2-87: Vertical Rate Discrete Values.....	184
Table 2-88: “EMITTER CATEGORY” Encoding Test Data	190
Table 2-89: “EMITTER CATEGORY” And Bytes 18 & 19 Encoding Test Data	191
Table 2-90: Bytes 20 & 21 Encoding Test Data.....	192
Table 2-91: Bytes 22 & 23 Encoding Test Data.....	194
Table 2-92: Geometric Vertical Accuracy Validation Values.....	208
Table 2-93: Secondary Altitude Field Encoding	211
Table 2-94: Selected Altitude Encoding Values.....	214
Table 2-95: Barometric Pressure Setting Encoding Values	215
Table 2-96: Selected Heading Encoding Values	216
Table 2-97: Payload Type and Tx Antenna Selection versus Equipment Class	226
Table 2-98: MSO Sequence Validation.....	229
Table 2-99: UAT ADS-B Transmitter Input Requirements	234
Table 2-100: Vector Mode Configuration	255

Table 2-101: Signal Generator Configuration	255
Table 2-102: Selectivity Rejection Ratios	258
Table 2-103: Tx Schedule and Power Level for A3, A2 and A1H Message Sources.....	266
Table 2-104: Tx Schedule and Power Level for A1S, A1L and A0 Message Sources	266
Table 2-105: ADS-B Message Reception – Set 1.....	269
Table 2-106: ADS-B Message Reception – Set 2.....	272
Table 2-107: Six consecutive De-Interleaved RS Block Values of a Ground Uplink Message – Set 1 ...	277
Table 2-108: Six consecutive De-Interleaved RS Block Values of a Ground Uplink Message – Set 2 ...	278
Table 2-109: Six consecutive De-Interleaved RS Block Values of a Ground Uplink Message – Set 3 ...	279
Table 2-110: Six consecutive De-Interleaved RS Block Values of a Ground Uplink Message – Set 4 ...	280
Table 2-111: Six consecutive De-Interleaved RS Block Values of a Ground Uplink Message – Set 5 ...	281
Table 2-112: Six consecutive De-Interleaved RS Block Values of a Ground Uplink Message – Set 6 ...	282
Table 2-113: Six consecutive De-Interleaved RS Block Values of a Ground Uplink Message – Set 7 ...	283
Table 2-114: Six consecutive De-Interleaved RS Block Values of a Ground Uplink Message – Set 8 ...	284
Table 2-115: Six consecutive De-Interleaved RS Block Values of a Ground Uplink Message – Set 9 ...	285
Table 3-1: Minimum Ranges for Receiving Capability	325
Table C-1: Example of Basic ADS-B Message Payloads.....	C-4
Table C-2: Example of Long Type 1 ADS-B Message Payloads	C-6
Table D-1: Example of Site ID Table	D-11
Table E-1: Typical Antennas	E-6
Table E-2: Diplexer Testing with ATC Transponders.....	E-10
Table F-1: Air-To-Air Link Budgets.....	F-3
Table G-1: Signal Level Analysis of the Sample Scenario	G-6
Table G-2: Interference Scenarios and Implementation Assumptions	G-8
Table G-3: Received Power Levels (dBm) for Current European DME/TACAN Environment	G-9
Table G-4: Received Power Levels (dBm) for 2015 European DME/TACAN Environment	G-9
Table G-5: Co-site Environment	G-9
Table G-6: Overview of Scenario Assessments	G-11
Table I-1: Transmitter to Receiver Time Offset Worst Case	I-5
Table J-1: Report Format	J-3
Table J-2: Report Packet Types	J-4
Table K-1: Ranges of ADS-B MASPS Compliance for UAT Transmit-Receive Combinations in the LA2020 Scenario.....	K-34
Table K-2: Ranges of ADS-B MASPS Compliance for UAT Transmit-Receive Combinations in CE 2015 Scenario	K-74
Table K-3: Acquisition Requirements.....	K-77
Table K-4: 99 th Percentile Range for Information Acquisition for Various Combinations of Transmit- Receive Pairs (NM)	K-77
Table K-5: 99 th Percentile Air-Ground Acquisition Ranges for Both Scenarios	K-78
Table K-6: 99 th Percentile Air-Air Acquisition Ranges for LA2020 Scenario	K-78
Table K-7: 99 th Percentile Air-Air Acquisition Ranges for CE2015 Scenario	K-79
Table K-8: 99 th Percentile Air-Air Acquisition Ranges for CE2015 Scenario	K-79
Table K-9: 95% Update Interval for Scenario 1 as a Function of Range and Transmit Power.....	K-93
Table K-10: 95% Update Interval for Scenario 2a as a Function of Multipath Effect and Ground Transmissions	K-94
Table K-11: 95% Update Interval for Scenario 2b as a Function of Multipath Effect and Ground Transmissions	K-94
Table L-1: Proposed Trajectory Change Report Elements	L-3
Table M-1: Maximum Undetected RS Word Error Rates.....	M-3
Table M-2: Upper Bounds on Undetected Message Error Probabilities	M-9
Table N-1: Files Associated with Test Procedures	N-3
Table Q-1: Platform Dynamics for the Horizontal Velocity Accuracy Test.....	Q-5
Table Q-2: Platform Dynamics for the Vertical Velocity Accuracy Test.....	Q-7

<u>Table Q-3: Heading Accuracy (RMS degrees)</u>	Q-9
<u>Table R-1: Version 2 versus Version 1 Message Fields</u>	R-3
<u>Table R-2: Version 1 “SIL” Encoding</u>	R-4
<u>Table S-1: Data Element Received Update Frequency Requirements</u>	S-11
<u>Table S-2: Availability of Meteorological and State Vector Data for ADS-B OUT Data Broadcasts</u> ...	S-23

1 PURPOSE AND SCOPE

1.1 Introduction

This document contains Minimum Operational Performance Standards for airborne equipment to support Automatic Dependent Surveillance - Broadcast (ADS-B) utilizing the Universal Access Transceiver (UAT). ADS-B is a system by which aircraft and certain equipped surface vehicles can share position, velocity, and other information with one another (and also with ground-based facilities/fixed locations such as air traffic services) via radio broadcast techniques. UAT is a multi-purpose aeronautical data link intended to support not only ADS-B, but also Flight Information Service - Broadcast (FIS-B), Traffic Information Service - Broadcast (TIS-B), and, if required in the future, supplementary ranging and positioning capabilities. While UAT has been expressly designed as a multi-purpose data link for surveillance-related applications, the focus of this document is on its support of ADS-B and basic ground uplink capabilities.

The standards contained in this document specify desired system characteristics that should prove useful to designers, manufacturers, installers and users of UAT equipment. Compliance with these standards is recommended as one means of ensuring that the equipment will satisfactorily perform its intended functions under conditions normally encountered in routine aeronautical operations. Some or all of these standards could be referenced by appropriate government agencies for certification and operational approval. Such regulatory application of any part of this document is solely the responsibility of appropriate government agencies. This version of these MOPS (RTCA DO-282B) reflects additional operational experience with UAT, lessons learned in certification of UAT equipment, and further inputs from the International aviation community during the development of International Civil Aviation Organization (ICAO) Standards and Recommended Practices (SARPs) for UAT.

Note: *The use of “shall” in the body of this document indicates a requirement. The use of “should” indicates a characteristic that is highly recommended, but is not required.*

Since the basic equipment implementation includes computer processing, RTCA DO-178B, *Software Considerations in Airborne Systems and Equipment Certification*, should be considered. Application of the software requirements of RTCA DO-178B should take into account the level of criticality of supported functions, consequences of equipment failure, and the presence and effectiveness of back-up and fault-monitoring features.

Section 1 of this document provides information and assumptions needed to understand the rationale for the equipment characteristics and requirements in this document. A high-level technical description of ADS-B and the UAT data link is provided, including the ability of UAT to support FIS-B, TIS-B, and independent ranging. The section also describes operational goals for ADS-B as envisioned by members of RTCA Special Committee SC-186 and the RTCA Free Flight Select Committee. This section, along with RTCA DO-242A, *Minimum Aviation System Performance Standards (MASPS) for ADS-B*, forms the basis for the standards stated in Sections 2 through 4.

Section 2 contains the minimum operational performance standards for the equipment. These standards define required performance under standard operating conditions, as well as under stressed physical environmental conditions. Also included are recommended bench test procedures to demonstrate equipment compliance with the stated minimum requirements. While the emphasis in this document is on UAT's support of ADS-B,