

RTCA, Inc.
1828 L Street, NW, Suite 805
Washington, D.C. 20036-5133 USA

**Minimum Operational Performance Standards
(MOPS) for Surveillance Transmit
Processing (STP)**

RTCA DO-302
December 13, 2006

Prepared by: SC-186
© 2006 RTCA, Inc.

Copies of this document may be obtained from

RTCA, Inc.

Telephone: 202-833-9339

Facsimile: 202-833-9434

Internet: www.rtca.org

Please visit the RTCA Online Store for document pricing and ordering information.

FOREWORD

This document was prepared by RTCA Special Committee 186 (SC-186) and approved by the RTCA Program Management Committee (PMC) on December 13, 2006.

RTCA, Incorporated is a not-for-profit corporation formed to advance the art and science of aviation and aviation electronic systems for the benefit of the public. The organization functions as a Federal Advisory Committee and develops consensus-based recommendations on contemporary aviation issues. RTCA's objectives include, but are not limited to:

- Coalescing aviation system user and provider technical requirements in a manner that helps government and industry meet their mutual objectives and responsibilities;
- Analyzing and recommending solutions to the system technical issues that aviation faces as it continues to pursue increased safety, system capacity and efficiency;
- Developing consensus on the application of pertinent technology to fulfill user and provider requirements, including development of Minimum Operational Performance Standards (MOPS) for electronic systems and equipment that support aviation; and
- Assisting in developing the appropriate technical material upon which positions for the International Civil Aviation Organization (ICAO) and the International Telecommunication Union (ITU) and other appropriate international organizations can be based.

The recommendations of RTCA are often used as the basis for government and private sector decisions as well as the foundation for many Federal Aviation Administration Technical Standard Orders (TSO).

Since RTCA is not an official agency of the United States Government, its recommendations may not be regarded as statements of official government policy unless so enunciated by the United States Government organization or agency having statutory jurisdiction over any matters to which the recommendations relate.

This page was intentionally left blank.

Currently in preview, click buy full version

TABLE OF CONTENTS

1	PURPOSE AND SCOPE	1
1.1	Introduction.....	1
1.2	Systems Overview	2
1.3	Operational Application(s).....	3
1.4	Intended Function	5
1.5	Assumptions.....	6
1.5.1	GNSS Assumptions.....	6
1.5.1.1	GNSS Position Output	6
1.5.1.1.1	Position Accuracy	6
1.5.1.1.1.1	HFOM.....	6
1.5.1.1.1.2	VFOM.....	7
1.5.1.1.2	GNSS Position Integrity.....	7
1.5.1.1.2.1	HPL or HIL.....	7
1.5.1.1.2.2	VPL or VIL.....	8
1.5.1.2	GNSS Velocity Accuracy	8
1.5.1.3	GPS Receiver Mode Annunciations	8
1.5.2	Flight Management System (FMS) Assumptions	8
1.5.2.1	FMS Position Output	9
1.5.2.1.1	Position Accuracy – ANP, EPU, and EPE Assumptions	9
1.5.2.1.2	Position Integrity	9
1.5.2.2	FMS Velocity Accuracy	9
1.6	Test Procedures.....	9
2	EQUIPMENT PERFORMANCE REQUIREMENTS AND TEST PROCEDURES.....	11
2.1	General Requirements.....	11
2.1.1	Airworthiness	11
2.1.2	Intended Function.....	11
2.1.3	Federal Communications Commission Rules	11
2.1.4	Fire Protection.....	11
2.1.5	Operation of Controls.....	11
2.1.6	Accessibility of Controls.....	11
2.1.7	Effects of Test	12
2.1.8	Hardware and Software Design Assurance (DO-289 R3.76, R3.77)	12
2.2	STP Subsystem Requirements	12
2.2.1	Introduction	12
2.2.2	General Requirements for STP.....	12
2.2.3	Reserved.....	14
2.2.4	State Data Processing	14
2.2.4.1	Position Accuracy (HEPU _{STP} and VEPU _{STP}).....	15
2.2.4.1.1	HEPU _{STP}	15
2.2.4.1.1.1	Definition of HEPU _{STP}	15
2.2.4.1.1.2	Requirements for the Determination of HEPU _{STP}	17
2.2.4.1.1.2.1	Case 1: Position Accuracy Metric(s) Reported by the Selected Position Source	17
2.2.4.1.1.2.2	Case 2: Position Accuracy Metric(s) not Reported by the Selected Position Source	18
2.2.4.1.1.3	Conditions for Limiting the Reported HEPU _{STP}	18
2.2.4.1.1.4	Requirements for the Delivery of HEPU _{STP}	21

2.2.4.1.1.4.1	STP and ADS-B Transmit Subsystem Are Not Integrated	21
2.2.4.1.1.4.2	STP and ADS-B Transmit Subsystem Are Integrated	21
2.2.4.1.2	VEPU _{STP}	21
2.2.4.1.2.1	Definition of VEPU _{STP}	21
2.2.4.1.2.2	Requirements for the Determination of VEPU _{STP}	22
2.2.4.1.2.2.1	Case 1: Position Accuracy Metric(s) Reported by the Selected Position Source	22
2.2.4.1.2.2.2	Case 2: Position Accuracy Metric(s) not Reported by the Selected Position Source	22
2.2.4.1.2.3	Conditions for Limiting the Reported VEPU _{STP}	22
2.2.4.1.2.4	Requirements for Delivery of VEPU _{STP}	22
2.2.4.1.2.4.1	STP and ADS-B Transmit Subsystem Are Not Integrated	23
2.2.4.1.2.4.2	STP and ADS-B Transmit Subsystem Are Integrated	23
2.2.4.2	Determination of Velocity Accuracy (HEVU _{STP} and VEVU _{STP})	23
2.2.4.2.1	HEVU _{STP}	23
2.2.4.2.1.1	Definition of HEVU _{STP}	23
2.2.4.2.1.2	Requirements for Determination of HEVU _{STP}	24
2.2.4.2.1.2.1	Case 1: Velocity Accuracy Metric(s) Reported by the Selected Velocity Source	24
2.2.4.2.1.2.2	Case 2: Velocity Accuracy Metric(s) Not Reported by the Selected Velocity Source, but a Position Accuracy Metric is Reported	24
2.2.4.2.1.2.2.1	Velocity Source is a GNSS Navigation Sensor that Provides HFOM	25
2.2.4.2.1.2.2.2	Velocity Source is an RNP Compliant FMS	28
2.2.4.2.1.2.2.3	Other Conditions Relative to Case 2	28
2.2.4.2.1.2.3	Case 3: No Position or Velocity Accuracy Metrics Reported	28
2.2.4.2.1.3	Requirements for the Delivery of HEVU _{STP}	28
2.2.4.2.1.3.1	STP and ADS-B Transmit Subsystem are not integrated	28
2.2.4.2.1.3.2	STP and ADS-B Transmit Subsystem are integrated	29
2.2.4.2.2	VEVU _{STP}	29
2.2.4.2.2.1	Definition of VEVU _{STP}	29
2.2.4.2.2.2	Requirements for Determination of VEVU _{STP}	29
2.2.4.2.2.2.1	Case 1: Velocity Accuracy Metric(s) Reported by the Selected Velocity Source	29
2.2.4.2.2.2.2	Case 2: Velocity Accuracy Metric(s) Not Reported by the Selected Velocity Source, but a Position Accuracy Metric is Reported	30
2.2.4.2.2.2.2.1	Velocity Source is a GNSS Navigation Sensor that Provides VFOM	30
2.2.4.2.2.2.2.2	Velocity Source is an RNP Compliant FMS	31
2.2.4.2.2.2.2.3	Other Conditions Relative to Case 2	31
2.2.4.2.2.2.3	Case 3: No Position or Velocity Accuracy Metrics Reported	31
2.2.4.2.2.3	Requirements for the Delivery of VEVU _{STP}	31
2.2.4.2.2.3.1	STP and ADS-B Transmit Subsystem Are Not Integrated	31
2.2.4.2.2.3.2	STP and ADS-B Transmit Subsystem are integrated	32
2.2.4.3	Position Integrity Containment Region (HPL _{STP} and VPL _{STP})	32
2.2.4.3.1	HPL _{STP}	32
2.2.4.3.1.1	Definition of HPL _{STP}	32
2.2.4.3.1.2	Requirements for Determination of HPL _{STP}	32
2.2.4.3.1.2.1	Case 1: Integrity Metric(s) Reported by the Selected Position Source	33
2.2.4.3.1.2.2	Case 2: Integrity Metric(s) not Reported by the Selected Position Source	33
2.2.4.3.1.3	Conditions for Limiting the Reported HPL _{STP}	33
2.2.4.3.1.4	Requirements for the Delivery of HPL _{STP}	36
2.2.4.3.1.4.1	STP and ADS-B Transmit Subsystem Are Not Integrated	36
2.2.4.3.1.4.2	STP and ADS-B Transmit Subsystem Are Integrated	36
2.2.4.3.2	VPL _{STP}	36
2.2.4.3.2.1	Definition of VPL _{STP}	36

2.2.4.3.2.2	Requirements for Determination of VPL_{STP}	37
2.2.4.3.2.2.1	Case 1: Integrity Metric(s) Reported by the Selected Position Source	37
2.2.4.3.2.2.2	Case 2: Integrity Metric(s) not Reported by the Selected Position Source	37
2.2.4.3.2.3	Conditions for Limiting the Reported VPL_{STP}	37
2.2.4.3.2.4	Requirements for the Delivery of VPL_{STP}	38
2.2.4.3.2.4.1	STP and ADS-B Transmit Subsystem Are Not Integrated	38
2.2.4.3.2.4.2	STP and ADS-B Transmit Subsystem Are Integrated	38
2.2.4.4	Surveillance Integrity Level (SIL)	38
2.2.4.4.1	SIL Encoding	39
2.2.4.4.2	Requirements for the Determination of SIL	40
2.2.4.4.2.1	Example Means of Compliance for Determining SIL	41
2.2.4.4.3	Providing SIL to the ADS-B Transmit Subsystem	41
2.2.4.5	Barometric Altitude Quality (BAQ) Level	42
2.2.4.6	Barometric Altitude Surveillance Integrity Level (SIL_{BARO})	42
2.2.4.7	Management of State Data Sources	43
2.2.4.7.1	Horizontal Position and Navigation Data Sources	44
2.2.4.7.2	Altitude Data Sources	45
2.2.4.7.3	Vertical Rate Sources	45
2.2.5	STP Input / Output Data Requirements	46
2.2.5.1	STP Input Data Requirements	46
2.2.5.1.1	Horizontal Figure of Merit, HFOM	46
2.2.5.1.2	Estimated Position Uncertainty, EPU	46
2.2.5.1.3	Actual Navigation Performance, ANP	47
2.2.5.1.4	GNSS/FMS Navigation Type Information	47
2.2.5.1.5	Vertical Figure of Merit, VFOM	47
2.2.5.1.6	Horizontal Figure of Merit_Rate, $HFCM_R$	48
2.2.5.1.7	Vertical Figure of Merit_Rate, $VFOM_R$	48
2.2.5.1.8	Horizontal Protection Limit, HPL	48
2.2.5.1.9	Vertical Protection Limit, VPL	48
2.2.5.1.10	Surveillance Integrity Level, SIL	48
2.2.5.1.11	Barometric Altitude Quality (BAQ) Level	48
2.2.5.1.12	Barometric Altitude Surveillance Integrity Level (SIL_{BARO})	48
2.2.5.1.13	Ground Speed	49
2.2.5.1.14	Altitude Select Data	49
2.2.5.1.15	Position Accuracy and Integrity Data	49
2.2.5.1.16	Velocity Accuracy Data	49
2.2.5.1.17	Time Merit Synchronization Data	50
2.2.5.2	STP Output Data Requirements	50
2.2.5.2.1	Horizontal Figure of Merit_STP ($HFOM_{STP}$)	50
2.2.5.2.2	Vertical Figure of Merit_STP ($VFOM_{STP}$)	50
2.2.5.2.3	Horizontal Figure of Merit_Rate_STP, $HFOM_{RSTP}$	51
2.2.5.2.4	Vertical Figure of Merit_Rate_STP, $VFOM_{RSTP}$	51
2.2.5.2.5	Horizontal Protection Limit_STP, HPL_{STP}	52
2.2.5.2.6	Vertical Protection Limit_STP, VPL_{STP}	52
2.2.5.2.7	Surveillance Integrity Level_STP, SIL_{STP}	53
2.2.5.2.8	Barometric Altitude Quality (BAQ) Level_STP (BAQ_{STP})	53
2.2.5.2.9	Barometric Altitude Surveillance Integrity Level_STP ($SIL_{BAROSTP}$)	53
2.2.5.2.10	Selected Data Source Annunciation	53
2.2.5.2.10.1	Selected ADS-B Position Source Annunciation	53
2.2.5.2.10.2	Selected ADS-B Vertical Rate Source Annunciation	54
2.2.5.2.10.3	Selected ADS-B Altitude Source Annunciation	55
2.3	Equipment Performance—Environmental Conditions	56
2.3.1	Environmental Test Conditions	56

2.3.2	Detailed Environmental Test Procedures	58
2.3.2.1	Horizontal Position and Navigation Data Sources	58
2.3.2.2	Altitude Data Sources	58
2.3.2.3	Vertical Rate Sources	58
2.4	STP Test Procedures	58
2.4.1	STP Subsystem Test Procedures	58
2.4.2	Definition of Terms and Conditions of Test	59
2.4.3	Special Terms and Conditions of Test	59
2.4.4	Detailed Test Procedures	59
2.4.4.1	Verification of Horizontal Position Accuracy (HEPU _{STP} and VEPU _{STP})	60
2.4.4.1.1	Verification of HEPU _{STP}	60
2.4.4.1.1.1	Verification of Definition of HEPU _{STP}	60
2.4.4.1.1.2	Verification of Requirements for the Determination of HEPU _{STP}	60
2.4.4.1.1.2.1	Verification of Case 1: Position Accuracy Metric(s) Reported by the Selected Position Source (§2.2.4.1.1.2.1, §2.2.4.1.1.3, §2.2.4.1.1.4, §2.2.5.1.1, §2.2.5.1.4, §2.2.5.1.13, §2.2.5.1.15, §2.2.5.1.17, and §2.2.5.2.1)	60
2.4.4.1.1.2.1.1	Purpose / Introduction	60
2.4.4.1.1.2.1.2	Measurement Procedure	60
2.4.4.1.1.2.2	Verification of Case 2: Position Accuracy Metric(s) not Reported by the Selected Position Source (2.2.4.1.1.2)	69
2.4.4.1.1.3	Verification of Conditions for Limiting the Reported HEPU _{STP}	70
2.4.4.1.1.4	Verification of Requirements for the Delivery of HEPU _{STP}	70
2.4.4.1.1.4.1	Verification of STP and ADS-B Transmit Subsystems that Are Not Integrated	70
2.4.4.1.1.4.2	Verification of STP and ADS-B Transmit Subsystems that Are Integrated	70
2.4.4.1.2	Verification of VEPU _{STP}	70
2.4.4.1.2.1	Verification of Definition of VEPU _{STP}	70
2.4.4.1.2.2	Verification of Requirements for the Determination of VEPU _{STP}	70
2.4.4.1.2.2.1	Verification of Case 1: Position Accuracy Metric(s) Reported by the Selected Position Source (§2.2.4.1.2.2.1, §2.2.4.1.2.3, §2.2.4.1.2.4, §2.2.5.1.3- §2.2.5.1.5, §2.2.5.1.7, §2.2.5.2.2)	70
2.4.4.1.2.2.1.1	Purpose / Introduction	70
2.4.4.1.2.2.1.2	Measurement Procedure	71
2.4.4.1.2.2.2	Verification of Case 2: Position Accuracy Metric(s) not Reported by the Selected Position Source	73
2.4.4.1.2.3	Verification of Conditions for Limiting the Reported VEPU _{STP}	73
2.4.4.1.2.4	Verification of Requirements for Delivery of VEPU _{STP}	73
2.4.4.1.2.4.1	Verification of STP and ADS-B Transmit Subsystem that Are Not Integrated	73
2.4.4.1.2.4.2	Verification of STP and ADS-B Transmit Subsystem that Are Integrated... ..	73
2.4.4.2	Verification of Determination of Velocity Accuracy (HEVU _{STP} and VEVU _{STP})	74
2.4.4.2.1	Verification of HEVU _{STP}	74
2.4.4.2.1.1	Verification of Definition of HEVU _{STP}	74
2.4.4.2.1.2	Verification of Requirements for Determination of HEVU _{STP}	74
2.4.4.2.1.2.1	Verification of Case 1: Velocity Accuracy Metric(s) Reported by the Selected Velocity Source	74
2.4.4.2.1.2.1.1	Measurement Procedure	74
2.4.4.2.1.2.2	Case 2: Velocity Accuracy Metric(s) Not Reported by the Selected Velocity Source, but a Position Accuracy Metric is Reported	75
2.4.4.2.1.2.2.1	Measurement Procedure	75
2.4.4.2.1.2.2.2	Verification of Velocity Source is a GNSS Navigation Sensor that Provides HFOM 79	75
2.4.4.2.1.2.2.3	Verification of Velocity Source is an RNP Compliant FMS	79

2.4.4.2.1.2.2.4	Verification of Other Conditions Relative to Case 2.....	79
2.4.4.2.1.2.3	Verification of Case 3: No position or Velocity Accuracy Metrics Reported 79	
2.4.4.2.2	Verification of VEVU _{STP}	80
2.4.4.2.2.1	Verification of Definition of VEVU _{STP}	80
2.4.4.2.2.2	Verification of Requirements for Determination of VEVU _{STP}	80
2.4.4.2.2.2.1	Verification of Case 1: Velocity Accuracy Metric(s) Reported by the Selected Velocity Source	80
2.4.4.2.2.2.2	Verification of Case 2: Velocity Accuracy Metric(s) Not Reported by the Selected Velocity Source, but a Position Accuracy Metric is Reported	80
2.4.4.2.2.2.2.1	Verification of Velocity Source is a GNSS Navigation Sensor that Provides VFOM 80	
2.4.4.2.2.2.2.2	Verification of Velocity Source is an RNP Compliant FMS	80
2.4.4.2.2.2.2.3	Verification of Other Conditions Relative to Case 2.....	80
2.4.4.2.2.2.3	Verification of Case 3: No Position or Velocity Accuracy Metrics Reported 80	
2.4.4.3	Verification of Position Integrity Containment Region (HPL _{STP} and VPL _{STP}).....	81
2.4.4.3.1	Verification of HPL _{STP}	81
2.4.4.3.1.1	Definition of HPL _{STP}	81
2.4.4.3.1.2	Verification of Requirements for Determination of HPL _{STP}	81
2.4.4.3.1.2.1	Verification of Case 1: Integrity Metric(s) Reported by the Selected Position Source (§2.2.4.3.1.2.1, §2.2.4.3.1.3, §2.2.4.3.1.4)	81
2.4.4.3.1.2.1.1	Purpose / Introduction	81
2.4.4.3.1.2.1.2	Measurement Procedure	81
2.4.4.3.1.2.2	Verification of Case 2: Integrity Metric(s) not Reported by the Selected Position Source	89
2.4.4.3.1.3	Verification of Conditions for Limiting the Reported HPL _{STP}	90
2.4.4.3.1.4	Verification of Requirements for the Delivery of HPL _{STP}	90
2.4.4.3.1.4.1	Verification of STP and ADS-B Transmit Subsystem Are Not Integrated... 90	
2.4.4.3.1.4.2	Verification of STP and ADS-B Transmit Subsystem Are Integrated..... 90	
2.4.4.3.2	Verification of VPL _{STP}	90
2.4.4.3.2.1	Verification of Definition of VPL _{STP}	90
2.4.4.3.2.2	Verification of Requirements for Determination of VPL _{STP}	90
2.4.4.3.2.2.1	Verification of Case 1: Integrity Metric(s) Reported by the Selected Position Source	90
2.4.4.3.2.2.1.1	Measurement Procedure	90
2.4.4.3.2.2.2	Verification of Case 2: Integrity Metric(s) not Reported by the Selected Position Source	97
2.4.4.3.2.3	Verification of Conditions for Limiting the Reported VPL _{STP}	97
2.4.4.3.2.4	Verification of Requirements for the Delivery of VPL _{STP}	97
2.4.4.3.2.4.1	Verification of STP and ADS-B Transmit Subsystem Are Not Integrated... 97	
2.4.4.3.2.4.2	Verification of STP and ADS-B Transmit Subsystem Are Integrated..... 97	
2.4.4.4	Verification of Surveillance Integrity Level (SIL)	97
2.4.4.4.1	Verification of SIL Encoding	98
2.4.4.4.2	Verification of Requirements for the Determination of SIL	98
2.4.4.4.2.1	Verification of Example Means of Compliance for Determining SIL.....	98
2.4.4.4.2.1.1	Purpose/Introduction.....	98
2.4.4.4.2.1.2	Measurement Procedure.....	98
2.4.4.4.3	Verification of Providing SIL to the ADS-B Transmit Subsystem	99
2.4.4.5	Verification of Barometric Altitude Quality (BAQ) Level.....	99
2.4.4.5.1	Purpose/Introduction	99
2.4.4.5.2	Measurement Procedure	99
2.4.4.6	Verification of Barometric Altitude Surveillance Integrity Level (SIL _{BARO})	100
2.4.4.6.1	Purpose/Introduction	100

2.4.4.6.2	Measurement Procedure	100
2.4.4.7	Verification of Management of State Data Sources	100
2.4.4.7.1	Verification of Horizontal Position and Navigation Data Sources	100
2.4.4.7.1.1	Purpose/Introduction	100
2.4.4.7.1.2	Measurement Procedure	101
2.4.4.7.2	Verification of Altitude Data Sources	104
2.4.4.7.2.1	Purpose/Introduction	104
2.4.4.7.2.2	Measurement Procedure	104
2.4.4.7.3	Verification of Vertical Rate Sources	105
2.4.4.7.3.1	Purpose/Introduction	105
2.4.4.7.3.2	Measurement Procedure	105
2.4.5	Verification of STP Input / Output Data Requirements	107
2.4.5.1	Verification of STP Input Data Requirements	107
2.4.5.1.1	Verification of STP Horizontal Figure of Merit, HFOM	108
2.4.5.1.2	Verification of STP Estimated Position Uncertainty, EPU	108
2.4.5.1.3	Verification of STP Actual Navigation Precision, ANP	108
2.4.5.1.4	Verification of STP GNSS/FMS Navigation Type Information	108
2.4.5.1.5	Verification of STP Vertical Figure of Merit, VFOM	108
2.4.5.1.6	Verification of STP Horizontal Figure of Merit_Rate, HFOM _R	108
2.4.5.1.7	Verification of STP Vertical Figure of Merit_Rate, VFOM _R	108
2.4.5.1.8	Verification of Horizontal Protection Limit, HPL	108
2.4.5.1.9	Verification of Vertical Protection Limit, VPL	108
2.4.5.1.10	Verification of Surveillance Integrity Level, SIL	109
2.4.5.1.11	Verification of Barometric Altitude Quality (BAQ) Level	109
2.4.5.1.12	Verification of Barometric Altitude Surveillance Integrity Level (SIL _{BARO})	109
2.4.5.1.13	Verification of Ground Speed	109
2.4.5.1.14	Verification of Altitude Select Data	109
2.4.5.1.15	Verification of Position and Validity Data	109
2.4.5.1.16	Verification of Velocity and Validity Data	109
2.4.5.1.17	Verification of Time Mark Synchronization Data	109
2.4.5.2	Verification of STP Output Data Requirements	109
2.4.5.2.1	Verification of Horizontal Figure of Merit_STP (HFOM _{STP})	110
2.4.5.2.2	Verification of Vertical Figure of Merit_STP (VFOM _{STP})	110
2.4.5.2.3	Verification of Horizontal Figure of Merit_Rate_STP, HFOM _{RSTP}	110
2.4.5.2.4	Verification of Vertical Figure of Merit_Rate_STP, VFOM _{RSTP}	110
2.4.5.2.5	Verification of Horizontal Protection Limit_STP, HPL _{STP}	110
2.4.5.2.6	Vertical Protection Limit_STP, VPL _{STP}	110
2.4.5.2.7	Surveillance integrity Level_STP, SIL _{STP}	110
2.4.5.2.8	Barometric Altitude Quality (BAQ) Level_STP (BAQ _{STP})	110
2.4.5.2.9	Barometric Altitude Surveillance Integrity Level_STP (SIL _{BAROSTP})	110
2.4.5.2.10	Selected Data Source Annunciation	111
2.4.5.2.10.1	Selected ADS-B Position Source Annunciation	111
2.4.5.2.10.2	Selected ADS-B Vertical Rate Source Annunciation	111
2.4.5.2.10.3	Selected ADS-B Altitude Source Annunciation	111
3	INSTALLED EQUIPMENT PERFORMANCE	113
4	EQUIPMENT OPERATIONAL PERFORMANCE CHARACTERISTICS	115
	MEMBERSHIP	117

LIST OF TABLES

<u>Table 1-1</u>	GNSS Assumptions Summary.....	5
<u>Table 1-2</u>	FMS Assumptions Summary.....	6
<u>Table 2-1</u>	HEPU _{UL} and VEPU _{UL} Based Upon Source Reported Accuracy Metrics.....	20
<u>Table 2-2</u>	Determining NAC _v if HFOM _R and VFOM _R are Provided.....	25
<u>Table 2-3</u>	HEVU _{STP} and VEVU _{STP} Based Upon Source Reported Accuracy Metrics.....	26
<u>Table 2-4</u>	HPL _{UL} and VPL _{UL} Based Upon Source Reported Integrity Metrics.....	34
<u>Table 2-5</u>	Surveillance Integrity Level (SIL) Encoding.....	39
<u>Table 2-6</u>	Determination of Surveillance Integrity Level (SIL) Based Upon the Selected Position Source	42
<u>Table 2-7a</u>	ADS-B Position Source.....	54
<u>Table 2-7b</u>	ADS-B Position Type.....	54
<u>Table 2-8a</u>	ADS-B Vertical Rate Source.....	54
<u>Table 2-8b</u>	ADS-B Vertical Rate Type.....	55
<u>Table 2-9</u>	ADS-B Altitude Source.....	55
<u>Table 2-10a</u>	Environmental Test Groups.....	57
<u>Table 2-10b</u>	Environmental Test Groups.....	58
<u>Table 2-11</u>	HFOM / VFOM Test Inputs.....	62
<u>Table 2-12</u>	HFOM _R / VFOM _R Test Inputs.....	75
<u>Table 2-13</u>	HFOM / VFOM Test Inputs.....	77
<u>Table 2-14</u>	HPL / VPL Test Inputs.....	84
<u>Table 2-15</u>	HPL / VPL Test Inputs for SIL=3 GPS.....	86
<u>Table 2-16</u>	VPL Test Inputs.....	93

LIST OF FIGURES

<u>Figure 1-1</u>	Overview of ASA Architecture.....	3
<u>Figure 2-1</u>	Subsystems for ASA Transmit Participant.....	13
<u>Figure 2-2</u>	STP Functional Architecture.....	14
<u>Figure 2-3</u>	State Data Quality Determination	16
<u>Figure 2-4</u>	Airborne Architecture for GPS Primary and FMS/RNP Backup for ADS-B for Air-Transport Type Aircraft	44

1 PURPOSE AND SCOPE

1.1 Introduction

This document contains Minimum Operational Performance Standards (MOPS) for *Surveillance Transmit Processing (STP)*.¹ These standards specify system characteristics that should be useful to designers, manufacturers, installers and users of the equipment.

These MOPS for STP contain requirements for interfacing ADS-B avionics to on-board position sources such as GPS and Flight Management Systems. Proper integration and installation of ADS-B equipment into aircraft is essential to successful implementation of ADS-B air-to-ground and air-to-air applications.

Compliance with these standards is recommended as one means of assuring that the equipment will perform its intended function(s) satisfactorily under all conditions normally encountered in routine aeronautical operation. Any regulatory application of this document is the sole responsibility of appropriate governmental agencies.

Section 1 of this document provides information needed to understand the rationale for equipment characteristics and requirements stated in the remaining sections. It describes typical equipment operations and operation goals, as envisioned by the members of RTCA Special Committee **186**, and establishes the basis for the standards stated in sections 2 through 3. Definitions and assumptions essential to proper understanding of this document are also provided in this section.

Section 2 contains the Minimum Performance Standards for the equipment. These standards specify the required performance under standard environmental conditions. Also included are recommended bench test procedures necessary to demonstrate equipment compliance with the stated minimum requirements.

Section 3 describes the performance required of installed equipment. Tests for the installed equipment are included when performance cannot be adequately determined through bench testing.

Section 4 describes the operational performance characteristics for equipment installations and defines conditions that will assure the equipment user that operations can be conducted safely and reliably in the expected operational environment.

These MOPS specify functional requirements for Surveillance Transmit Processing (STP). Operational performance standards for functions or components that refer to equipment capabilities that exceed the stated minimum requirements are identified as optional features.

The word “function” as used in this document includes all components and units necessary for the system to properly perform its intended function(s). For example, the “function” may be implemented in hardware or software, as appropriate, and the function

¹ Bold-italic text in this Guide pertains to the specific equipment described in the MOPS and provides guidance on what type of text needs to be developed.