

RTCA, Inc.
1150 18th Street, NW, Suite 910
Washington, DC 20036
USA

**Minimum Operational Performance Standards (MOPS)
for
Detect and Avoid (DAA) Systems**

RTCA DO-365B
March 18, 2021

Prepared by: SC-228
©2021, RTCA, Inc.

Copies of this document may be obtained from:

RTCA, Inc.
1150 18th Street, NW, Suite 910
Washington, DC 20036-4001, USA
Telephone: 202-833-9339
Facsimile: 202-833-9434
Internet: rtca.org

Please visit the RTCA online store for document pricing and ordering information.

FOREWORD

This document was prepared by Special Committee 228 (SC-228) and approved by the RTCA Program Management Committee (PMC) on March 18, 2021.

RTCA, Incorporated is a not-for-profit corporation formed to advance the art and science of aviation and aviation electronic systems for the benefit of the public. The organization functions as a Standards Development Organization and develops consensus based recommendations on contemporary aviation issues. RTCA's objectives include, but are not limited to:

- coalescing aviation system user and provider technical requirements in a manner that helps government and industry meet their mutual objectives and responsibilities;
- analyzing and recommending solutions to the system technical issues that aviation faces as it continues to pursue increased safety, system capacity, and efficiency;
- developing consensus on the application of pertinent technology to fulfill user and provider requirements, including development of minimum operational performance standards for electronic systems and equipment that support aviation; and
- assisting in developing the appropriate technical material upon which positions for the International Civil Aviation Organization and the International Telecommunication Union and other appropriate international organizations can be based.

The organization's recommendations are often used as the basis for government and private sector decisions as well as the foundation for many Federal Aviation Administration Technical Standard Orders.

Since RTCA is not an official agency of the United States Government, its recommendations may not be regarded as statements of official government policy unless so enunciated by the U.S. government organization or agency having statutory jurisdiction over any matters to which the recommendations relate.

DISCLAIMER

This publication is based on materials submitted by various participants during the SC approval process. Neither the SC nor RTCA has made any determination whether these materials could be subject to valid claims of patent, copyright or other proprietary rights by third parties, and no representation or warranty, expressed or implied is made in this regard. Any use of or reliance on this document constitutes an acceptance thereof "as is" and is subject to this disclaimer.

REVISION (REV) HISTORY

Rev Level	Description	Date	Effective Sections
-	Initial Publication	05/31/2017	All
A	Added Terminal Area DWC, Transit through Class B, Support for GBSS	03/26/2020	All
B	Added Class 3 – ACAS Xu, Non-cooperative DWC applicable to all classes, updated ATAR classes for different performance levels	03/18/2021	All

Currently in preview, click buy full version

EXECUTIVE SUMMARY

RTCA has been developing the Minimum Operational Performance Standards (MOPS) for equipment needed to support the safe operations of Unmanned Aircraft (UA) flights within the National Airspace System (NAS) and beyond the operational limits placed on small Unmanned Aircraft Systems (UAS) (see Section [107](#) of Title 14 (Aeronautics and Space) of the United States Code of Federal Regulations (14 U.S. CFR)). In 2013, RTCA initiated Special Committee 228 (SC-228) with a narrower scope; namely, to develop MOPS needed for (a) a Detect and Avoid (DAA) system (the focus of Working Group 1 (WG-1) and (b) a Control and Non-Payload Communications (CNPC) link system (the focus of WG-2).

The DAA system was specified to assist the remote pilot with operating an aircraft safely in the NAS. All aircraft flying in the NAS must comply with the operating rules of 14 CFR, specifically, §§ [91.109](#), [91.111](#), [91.113](#), [91.123](#) and [91.181\(b\)](#), which address see and avoid, collision avoidance, right-of-way rules, and remaining well clear. The DAA equipment may also be used to comply with the duties in International Civil Aviation Organization (ICAO) Annex 2 to the Convention on International Civil Aviation, specifically Chapter 2, Paragraph 2.3.1. These operating regulations assumed that a pilot would be onboard the aircraft and would be able to fully comply with these rules.

This document contains MOPS for DAA systems used in aircraft transiting and performing extended operations in Class D, E, and G airspace along with transiting Class B and C airspace. It includes equipment to enable UAS operations near Terminal Areas during approach and departure in Class C, D, E, and G airspace, and off-airport locations, but not operating in the visual traffic pattern or on the surface. It does not apply to small UAS (under 55 pounds (lbs)) operating in low-level environments (below 400') or other segmented areas.

Currently in preview, click buy full version

This page intentionally left blank.

TABLE OF CONTENTS

1	PURPOSE AND SCOPE	1
1.1	Introduction.....	1
1.2	Document Hierarchy	2
1.3	System Overview	4
1.3.1	DAA Equipment Description – Unmanned Aircraft.....	7
1.3.2	DAA Equipment Description – Control Station	10
1.3.3	DAA Equipment Description – Ground Based Surveillance	11
1.3.4	DAA Equipment Description – Airborne Collision Avoidance System for Unmanned Aircraft.....	12
1.3.5	System Limitations	12
1.4	Operational Application(s).....	13
1.5	Intended Function	14
1.6	Operational Goals	14
1.6.1	General.....	14
1.6.2	Unmanned Aircraft (UA).....	15
1.6.3	UA DAA Surveillance Equipment.....	16
1.6.4	GBSS Equipment	16
1.6.5	DAA Alerting, Guidance Processing and DAA Traffic Display	16
1.6.6	Control Station.....	16
1.6.7	Compatibility with Other Systems.....	16
1.7	Assumptions.....	17
1.7.1	Equipage and Airworthiness Assumptions	17
1.7.2	Remote Pilot Assumptions.....	17
1.7.3	Operational Assumptions.....	18
1.7.4	Modeling and Simulation Assumptions.....	19
1.7.5	Control Station (CS) Assumptions	19
1.7.6	Performance Assumptions for UA and Intruder Avionics	20
1.7.6.1	Performance Assumptions for UA Avionics.....	20
1.7.6.2	Performance Assumptions for Cooperative Intruder Avionics	21
1.8	Test Procedures.....	22
1.8.1	Environmental Tests	22
1.8.2	Bench Tests	22
1.8.3	Installed Equipment Considerations	22
1.8.4	Operational Tests	23
1.9	Definition of Terms	23
1.10	Aircraft Equipment Information Vulnerabilities.....	23
2	FAA EQUIPMENT PERFORMANCE REQUIREMENTS AND TEST PROCEDURES	25
2.1	General Requirements.....	25
2.1.1	Airworthiness	25
2.1.2	Intended Function	25
2.1.3	Federal Communications Commission Rules	25
2.1.4	Fire Protection.....	25
2.1.5	Operation of CS Controls.....	25
2.1.6	Accessibility of Controls.....	25
2.1.7	Effects of Test	25

2.1.8	DAA Equipment Interfaces.....	25
2.1.9	Design Assurance.....	26
2.1.10	DAA Equipment Classes and Articles	26
2.1.10.1	DAA Equipment Classes	28
2.1.10.2	DAA Equipment Articles.....	30
2.2	DAA Equipment Performance Requirements – Standard Conditions	33
2.2.1	General DAA Equipment Characteristics	33
2.2.1.1	Latency.....	33
2.2.1.2	DAA Surveillance Equipment.....	34
2.2.1.3	ATAR.....	35
2.2.1.4	Airborne Active Surveillance.....	35
2.2.1.5	ADS-B In System.....	35
2.2.1.6	TCAS II System (Class 2).....	36
2.2.1.7	ACAS Xu System (Class 3)	36
2.2.1.8	GBSS (Class 6, Class 7, Class 8).....	36
2.2.2	DAA Input/Output (I/O) Requirements	37
2.2.2.1	UA DAA Processor Input Data.....	39
2.2.2.1.1	Ownship State Data.....	39
2.2.2.1.1.1	Flight Intent and Active Runway Center Point Data (Optional).....	42
2.2.2.1.2	ATAR Intruder Data	43
2.2.2.1.3	Active Surveillance Intruder Data.....	45
2.2.2.1.4	ADS-B In Intruder Data.....	47
2.2.2.1.4.1	Intruder ADS-B Traffic State Vector Report Data.....	47
2.2.2.1.4.2	ADS-B Intruder Mode Status Data	49
2.2.2.1.4.3	TIS-B/ADS-R Service Status Data – Optional	50
2.2.2.1.4.4	TCAS II RA Report Data.....	50
2.2.2.1.4.5	Operational Coordination Message Data	51
2.2.2.1.5	TCAS II RA and Coordination Data.....	52
2.2.2.1.6	Surveillance Equipment Operating Status and Health Data.....	53
2.2.2.1.7	Reserved.....	54
2.2.2.1.8	C2 Link Data.....	54
2.2.2.1.9	GBSS Data –DAA Equipment Class 6	54
2.2.2.1.9.1	GBSS Status Data	54
2.2.2.1.9.2	GBSS Prioritized Track Data.....	55
2.2.2.2	UA DAA Processor Output Data.....	57
2.2.2.2.1	Prioritized Track Data.....	57
2.2.2.2.1.1	Unique Track ID (Track Number)	58
2.2.2.2.1.2	Flight ID.....	58
2.2.2.2.1.3	Time of Applicability (TOA).....	58
2.2.2.2.1.4	Intruder Alert/Priority	59
2.2.2.2.1.5	Source Data Type.....	59
2.2.2.2.1.6	Validated ADS-B	59
2.2.2.2.1.7	Air/Ground Status	59
2.2.2.2.1.8	Relative Horizontal Position	59
2.2.2.2.1.9	Relative Horizontal Position Accuracy.....	60
2.2.2.2.1.10	Bearing Invalid.....	60
2.2.2.2.1.11	Relative Horizontal Velocity.....	60
2.2.2.2.1.12	Relative Horizontal Velocity Accuracy.....	60
2.2.2.2.1.13	Relative Altitude.....	61
2.2.2.2.1.14	Relative Altitude Accuracy	61
2.2.2.2.1.15	Altitude Invalid.....	61

2.2.2.2.1.16	Relative Vertical Rate	61
2.2.2.2.1.17	Relative Vertical Rate Accuracy	62
2.2.2.2.1.18	DAA Alerting Data	62
2.2.2.2.1.19	Traffic Track Angle.....	62
2.2.2.2.2	DAA System Modes of Operation and Health Status	62
2.2.2.2.3	TCAS II TA/RA – DAA Equipment Class 2	63
2.2.2.2.4	Onboard Data Recording Capability.....	63
2.2.2.2.5	Input/Output Required to Enable Visual-Like Clearances.....	63
2.2.2.3	CS DAA Processor Input Data.....	64
2.2.2.4	CS DAA Processor Output Data.....	64
2.2.2.4.1	CS DAA Processor Health Status Data.....	64
2.2.2.4.2	CS DAA Processor GBSS Prioritized Track Data –DAA Equipment Class 6	65
2.2.2.5	DAA Control Panel Input	65
2.2.2.6	DAA Control Panel Output.....	65
2.2.2.7	CS DAA Traffic Display Input Data.....	65
2.2.2.7.1	Ownship Pressure Altitude.....	67
2.2.2.7.2	Ownship Length and Width Code.....	67
2.2.3	Active Surveillance, Equipment Class 2 RA Function, and Tracker Performance Requirements	67
2.2.3.1	DAA Active Surveillance and DAA Equipment Class 2 RA Function	67
2.2.3.1.1	DAA Active Surveillance	68
2.2.3.1.2	DAA with TCAS II RA Functionality (DAA Equipment Class 2).....	70
2.2.3.2	DAA Track Processing – Surveillance Data Processing and Tracking.....	70
2.2.3.2.1	Track Management	71
2.2.3.2.1.1	Track Initiation.....	72
2.2.3.2.1.2	Track Capacity and Output Prioritization	72
2.2.3.2.1.3	ADS-B Report Processing and Track Maintenance.....	73
2.2.3.2.1.4	Track Termination.....	81
2.2.3.2.2	Data Association	81
2.2.3.2.3	Intruder State Estimation	83
2.2.3.2.3.1	Individual Time of Track Extension and Traffic State File Generation.....	86
2.2.4	DAA Alerting and Guidance Processing Requirements	86
2.2.4.1	DAA Alerting and Guidance Suppression	86
2.2.4.1.1	Intruder-Specific Alerting and Guidance Suppression.....	87
2.2.4.2	Ownship Intent Information.....	88
2.2.4.3	DAA Alerting	88
2.2.4.3.1	DAA Well Clear (DWC) Definition	88
2.2.4.3.2	Hazard Alert Zone (HAZ) Definition	89
2.2.4.3.3	Non-Hazard Zone (NHZ) Definition	92
2.2.4.3.4	Slant Range Equation.....	92
2.2.4.3.5	Alert Types and Prioritization.....	93
2.2.4.3.5.1	Preventive Alert	93
2.2.4.3.5.2	Corrective Alert.....	94
2.2.4.3.5.3	Warning Alert	94
2.2.4.3.5.4	Prioritization of Alert Types	95
2.2.4.3.6	Alert Parameters by DWC	96
2.2.4.3.6.1	En Route DWC Alerts.....	96
2.2.4.3.6.2	Terminal DWC Alerts.....	102
2.2.4.3.6.3	Non-Cooperative DWC Alerts.....	105
2.2.4.3.7	Alerting Special Cases	108
2.2.4.3.7.1	Special Cases – ATAR Only.....	108

2.2.4.3.7.2	Special Cases – No Bearing	109
2.2.4.3.7.3	Special Cases – No Altitude.....	110
2.2.4.3.7.4	Special Cases – Unvalidated ADS-B	112
2.2.4.4	Guidance Processing	112
2.2.4.4.1	Guidance Processing – En Route and Non-Cooperative.....	117
2.2.4.4.1.1	DAA Maneuver Guidance to Maintain DWC – En Route and Non-Cooperative	117
2.2.4.4.1.2	DAA Maneuver Guidance to Regain DWC – En Route and Non-Cooperative	124
2.2.4.4.2	Guidance Processing in the Terminal Area.....	128
2.2.4.4.2.1	DAA Maneuver Guidance to Maintain DWC – DTA.....	128
2.2.4.4.2.2	DAA Maneuver Guidance to Regain DWC – DTA.....	131
2.2.4.4.3	Guidance Processing Special Cases	134
2.2.4.4.3.1	Special Cases – Maintain DAA Well Clear	134
2.2.4.4.3.2	Special Cases – Regain DAA Well Clear	138
2.2.4.5	Collision Avoidance Interoperability with Guidance.....	140
2.2.4.5.1	Class 2 RA Guidance	140
2.2.4.5.1.1	Guidance Processing for an MTE with Directive RA and DAA Warning Alert	143
2.2.4.5.2	Vertical DAA Guidance.....	144
2.2.4.5.2.1	Determining Intruders' Vertical RA Capability	145
2.2.4.5.2.2	Determining Intruders' Vertical RA Complement (VRC) Information	146
2.2.4.5.2.3	Vertical DAA Guidance Modification	149
2.2.4.5.3	Horizontal DAA Guidance.....	152
2.2.4.6	Class 3 RA Alerting and Guidance	153
2.2.5	DAA Traffic Display Subsystem Requirements	154
2.2.5.1	General DAA Traffic Display	154
2.2.5.2	Traffic Display Criteria (TDC).....	155
2.2.5.2.1	Default Traffic Display Criteria	155
2.2.5.3	DAA Traffic Display Information	155
2.2.5.4	Interfaces	156
2.2.5.4.1	DAA Traffic Display Latency.....	156
2.2.5.4.2	Time of Applicability of Traffic State Selector Data	156
2.2.5.5	Display Design – General.....	157
2.2.5.5.1	Display Characteristics.....	157
2.2.5.5.2	Dynamics	157
2.2.5.5.3	Labels	157
2.2.5.5.4	Symbols.....	157
2.2.5.6	Display Elements.....	157
2.2.5.6.1	Ownship Symbols	158
2.2.5.6.2	Traffic Information Formats	158
2.2.5.6.2.1	Data Tags	159
2.2.5.6.2.2	Data Blocks	159
2.2.5.6.2.3	Traffic Symbols	160
2.2.5.6.3	Number of Traffic Elements.....	166
2.2.5.6.4	Information Elements.....	166
2.2.5.6.4.1	Traffic Monitored by TCAS II.....	166
2.2.5.6.4.2	Traffic Application Capability.....	166
2.2.5.6.4.3	Traffic Altitude.....	167
2.2.5.6.4.4	Traffic Vertical Direction	169
2.2.5.6.4.5	Traffic Identification	169
2.2.5.6.4.6	Traffic Ground Speed	169
2.2.5.6.4.7	Traffic Category (Emitter Category)	170
2.2.5.6.4.8	Traffic Emergency Priority Status	170

2.2.5.6.4.9	Traffic Horizontal Velocity Vector.....	170
2.2.5.6.4.10	Traffic Range.....	170
2.2.5.6.5	Operational Elements.....	171
2.2.5.7	Guidance Display.....	171
2.2.5.7.1	DAA Guidance to Maintain DWC.....	171
2.2.5.7.2	DAA Guidance to Regain DWC.....	177
2.2.5.7.3	RA Guidance for Class 2 DAA Systems.....	178
2.2.5.7.4	RA Guidance for Class 3 DAA Systems.....	180
2.2.5.7.4.1	Horizontal RA Guidance.....	181
2.2.5.7.4.2	Vertical RA Guidance.....	185
2.2.5.7.4.3	Visual RA Alerts.....	189
2.2.5.8	DAA Traffic Display Characteristics.....	191
2.2.5.8.1	Display Range.....	191
2.2.5.8.2	Range Rings.....	191
2.2.5.8.3	Altitude Tape.....	192
2.2.5.8.4	Display Orientation.....	192
2.2.5.8.5	Traffic Coasting Indicator.....	192
2.2.5.9	Display Design – Other.....	193
2.2.5.9.1	Traffic Display Symbol Prioritization for Overlay.....	193
2.2.5.9.2	DAA System Health Display Monitoring Function.....	193
2.2.5.9.3	Display of Status Indication.....	193
2.2.5.10	Input and Control – General.....	194
2.2.5.10.1	Display Range.....	194
2.2.5.10.2	Altitude Bands.....	194
2.2.5.10.3	Traffic Altitude Selection.....	194
2.2.5.10.4	Traffic Selection.....	194
2.2.5.10.5	Decluttering.....	194
2.2.5.10.6	Brightness Control.....	195
2.2.5.11	CS Integration.....	195
2.2.5.11.1	Multi-function Display.....	195
2.2.5.12	DAA Aural Alerts.....	196
2.2.5.12.1	DAA Aural Alerts – En Route and Non-Cooperative.....	197
2.2.5.12.2	DAA Aural Alerts – DTA.....	197
2.2.5.12.2.1	Class 2 RA Aural Alerts.....	197
2.2.5.12.2.2	Class 3 RA Aural Alerts.....	198
2.2.5.13	DAA Display Features to Enable Visual-Like Clearances.....	202
2.2.6	Pilot Entry Subsystem.....	203
2.2.7	DAA Pilot-Selected Modes.....	203
2.2.8	High-level DAA Operational Monitoring Function.....	205
2.2.8.1	High-level DAA Operational Monitoring Display.....	206
2.2.8.2	High-level DAA Operational Monitoring Master Caution Warning Light/System.....	206
2.2.9	DAA Subsystem Operational Status.....	206
2.2.9.1	DAA Subsystem Operational Status Reporting.....	208
2.2.9.2	DAA Subsystem Initiation Test.....	208
2.2.9.3	DAA Subsystem Initiation Operational Status Test Report.....	209
2.2.9.4	DAA Subsystem Operational Status Display.....	209
2.2.9.5	DAA Subsystem Lack of Operating Mode Report.....	209
2.2.10	Restart after Power Interruption while in Flight.....	209
2.3	DAA Equipment Environmental Testing – Overview.....	209
2.3.1	Use of Special Purpose Software.....	209
2.3.2	DAA Airborne Equipment Required Performance – Environmental Test Conditions.....	210

2.3.3	DAA Ground Based Equipment Required Performance – Environmental Test Conditions	214
2.4	DAA Equipment Performance Requirements – Standard Conditions Test Procedures	219
2.4.1	General DAA Equipment Characteristics (§2.2.1)	220
2.4.1.1	Latency (§2.2.1.1)	220
2.4.1.2	DAA Surveillance Equipment (§2.2.1.2)	220
2.4.1.3	ATAR (§2.2.1.3)	221
2.4.1.4	Airborne Active Surveillance (§2.2.1.4)	221
2.4.1.5	ADS-B In System (§2.2.1.5)	221
2.4.1.6	TCAS II System (Class 2) (§2.2.1.6)	221
2.4.1.7	ACAS Xu System (Class 3) (2.2.1.7)	221
2.4.1.8	GBSS (Class 6, Class 7, Class 8) (§2.2.1.7)	221
2.4.2	DAA Input/Output (I/O) Requirements (§2.2.2)	222
2.4.2.1	UA DAA Processor Input Data (§2.2.2.1)	222
2.4.2.1.1	Ownship State Data (§2.2.2.1.1)	222
2.4.2.1.1.1	Flight Intent and Active Runway Center Point Data (Optional) (§2.2.2.1.1.1)	223
2.4.2.1.2	ATAR Intruder Data (§2.2.2.1.2)	224
2.4.2.1.3	Active Surveillance Intruder Data (§2.2.2.1.3)	224
2.4.2.1.4	ADS-B In Intruder Data (§2.2.2.1.4)	224
2.4.2.1.4.1	Intruder ADS-B Traffic State Vector Report Data (§2.2.2.1.4.1)	224
2.4.2.1.4.2	ADS-B Intruder Mode Status Data (§2.2.2.1.4.2)	225
2.4.2.1.4.3	TIS-B/ADS-R Service Status Data – Optional (§2.2.2.1.4.3)	225
2.4.2.1.4.4	TCAS II RA Report Data (§2.2.2.1.4.4)	225
2.4.2.1.4.5	Operational Coordination Message Data (§2.2.2.1.4.5)	226
2.4.2.1.5	TCAS II RA and Coordination Data (§2.2.2.1.5)	226
2.4.2.1.6	Surveillance Equipment Operating Status and Health Data (§2.2.2.1.6)	226
2.4.2.1.7	Flight Control System (FCS) (§2.2.2.1.7)	226
2.4.2.1.8	C2 Link (§2.2.2.1.7)	226
2.4.2.1.9	GBSS Data – DAA Equipment Class 6 (§2.2.2.1.9)	226
2.4.2.1.9.1	GBSS Status Data (§2.2.2.1.9.1)	226
2.4.2.1.9.2	GBSS Prioritized Track Data (§2.2.2.1.9.2)	226
2.4.2.2	UA DAA Processor Output Data (§2.2.2.2)	227
2.4.2.2.1	Prioritized Track Data (§2.2.2.2.1)	227
2.4.2.2.1.1	Unique Track ID (Track Number) (§2.2.2.2.1.1)	227
2.4.2.2.1.2	Flight ID (§2.2.2.2.1.2)	227
2.4.2.2.1.3	Time of Applicability (TOA) (§2.2.2.2.1.3)	227
2.4.2.2.1.4	Intruder Alert/Priority (§2.2.2.2.1.4)	227
2.4.2.2.1.5	Source Data Type (§2.2.2.2.1.5)	227
2.4.2.2.1.6	Validated ADS-B (§2.2.2.2.1.6)	228
2.4.2.2.1.7	Air/Ground Status (§2.2.2.2.1.7)	228
2.4.2.2.1.8	Relative Horizontal Position (§2.2.2.2.1.8)	228
2.4.2.2.1.9	Relative Horizontal Position Accuracy (§2.2.2.2.1.9)	228
2.4.2.2.1.10	Bearing Invalid (§2.2.2.2.1.10)	228
2.4.2.2.1.11	Relative Horizontal Velocity (§2.2.2.2.1.11)	228
2.4.2.2.1.12	Relative Horizontal Velocity Accuracy (§2.2.2.2.1.12)	228
2.4.2.2.1.13	Relative Altitude (§2.2.2.2.1.13)	228
2.4.2.2.1.14	Relative Altitude Accuracy (§2.2.2.2.1.14)	228
2.4.2.2.1.15	Altitude Invalid (§2.2.2.2.1.15)	229
2.4.2.2.1.16	Relative Vertical Rate (§2.2.2.2.1.16)	229
2.4.2.2.1.17	Relative Vertical Rate Accuracy (§2.2.2.2.1.17)	229
2.4.2.2.1.18	DAA Alerting Data (§2.2.2.2.1.18)	229
2.4.2.2.1.19	Traffic Track Angle (§2.2.2.2.1.19)	229

2.4.2.2.2	DAA System Modes of Operation and Health Status (§2.2.2.2.2)	230
2.4.2.2.3	TCAS II TA/RA – DAA Equipment Class 2 (§2.2.2.2.3)	230
2.4.2.2.4	Onboard Data Recording Capability (§2.2.2.2.4)	230
2.4.2.2.5	Input/Output Required to Enable Visual-Like Clearances (§2.2.2.2.5)	230
2.4.2.3	CS DAA Processor Input Data (§2.2.2.3)	230
2.4.2.4	CS DAA Processor Output Data (§2.2.2.4)	230
2.4.2.4.1	CS DAA Processor Health Status Data (§2.2.2.4.1)	231
2.4.2.4.2	CS DAA Processor GBSS Prioritized Track Data –DAA Equipment Class 6 (2.2.2.4.2)	231
2.4.2.5	DAA Control Panel Input (§2.2.2.5)	231
2.4.2.6	DAA Control Panel Output (§2.2.2.6)	231
2.4.2.7	CS DAA Traffic Display Input Data (§2.2.2.7)	231
2.4.2.7.1	Ownship Pressure Altitude (§2.2.2.7.1)	231
2.4.2.7.2	Ownship Length and Width Code (§2.2.2.7.2)	232
2.4.3	Active Surveillance, Equipment Class 2 RA Function, and Tracker Performance Requirements	232
2.4.3.1	DAA Active Surveillance and DAA Equipment Class 2 RA Function (§2.2.3.1)	232
2.4.3.1.1	DAA Active Surveillance (§2.2.3.1.1)	232
2.4.3.1.2	DAA with TCAS II RA Functionality (DAA Equipment Class 2) (§2.2.3.1.2)	241
2.4.3.2	DAA Track Processing – Surveillance Data Processing and Tracking (§2.2.3.2)	241
2.4.3.2.1	Track Management (§2.2.3.2.1)	242
2.4.3.2.1.1	Track Initiation (§2.2.3.2.1.1)	242
2.4.3.2.1.2	Track Capacity and Output Prioritization (§2.2.3.2.1.2)	242
2.4.3.2.1.3	ADS-B Report Processing and Track Maintenance (§2.2.3.2.1.3)	243
2.4.3.2.1.4	Track Termination (§2.2.3.2.1.4)	245
2.4.3.2.2	Data Association (§2.2.3.2.2)	245
2.4.3.2.3	Intruder State Estimation (§2.2.3.2.3)	246
2.4.3.2.3.1	Individual Time of Track Extrapolation and Traffic State File Generation (§2.2.3.2.3.1)	247
2.4.4	DAA Alerting and Guidance Processing Requirements (§2.2.4)	247
2.4.4.1	DAA Alerting and Guidance Suppression (§2.2.4.1)	247
2.4.4.1.1	Intruder-Specific Alerting and Guidance Suppression (§2.2.4.1.1)	248
2.4.4.2	Ownship Intent Information (§2.2.4.2)	248
2.4.4.3	DAA Alerting (§2.2.4.3)	249
2.4.4.3.1	DAA Well Clear (DWC) Definition (§2.2.4.3.1)	250
2.4.4.3.2	Hazard Alert Zone (HAZ) Definition (§2.2.4.3.2)	250
2.4.4.3.3	Non-Hazard Zone (NHZ) Definition (§2.2.4.3.3)	250
2.4.4.3.4	Slant Range Equation (§2.2.4.3.4)	250
2.4.4.3.5	Alert Types and Prioritization (§2.2.4.3.5)	250
2.4.4.3.5.1	Preventive Alert (§2.2.4.3.5.1)	250
2.4.4.3.5.2	Corrective Alert (§2.2.4.3.5.2)	250
2.4.4.3.5.3	Warning Alert (§2.2.4.3.5.3)	250
2.4.4.3.5.4	Prioritization of Alert Types (§2.2.4.3.5.4)	250
2.4.4.3.6	Alert Parameters by DWC (§2.2.4.3.6)	251
2.4.4.3.6.1	En Route DWC Alerts (§2.2.4.3.6.1)	251
2.4.4.3.6.2	Terminal DWC Alerts (§2.2.4.3.6.2)	254
2.4.4.3.6.3	Non-Cooperative DWC Alerts (§2.2.4.3.6.3)	256
2.4.4.3.7	Alerting Special Cases (§2.2.4.3.7)	258
2.4.4.3.7.1	Special Cases – ATAR Only (§2.2.4.3.7.1)	258
2.4.4.3.7.2	Special Cases – No Bearing (§2.2.4.3.7.2)	258
2.4.4.3.7.3	Special Cases – No Altitude (§2.2.4.3.7.3)	259
2.4.4.3.7.4	Special Cases – Unvalidated ADS-B (§2.2.4.3.7.4)	261
2.4.4.4	Guidance Processing (§2.2.4.4)	261

2.4.4.4.1	Guidance Processing – En Route and Non-Cooperative (§2.2.4.4.1)	262
2.4.4.4.1.1	DAA Maneuver Guidance to Maintain DWC – En Route and Non-Cooperative	262
2.4.4.4.1.2	DAA Maneuver Guidance to Regain DWC – En Route and Non-Cooperative (§2.2.4.4.1.2)	269
2.4.4.4.2	Guidance Processing in the Terminal Area (§2.2.4.4.2)	270
2.4.4.4.2.1	DAA Maneuver Guidance to Maintain DWC – DTA (§2.2.4.4.2.1)	270
2.4.4.4.2.2	DAA Maneuver Guidance to Regain DWC – DTA (§2.2.4.4.2.2)	275
2.4.4.4.3	Guidance Processing Special Cases (§2.2.4.4.3)	276
2.4.4.4.3.1	Special Cases – Maintain DAA Well Clear (§2.2.4.4.3.1)	276
2.4.4.4.3.2	Special Cases – Regain DAA Well Clear (§2.2.4.4.3.2)	279
2.4.4.5	Collision Avoidance Interoperability with Guidance (§2.2.4.5)	280
2.4.4.5.1	Class 2 RA Guidance (§2.2.4.5.1)	280
2.4.4.5.1.1	Guidance Processing for an MTE with Directive RA and DAA Warning Alert	281
2.4.4.5.2	Vertical DAA Guidance (§2.2.4.5.2)	281
2.4.4.5.2.1	Determining Intruders' Vertical RA Capability (§2.2.4.5.2.1)	281
2.4.4.5.2.2	Determining Intruders' Vertical RA Complement (VRC) Information (§2.2.4.5.2.2)	282
2.4.4.5.2.3	Vertical DAA Guidance Modification (§2.2.4.5.2.3)	284
2.4.4.5.3	Horizontal DAA Guidance (§2.2.4.5.3)	285
2.4.4.6	Class 3 RA Alerting and Guidance (§2.2.4.6)	287
2.4.5	DAA Traffic Display Subsystem Requirements (§2.2.5)	287
2.4.5.1	General DAA Traffic Display (§2.2.5.1)	287
2.4.5.2	Traffic Display Criteria (TDC) (§2.2.5.2)	287
2.4.5.2.1	Default Traffic Display Criteria (§2.2.5.2.1)	290
2.4.5.3	DAA Traffic Display Information (§2.2.5.3)	290
2.4.5.4	Interfaces (§2.2.5.4)	290
2.4.5.4.1	DAA Traffic Display Latency (§2.2.5.4.1)	290
2.4.5.4.2	Time of Applicability of Traffic State Vector Data (§2.2.5.4.2)	291
2.4.5.5	Display Design – General (§2.2.5.5)	291
2.4.5.5.1	Display Characteristics (§2.2.5.5.1)	291
2.4.5.5.2	Dynamics (§2.2.5.5.2)	291
2.4.5.5.3	Labels (§2.2.5.5.3)	292
2.4.5.5.4	Symbols (§2.2.5.5.4)	292
2.4.5.6	Display Elements (§2.2.5.6)	292
2.4.5.6.1	Ownship Symbol (§2.2.5.6.1)	292
2.4.5.6.2	Traffic Information Formats (§2.2.5.6.2)	293
2.4.5.6.2.1	Data Tags (§2.2.5.6.2.1)	293
2.4.5.6.2.2	Data Blocks (§2.2.5.6.2.2)	294
2.4.5.6.2.3	Traffic Symbols (§2.2.5.6.2.3)	294
2.4.5.6.3	Number of Traffic Elements (§2.2.5.6.3)	301
2.4.5.6.4	Information Elements (§2.2.5.6.4)	301
2.4.5.6.4.1	Traffic Monitored by TCAS II (§2.2.5.6.4.1)	302
2.4.5.6.4.2	Traffic Application Capability (§2.2.5.6.4.2)	302
2.4.5.6.4.3	Traffic Altitude (§2.2.5.6.4.3)	302
2.4.5.6.4.4	Traffic Vertical Direction (§2.2.5.6.4.4)	305
2.4.5.6.4.5	Traffic Identification (§2.2.5.6.4.5)	305
2.4.5.6.4.6	Traffic Ground Speed (§2.2.5.6.4.6)	306
2.4.5.6.4.7	Traffic Category (Emitter Category) (§2.2.5.6.4.7)	306
2.4.5.6.4.8	Traffic Emergency Priority Status (§2.2.5.6.4.8)	306
2.4.5.6.4.9	Traffic Horizontal Velocity Vector (§2.2.5.6.4.9)	307
2.4.5.6.4.10	Traffic Range (§2.2.5.6.4.10)	307
2.4.5.6.5	Operational Elements (§2.2.5.6.5)	308

2.4.5.7	Guidance Display (§2.2.5.7)	308
2.4.5.7.1	DAA Guidance to Maintain DWC (§2.2.5.7.1)	308
2.4.5.7.2	DAA Guidance to Regain DWC (§2.2.5.7.2)	310
2.4.5.7.3	TCAS II RA Guidance for TCAS II/DAA Integrated Systems (§2.2.5.7.3)	310
2.4.5.7.4	RA Guidance for Class 3 DAA Systems (§2.2.5.7.4)	311
2.4.5.7.4.1	Horizontal RA Guidance (§2.2.5.7.4.1)	311
2.4.5.7.4.2	Vertical RA Guidance (§2.2.5.7.4.2)	312
2.4.5.7.4.3	Visual RA Alerts	314
2.4.5.8	DAA Traffic Display Characteristics (§2.2.5.8)	314
2.4.5.8.1	Display Range (§2.2.5.8.1)	314
2.4.5.8.2	Range Rings (§2.2.5.8.2)	315
2.4.5.8.3	Altitude Tape (§2.2.5.8.3)	315
2.4.5.8.4	Display Orientation (§2.2.5.8.4)	316
2.4.5.8.5	Traffic Coasting Indicator (§2.2.5.8.5)	316
2.4.5.9	Display Design – Other (§2.2.5.9)	316
2.4.5.9.1	Traffic Display Symbol Prioritization for Overlay (§2.2.5.9.1)	316
2.4.5.9.2	DAA System Health Display Monitoring Function (§2.2.5.9.2)	317
2.4.5.9.3	Display of Status Indication (§2.2.5.9.3)	317
2.4.5.10	Input and Control – General (§2.2.5.10)	318
2.4.5.10.1	Display Range (§2.2.5.10.1)	319
2.4.5.10.2	Altitude Bands (§2.2.5.10.2)	319
2.4.5.10.3	Traffic Altitude Selection (§2.2.5.10.3)	319
2.4.5.10.4	Traffic Selection (§2.2.5.10.4)	319
2.4.5.10.5	Decluttering (§2.2.5.10.5)	320
2.4.5.10.6	Brightness Control (§2.2.5.10.6)	320
2.4.5.11	CS Integration (§2.2.5.11)	321
2.4.5.11.1	Multi-function Display (§2.2.5.11.1)	321
2.4.5.12	DAA Aural Alerts (§2.2.5.12)	322
2.4.5.12.1	DAA Aural Alerts – En Route and Non-Cooperative (§2.2.5.12.1)	323
2.4.5.12.2	DAA Aural Alerts - DTA (§2.2.5.12.2)	324
2.4.5.12.2.1	Class 2 RA Aural Alerts (§2.2.5.12.2.1)	324
2.4.5.12.2.2	Class 3 RA Aural Alerts (§2.2.5.12.2.2)	325
2.4.5.13	DAA Display Features to Enable Visual-Like Clearances (§2.2.5.13)	326
2.4.6	Pilot Entry Subsystem (§2.2.6)	326
2.4.7	DAA Pilot-Selected Modes (§2.2.7)	326
2.4.8	High-level DAA Operational Monitoring Function (§2.2.8)	335
2.4.8.1	High-level DAA Operational Monitoring Display (§2.2.8.1)	337
2.4.8.2	High-level DAA Operational Monitoring Master Caution Warning Light/System (§2.2.8.2)	337
2.4.9	DAA Subsystem Operational Status (§2.2.9)	337
2.4.9.1	DAA Subsystem Operational Status Reporting (§2.2.9.1)	337
2.4.9.2	DAA Subsystem Initiation Test (§2.2.9.2)	338
2.4.9.3	DAA Subsystem Initiation Operational Status Test Report (§2.2.9.3)	339
2.4.9.4	DAA Subsystem Operational Status Display (§2.2.9.4)	339
2.4.9.5	DAA Subsystem Lack of Operating Mode Report (§2.2.9.5)	340
2.4.10	Restart after Power Interruption while in Flight (§2.2.10)	341
2.5	Environmental Qualification for UA DAA Processor Test Procedure – Airborne	342
2.5.1	Verification of Ownship Input Data	342
2.5.2	Verification of ATAR Input Data	342
2.5.3	Verification of Active Surveillance Input Data	342
2.5.4	Verification of ADS-B/ADS-R Input Data	343

2.5.5	Verification of TCAS II Input Data (Class 2).....	343
2.5.6	Verification of All Surveillance Sources	343
2.5.7	Verification of Alerting Prioritization.....	344
2.5.8	Verification of Guidance Processing	344
2.6	Environmental Qualification for CS DAA Processor Test Procedure (§2.3.3 Ground Testing)	344
2.6.1	Verification of Guidance Processing	344
2.6.2	Environmental Qualification for CS DAA Control Panel Test Procedure – Ground	345
2.6.3	Environmental Qualification for DAA Traffic Display Test Procedure – Ground.....	345
2.7	Requirement-to-Test Procedure Application Coverage	345
3	MANUFACTURER CONSIDERATIONS FOR INSTALLED EQUIPMENT.....	363
3.1	Equipment Installation	363
3.1.1	Accessibility.....	363
3.1.2	Aircraft/Control Station Environment.....	363
3.1.3	Display Visibility	363
3.1.4	Dynamic Range.....	363
3.1.5	Failure Protection.....	363
3.1.6	Interference Effects	364
3.1.7	Inadvertent Turnoff	364
3.1.8	UA and CS Power Sources	364
3.2	Installed Equipment Performance Considerations	364
3.3	Installed Equipment Tests	365
3.3.1	Ground Tests.....	365
3.3.1.1	Equipment Function.....	365
3.3.1.2	Interference Effects	365
3.3.2	Flight Evaluation Test Procedures	366
4	AIRCRAFT OPERATIONAL PERFORMANCE CHARACTERISTICS.....	367
5	MEMBERSHIP	369
A	APPENDIX A OPERATIONAL SERVICES AND ENVIRONMENT DESCRIPTION	
	A-1	
A.1	Introduction.....	A-1
A.1.1	OSD References and ICAO Standards And Recommended Practices and Procedures.....	A-2
A.2	Environment.....	A-6
A.2.1	Airspace	A-10
A.2.2	Extended Operations	A-17
A.2.3	Airspace Traffic Density	A-19
A.2.4	Altitudes	A-21
A.2.5	Flight Rules	A-24
A.2.6	Intruders	A-25
A.2.7	Meteorological, Topographical, and Environmental Conditions	A-33
A.2.8	Equipment Environment	A-34
A.3	DAA System Description.....	A-36
A.3.1	Top-level Architecture	A-40
A.4	DAA Actors and Activities	A-57
A.4.1	Actors	A-57

A.4.2	Activity Diagrams	A-57
A.4.3	DAA Activity Descriptions.....	A-60
A.4.4	Activity Diagram for DAA Class 2 and Class 3 Resolution Advisories.....	A-70
A.4.5	Roles and Responsibilities	A-75
A.4.6	Impact on Communications with ATC	A-82
A.5	Nominal Scenarios	A-83
A.5.1	UA and Overtaking IFR Traffic Receiving IFR Separation Services from ATC	A-85
A.5.2	ATC Calls Out Visual Flight Rules (VFR) Traffic to Remote Pilot.....	A-87
A.5.3	Remote Pilot Calls Out VFR Traffic to ATC and Coordinates Maneuver	A-89
A.5.4	UA Climbing IFR through Class G Airspace and Encounters VFR Traffic	A-91
A.5.5	Non-towered Airport in Class G Airspace Involving One-In, One-Out Procedures.....	A-94
A.5.6	Operations in Class A; DAA System Supporting Enhanced Communications with ATC	A-98
A.5.7	Class E VFR Intruder Separated Vertically by 500'.....	A-99
A.5.8	ATC Issues Instructions to IFR Intruder	A-101
A.5.9	ATC Issues Alternate Maneuver Unacceptable to the Remote Pilot	A-104
A.5.10	Intruder Maneuvers after RWC Maneuver Has Begun; Causes Change in RWC Maneuver	A-106
A.5.11	Controller Instructs Intruder.....	A-109
A.5.12	Overtake by VFR/Non-Cooperative with No Alert	A-110
A.5.13	IMC Transition to VMC Operation with EO/IR Surveillance with Short Alert	A-112
A.5.14	UA Departing Class D with VFR Intruder.....	A-115
A.5.15	UA Arrival with GPS Approach in Class D with VFR Intruder.....	A-118
A.5.16	Intruder Visually Separates from UA	A-121
A.5.17	Non-cooperative Intruder Visual Separation from Climbing HALE UA	A-124
A.5.18	Cooperative Intruder Separated from Climbing HALE UA	A-127
A.5.19	Non-cooperative Intruder Causes UA to be Re-vectorred for Second Approach	A-129
A.5.20	UA Linear Infrastructure Survey through Class D Airspace	A-131
A.5.21	DAA Separation on Final.....	A-133
A.5.22	UAS Traffic Monitoring	A-136
A.5.23	Power Line Inspection	A-140
A.6	Off-Nominal Scenarios	A-144
A.6.1	UA Encounters VFR Traffic and Maneuvers Prior to ATC Approval.....	A-144
A.6.2	Collision Avoidance RA (with No Automation).....	A-148
A.6.3	Automated Collision Avoidance RA (Optional Capability)	A-151
A.6.4	Remote Pilot Loses C2 Link with UA	A-153
A.6.5	Automated Collision Avoidance RA during Loss of C2 Link (Optional Capability).....	A-156
A.6.6	Remote Pilot Loses Communications with ATC (Lost ATC Comms, but Not Lost C2 Link)	A-159
A.6.7	Remote Pilot Can't Control the UA and Can't Communicate with ATC or the Intruder	A-163
A.6.8	DAA Equipment Failure	A-165
A.6.9	UA Maneuvers to Regain DWC	A-167
A.6.10	UA Actions On Loss of GB Surveillance Data.....	A-170
A.6.11	VFR Intruder Blunder in Non-towered Airport Traffic Pattern.....	A-172
A.6.12	Aircraft Blunder in Towered Airport Traffic Pattern.....	A-175
A.6.13	DAA Spacing on Instrument Approach with Missed Approach.....	A-178
A.7	Assumptions.....	A-181
A.8	Operational Requirements.....	A-183
A.8.1	Operational Requirements Sources and Organization	A-183
A.8.2	Operational Requirement List.....	A-186

B APPENDIX B ACRONYMS, ABBREVIATIONS AND DEFINITIONS B-1

B.1	Acronyms and Abbreviations.....	B-1
B.2	Definitions.....	B-18
C	APPENDIX C DEVELOPMENT OF DETECT AND AVOID WELL CLEAR.....	C-1
C.1	Background.....	C-1
C.2	Development of DAA Well Clear for En Route.....	C-1
C.2.1	SaRP Well Clear Efforts.....	C-1
C.2.2	FAA White Paper on DAA Well Clear.....	C-3
C.2.3	Implications of the En Route DWC Definition.....	C-4
C.2.4	En Route DWC.....	C-4
C.3	Terminal DWC Development.....	C-5
C.3.1	Fast-Time Simulation of Terminal DWC Variations.....	C-5
C.3.2	TOPS 1a and 1b results.....	C-6
C.3.3	TOPS2 Results.....	C-8
C.3.4	DTA Definition.....	C-12
C.4	Non-Cooperative DWC.....	C-12
C.4.1	Metrics.....	C-13
C.4.2	Encounter Sets.....	C-13
C.4.3	Selection of Four Candidate DWCs.....	C-14
C.4.4	Evaluation with Open-loop and Closed-Loop Fast-Time Simulations.....	C-15
C.4.5	Human-in-the-Loop Simulation Results.....	C-18
C.4.6	Selection of the En Route Non-Cooperative DWC.....	C-19
C.5	Mathematical DWC Definitions.....	C-20
C.6	Conclusion.....	C-21
C.7	References.....	C-22
D	APPENDIX D UAS MANEUVER PERFORMANCE REQUIREMENTS.....	D-1
D.1	Introduction.....	D-1
D.2	Domain/Assumptions.....	D-1
D.2.1	DAA Turn Maneuvers.....	D-1
D.2.2	DAA Vertical Maneuvers.....	D-2
D.2.3	Derivation of Maneuver Initiation Requirements for DAA Vertical Maneuvers.....	D-3
D.3	En Route DAA Well Clear.....	D-7
D.3.1	Assumptions.....	D-7
D.3.2	Application.....	D-8
D.4	Non-Cooperative DAA Well Clear.....	D-14
D.4.1	Assumptions.....	D-14
D.4.2	Application.....	D-15
D.5	Terminal DAA Well Clear.....	D-21
D.5.1	Assumptions.....	D-21
D.5.2	Application.....	D-22
D.6	References.....	D-27
E	APPENDIX E LATENCY ANALYSIS.....	E-1
E.1	Definitions and Terminology.....	E-1
E.2	Data Flow for Latency Calculation.....	E-3
E.2.1	Latency Example for Class 6 DAA System.....	E-3
E.2.2	Latency Example for Class 7 DAA System.....	E-5

E.2.3	Latency Example for Class 8 DAA System	E-6
E.3	Specific Latency Allocations	E-7
E.3.1	Surveillance Sources	E-7
E.3.2	Tracker Latency	E-9
E.3.3	GNSS Latency.....	E-9
E.3.4	Alerting Latency	E-9
E.3.5	C2 Link System Latency.....	E-10
E.3.6	Guidance and Display Latency	E-10
E.3.7	Additional Total Latency Between Tracker and Display.....	E-10
E.3.8	C2 Link System Uplink Latency (Formerly Command-to-Execute Latency)	E-10
E.4	Interoperability Considerations of Class 2 and Class 3 Systems	E-10
E.4.1	Class 2 TCAS II Interoperability Considerations	E-10
E.4.2	Class 3 ACAS Xu Interoperability Considerations.....	E-10

F APPENDIX F EXAMPLE FUNCTIONAL DESCRIPTION FOR AIRBORNE SURVEILLANCE DATA PROCESSOR (ASDP) SUBSYSTEM..... F-1

F.1	Introduction.....	F-1
F.2	Assumptions.....	F-1
F.3	Airborne Track Processing Subsystem	F-2
F.4	Radar Tracker.....	F-3
F.4.1	Track Initiation.....	F-4
F.4.2	Track Establishment.....	F-11
F.4.3	Extended Kalman Filter	F-12
F.5	AST Tracker.....	F-20
F.5.1	Track Measurement/Association.....	F-21
F.5.2	Track Initiation.....	F-21
F.5.3	Track Establishment.....	F-23
F.5.4	Polar Filter Update	F-25
F.5.5	Extended Kalman Filter Update.....	F-28
F.6	Tracker for Sensor Messages with Full State information.....	F-44
F.7	Inter-Sensor Linking	F-44
F.7.1	ADS-B Link Update.....	F-46
F.7.2	Radar Link Update	F-46
F.7.3	AST Link Update	F-47
F.7.4	GBSS Link Update.....	F-47
F.8	Best Sensor Selection.....	F-57
F.9	Track Management	F-60
F.9.1	Common Time Track Extrapolation	F-60
F.10	Adding Bias Effects to Error Covariance.....	F-61
F.10.1	Radar Tracker.....	F-62
F.10.2	AST Tracker – Horizontal.....	F-64
F.10.3	Altitude Tracker	F-64

G APPENDIX G DAA ALERTING LOGIC AND MANEUVER GUIDANCE FOR UAS REFERENCE IMPLEMENTATION.....G-1

G.1	Conceptual Overview of the DAIDALUS Reference Implementation.....	G-1
G.2	High-Level Functional Block Diagram of the DAIDALUS Reference Implementation.....	G-1
G.2.1	Hazard Tables and Alerters	G-3
G.2.2	Detection Logic.....	G-3

G.2.3	Guidance-Processing Logic	G-4
G.2.4	Alerting Logic	G-8
G.3	Data Requirements for DAIDALUS Reference Implementation.....	G-8
G.4	Mathematical Description of the DAIDALUS Reference Implementation	G-12
G.4.1	Nomenclature	G-12
G.4.2	Geometric Assumptions.....	G-13
G.4.3	DWC Logic.....	G-14
G.4.4	Detection Logic.....	G-14
G.4.5	Guidance Processing Logic.....	G-16
G.4.6	Alerting Logic	G-21
G.5	Verification and Validation.....	G-22
G.6	Sensor Uncertainty Mitigation	G-23
G.7	References	G-24
H	APPENDIX H RIGHT OF WAY	H-1
H.1	Introduction.....	H-1
H.2	References.....	H-1
H.2.1	ROW References.....	H-2
H.2.2	References for Modeling & Simulation Analysis	H-2
H.3	Quantified Right of Way.....	H-3
H.3.1	Vertically Converging Encounters.....	H-3
H.3.2	Horizontally Unambiguous Encounters	H-4
H.3.3	Horizontally Ambiguous Encounters.....	H-4
H.3.4	QROW Summary for Ambiguous Encounters.....	H-12
I	APPENDIX I TCAS II GUIDANCE MATERIAL	I-1
I.1	Introduction.....	I-1
I.2	Antenna Installation Guidance.....	I-1
I.3	Antenna Installed Performance.....	I-1
I.4	Interference Limiting	I-2
J	APPENDIX J CLASS 3 RESOLUTION ADVISORY (RA) TYPES AND OUTPUTS.....	J-1
J.1	Mapping Vertical RAs to Control Station Outputs and Displays	J-2
J.2	Mapping Horizontal RAs to Control Station Outputs and Displays	J-15
K	APPENDIX K CLASS 3 DAA SYSTEM-SPECIFIC REQUIREMENT	
	EXPLANATIONS AND EXEMPTIONS	K-1
K.1	Class 3 DAA Equipment (ACAS Xu) Overview	K-6
K.2	Ownship State Data (§2.2.2.1.1).....	K-7
K.3	ATAR Intruder Data (§2.2.2.1.2).....	K-7
K.4	Active Surveillance Intruder Data (§2.2.2.1.3).....	K-7
K.5	ADS-B In Intruder Data (§2.2.2.1.4)	K-8
K.6	Surveillance Equipment Operating Status and Health Data (§2.2.2.1.6).....	K-8
K.7	Prioritized Track Data (§2.2.2.1)	K-8
K.8	Relative Horizontal Position (§2.2.2.1.8).....	K-8
K.9	Relative Horizontal Velocity (§2.2.2.1.11).....	K-8
K.10	Relative Altitude (§2.2.2.1.13).....	K-8

K.11	Relative Vertical Rate (§2.2.2.2.1.16).....	K-9
K.12	DAA System Modes of Operation and Health Status (§2.2.2.2.2)	K-9
K.13	Active Surveillance, Equipment Class 2 RA Function, and Tracker Performance Requirements (§2.2.3).....	K-9
K.13.1	Track Initiation (§2.2.3.2.1.1)	K-9
K.13.2	ADS-B Report Processing and Track Maintenance (§2.2.3.2.1.3)	K-9
K.13.3	Track Termination (§2.2.3.2.1.4).....	K-11
K.13.4	Intruder State Estimation (§2.2.3.2.3).....	K-11
K.14	Warning – En Route DWC (§2.2.4.3.6.1.3).....	K-11
K.15	Guidance Processing	K-13
K.16	Corrective Maneuver Guidance – En Route – Class 3 (§2.2.4.4.1.1.1.3)	K-14
K.17	DAA Maneuver Guidance to Regain DWC – En Route and Non-Cooperative (§2.2.4.4.1.2)	K-15
K.18	Special Cases – Corrective Maneuver Guidance – ATAR Only (§2.2.4.4.3.1.1.1)	K-15
K.19	Special Cases – Regain DAA Well Clear (§2.2.4.4.3.2).....	K-15
K.20	Collision Avoidance Interoperability with Guidance (§2.2.4.5).....	K-15
K.20.1	Class 2 RA Guidance (§2.2.4.5.1).....	K-16
K.20.2	Vertical and Horizontal DAA Guidance (§2.2.4.5.2 and §2.2.4.5.3).....	K-16
K.21	Resolution Advisory Symbols for Class 2 and Class 3 Systems (§2.2.5.6.2.3.2.8).....	K-16
K.22	DAA Guidance to Maintain DWC (§2.2.5.7.2)	K-17
K.23	RA Guidance for Class 3 DAA Systems (§2.2.5.7.4).....	K-19
K.24	Class 3 RA Aural Alerts (§2.2.5.12.2.2).....	K-19
K.25	En Route DWC Alerts (§2.2.4.3.6.1).....	K-19
K.25.1	Exemption Agreement	K-25
K.25.2	Agreed Upon Justification Categories	K-31
K.26	Corrective Maneuver Guidance – En Route and Non-Cooperative (§2.2.4.4.1.1.1)	K-55
K.27	Special Cases – Unvalidated ADS-B Only (§2.2.4.4.3.1.4).....	K-56
K.28	References.....	K-57

L APPENDIX L OPEN- AND CLOSED-LOOP DAA METRICS L-1

L.1	Purpose and Background	L-1
L.1.1	Open-Loop Metrics	L-1
L.1.2	Closed-Loop Metrics.....	L-1
L.2	Hazard Definition and Encounter Characterization for Open-Loop Metrics	L-2
L.2.1	Mathematical Definition of the HAZ.....	L-3
L.2.2	Mathematical Definition of the NHZ.....	L-5
L.2.3	Definition of Hazard and NHZ Parameters.....	L-5
L.3	Definition of Open-Loop Technical Performance Metrics	L-10
L.3.1	Performance Metrics Analyzing Tracks with HAZ Violation (Alert Required).....	L-12
L.3.2	Performance Metrics Analyzing Tracks with MAZ Violation (Alerts Permissible).....	L-16
L.3.3	Performance Metrics Analyzing Tracks in the NHZ (Alerts Undesirable).....	L-18
L.3.4	Additional Open-Loop Considerations	L-20
L.4	Generating an Encounter Timeline for Closed-Loop Metrics.....	L-23
L.5	Closed-Loop Safety Metrics	L-24
L.5.1	Maintain DWC Safety Metrics.....	L-24
L.5.2	Collision Avoidance Safety Metrics	L-28
L.5.3	Operational Suitability Metrics	L-31
L.6	Severity of LoWC (SLoWC) Details	L-34
L.6.1	Fernandez-Guasti's Squirle Mapping	L-35
L.6.2	En Route SLoWC Examples.....	L-36

L.6.3	SLoWC Metric Distribution Against Unmitigated Uncorrelated Encounters.....	L-43
L.6.4	Potential for Over-Assessing Penetration	L-45
L.6.5	Examples of Terminal Area SLoWC	L-47
L.7	References.....	L-49
M	APPENDIX M INTEROPERABILITY OF DAA AND ACAS	M-1
M.1	Purpose and Scope	M-1
M.2	Minimum Aviation SYSTEM Performance Standards for the Interoperability of Airborne Collision Avoidance Systems	M-1
M.3	Collision Avoidance Region	M-1
M.4	Previous Studies Related to TCAS on UAs	M-4
N	APPENDIX N ADS-B POSITION VALIDATION CRITERIA USING TCAS II OR RADAR FOR DAA	N-1
N.1	Background	N-1
N.2	Experience with ADS-B Position Validation Using Active Surveillance Position.....	N-1
N.3	Slant Range within which ADS-B Position Validation is Required	N-1
N.4	Range, Bearing and Altitude Criteria for ADS-B Position Validation Using TCAS II.....	N-5
N.4.1	TCAS II Range Validation Threshold.....	N-5
N.4.2	TCAS II Altitude Validation Threshold.....	N-6
N.4.3	TCAS II Bearing Validation Threshold	N-6
N.5	Range, Bearing and Altitude Criteria for ADS-B Position Validation Using Radar	N-7
N.5.1	Radar Range Validation Threshold.....	N-8
N.5.2	Altitude Validation Threshold.....	N-8
N.5.3	Bearing Validation Threshold	N-9
N.6	Position Validation Interval	N-10
O	APPENDIX O EQUIPMENT CLASS TO REQUIREMENT CROSS –REFERENCES O-1	
P	APPENDIX P TEST VECTORS	P-1
P.1	Summary and Assumptions	P-1
P.1.1	Sources Used for Test Vector Derivation	P-1
P.1.2	Intruder and Ownship Assumptions.....	P-2
P.1.3	Verification of Achievability	P-2
P.2	Description of Individual Test Vector Sets.....	P-2
P.2.1	Head-on.....	P-2
P.2.2	Convergence at Fix	P-3
P.2.3	Convergence with Fast-Moving Jet	P-3
P.2.4	Overtake	P-3
P.2.5	Maneuver	P-4
P.2.6	Designer	P-4
P.2.7	Dynamic	P-4
P.2.8	Peripheral Guidance.....	P-4
P.2.9	Dynamic Terminal	P-4
P.2.10	Terminal Area	P-5
P.3	Track File Description	P-5
P.3.1	Test Vector Information File Format and Contents	P-6

P.3.2	Truth Track Format and Contents	P-8
P.3.3	Format and Contents of Degraded Ownship Track.....	P-8
P.3.4	Format and Contents of Degraded Intruder Track – ADS-B	P-9
P.3.5	Format of Degraded Intruder Track – Mode C and Mode S Active Surveillance	P-10
P.3.6	Format of Degraded Intruder Track – Air-to-Air Radar Surveillance	P-10
P.3.7	Format of Tracker Output	P-11
P.3.8	Encounter Characterization and Required Performance Files	P-12
P.4	Test Vector Model Parameters.....	P-14
P.4.1	Ownship Error Model	P-14
P.4.2	ADS-B Error Model.....	P-15
P.4.3	Air-to-Air Radar Model	P-15
P.4.4	Ground Based Surveillance System Model.....	P-18
P.4.5	Active Surveillance Model.....	P-18
P.5	References	P-19
Q	APPENDIX Q SENSOR, TRACKING, AND ALERTING ASSESSMENT	Q-1
Q.1	Introduction.....	Q-1
Q.2	Analysis Approach Overview	Q-1
Q.3	Encounter Trajectories	Q-3
Q.4	Sensor Model Descriptions	Q-4
Q.4.1	ADS-B.....	Q-4
Q.4.2	ATAR.....	Q-5
Q.4.3	Ground Based Surveillance Derivation.....	Q-6
Q.4.4	Active Surveillance	Q-7
Q.4.5	Ownship Navigation (NAV) Model.....	Q-8
Q.5	Tracking Assessment	Q-8
Q.6	DAIDALUS and SUM Algorithm Implementations	Q-11
Q.6.1	Overview.....	Q-11
Q.6.2	DAIDALUS	Q-11
Q.6.3	SUM.....	Q-13
Q.7	Alerting and Guidance “Wrappers”	Q-14
Q.8	Alerting Assessment	Q-15
R	APPENDIX R AUTOMATION REQUIREMENTS.....	R-1
R.1	Introduction.....	R-1
R.2	Assumptions and Limitations.....	R-2
R.3	Automated RA Processing and Execution Requirements	R-3
R.4	Automated RTC Processing and Execution Requirements.....	R-5
R.5	Automation Control Requirements for RA and RTC.....	R-6
R.6	Automation Display Requirements	R-7
R.7	Terms and Definitions.....	R-8

TABLE OF FIGURES

Figure 1-1	Top-Level DAA System	6
Figure 1-2	Class 1 and 2 DAA Equipment Onboard the Aircraft	8
Figure 1-3	Class 3 DAA Equipment Onboard the Aircraft	9
Figure 1-4	DAA Equipment in the Control Station.....	11
Figure 2-1	Class 1 with Class 5, 6, and 7 Options.....	30
Figure 2-2	Class 2 with Class 5, 6, and 7 Options.....	31
Figure 2-3	Class 3 DAA System Overview with Article Information	32
Figure 2-4	Class 8 with Class 5 Option.....	33
Figure 2-5	DAA Input/Output Data Diagram.....	37
Figure 2-6	DAA Track Processing Objectives	71
Figure 2-7	ADS-B Track Validation State Transition Diagram	78
Figure 2-8	Illustration of Safe Non-Contiguous Guidance.....	116
Figure 2-9	Illustration of Corrective Guidance Information	120
Figure 2-10	Illustration of Peripheral Corrective Guidance Information	120
Figure 2-11	Illustration of Class 3 Peripheral Corrective Guidance Information.	121
Figure 2-12	Illustration of Warning Guidance Information	124
Figure 2-13	Illustration of (a) Horizontal and (b) Vertical Guidance to Regain DWC	127
Figure 2-14	Illustration of Guidance to Maintain and Regain DWC for Class 5 Equipment During Approach/Landing when a Climb is Predicted to Increase Vertical Separation at CPA.....	132
Figure 2-15	Illustration of Guidance to Maintain and Regain DWC for Class 5 Equipment During Approach/Landing when a Climb is Predicted to Decrease Vertical Separation at CPA.....	134
Figure 2-16	Illustration of Guidance during a Directive RA and Warning Alert.....	144
Figure 2-17	Example Means of Determining Intruder VRC Information.....	149
Figure 2-18	Basic Directional Traffic Symbol (Example).....	161
Figure 2-19	Basic Non-directional Traffic Symbol (Example).....	161
Figure 2-20	Directional and Non-directional Designated Traffic Symbols.....	162
Figure 2-21	Directional and Non-directional Maneuver Guidance Traffic Symbols	162
Figure 2-22	Directional and Non-Directional Preventive Alert Symbols	163
Figure 2-23	Directional and Non-Directional Corrective Alert Symbols.....	163
Figure 2-24	Directional and Non-Directional Warning Alert Symbols	164
Figure 2-25	Unvalidated ADS-B Only Corrective Alert	165
Figure 2-26	Directional and Non-Directional RA Symbol for Class 2 and Class 3 Systems.....	165
Figure 2-27	Using Transparent Bands for Positive Maintain-DWC Guidance	175
Figure 2-28	Using Green Bands for Positive Maintain-DWC Guidance	176
Figure 2-29	Using Transparent Bands for Unassessed Trajectories.....	176
Figure 2-30	Using Dashed Grey Bands for Unassessed Trajectories.....	177
Figure 2-31	Vertical and Horizontal Maneuver Guidance to Regain DWC.....	178
Figure 2-32	RA Vertical Guidance: Altitude Tape with Transparent Bands for Positive Guidance	179
Figure 2-33	RA Vertical Guidance: Altitude Tape with Green Bands for Positive Guidance	180
Figure 2-34	Example Depiction of a Horizontal RA - Target Heading = 300 deg and Left Turn issued by CAS Logic. Vertical DAA Guidance depicted within an Altitude Tape	183
Figure 2-35	Example Methods for depicting Non-assessed Trajectories for Class 3 systems using Grey Dashed Bandings (a), or Compass Rose Markings (b).....	184
Figure 2-36	Example Methods for depicting Non-assessed Trajectories during a Class 3 Horizontal RA. The Markings have been modified to indicate that the Avoidance Band extends to -180 deg rather than -97.5deg	185

Figure 2-37	Example Methods for depicting Non-assessed Trajectories during a Class 3 Horizontal RA with a Secondary Intruder generating Horizontal Corrective Guidance	185
Figure 2-38	Example Depiction of a Single-Intruder Vertical RA, with a Target Vertical Rate of +1000 FPM.....	188
Figure 2-39	Example Depiction of a Blended RA, with a Target Heading of 300 deg and a Target Vertical Rate of +1000 FPM	189
Figure A-1	DAA System Environment – En Route, Extended and Transit Ops.....	A-7
Figure A-2	DAA System Environment – En Route, Extended and Transit Ops using GBSS	A-8
Figure A-3	DAA System Environment – Terminal Ops using GBSS.....	A-9
Figure A-4	Airspace Classes (faasafety.gov)	A-10
Figure A-5	ADS-B Out Required Airspace.....	A-15
Figure A-6	Examples of Survey Extended Operation (NASA).....	A-18
Figure A-7	Examples of Extended Infrastructure Inspection Operations (NASA)	A-18
Figure A-8	Sample LOS Analysis Results for GB Radar	A-22
Figure A-9	GB Coverage Volumes	A-23
Figure A-10	Aircraft Behavior Distributions – Correlated Encounter Model.....	A-27
Figure A-11	Aircraft Behavior Distributions – Uncorrelated Encounter Model.....	A-28
Figure A-12	Example of NASA ACES Relative Heading Data.....	A-30
Figure A-13	Example of NASA ACES Horizontal Angle of Threats.....	A-31
Figure A-14	Example of NASA ACES Relative Heading Data – Non-cooperative Intruders	A-32
Figure A-15	Example of NASA ACES Horizontal Angle of Threats – Non-Cooperative Intruders.....	A-33
Figure A-16	Class 1/2/3 with Optional Class 7 Incorporation of GB Surveillance Data by CDP	A-45
Figure A-17	Class 1/2/3 with Optional Class 6 Incorporation of GB Surveillance Data by UDP....	A-48
Figure A-18	Class 1/2/3.....	A-49
Figure A-19	Class 1/2 with Alerting and Guidance in the CDP.....	A-50
Figure A-20	Class 8 – Ground Based Surveillance Only.....	A-51
Figure A-21	GBSS and ATAR Track Data Incorporation	A-53
Figure A-22	Activity Diagram for DAA with ATC Interaction.....	A-59
Figure A-23	Activity Diagram for Class 2 and Class 3 DAA Resolution Advisories.....	A-70
Figure A-24	Scenario A.5.1 – UA and Overtaking IFR AC under ATC Control	A-86
Figure A-25	Scenario A.5.2 – ATC Calls Out VFR Traffic to Remote Pilot.....	A-87
Figure A-26	Scenario A.5.3.a – Remote Pilot Calls Out Co-altitude VFR Traffic to ATC.....	A-90
Figure A-27	Scenario A.5.3.b – Remote Pilot Calls Out Descending VFR Traffic to ATC.....	A-90
Figure A-28	Scenario A.5.4 – UA Climbing through Class G and Encounters VFR Traffic	A-92
Figure A-29	Scenario A.5.5 – Non-towered Class G Airport with One-In, One-Out	A-95
Figure A-30	Scenario A.5.6 – DAA Supporting Enhanced Communications with ATC	A-99
Figure A-31	Scenario A.5.7 – Class E VFR Intruder Separated Vertically by 500'.....	A-100
Figure A-32	Scenario A.5.8 – ATC Issues Instructions to IFR Intruder	A-102
Figure A-33	Scenario A.5.9 – ATC Issues Alternate Maneuver, Pilot “Unable”	A-104
Figure A-34	Scenario A.5.10 – Change in RWC Maneuver due to Intruder Maneuver	A-107
Figure A-35	Scenario A.5.11 – Controller Instructs Intruder.....	A-109
Figure A-36	Scenario A.5.12 – Controller Instructs UAS.....	A-111
Figure A-37	Scenario A.5.13 – Immediate DAA Warning.....	A-113
Figure A-38	Scenario A.5.14 – UA Departs Class D with VFR Intruder	A-116
Figure A-39	Scenario A.5.15 – UA Arrival with GPS Approach in Class D with VFR Intruder...	A-119
Figure A-40	Scenario A.5.16 – Intruder Visually Separates from UA	A-121
Figure A-41	Scenario A.5.17 – Non-coop Separation from Climbing HALE UA	A-125
Figure A-42	Scenario A.5.18 – Cooperative Separation from Climbing HALE UA.....	A-128
Figure A-43	Scenario A.5.19 – Non-Coop Intruder Visual Separation from UA on Approach	A-129

Figure A-44	Scenario A.5.20 – Linear Infrastructure Survey Penetrating Class D.....	A-132
Figure A-45	Scenario A.5.21 – DAA Separation during Instrument Approach.....	A-134
Figure A-46	Scenario A.5.22 – UAS Traffic Monitoring	A-138
Figure A-47	Scenario A.5.23 – Power Line Inspection.....	A-142
Figure A-48	Scenario A.6.1 – UA Maneuvers against VFR Intruder before Contacting ATC.....	A-146
Figure A-49	Scenario A.6.2 – Collision Avoidance RA Scenario	A-149
Figure A-50	Scenario A.6.3 – Automatic Collision Avoidance RA Scenario	A-151
Figure A-51	Scenario A.6.4 – Remote Pilot Loses C2 Link with UA	A-155
Figure A-52	Scenario A.6.5 – Remote Pilot Loses C2 Link with UA with Automated CA RA	A-158
Figure A-53	Scenario A.6.6 – Remote Pilot Loses Communications with ATC.....	A-161
Figure A-54	Scenario A.6.7 – Remote Pilot Loss of Control and Comms	A-164
Figure A-55	Scenario A.6.8 – DAA Equipment Failure	A-166
Figure A-56	Scenario A.6.9 – UA Maneuvers to Regain DWC	A-168
Figure A-57	Scenario A.6.10 – UA Actions on Loss of GB Surveillance Data.....	A-171
Figure A-58	Scenario A.6.11 – AC Blunder in Non-towered Traffic Pattern.....	A-173
Figure A-59	Scenario A.6.12 – AC Blunder in Towered Airport Traffic Pattern.....	A-176
Figure A-60	Scenario A.6.13 – DAA Spacing on IAP with Missed Approach	A-179
Figure C-1	DWC Recommendation from SaRP to SC-228 (not to scale or shape).....	C-3
Figure C-2	DWC Proposal from the FAA White Paper (not to scale or shape)	C-4
Figure C-3	Traffic Pattern Legs (FAA Airplane Flying Handbook).....	C-6
Figure C-4	TOPS2 Simulated Terminal Area Traffic	C-9
Figure C-5	UAS and VFR Speed and Altitude	C-14
Figure C-6	DWC Average Warning Alert	C-16
Figure C-7	C20+C21 Metric with Various Surveillance Volumes	C-16
Figure C-8	LRs Binned by UA Speed.....	C-17
Figure C-9	RRs Binned by UA Speed	C-18
Figure C-10	Minimum, Median, Maximum Alert Look-ahead Time by DWC Definition (HITL).....	C-19
Figure D-1	Vertical Maneuver Profile.....	D-3
Figure D-2	Maneuver Initiation Range for Level-Turn Maneuvers, Altitude < 10000'.....	D-8
Figure D-3	Maneuver Initiation Time to LoWC for Level-Turn Maneuvers, Altitude < 10000'	D-9
Figure D-4	Maneuver Initiation Range for Level-Turn Maneuvers, 10000' ≤ Altitude < 18000'	D-9
Figure D-5	Maneuver Initiation Range for Vertical Maneuvers against Non-Cooperative intruders, Altitude < 10000'	D-10
Figure D-6	Maneuver Initiation Range for Vertical Maneuvers against Cooperative Intruders, Altitude < 10000'	D-11
Figure D-7	Maneuver Initiation Range for Vertical Maneuvers against Cooperative Intruders, 10000' ≤ Altitude < 18000'	D-11
Figure D-8	Maneuver Initiation Range for Horizontal & Vertical Maneuvers against Transit DWC, Non-Cooperative Intruders, Altitude < 10000'	D-12
Figure D-9	Maneuver Initiation Range for Horizontal & Vertical Maneuvers against Transit DWC, Cooperative Intruders, Altitude < 10000'	D-13
Figure D-10	Maneuver Initiation Range for Horizontal & Vertical Maneuvers against Transit DWC, Cooperative Intruders, 10000' ≤ Altitude < 18000'	D-13
Figure D-11	Class A1 Maneuver Initiation Range for Level-Turn Maneuvers, Altitude < 10000'	D-16
Figure D-12	Class A1 Maneuver Initiation Time to LoWC for Level-Turn Maneuvers, Altitude < 10000'	D-17

Figure D-13	Class A2 Maneuver Initiation Range for Level-Turn Maneuvers, Altitude < 10000'	D-17
Figure D-14	Class A2 Maneuver Initiation Time to LoWC for Level-Turn Maneuvers, Altitude < 10000'	D-18
Figure D-15	Class A3 Maneuver Initiation Range for Level-Turn Maneuvers, Altitude < 10000'	D-18
Figure D-16	Class A3 Maneuver Initiation Time to LoWC for Level-Turn Maneuvers, Altitude < 10000'	D-19
Figure D-17	Maneuver Initiation Range for Vertical Maneuvers against Non-Cooperative Intruders, Altitude < 10000'	D-19
Figure D-18	Maneuver Initiation Range for Vertical Maneuvers against Cooperative Intruders, Altitude < 10000'	D-20
Figure D-19	Maneuver Initiation Range for Vertical Maneuvers against Cooperative Intruders, 10000' ≤ Altitude < 18000'	D-20
Figure D-20	Maneuver Initiation Range for Level-Turn Maneuvers against 90-kt DTA Intruder	D-23
Figure D-21	Maneuver Initiation Time to LoWC for Level-Turn Maneuvers against 90-kt DTA Intruder	D-23
Figure D-22	Maneuver Initiation Range for Level-Turn Maneuvers against 140-kt DTA Intruder	D-24
Figure D-23	Maneuver Initiation Time to LoWC for Level-Turn Maneuvers against 140-kt DTA Intruder	D-24
Figure D-24	Maneuver Initiation Range for Vertical Maneuvers against 90-kt DTA Intruder	D-25
Figure D-25	Maneuver Initiation Time to LoWC for Vertical Maneuvers against 90-kt DTA Intruder	D-26
Figure D-26	Maneuver Initiation Range for Vertical Maneuvers against 140-kt DTA Intruder	D-26
Figure D-27	Maneuver Initiation Time to LoWC for Vertical Maneuvers against 140-kt DTA Intruder	D-27
Figure E-1	Notional Representation of Latency Terminology	E-3
Figure E-2	Notional Class 6 DAA System with Simplified Data Flow	E-4
Figure E-3	Notional Class 7 DAA System with Simplified Data Flow	E-5
Figure E-4	Notional Class 8 DAA System with Simplified Data Flow	E-7
Figure F-1	Surveillance Processing Module	F-2
Figure F-2	Radar Tracker	F-4
Figure F-3	Geometry of Ownship/Target in an ECEF Coordinate System	F-6
Figure F-4	AST Tracker	F-20
Figure F-5	Linking Parameters	F-45
Figure F-6	ADS-B Sensor Track Linking Update Algorithm (Sheet 1 of 2)	F-49
Figure F-7	ADS-B Sensor Track Linking Update Algorithm (Sheet 2 of 2)	F-50
Figure F-8	Radar Sensor Track Linking Update Algorithm (Sheet 1 of 2)	F-51
Figure F-9	Radar Sensor Track Linking Update Algorithm (Sheet 2 of 2)	F-52
Figure F-10	AST Sensor Track Linking Update Algorithm (Sheet 1 of 2)	F-53
Figure F-11	AST Sensor Track Linking Update Algorithm (Sheet 2 of 2)	F-54
Figure F-12	GBSS Sensor Track Linking Update Algorithm (Sheet 1 of 2)	F-55
Figure F-13	GBSS Sensor Track Linking Update Algorithm (Sheet 2 of 2)	F-56
Figure F-14	Best Sensor Selection Algorithm Flowchart	F-59
Figure G-1	Notional Functional Block Diagram of DAIDALUS	G-2
Figure G-2	Constant Velocity Aircraft Projection	G-4
Figure G-3	Concept of DAIDALUS Horizontal Maneuver Guidance to Maintain DWC	G-5
Figure G-4	Notional Illustration of Maneuver Guidance Evolution for an Example Encounter	G-7
Figure H-1	Vertically Converging Encounter with the UA Climbing	H-3

Figure H-2	Vertically Converging Encounter with the UA Descending.....	H-4
Figure H-3	Horizontally Unambiguous Encounter with a Sufficiently Large HMD	H-4
Figure H-4	Head-On Geometry with Bearing and Relative Heading Criteria	H-6
Figure H-5	Overtaken Geometry with Bearing Criteria.....	H-7
Figure H-6	Overtaking Geometry with Bearing and Relative Heading Criteria	H-8
Figure H-7	Left Oblique Overtaking Geometry with Bearing Criteria	H-9
Figure H-8	Right Oblique Overtaking Geometry with Bearing Criteria.....	H-10
Figure H-9	Converging from Left	H-11
Figure H-10	Converging from Right.....	H-12
Figure I-1	Interrogation Range Reduction as a Function of Attenuation.....	I-2
Figure K-1	Elements of ACAS Xu RAs.....	K-12
Figure K-2	Timing of the ACAS Xu RA compared to other DAA Alerting and Guidance Events	K-13
Figure K-3	Visualization of Surveillance Noise Impacts on Non-Maneuvering Encounters, with Respect to Altitude Separation (ADS-B Surveillance).....	K-34
Figure K-4	Visualization of Surveillance Noise Impacts on Non-Maneuvering Encounters, with Respect to Horizontal Offset (ADS-B Surveillance)	K-35
Figure K-5	Visualization of Surveillance Noise Impacts on Non-Maneuvering Encounters, with Respect to Horizontal Offset (Active Surveillance)	K-36
Figure K-6	Encounter Visualization Example: Projected CPA versus Range along the Relative Velocity Vector.....	K-37
Figure K-7	Encounter Example in Ground-Fixed Frame	K-38
Figure K-8	Encounter Example.....	K-39
Figure K-9	Encounter Visualization Example of Head-On Encounters.....	K-40
Figure K-10	Justification Category B Example: Late Alert Failure DAA Test Vector LL132 (ADS-B Surveillance).....	K-41
Figure K-11	Justification Category B Example: Late Alert Failure DAA Test Vector P8 (Mode S)	K-42
Figure K-12	Justification Category B Example: Early Alert Failure DAA Test Vector LL145 (Mode S Surveillance)	K-43
Figure K-13	Justification Category B Example: Early Alert Failure DAA Test Vector LL168 (Mode S Surveillance)	K-44
Figure K-14	Justification Category B Example: Must Not Alert Failure DAA Test Vector H28 (ADS-B Surveillance).....	K-45
Figure K-15	Justification Category B Example: Must Not Alert Failure DAA Test Vector LL174 (Mode S Surveillance)	K-46
Figure K-16	Justification Category B Example: Must Alert Failure DAA Test Vector LL121 (ADS-B Surveillance).....	K-47
Figure K-17	Justification Category B Example: Must Alert Failure DAA Test Vector LL171 (ADS-B Surveillance).....	K-48
Figure L-1	Summary of Closed-Loop TPMs	L-2
Figure L-2	Zones Used in Alert Evaluation.....	L-3
Figure L-3	Horizontal Expansion of Hazard and NHZ for a Head-on Encounter	L-7
Figure L-4	Alert Scoring Process.....	L-12
Figure L-5	Sample Horizontal Plot of Prolonged Proximity Encounter.....	L-21
Figure L-6	Notional Performance Visualization (Not Real Data)	L-22
Figure L-7	Deviation Diagram.....	L-32
Figure L-8	Horizontal and Vertical Course Deviations	L-33
Figure L-9	Fernandez-Guasti's Squircle Mapping	L-36
Figure L-10	SLoWC Propagation for Co-altitude Head-on Intruders with different HMDs.....	L-37

Figure L-11	SLoWC Propagation for Head-on Intruders with 100 ft Vertical Offset with different HMDs.....	L-38
Figure L-12	SLoWC Propagation for Vertically Converging and Altitude-crossing Head-on Intruders with different HMDs	L-39
Figure L-13	SLoWC Propagation for Vertically Converging Head-on Intruders with Altitude-crossing after CPA.....	L-40
Figure L-14	SLoWC Propagation for Turning Away against Head-on Intruders with different HMDs	L-41
Figure L-15	SLoWC Propagation for Co-altitude Crossing Intruders	L-42
Figure L-16	SLoWC Propagation for Co-altitude Overtaking Geometries	L-43
Figure L-17	SLoWC Distribution for 15,000 Unmitigated Encounters with LoWC.....	L-44
Figure L-18	Comparison of Unmitigated and Mitigated SLoWC Distribution	L-45
Figure L-19	SLoWC Assessed Against Turning Geometry with Momentary LoWC.....	L-46
Figure L-20	SLoWC vs. Horizontal CPA for 100K Unmitigated MALE Correlated Encounters	L-47
Figure L-21	TA_SLoWC for a Co-altitude Arrival	L-48
Figure L-22	TA_SLoWC for Overlapping Arrival and Departure	L-48
Figure L-23	TA_SLoWC for Turning Convergence	L-49
Figure Q-1	Analysis Process Flow Chart	Q-2
Figure Q-2	Horizontal Position Tracking Error as a Function of Horizontal Range.....	Q-9
Figure Q-3	Relative Altitude Tracking Error as a Function of Horizontal Range	Q-9
Figure Q-4	Relative Velocity Tracking Error as a Function of Horizontal Range.....	Q-10
Figure Q-5	Vertical Rate Tracking Error as a Function of Horizontal Range.....	Q-10
Figure Q-6	Alerting Metrics Definitions	Q-15

TABLE OF TABLES

Table 1-1	DAA Data Flows, Interfaces and Associated Requirement Locations	5
Table 2-1	DAA Class Table and DAA Article Labels	26
Table 2-2	Radar Classes	28
Table 2-3	Allowable Latency Contributions for DAA Subsystems	34
Table 2-4	DAA Ownship State Data Input	40
Table 2-5	ATAR Intruder Data Input.....	44
Table 2-6	Traffic Data Input from Onboard Active Surveillance	46
Table 2-7	DAA Traffic State Data Input from ADS-B	48
Table 2-8	DAA Intruder Mode Status Data Input from ADS-B	50
Table 2-9	RA Report Data Input from ADS-B	51
Table 2-10	Operational Coordination Message Data Content	52
Table 2-11	TCAS Coordination Data if RA is Issued against Ownship	53
Table 2-12	Surveillance Equipment Health Data.....	54
Table 2-13	GBSS Prioritized Track Data.....	56
Table 2-14	UA DAA Prioritized Track Report Data.....	58
Table 2-15	Acceptable Minimum Combinations of Velocity Uncertainty and Ground Speed to Support Traffic Directionality	62
Table 2-16	Data Received by the CS DAA Processor	64
Table 2-17	CS DAA Processor Output Data.....	64
Table 2-18	DAA Traffic Display Input.....	66
Table 2-19	RTCA DO-185B Requirements to Support DAA Active Surveillance	69
Table 2-20	Summary of Acceptable Means for Velocity Qualification.....	74
Table 2-21	UA DAA Prioritized Track State Output Data	84
Table 2-22	Single-Source Integrated Track Performance	85
Table 2-23	DWC Applicability	89
Table 2-24	Parameters for En Route DWC Alerting Requirements	98
Table 2-25	Parameters for Terminal DWC Alerting Requirements.....	103
Table 2-26	Parameters for Non-Cooperative DWC Alerting Requirements.....	106
Table 2-27	Types of Corrective TCAS II RAs.....	141
Table 2-28	Types of Preventive TCAS II RAs	142
Table 2-29	DAA Vertical Interoperability and Coordination Summary	145
Table 2-30	Written Message per RA Type	190
Table 2-31	Aural Annunciations per RA Type	198
Table 2-32	Aural Annunciations per Vertical RA Type	200
Table 2-33	Aural Annunciations per Horizontal RA Type	201
Table 2-34	Aural Annunciations per Blended RA Type	202
Table 2-35	Minimum DAA Operational Modes – Equipment Class 1/8.....	203
Table 2-36	Minimum DAA Operational Modes – Equipment Class 2	203
Table 2-37	DAA Subsystems and Operating Statuses	207
Table 2-38	DAA Airborne Equipment Environmental Test Requirements	211
Table 2-39	CS Equipment Environmental Test Conditions and Performance Matrix	215
Table 2-40	Cross-Reference of DAA Surveillance Reqs to RTCA DO-185B Test Procedures.....	233
Table 2-41	Cross-Reference of DAA Surveillance Reqs to RTCA DO-300A Test Procedures.....	238
Table 2-42	List of Sensor Combinations.....	246
Table 2-43	Requirement-to-Test Matrix	345
Table A-1	References.....	A-2
Table A-2	Differences between ICAO SARPs and 14 CFR	A-5
Table A-3	Airspace Class And Operational Scope	A-11
Table A-4	Intruder Equipage Assumptions.....	A-16
Table A-5	Airspace Traffic Density Based on 2011 JFK Data.....	A-20

Table A-6	DAA Class Table and DAA Article Labels.....	A-42
Table A-7	Mapping of Classes to Operational Usage.....	A-44
Table A-8	Descriptions of Activities Outlined in Figure A-22.....	A-60
Table A-9	Descriptions of Activities Outlined in Figure A-23.....	A-71
Table A-10	Phraseology Meanings.....	A-83
Table A-11	Nominal Scenario Breakdown.....	A-84
Table A-12	Scenario Operational Type.....	A-85
Table A-13	Scenario A.5.1 – Timeline for IFR AC under ATC Control.....	A-86
Table A-14	Scenario A.5.2 – Timeline for ATC Calls out VFR Traffic to Remote Pilot.....	A-88
Table A-15	Scenario A.5.3.a/b – Timeline for Remote Pilot Calls Out VFR Traffic to ATC.....	A-91
Table A-16	Scenario A.5.4 – Timeline for UA Climbing through Class G with VFR Traffic.....	A-93
Table A-17	Scenario A.5.5 – Timeline for Non-towered Class G Airport w/ One-In, One-Out.....	A-97
Table A-18	Scenario A.5.6 – Timeline for DAA Enhanced Communications with ATC.....	A-99
Table A-19	Scenario A.5.7 – Timeline for Class E VFR Intruder Separated Vertically by 500'...	A-101
Table A-20	Scenario A.5.8 – Timeline for ATC Issues Instructions to IFR Intruder.....	A-103
Table A-21	Scenario A.5.9 – Timeline for ATC Issues Alternate Maneuver, Pilot “Unable”.....	A-105
Table A-22	Scenario A.5.10 – Timeline for Change in RWC Maneuver.....	A-108
Table A-23	Scenario A.5.11 – Timeline for Controller Instructs Intruder.....	A-110
Table A-24	Scenario A.5.12 – Timeline for Controller Instructs UAS.....	A-112
Table A-25	Scenario A.5.13 – Timeline for Immediate DAA Warning.....	A-114
Table A-26	Scenario A.5.14 – Timeline for UA Departs Class D with VFR Intruder.....	A-116
Table A-27	Scenario A.5.15 – Timeline for UA GPS Approach in Class D with VFR Intruder ..	A-120
Table A-28	Scenario A.5.16 – Timeline for Intruder Visually Separates from UA.....	A-122
Table A-29	Scenario A.5.17 – Timeline for NC Separation from HALE UA.....	A-126
Table A-30	Scenario A.5.18 – Timeline for Cooperative Separation from HALE UA.....	A-128
Table A-31	Scenario A.5.19 – Timeline for NC Intruder Visual Separation on Approach.....	A-130
Table A-32	Scenario A.5.20 – Timeline for Linear Infrastructure Survey Penetrating Class D ...	A-133
Table A-33	Scenario A.5.21 – Timeline for UA DAA Separation on Instrument Approach.....	A-135
Table A-34	Scenario A.5.22 – Timeline for UAS Traffic Monitoring.....	A-139
Table A-35	Scenario A.5.23 – Timeline for Power Line Inspection.....	A-143
Table A-36	Off-Nominal Scenario Breakdown.....	A-144
Table A-37	Scenario A.6.1 – Timeline for UA Maneuvers Prior to ATC Approval.....	A-147
Table A-38	Scenario A.6.2 – Timeline for Collision Avoidance RA Scenario.....	A-150
Table A-39	Scenario A.6.3 – Timeline for Automatic Collision Avoidance RA Scenario.....	A-152
Table A-40	Scenario A.6.4 – Timeline for Remote Pilot Loses C2 Link with UA.....	A-155
Table A-41	Scenario A.6.5 – Timeline for Automated CA RA during Loss of C2 Link.....	A-159
Table A-42	Scenario A.6.6 – Timeline for Remote Pilot Loses Communications with ATC.....	A-162
Table A-43	Scenario A.6.7 – Timeline for Remote Pilot Loss of Control and Comms.....	A-164
Table A-44	Scenario A.6.8 – Timeline for DAA Equipment Failure.....	A-167
Table A-45	Scenario A.6.9 – Timeline for UA Maneuvers to Regain DWC.....	A-169
Table A-46	Scenario A.6.10 – UA Actions on Loss of GB Surveillance Data.....	A-171
Table A-47	Scenario A.6.11 – Timeline for AC Blunder in Non-towered Traffic Pattern.....	A-174
Table A-48	Scenario A.6.12 – Timeline for AC Blunder in Towered Traffic Pattern.....	A-177
Table A-49	Scenario A.6.13 – Timeline for DAA Spacing on IAP with Missed Approach.....	A-180
Table C-1	TOPS 1b Metrics by DWC Candidate.....	C-8
Table C-2	Metrics Considered for the En Route Non-cooperative DWC.....	C-13
Table C-3	Four Candidate DWC Definitions and En Route Cooperative Definition.....	C-15
Table C-4	UA Speed Bins.....	C-17
Table C-5	Proportion of LoWC by DWC Definition (HITL).....	C-19
Table D-1	Aircraft Speed Bounds per Altitude and Turn Capability.....	D-7
Table D-2	UAS Performance per Air-to-Air Radar Class.....	D-15

Table D-3	Intruder RCS/Airspeed Bins	D-15
Table D-4	Aircraft Speed Bounds per Turn Capability	D-22
Table E-1	Allowable Latency Contributions for DAA Subsystems	E-2
Table E-2	Sample GBSS Latency Calculations for a Class 6 DAA System	E-4
Table E-3	Sample GBSS Latency Calculations for Class 7 DAA System	E-6
Table E-4	Sample GBSS Latency Calculations for a Class 8 DAA System	E-7
Table E-5	Latency Requirements from MOPS of Sensors Used in DAA	E-8
Table G-1	Ownship Input State.....	G-8
Table G-2	Traffic Input State.....	G-9
Table G-3	Ownship Performance Limits	G-9
Table G-4	Output Data Types	G-10
Table G-5	Output Requirements	G-10
Table G-6	Hazard Table Parameters	G-11
Table G-7	Default Hazard Tables in DAIDALUS.....	G-12
Table G-8	Configuration Parameters	G-12
Table G-9	Nomenclature Unique to This Appendix	G-13
Table G-10	Aircraft Uncertainty Information Data Requirements	G-23
Table G-11	Sensor Uncertainty Mitigation Scaling Factors	G-24
Table H-1	Summary of QROW for Ambiguous Geometries.....	H-12
Table I-1	90% Detection Range as a Function of Interference Limiting.....	I-3
Table I-2	Adjusted 90% Detection Range as a Function of Interference Limiting	I-4
Table I-3	Supported Alert Times at Maximum IL.....	I-5
Table I-4	Supported Alert Times in High IL Conditions.....	I-5
Table J-1	Mapping Vertical RAs to Control Station Outputs and Displays	J-2
Table J-2	Combined Control Label 270 Bit Mapping	J-9
Table J-3	Vertical Control Label 270 Bit Mapping	J-9
Table J-4	Up Advisory Label 270 Bit Mapping	J-10
Table J-5	Down Advisory Label 270 Bit Mapping	J-10
Table J-6	AVRA Subfield Vertical Strength Bit Mapping	J-12
Table J-7	RA Message Format Bit Mapping	J-12
Table J-8	Mapping Horizontal RAs to Control Station Outputs and Displays	J-15
Table J-9	Combined Control Label 271 Bit Mapping	J-17
Table J-10	AHRA Subfield Target Track Angle Bit Mapping	J-19
Table J-11	RA Message Format Bit Mapping	J-20
Table K-1	Mapping of DO-365 Requirements to Appendix K – Explanations.....	K-2
Table K-2	Mapping of DO-365 Requirements to Appendix K – Exemptions.....	K-5
Table K-3	Converting Class 3 Vertical Rate Output to Altitude	K-18
Table K-4	ACAS Xu En Route DWC Alerting Report Card – Preventive.....	K-20
Table K-5	ACAS Xu En Route DWC Alerting Report Card – Corrective.....	K-21
Table K-6	ACAS Xu Special Case Alerting Report Card – Radar-Only.....	K-22
Table K-7	ACAS Xu Special Case Alerting Report Card – No Bearing.....	K-22
Table K-8	ACAS Xu Special Case Alerting Report Card – No Altitude.....	K-23
Table K-9	ACAS Xu Special Case Alerting Report Card – Unvalidated ADS-B	K-24
Table K-10	Late Alert Exemptions	K-26
Table K-11	Early Alert Exemptions	K-27
Table K-12	Must Not Alert Exemptions.....	K-28
Table K-13	Must Alert Exemptions.....	K-29
Table K-14	Radar Only Special Case Alerting Exemptions	K-29
Table K-15	No Bearing Special Case Alerting Exemptions	K-30
Table K-16	No Altitude Special Case Alerting Exemptions.....	K-31
Table K-17	ADS-B Noise Parameters	K-50

Table K-18	Mode S Noise Parameters.....	K-50
Table K-19	Active Mode C Noise Parameters.....	K-50
Table K-20	Air-to-Air Radar Noise Parameters	K-51
Table K-21	Passing Cases in Report Card, but >10% Surveillance Failures – Converging.....	K-51
Table K-22	Passing Cases in Report Card, but >10% Surveillance Failures – Head-on.....	K-52
Table K-23	Passing Cases in Report Card, but >10% Surveillance Failures – Maneuvering.....	K-52
Table K-24	Passing Cases in Report Card, but >10% Surveillance Failures – Overtake	K-53
Table K-25	Passing Cases in Report Card, but >10% Surveillance Failures – Peripheral	K-53
Table K-26	Passing Cases in Report Card, but >10% Surveillance Failures – Dynamic	K-54
Table K-27	ACAS Xu En Route Corrective Maneuver Report Card	K-56
Table L-1	Parameters for Calculating the Size of HAZ and NHZ – En Route.....	L-5
Table L-2	Parameters for Calculating the Size of HAZ and NHZ – DAA Terminal Area	L-8
Table L-3	Parameters for Calculating the Size of HAZ and NHZ – Non-Cooperative.....	L-9
Table L-4	Possible Reference Intruders.....	L-23
Table N-1	Position Validation Range	N-3
Table N-2	Surveillance Range for Different Levels of Interference Limiting(NM).....	N-4
Table N-3	Range Validation Error Budget for ADS-B Position Using TCAS II or Radar.....	N-6
Table N-4	Bearing Error for a 0.1 NM 95% Position Error for Ownship and Traffic	N-7
Table N-5	Altitude Validation Error Budget for ADS-B Position Using Radar.....	N-9
Table N-6	Bearing Validation Error Budget for ADS-B Position Using Radar	N-9
Table N-7	Distance Closed During Interval between Revalidations	N-10
Table N-8	Hybrid Surveillance Validation Interval.....	N-11
Table O-1	Article Matrix for Partial Standard Compliance	O-2
Table P-1	Categories and Numbers of DAA Test Vectors.....	P-1
Table P-2	Contents of Test Vector Information File.....	P-6
Table P-3	Data Fields in Test Vector Truth Tracks.....	P-8
Table P-4	Data Fields in Ownship Test Vector Tracks	P-9
Table P-5	Data Fields in ADS-B Test Vector Tracks	P-9
Table P-6	Data Fields in Mode C and Mode S Test Vector Tracks	P-10
Table P-7	Data Fields in Radar Test Vector Tracks.....	P-10
Table P-8	Data Fields in Tracker Output Test Vector Tracks.....	P-11
Table P-9	Notional Contents of an Encounter Characterization File	P-12
Table P-10	Key for Interpreting the HAZ and the NHZ Columns in Table P-9	P-14
Table P-11	Ownship Error Model Parameters	P-14
Table P-12	Altitude Layer B Values	P-15
Table P-13	ADS-B Model Parameters	P-15
Table P-14	ATAR Model Parameters	P-16
Table P-15	ATAR FOR Model Parameters.....	P-17
Table P-16	GBSS Model.....	P-18
Table P-17	Active Surveillance Model Parameters.....	P-19
Table Q-1	ADS-B Model Parameters Pt 1	Q-4
Table Q-2	ADS-B Model Parameters Pt 2.....	Q-5
Table Q-3	ATAR Model Parameters Pt 1	Q-5
Table Q-4	ATAR Model Parameters Pt 2.....	Q-6
Table Q-5	Active Surveillance Model Parameters Pt 1	Q-7
Table Q-6	Active Surveillance Model Parameters Pt 2	Q-7
Table Q-7	Ownship Navigation (NAV) Model Parameters.....	Q-8
Table Q-8	Sensor Uncertainty Mitigation Scaling Factors	Q-14
Table Q-9	Alerting Metric Results Given Representative DAA Open-Loop System.....	Q-16
Table Q-10	Alerting Jitter Results Given Representative DAA Open-Loop System	Q-16

This Page Intentionally Left Blank

1 PURPOSE AND SCOPE

1.1 INTRODUCTION

This document contains Minimum Operational Performance Standards (MOPS) for Detect and Avoid (DAA) systems used in Unmanned Aircraft Systems (UAS) transiting through Class B, C, D, E, and G airspace and performing extended operations higher than 400' Above Ground Level (AGL) in Class D, E (up to Flight Level (FL) 180), and G airspace. It includes equipment to enable UAS operations in Terminal Areas during approach and departure in Class C, D, E and G airspace and off-airport locations. It does not apply to small UAS (sUAS) operating in low-level environments (below 400') or other segmented areas. Likewise, it does not apply to operations in the Visual Flight Rules (VFR) traffic pattern of an airport or to surface operations. For a complete description of operations and environments, refer to Appendix A. These standards specify DAA system characteristics that should be useful for designers, manufacturers, installers and users of the equipment.

These MOPS focus on Unmanned Aircraft (UA) to enable safe flight in airspace normally frequented by commercial transport and general aviation aircraft. Aircraft operations in all classes of airspace vary, from operation under Instrument Flight Rules (IFR) in Reduced Vertical Separation Minimum (RVSM) airspace to VFR operations with minimal onboard equipment. The UA may need to carry relatively large and high-power sensor systems, depending on the class of sensors required for the speed of the UA. Alternatively, these MOPS also allow a class of equipment where all sensors are on the ground, which enables operations of UAS with reduced payload capabilities (see Subparagraph 2.1.10.1 for descriptions of all equipment classes). This version of the document adds a class of non-cooperative sensor that does allow some weight and power savings. Future revisions of this document may address other operational scenarios and sensors better suited to smaller UAS needs, pending further negotiation with airspace regulators.

During the original development of this document, members of the committee expressed concern about equipment without an explicit collision avoidance function providing an appropriate level of safety for the in-scope operations. Concerns were expressed regarding the safety of the system when compared to manned see-and-avoid capability, the usability of the well clear definition developed herein, and the impacts of replacing "collision avoidance" with a "regain well clear" concept. Concerns were also expressed that a formal safety analysis was not available to guide MOPS development, and that a top-level performance requirement was not established to provide a means for requirement traceability to lower-level requirements. To this end, the Federal Aviation Administration (FAA) commissioned an internal Safety Risk Management Panel during development of RTCA Document 365 (DO-365) to analyze and identify the conditions under which Equipment Class 1 or Equipment Class 2 is sufficient for the intended operations in the National Airspace System (NAS) (see Subparagraph 2.1.10.1 for a description of equipment classes). The FAA is using this safety analysis to determine required equipment and any necessary operational mitigations. Going forward, the committee expects the FAA to update the safety analysis based on changes to DAA systems or the NAS.

Compliance with these standards is recommended as one means of assuring that the equipment will perform its intended function(s) satisfactorily under the conditions specified herein. Any regulatory application of this document is the sole responsibility of appropriate governmental agencies.