

RTCA, Inc.
1150 18th Street NW, Suite 910
Washington, DC 20036
USA

**Minimum Aviation System Performance
Standards for C2 Link Systems
Supporting Operations of Unmanned Aircraft Systems
in U.S. Airspace**

RTCA DO-377A
September 16, 2021

Prepared by: SC-228
© 2021 RTCA, Inc.

Copies of this document may be obtained from

RTCA, Inc.

Telephone: 202-833-9339

Facsimile: 202-833-9434

Internet: www.rtca.org

Please visit the RTCA Online Store for document pricing and ordering information.

FOREWORD

This document was prepared by Special Committee 228 (SC-228) Unmanned Aircraft Systems and approved by the RTCA Program Management Committee (PMC) on September 16, 2021.

RTCA, Incorporated is a not-for-profit corporation formed to advance the art and science of aviation and aviation electronic systems for the benefit of the public. The organization develops consensus-based recommendations on contemporary aviation issues. RTCA's objectives include, but are not limited to:

- Coalescing aviation system user and provider technical requirements in a manner that helps government and industry meet their mutual objectives and responsibilities;
- Analyzing and recommending solutions to the system technical issues that aviation faces as it continues to pursue increased safety, system capacity and efficiency;
- Developing consensus on the application of pertinent technology to fulfill user and provider requirements, including development of Minimum Operational Performance Standards (MOPS) for equipment and electronic systems that support aviation; and
- Assisting in developing the appropriate technical material upon which positions for the International Civil Aviation Organization (ICAO) and the International Telecommunication Union (ITU) and other appropriate international organizations can be based.

The recommendations of RTCA are often used as the basis for government and private sector decisions as well as the foundation for many Federal Aviation Administration Technical Standard Orders (TSOs).

Since RTCA is not an official agency of the United States Government, its recommendations may not be regarded as statements of official government policy unless so enunciated by the United States Government organization or agency having statutory jurisdiction over any matters to which the recommendations relate.

DISCLAIMER

This publication is based on material submitted by various participants during the SC approval process. Neither the SC nor RTCA has made any determination whether these materials could be subject to valid claims of patent, copyright or other proprietary rights by third parties, and no representation or warranty, expressed or implied is made in this regard. Any use of or reliance on this document shall constitute an acceptance thereof "as is" and be subject to this disclaimer.

This Page Intentionally Left Blank

TABLE OF CONTENTS

1	PURPOSE AND SCOPE.....	1
1.1	Introduction and Purpose of Document	1
1.1.1	Introduction.....	1
1.1.2	Purpose.....	1
1.2	Scope of the Document.....	2
1.3	Structure of the Document.....	3
1.4	Relationship to International Civil Aviation Organization (ICAO) Documents.....	5
1.5	References.....	6
1.6	Aircraft Equipment Information Vulnerabilities.....	6
2	APPROACH AND METHODOLOGY	9
2.1	Document Development Process	9
2.2	Methodology.....	9
2.2.1	Operational Services and Environment Definition (OSED).....	9
2.2.2	Operational Safety Assessment (OSA).....	10
2.2.3	Operational Security Analysis	10
2.2.4	Operational Performance Assessment (OPA).....	10
2.3	Key Terms.....	11
2.3.1	Use of Requirements and Recommendations and Key Terms	11
2.3.2	Assumptions.....	11
2.3.3	Mitigation Means	11
2.3.4	Requirements	12
2.3.5	Recommendations.....	12
2.4	References.....	13
3	SYSTEM REQUIREMENTS	15
3.1	Requirements and Traceability	15
3.1.1	Requirements Overview	15
3.1.2	Traceability	16
3.2	Definitions and Terminology.....	16
3.2.1	C2 Link System Definition, Key Functions and Performance Context.....	16
3.2.2	C2 Link System TLP in the Context of the C2 Link Specification and QoSR.....	18
3.2.3	Definition of Key Terms.....	19
3.3	Assumptions	21
3.3.1	Assumptions from the OSED.....	21
3.3.1.1	Operational Assumptions from the OSED.....	21
3.3.1.2	Technical Assumptions from the OSED.....	23
3.3.2	Assumptions from the OSA.....	24
3.3.2.1	Scope Assumptions from the OSA	24
3.3.2.2	General Assumptions from the OSA	26
3.3.2.3	Automatic Takeoff and Landing System Assumptions from the OSA.....	27
3.4	Operational Requirements	28
3.5	Functional Requirements	29
3.5.1	C2 Link System Functional Requirements	29
3.5.2	Interworking Requirements to Support FR-2.1	31
3.5.3	Interworking Requirements to Support FR-2.2	35
3.5.4	Interworking Requirements to Support FR-2.3	38
3.6	Operational Hazards and Safety Objectives.....	40

3.6.1	OH, and SO for FR-1.....	42
3.6.2	OH, and SO for FR-2.....	51
3.6.3	OH and SO for FR-3.....	55
3.7	Performance Requirements.....	57
3.7.1	Surface, Non-Towered.....	59
3.7.2	Surface, Towered.....	60
3.7.3	Departure and Arrival, Non-Towered.....	61
3.7.4	Departure and Arrival, Towered.....	62
3.7.5	Transit/Extended Operations, Class A Airspace.....	63
3.7.6	Transit/Extended Operations, Class B, C, and E Airspace.....	64
3.7.7	Transit/Extended Operations, Class G Airspace.....	65
3.7.8	Transit/Extended Operations, Class Oceanic A Airspace.....	66
3.8	Security Requirements.....	67
3.9	UAS Level Recommendations.....	70
4	REQUIREMENTS VERIFICATION FOR C2 LINK SYSTEMS.....	73
4.1	Assumptions.....	73
4.2	Verification Test Plan and Procedures Content.....	73
4.2.1	Verification Methods.....	73
4.3	C2 Link System Performance Requirements Verification Test Plan.....	75
4.3.1	Detailed Pre-Approval Verification Plan.....	75
4.3.2	C2 Link System Availability Requirement Verification.....	75
4.3.3	C2 Link System Latency Requirement Verification.....	76
4.3.4	C2 Link System Continuity Requirement Verification.....	77
4.3.5	C2 Link System Integrity Requirement Verification.....	78
4.3.6	Post Implementation Monitoring of System Performance.....	79
4.4	C2 Link System Functional, Interworking and Security Requirements Verification.....	80
4.4.1	Test Configuration.....	80
4.4.2	Verification Test Procedures Format.....	80
4.4.2.1	Test_Procedure_Name – Nominal.....	80
4.4.2.1.1	Test_Procedure_Name.N01.....	81
4.4.2.2	Test_Procedure_Name – Non-Nominal.....	81
4.4.2.2.1	Test_Procedure_Name.N01.....	81
4.4.2.3	Test Action Definitions.....	81
4.4.3	C2 Link System Security Requirements Verification.....	82
4.4.3.1	UAS_C2_SER_TP_001.....	82
4.4.3.1.1	UAS_C2_SER_TP_001 – Nominal.....	82
4.4.3.1.1.1	UAS_C2_SER_TP_001_N01.....	83
4.4.3.1.2	UAS_C2_SER_TP_001 – Non-Nominal.....	83
4.4.3.1.2.1	UAS_C2_SER_TP_001_X01.....	83
4.4.3.1.2.2	UAS_C2_SER_TP_001_X02.....	83
4.4.3.2	UAS_C2_SER_TP_002.....	84
4.4.3.2.1	UAS_C2_SER_TP_002 – Nominal.....	84
4.4.3.2.1.1	UAS_C2_SER_TP_002_N01.....	85
4.4.3.2.2	UAS_C2_SER_TP_002 – Non-Nominal.....	85
4.4.3.2.2.1	UAS_C2_SER_TP_002_X01.....	85
4.4.3.3	UAS_C2_SER_TP_003.....	85
4.4.3.3.1	UAS_C2_SER_TP_003 – Nominal.....	86
4.4.3.3.1.1	UAS_C2_SER_TP_003_N01.....	86
4.4.3.3.1.2	UAS_C2_SER_TP_003_N02.....	86
4.4.3.3.2	UAS_C2_SER_TP_003 – Non-Nominal.....	87
4.4.3.4	UAS_C2_SER_TP_004.....	87
4.4.3.4.1	UAS_C2_SER_TP_004 – Nominal.....	87
4.4.3.4.1.1	UAS_C2_SER_TP_004_N01.....	87

4.4.3.4.2	UAS_C2_SER_TP_004 – Non-Nominal.....	88
4.4.3.5	UAS_C2_SER_TP_005.....	88
4.4.3.5.1	UAS_C2_SER_TP_005 – Nominal.....	88
4.4.3.5.1.1	UAS_C2_SER_TP_005_N01.....	88
4.4.3.5.2	UAS_C2_SER_TP_005 – Non-Nominal.....	89
4.4.3.6	UAS_C2_SER_TP_006.....	89
4.4.3.6.1	UAS_C2_SER_TP_006_N01.....	89
4.4.3.7	UAS_C2_SER_TP_007.....	90
4.4.3.7.1	UAS_C2_SER_TP_007 – Nominal.....	90
4.4.3.7.1.1	UAS_C2_SER_TP_007_N01.....	90
4.4.3.7.1.2	UAS_C2_SER_TP_007_N02.....	91
4.4.3.7.2	UAS_C2_SER_TP_007 – Non-Nominal.....	91
4.4.3.8	UAS_C2_SER_TP_008.....	91
4.4.3.8.1	UAS_C2_SER_TP_008 – Nominal.....	92
4.4.3.8.1.1	UAS_C2_SER_TP_008_N01.....	92
4.4.3.8.2	UAS_C2_SER_TP_008 – Non-Nominal.....	92
4.4.3.8.2.1	UAS_C2_SER_TP_008_X01.....	92
4.4.3.8.2.2	UAS_C2_SER_TP_008_X02.....	93
4.4.3.9	UAS_C2_SER_TP_009.....	94
4.4.3.9.1	UAS_C2_SER_TP_009 – Nominal.....	94
4.4.3.9.1.1	UAS_C2_SER_TP_009_N01.....	94
4.4.3.9.2	UAS_C2_SER_TP_009 – Non-Nominal.....	95
4.4.3.10	UAS_C2_SER_TP_010.....	95
4.4.3.10.1	UAS_C2_SER_TP_010 – Nominal.....	95
4.4.3.10.1.1	UAS_C2_SER_TP_010_N01.....	95
4.4.3.10.1.2	UAS_C2_SER_TP_010_N02.....	96
4.4.3.10.2	UAS_C2_SER_TP_010 – Non-Nominal.....	97
4.4.3.11	UAS_C2_SER_TP_011.....	97
4.4.3.11.1	UAS_C2_SER_TP_011 – Nominal.....	97
4.4.3.11.1.1	UAS_C2_SER_TP_011_N01.....	97
4.4.3.11.2	UAS_C2_SER_TP_011 – Non-Nominal.....	98
4.4.3.12	UAS_C2_SER_TP_012.....	98
4.4.3.12.1	UAS_C2_SER_TP_012 – Nominal.....	98
4.4.3.12.1.1	UAS_C2_SER_TP_012_N01.....	99
4.4.3.12.2	UAS_C2_SER_TP_012 – Non-Nominal.....	99
4.4.3.13	UAS_C2_SER_TP_013.....	99
4.4.3.13.1	UAS_C2_SER_TP_013 – Nominal.....	100
4.4.3.13.1.1	UAS_C2_SER_TP_013_N01.....	100
4.4.3.13.2	UAS_C2_SER_TP_013 – Non-Nominal.....	100
4.4.3.14	UAS_C2_SER_TP_014.....	100
4.4.3.14.1	UAS_C2_SER_TP_014 – Nominal.....	101
4.4.3.14.1.1	UAS_C2_SER_TP_014_N01.....	101
4.4.3.14.2	UAS_C2_SER_TP_014 – Non-Nominal.....	101
4.4.3.15	Security Requirements Verification Traceability Matrix.....	101
4.4.4	C2 Link System Functional and Interworking Requirements Verification.....	101
4.4.4.1	UAS_C2_IR_TP_001.....	102
4.4.4.1.1	UAS_C2_IR_TP_001 – Nominal.....	102
4.4.4.1.1.1	UAS_C2_IR_TP_001.N01.....	102
4.4.4.1.1.2	UAS_C2_IR_TP_001.N02.....	102
4.4.4.1.2	UAS_C2_IR_TP_001 – Non-Nominal.....	103
4.4.4.2	UAS_C2_IR_TP_002.....	103
4.4.4.2.1	UAS_C2_IR_TP_002 – Nominal.....	103
4.4.4.2.1.1	UAS_C2_IR_TP_002.N01.....	103
4.4.4.2.1.2	UAS_C2_IR_TP_002.N02.....	103

4.4.4.2.2	UAS_C2_IR_TP_002 – Non-Nominal	104
4.4.4.2.2.1	UAS_C2_IR_TP_002.X01	104
4.4.4.2.2.2	UAS_C2_IR_TP_002.X02	104
4.4.4.3	UAS_C2_IR_TP_003	104
4.4.4.3.1	UAS_C2_IR_TP_003 – Nominal	104
4.4.4.3.1.1	UAS_C2_IR_TP_003.N01	105
4.4.4.3.1.2	UAS_C2_IR_TP_003.N02	105
4.4.4.3.2	UAS_C2_IR_TP_003 – Non-Nominal	105
4.4.4.3.2.1	UAS_C2_IR_TP_003.X01	105
4.4.4.3.2.2	UAS_C2_IR_TP_003.X02	105
4.4.4.4	UAS_C2_IR_TP_004	105
4.4.4.4.1	UAS_C2_IR_TP_004 – Nominal	106
4.4.4.4.1.1	UAS_C2_IR_TP_004.N01	106
4.4.4.4.1.2	UAS_C2_IR_TP_004.N02	106
4.4.4.4.1.3	UAS_C2_IR_TP_004 – Non-Nominal	106
4.4.4.5	UAS_C2_IR_TP_005	106
4.4.4.5.1	UAS_C2_IR_TP_005 – Nominal	107
4.4.4.5.1.1	UAS_C2_IR_TP_005.N01	107
4.4.4.5.2	UAS_C2_IR_TP_005 – Non-Nominal	107
4.4.4.5.2.1	UAS_C2_IR_TP_005.X01	107
4.4.4.6	UAS_C2_IR_TP_006	107
4.4.4.6.1	UAS_C2_IR_TP_006 – Nominal	108
4.4.4.6.1.1	UAS_C2_IR_TP_006.N01	108
4.4.4.6.1.2	UAS_C2_IR_TP_006.N02	108
4.4.4.6.1.3	UAS_C2_IR_TP_006.N03	109
4.4.4.6.1.4	UAS_C2_IR_TP_006.N04	109
4.4.4.6.1.5	UAS_C2_IR_TP_006.N05	109
4.4.4.6.2	UAS_C2_IR_TP_006 – Non-Nominal	109
4.4.4.7	UAS_C2_IR_TP_007	109
4.4.4.7.1	UAS_C2_IR_TP_007 – Nominal	110
4.4.4.7.1.1	UAS_C2_IR_TP_007.N01	110
4.4.4.7.1.2	UAS_C2_IR_TP_007.N02	110
4.4.4.7.2	UAS_C2_IR_TP_007 – Non-Nominal	110
4.4.4.8	UAS_C2_IR_TP_008	110
4.4.4.8.1	UAS_C2_IR_TP_008 – Nominal	111
4.4.4.8.1.1	UAS_C2_IR_TP_008.N01	111
4.4.4.8.1.2	UAS_C2_IR_TP_008.N02	111
4.4.4.8.1.3	UAS_C2_IR_TP_008.N03	112
4.4.4.8.2	UAS_C2_IR_TP_008 – Non-Nominal	112
4.4.4.9	UAS_C2_IR_TP_009	112
4.4.4.9.1	UAS_C2_IR_TP_009 – Nominal	112
4.4.4.9.1.1	UAS_C2_IR_TP_009.N01	112
4.4.4.9.2	UAS_C2_IR_TP_009 – Non-Nominal	113
4.4.4.10	UAS_C2_IR_TP_010	113
4.4.4.10.1	UAS_C2_IR_TP_010 – Nominal	113
4.4.4.10.1.1	UAS_C2_IR_TP_010.N01	113
4.4.4.10.1.2	UAS_C2_IR_TP_010.N02	114
4.4.4.10.2	UAS_C2_IR_TP_010 – Non-Nominal	114
4.4.4.11	UAS_C2_IR_TP_011	114
4.4.4.11.1	UAS_C2_IR_TP_011 – Nominal	115
4.4.4.11.1.1	UAS_C2_IR_TP_011.N01	115
4.4.4.11.1.2	UAS_C2_IR_TP_011.N02	115
4.4.4.11.2	UAS_C2_IR_TP_011 – Non-Nominal	116
4.4.4.12	UAS_C2_IR_TP_012	116

4.4.4.12.1	UAS_C2_IR_TP_012 – Nominal	116
4.4.4.12.1.1	UAS_C2_IR_TP_012.N01	116
4.4.4.12.2	UAS_C2_IR_TP_012 – Non-Nominal	116
4.4.4.12.2.1	UAS_C2_IR_TP_012.X01	117
4.4.4.13	UAS_C2_IR_TP_013	117
4.4.4.13.1	UAS_C2_IR_TP_013 – Nominal	117
4.4.4.13.1.1	UAS_C2_IR_TP_013.N01	118
4.4.4.13.2	UAS_C2_IR_TP_013 – Non-Nominal	118
4.4.4.14	UAS_C2_IR_TP_014	118
4.4.4.14.1	UAS_C2_IR_TP_014 – Nominal	118
4.4.4.14.1.1	UAS_C2_IR_TP_014.N01	118
4.4.4.14.2	UAS_C2_IR_TP_014 – Non-Nominal	119
4.4.4.15	UAS_C2_IR_TP_015	119
4.4.4.15.1	UAS_C2_IR_TP_015 – Nominal	119
4.4.4.15.1.1	UAS_C2_IR_TP_015.N01	120
4.4.4.15.1.2	UAS_C2_IR_TP_015.N02	120
4.4.4.15.2	UAS_C2_IR_TP_015 – Non-Nominal	120
4.4.4.16	UAS_C2_IR_TP_016	120
4.4.4.16.1	UAS_C2_IR_TP_016 – Nominal	121
4.4.4.16.1.1	UAS_C2_IR_TP_016.N01	121
4.4.4.16.1.2	UAS_C2_IR_TP_016.N02	121
4.4.4.16.1.3	UAS_C2_IR_TP_016.N03	121
4.4.4.16.1.4	UAS_C2_IR_TP_016.N04	121
4.4.4.16.2	UAS_C2_IR_TP_016 – Non-Nominal	122
4.4.4.17	UAS_C2_IR_TP_017	122
4.4.4.17.1	UAS_C2_IR_TP_017 – Nominal	123
4.4.4.17.1.1	UAS_C2_IR_TP_017.N01	123
4.4.4.17.2	UAS_C2_IR_TP_017 – Non-Nominal	123
4.4.4.17.2.1	UAS_C2_IR_TP_017.X01	124
4.4.4.17.2.2	UAS_C2_IR_TP_017.X02	124
4.4.4.18	Interworking Requirements Verification Trace Matrix	124

5 MEMBERSHIP..... 127

APPENDIX A CONCEPT OF OPERATIONS.....A-1

A.1	Introduction	A-1
A.2	Stakeholders	A-2
A.2.1	UAS operations	A-2
A.2.1.1	Goals	A-2
A.2.1.2	Constraints	A-2
A.2.2	UAS Original Equipment Manufacturers (OEM).....	A-3
A.2.2.1	Goals	A-3
A.2.2.2	Constraints	A-3
A.2.3	Aircraft Maintenance and Repair Organizations (MRO).....	A-3
A.2.3.1	Goals	A-3
A.2.3.2	Constraints	A-4
A.2.4	Equipment Manufacturers.....	A-4
A.2.4.1	Goals	A-4
A.2.4.2	Constraints	A-4
A.2.5	FAA Air Traffic Organization (ATO)	A-4
A.2.5.1	Goals	A-4
A.2.5.2	Constraints	A-4
A.2.5.3	Airspace Classification	A-5

A.2.6	FAA Aviation Safety Organization	A-5
A.2.6.1	Goals	A-5
A.2.6.2	Constraints	A-5
A.2.7	Radio Frequency (RF) Frequency Management Organization	A-6
A.2.7.1	Goals	A-7
A.2.7.2	Constraints	A-7
A.2.7.3	Approaches to Frequency Management for UAS Terrestrial System.....	A-8
A.2.8	UAS Traffic Management Organization.....	A-9
A.2.8.1	UAS Traffic Management.....	A-9
A.2.8.1.1	Goals	A-9
A.2.8.1.2	Constraints	A-9
A.2.9	C2 Link System Communications Service Providers	A-9
A.2.9.1	Goals	A-10
A.2.9.2	Constraints	A-10
A.2.10	International Civil Aviation Organization	A-11
A.2.10.1	Goals	A-11
A.2.10.2	Constraints	A-11
A.2.11	International Telecommunications Union Radiocommunications Sector (ITU-R)	A-11
A.2.11.1	Goals	A-12
A.2.11.2	Constraints	A-12
A.3	Life Cycle Aspects.....	A-12
A.3.1	Development.....	A-12
A.3.2	Operation	A-13
A.3.3	Maintenance.....	A-14
A.3.4	Disposal	A-14
A.3.5	Life Cycle Costs.....	A-14
A.3.6	Schedule.....	A-15
A.3.7	Risk Management	A-15
A.4	Existing Operational Conditions.....	A-15
A.4.1	Basic Definitions.....	A-15
A.4.2	Flight Phases Definitions	A-16
A.4.3	Airspace Classes	A-18
A.5	Assessment Of Whole UAS Impact On C2 Link System.....	A-21
A.5.1	Control the UA.....	A-21
A.5.2	Avionics.....	A-21
A.5.2.1	Flight Guidance System.....	A-22
A.5.2.2	Flight Management System	A-22
A.5.2.3	ATC Communication.....	A-22
A.5.2.4	DAA.....	A-22
A.5.2.5	Weather Radar	A-22
A.5.2.6	Status Reporting System.....	A-23
A.6	CONOPS Derivation.....	A-23
A.6.1	Summary of Key Aspects	A-23
A.6.1.1	How Those Aspects Impact UAS Operations.....	A-23
A.6.1.2	How Those Aspects Impact the C2 Link System	A-25
A.6.2	Previous UAS CONOPS Efforts.....	A-25
A.6.2.1	SC-203 CONOPS	A-25
A.6.2.2	FAA CONOPS.....	A-26
A.6.2.3	Earlier SC-228 Efforts	A-27
A.6.3	Payload.....	A-27
A.6.4	Derived CONOPS.....	A-27
A.6.4.1	Selection of the CONOPS in the Initial C2 Link System MASPS	A-29
A.6.4.1.1	Local Linear Sensing	A-29
A.6.4.1.2	Local Aerial Operations.....	A-30

A.6.4.1.3	Extended Aerial Operations.....	A-30
A.6.4.1.4	High Altitude Long Endurance (HALE).....	A-31
A.6.4.2	Relationship with DAA CONOPS Developments.....	A-32
A.7	References.....	A-32

APPENDIX B OPERATIONAL SERVICES AND ENVIRONMENT DEFINITION (OSD).....B-1

B.1	Introduction.....	B-1
B.2	Environment.....	B-4
B.2.1	Current FAA Regulations and Related Guidance.....	B-4
B.2.2	Safety.....	B-11
B.2.2.1	Introduction.....	B-11
B.2.2.2	Safety Related FAA Rules.....	B-12
B.3	Services.....	B-13
B.3.1	FAA Air Traffic Services (ATS).....	B-13
B.3.1.1	Data Services.....	B-13
B.3.1.2	Voice Communications.....	B-14
B.3.1.2.1	Introduction.....	B-14
B.3.1.2.2	Current FAA ATS Ground Voice Communications Services.....	B-14
B.3.1.2.3	Voice Communications Latency.....	B-14
B.3.1.2.4	Future FAA Voice Communications Services.....	B-14
B.3.1.2.5	Possible Architecture Alternatives.....	B-15
B.3.1.2.5.1	Relay the Voice Communications through the UA (Method 1).....	B-15
B.3.1.2.5.2	Ground to Ground Connectivity Directly Using the FAA Provided Voice Systems (Method 2).....	B-16
B.3.1.2.5.3	Ground-Based Remote Pilot Voice Radio (Method 3).....	B-16
B.3.2	Separation Service (ATS).....	B-16
B.3.3	C2 Link System Communication Service Providers.....	B-17
B.3.3.1	SATCOM.....	B-17
B.3.3.2	Terrestrial Services.....	B-17
B.3.3.3	Connections Between the CS and the Ground Components of either SATCOM or Terrestrial Services.....	B-17
B.4	Operations – Specific Scenarios.....	B-17
B.4.1	Operational and Technical Assumptions.....	B-17
B.4.1.1	Operational Assumptions.....	B-18
B.4.1.2	Technical Assumptions.....	B-20
B.4.2	CONOPS 1, Local Linear Sensing Scenarios.....	B-21
B.4.2.1	Power Line Scenario.....	B-21
B.4.2.2	Overview.....	B-21
B.4.2.3	Additional Assumptions for this Power Line Inspection Scenario.....	B-22
B.4.2.4	Flight Profile.....	B-22
B.4.2.5	Description of the Scenario.....	B-23
B.4.2.6	Use Cases.....	B-24
B.4.2.7	Use Case Descriptions.....	B-24
B.4.2.7.1	Use Case 0.1 (C1-S1-UC0.1) Continuous Monitoring.....	B-24
B.4.2.7.2	Use Case 0.2 (C1-S1-UC0.2) Parameter Change within C2 Link System.....	B-25
B.4.2.7.3	Use Case 0.3 (C1-S1-UC0.3) Parameter Change within a C2CSP's System.....	B-25
B.4.2.7.4	Use Case 1 (C1-S1-UC1) - Pre-Flight/Takeoff.....	B-25
B.4.2.7.5	Use Case 2 (C1-S1-UC2).....	B-26
B.4.2.7.6	Use Case 3 (C1-S1-UC13) – DAA Event.....	B-27
B.4.2.7.7	Use Case 4 (C1-S1-UC4) – ATC Vectors.....	B-27
B.4.2.7.8	Use Case 5.....	B-27
B.4.2.7.9	Use Case 6.....	B-28
B.4.2.7.10	Use Case 7 (C1-S1-UC7) – Landing/Post-Flight.....	B-28

B.4.3	CONOPS 2, Local Area Operations	B-28
B.4.3.1	Media and Incident Reporting Scenario (C2-S1).....	B-28
B.4.3.1.1	Overview.....	B-28
B.4.3.1.2	Additional Assumptions	B-29
B.4.3.1.3	Flight Profile.....	B-29
B.4.3.1.4	Scenario Description.....	B-30
B.4.3.1.5	Use Cases.....	B-30
B.4.3.1.6	Use Case Descriptions	B-31
B.4.3.1.6.1	Use Case 0. (C2-S1-UC0.) Continuous Monitoring and Parameter Changes.....	B-31
B.4.3.1.6.2	Use Case 0.1 (C2-S1-UC0.1) Continuous Monitoring	B-31
B.4.3.1.6.3	Use Case 0.2 (C2-S1-UC0.2) Parameter Change within C2 Link System	B-31
B.4.3.1.6.4	Use Case 0.3 (C2-S1-UC0.3) Parameter Change within a C2CSP's System.....	B-31
B.4.3.1.6.5	Use Case 1 (C2-S1-UC1) - Pre-Flight/Takeoff.....	B-31
B.4.3.1.6.6	Use Case 2 (C2-S1-UC2) - Departure	B-32
B.4.3.1.6.7	Use Case 3 (C2-S1-UC3) – Terrestrial → Terrestrial.....	B-32
B.4.3.1.6.8	Use Case 4 (C2-S1-UC4) – Reroute	B-32
B.4.3.1.6.9	Use Case 5 (C2-S1-UC5) – Arrival	B-33
B.4.3.1.6.10	Use Case 6 (C2-S1-UC6) - Terrestrial → Terrestrial	B-33
B.4.3.1.6.11	Use Case 7 (C2-S1-UC7) – Landing/Post-Flight.....	B-33
B.4.3.1.7	Use Case 8 (C2-S1-UC-8 Post-Flight).....	B-33
B.4.3.2	Local Cargo Delivery (C2-S2).....	B-33
B.4.3.2.1	Overview.....	B-33
B.4.3.2.2	Additional Assumptions for Local Cargo Delivery Aircraft (LCDA).....	B-34
B.4.3.2.2.1	Technical Assumptions.....	B-34
B.4.3.2.2.2	Other Assumptions	B-34
B.4.3.2.3	Scenario Description.....	B-34
B.4.3.2.4	Flight Profile	B-35
B.4.3.2.5	Use Cases.....	B-35
B.4.3.2.6	Use Case Descriptions	B-35
B.4.4	CONOPS 3 Extended Aerial Work.....	B-40
B.4.4.1	Remote Area Operations Scenario - Alaska Pipeline Inspection (C3-S1).....	B-40
B.4.4.1.1	Overview.....	B-40
B.4.4.1.2	Additional Assumptions	B-41
B.4.4.1.3	Flight Profile.....	B-41
B.4.4.1.4	Scenario Description.....	B-42
B.4.4.1.5	Use Cases.....	B-42
B.4.4.1.6	Use Case Descriptions	B-43
B.4.4.2	Maritime Surveillance Scenario (C3-S2).....	B-47
B.4.4.2.1	Overview.....	B-47
B.4.4.2.2	Additional Assumptions	B-48
B.4.4.2.3	Flight Profile.....	B-48
B.4.4.2.4	Scenario Description.....	B-48
B.4.4.2.5	Use Cases.....	B-49
B.4.4.2.6	Use Case Descriptions	B-50
B.4.4.3	Coast-to-Coast Aerial Work Surveys Scenario.....	B-54
B.4.4.3.1	Overview.....	B-54
B.4.4.3.2	Additional Assumptions	B-55
B.4.4.3.3	Flight Profile.....	B-55
B.4.4.3.4	Scenario Description.....	B-55
B.4.4.3.5	Use Cases.....	B-56
B.4.4.3.6	Use Case Descriptions	B-57
B.4.4.4	Containment Volume Aerial Work Scenario (C3-S4).....	B-63
B.4.4.5	Regional Cargo Delivery (C3-S5)	B-63
B.4.4.5.1	Overview.....	B-63

B.4.4.5.2	Additional Assumptions.....	B-63
B.4.4.5.2.1	Technical Assumptions.....	B-63
B.4.4.5.3	Other Assumptions.....	B-63
B.4.4.5.4	Flight Profile.....	B-64
B.4.4.5.5	Scenario Description.....	B-64
B.4.4.5.6	Use Cases.....	B-64
B.4.4.5.7	Use Case Descriptions.....	B-65
B.4.5	CONOPS 4 High Altitude Long Endurance (HALE) Operations.....	B-68
B.4.5.1	High Altitude Platform System (HAPS) (C4-S1).....	B-69
B.4.5.1.1	Overview.....	B-69
B.4.5.1.2	Additional Assumptions.....	B-69
B.4.5.1.3	Flight Profile.....	B-70
B.4.5.1.4	Scenario Description.....	B-70
B.4.5.1.5	Use Cases.....	B-71
B.4.5.2	Use Case Descriptions.....	B-72
B.4.5.3	Scenario High Altitude Relay System Scenario (C4-S2).....	B-75
B.4.5.3.1	Additional Assumptions.....	B-75
B.4.5.3.2	Flight Profile.....	B-76
B.4.5.3.3	Scenario Description.....	B-76
B.4.5.3.4	Use Cases.....	B-78
B.4.5.4	Use Case Descriptions.....	B-78
B.5	The SE Process Operational And System Views.....	B-81
B.5.1	Operational View of C2 Link System (OV-1).....	B-82
B.5.1.1	Overview of a Reprehensive Scenario.....	B-82
B.5.1.2	Use Cases Potentially Stressing the Effectiveness of the C2 Link System.....	B-84
B.5.2	Configuration Options for the C2 Link System (SV-1).....	B-85
B.5.2.1	Possible Configurations of C2 Link Systems.....	B-85
B.5.2.2	C2 Link System Switchovers.....	B-86
B.5.2.3	C2 Link System Control Station Handovers.....	B-87
B.5.3	C2 Link System Architectural View (SV-3).....	B-87
B.5.3.1	Types of Air/Ground Links.....	B-88
B.5.3.1.1	Terrestrial-Based Air/Ground Links.....	B-88
B.5.3.1.2	High Altitude Relay Air/Ground Links.....	B-89
B.5.3.1.3	Satellite Air/Ground Links.....	B-89
B.5.3.2	Types of Ground/Ground Links.....	B-91
B.5.3.3	Link System Implementation Responsibilities.....	B-91
B.5.4	Needed Information Exchanges - OV-2 Operational Resource Flow Description/Node Connectivity Description.....	B-92
B.5.5	Operational Activity Identification – OV-5.....	B-94
B.5.6	C2 Link System Functionality Description (OV-4).....	B-95
B.5.7	Key Subsystems of the C2 Link System and Those to Which It Connects (SV-2).....	B-96
B.5.8	The Information Exchanges supporting All the Scenarios in Appendix B.4 (OV-3).....	B-100
B.5.8.1	Operations and Activities Performed in Each Phases of Flight.....	B-101
B.5.8.1.1	Pre-Flight Planning.....	B-101
B.5.8.1.2	Start/Ground Movement/Taxi Phase.....	B-102
B.5.8.1.3	Takeoff/Departure Phase.....	B-102
B.5.8.1.4	Cruise Phase.....	B-103
B.5.8.1.5	Aerial Work Phase.....	B-103
B.5.8.1.6	Descent/Final Approach/Landing Phase.....	B-103
B.5.8.1.7	Post Landing (Ground Movement/Taxi/Shutdown) Phase.....	B-104
B.5.8.2	Airspace Class and Phase of Flight Simplification.....	B-104
B.5.8.3	Airspace Class, Operational Environment, Types of Loss of C2 Link System Functionality Addressed on OV-3.....	B-105
B.6	Resulting Operational And Functional Requirements.....	B-107

B.6.1	Operational Requirements (OR)	B-107
B.6.2	Functional Requirements (FR).....	B-109
B.7	References.....	B-110

APPENDIX C OPERATIONAL SAFETY ASSESSMENT.....C-1

C.1	Introduction.....	C-1
C.2	Scope.....	C-2
C.2.1	Automatic Takeoff And Landing System Assumptions (Atol).....	C-8
C.3	Safety Risk Management Panel	C-9
C.4	Risk Assessment	C-9
C.4.1	Analysis Method.....	C-9
C.4.2	Risk Determination.....	C-17
C.4.3	Identification of Mitigations	C-22
C.4.4	Description of the Hazards.....	C-24
C.4.4.1	Hazard Results Based on Causes	C-25
C.4.4.1.1	Hazards caused by Corrupted C2 Link (FR-1)	C-25
C.4.4.1.1.1	Corrupted C2 Link for Aviate Activity (FR-1.1) - UA Executes Unexpected Action..	C-26
C.4.4.1.1.2	Corrupted C2 Link for Communicate Activity (FR-1.2)	C-28
C.4.4.1.1.3	Corrupted C2 Link for Navigate Activity (FR-1.3) - Corrupted Data Causes the UA to Deviate From its Intended Course or Flight Plan	C-28
C.4.4.1.1.4	Corrupted C2 Link for Integrate Activity (FR-1.4) – Remote Pilot Receives Incorrect Information/Alert. Incorrect Information is Received at the CS.....	C-31
C.4.4.1.2	Hazard Results Based on Interrupted C2 Link.....	C-31
C.4.4.1.2.1	Interrupted C2 Link for Aviate Activity (FR-1.1) - Inadequate or Lack of Maneuver When One is Required.....	C-32
C.4.4.1.2.2	Interrupted C2 Link for Communicate Activity (FR-1.2)- Remote Pilot Does Not Receive ATC Instruction	C-39
C.4.4.1.2.3	Interrupted C2 Link for Navigate Activity (FR1.3) - Inadequate or Lack of Maneuver When One is Required or UA Deviates From Intended Course	C-42
C.4.4.1.2.4	Interrupted C2 Link for Integrate Activity (FR-1.4) – Remote Pilot Does Not Receive Alert in a Timely Manner	C-44
C.4.4.2	Manage C2 Link	C-47
C.4.4.2.1	Manage C2 Link – Establish/Terminate (FR-2.1) – Failed C2 Link	C-47
C.4.4.2.2	Manage C2 Link – Failed Switchovers (FR-2.2) Failed C2 Link.....	C-48
C.4.4.2.3	Manage C2 Link – Failed Handover (FR-2.3) – Failed C2 Link.....	C-50
C.4.4.2.4	Manage C2 Link – Establish/Terminate (FR-2.1)– Misdirected C2 Link	C-50
C.4.4.2.5	Manage C2 Link – Switchovers (FR-2.2)– Misdirected C2 Link.....	C-51
C.4.4.2.6	Manage C2 Link – Handovers (FR-2.3)– Misdirected C2 Link.....	C-52
C.4.4.3	FUNCTIONAL REQUIREMENT (FR-3) DESCRIBES THE FUNCTIONS THE C2 LINK SYSTEM NEEDS TO ENABLE THE REMOTE PILOT TO MANAGE THE PERFORMANCE OF THE C2 LINK SYSTEM	C-52
C.4.4.3.1	Manage C2 Link – Missing Status Report (FR-3.1).....	C-52
C.4.4.3.2	Manage C2 Link – Status Reports (FR-3.1) – Erroneous Status Reports.....	C-55
C.4.4.3.3	Change to C2 Link Systems Operating Parameter – (FR-3.2 and FR-3.3).....	C-55
C.4.4.3.4	Operating Parameters of the C2 Link System Air/Ground Link – (FR-3.2) and the C2 Link System Ground/Ground Link – (FR-3.3) Use Cases/Information Exchanges	C-56
C.4.4.4	Summary of Safety Requirements, Mitigations, and Recommendations	C-57
C.4.5	Operational Hazards and Safety Objectives (Required Likelihoods)	C-58
C.5	Current Regulations Used As Existing Controls.....	C-77
C.5.1	Regulations	C-77
C.5.2	See and Avoid.....	C-88
C.5.3	DAA System Overview	C-88
C.5.4	Top-Level Architecture.....	C-88

C.5.5	DAA Well Clear Definition.....	C-89
C.5.6	Flyaway.....	C-90
C.5.7	Single Point of Failure	C-90
C.5.8	Safety Risk Management Term Definitions	C-90
C.6	References.....	C-91

APPENDIX D OPERATIONAL PERFORMANCE ASSESSMENTD-1

D.1	Introduction.....	D-1
D.1.1	RLTP Availability.....	D-4
D.1.2	RLTP Continuity.....	D-4
D.1.3	RLTP Integrity	D-5
D.1.4	RLTP Latency.....	D-5
D.1.5	Per Flight Hour Considerations	D-5
D.1.6	Overview of OPA Methodology to Determine RLTP	D-6
D.1.7	RLTP Requirements	D-7
D.1.8	Organization of the OPA Assessments	D-7
D.1.9	Corrupted Cause	D-11
D.1.9.1	Example of a Corrupted Cause RLTP Assessment.....	D-11
D.1.10	Interrupted Cause	D-14
D.1.10.1	Example of a Interrupted Cause RLTP Assessment.....	D-14
D.1.11	Summary of RLTP Assessments	D-16
D.2	C2 Link System Latency.....	D-16
D.2.1	C2 Link Latency for the Remote Pilot Aviate, Navigate and Integrate Activities.....	D-16
D.2.1.1	Latency Assumptions.....	D-17
D.2.1.2	Considerations Regarding the C2 Link System Latency Estimates.....	D-23
D.2.2	C2 Link Latency for the Remote Pilot Communicate Activity	D-23
D.2.2.1	Communicate Latency Considerations	D-25
D.3	Opa Assessment For Surface Operations.....	D-27
D.3.1	Non-Towered.....	D-27
D.3.1.1	Corrupted Cause	D-27
D.3.1.1.1	RLTP Integrity for Aviate.....	D-27
D.3.1.1.2	RLTP Integrity for Navigate.....	D-27
D.3.1.2	Interrupted Cause.....	D-27
D.3.1.2.1	Transaction Timelines.....	D-27
D.3.1.2.2	TET	D-28
D.3.1.2.3	RLTP Availability and Continuity for Aviate.....	D-29
D.3.1.2.3.1	RLTP Availability for Aviate	D-29
D.3.1.2.3.2	RLTP Continuity for Aviate	D-29
D.3.2	Towered	D-29
D.3.2.1	Corrupted Cause	D-29
D.3.2.1.1	RLTP Integrity for Aviate.....	D-29
D.3.2.1.2	RLTP Integrity for Navigate.....	D-29
D.3.2.2	Interrupted Cause.....	D-29
D.3.2.2.1	Transaction Timelines.....	D-30
D.3.2.2.2	TET	D-30
D.3.2.2.3	RLTP Availability and Continuity for Aviate.....	D-30
D.3.2.2.3.1	RLTP Availability for Aviate	D-30
D.3.2.2.3.2	RLTP Continuity for Aviate	D-30
D.3.2.2.4	RLTP Availability and Continuity for Communicate.....	D-30
D.3.2.2.4.1	RLTP Availability for Communicate.....	D-31
D.3.2.2.4.2	RLTP Continuity for Communicate.....	D-31
D.4	OPA Assessment For Departure And Arrival Operations	D-31
D.4.1	Non-Towered.....	D-31

D.4.1.1	Corrupted Cause	D-31
D.4.1.1.1	RLTP Integrity for Aviate.....	D-31
D.4.1.1.2	RLTP Integrity for Navigate.....	D-31
D.4.1.1.3	RLTP Integrity for Integrate.....	D-31
D.4.1.2	Interrupted Cause.....	D-31
D.4.1.2.1	Transaction Timelines.....	D-32
D.4.1.2.2	TET	D-32
D.4.1.2.2.1	ATC initiated Approach Not Executed by RP/UA	D-32
D.4.1.2.2.2	RP Initiated Missed Approach/Go Around Not Executed by UA	D-33
D.4.1.2.2.3	DAA Initiated Maneuver for Separation Not Executed by RP/UA	D-34
D.4.1.2.3	RLTP Availability and Continuity for Aviate.....	D-34
D.4.1.2.3.1	RLTP Availability for Aviate	D-34
D.4.1.2.3.2	RLTP Continuity for Aviate	D-34
D.4.1.2.4	RLTP Availability and Continuity for Communicate.....	D-34
D.4.1.2.4.1	RLTP Availability for Communicate.....	D-34
D.4.1.2.4.2	RLTP Continuity for Communicate.....	D-35
D.4.1.2.5	RLTP Availability and Continuity for Navigate.....	D-35
D.4.1.2.5.1	RLTP Availability for Navigate.....	D-35
D.4.1.2.5.2	RLTP Continuity for Navigate.....	D-35
D.4.1.2.6	RLTP Availability and Continuity for Integrate.....	D-35
D.4.1.2.6.1	RLTP Availability for Integrate.....	D-35
D.4.1.2.6.2	RLTP Continuity for Integrate.....	D-35
D.4.2	Towered	D-35
D.4.2.1	Corrupted Cause	D-35
D.4.2.1.1	RLTP Integrity for Aviate.....	D-36
D.4.2.1.2	RLTP Integrity for Navigate.....	D-36
D.4.2.1.3	RLTP Integrity for Integrate	D-36
D.4.2.2	Interrupted Cause.....	D-36
D.4.2.2.1	Transaction Timelines.....	D-36
D.4.2.2.2	TET	D-37
D.4.2.2.2.1	ATC initiated Approach Not Executed by RP/UA	D-37
D.4.2.2.2.2	ATC Initiated Missed Approach/Go Around Not Executed by RP/UA	D-37
D.4.2.2.2.3	DAA initiated Maneuver for Separation Not Executed by RP/UA	D-37
D.4.2.2.3	RLTP Availability and Continuity for Aviate.....	D-38
D.4.2.2.3.1	RLTP Availability for Aviate	D-38
D.4.2.2.3.2	RLTP Continuity for Aviate	D-38
D.4.2.2.4	RLTP Availability and Continuity for Communicate.....	D-38
D.4.2.2.4.1	RLTP Availability for Communicate.....	D-38
D.4.2.2.4.2	RLTP Continuity for Communicate.....	D-38
D.4.2.2.5	RLTP Availability and Continuity for Navigate.....	D-39
D.4.2.2.5.1	RLTP Availability for Navigate.....	D-39
D.4.2.2.5.2	RLTP Continuity for Navigate.....	D-39
D.4.2.2.6	RLTP Availability and Continuity for Integrate.....	D-39
D.4.2.2.6.1	RLTP Availability for Integrate.....	D-39
D.4.2.2.6.2	RLTP Continuity for Integrate.....	D-39
D.5	OPA Assessment For Transit/Extended Operations	D-39
D.5.1	Class A Airspace.....	D-39
D.5.1.1	Corrupted Cause	D-39
D.5.1.1.1	RLTP Integrity for Aviate.....	D-40
D.5.1.1.2	RLTP Integrity for Navigate.....	D-40
D.5.1.2	Interrupted Cause.....	D-40
D.5.1.2.1	Transaction Timelines.....	D-40
D.5.1.2.2	TET	D-40
D.5.1.2.2.1	ATC initiated Maneuver for Separation Not Executed by RP/UA	D-40

D.5.1.2.2.2	RP initiated Maneuver Not Executed by RP/UA in FMS Mode	D-41
D.5.1.2.3	RLTP Availability and Continuity for Aviate.....	D-41
D.5.1.2.3.1	RLTP Availability for Aviate	D-41
D.5.1.2.3.2	RLTP Continuity for Aviate	D-41
D.5.1.2.4	RLTP Availability and Continuity for Communicate.....	D-41
D.5.1.2.4.1	RLTP Availability for Communicate.....	D-41
D.5.1.2.4.2	RLTP Continuity for Communicate.....	D-42
D.5.1.2.5	RLTP Availability and Continuity for Navigate.....	D-42
D.5.1.2.5.1	RLTP Availability for Navigate.....	D-42
D.5.1.2.5.2	RLTP Continuity for Navigate.....	D-42
D.5.2	Class B, C, and E Airspace	D-42
D.5.2.1	Corrupted Cause	D-42
D.5.2.1.1	RLTP Integrity for Aviate.....	D-42
D.5.2.1.2	RLTP Integrity for Navigate.....	D-42
D.5.2.1.3	RLTP Integrity for Integrate	D-42
D.5.2.2	Interrupted Cause.....	D-43
D.5.2.2.1	Transaction Timelines.....	D-43
D.5.2.2.2	TET	D-43
D.5.2.2.2.1	ATC initiated Maneuver for Separation Not Executed by RP/UA	D-43
D.5.2.2.2.2	DAA initiated Maneuver for Separation Not Executed by RP/UA	D-43
D.5.2.2.2.3	RP initiated Maneuver Not Executed by RP/UA in FMS Mode	D-44
D.5.2.2.3	RLTP Availability and Continuity for Aviate.....	D-44
D.5.2.2.3.1	RLTP Availability for Aviate	D-45
D.5.2.2.3.2	RLTP Continuity for Aviate	D-45
D.5.2.2.4	RLTP Availability and Continuity for Communicate.....	D-45
D.5.2.2.4.1	RLTP Availability for Communicate.....	D-45
D.5.2.2.4.2	RLTP Continuity for Communicate.....	D-45
D.5.2.2.5	RLTP Availability and Continuity for Navigate.....	D-45
D.5.2.2.5.1	RLTP Availability for Navigate.....	D-45
D.5.2.2.5.2	RLTP Continuity for Navigate.....	D-45
D.5.2.2.6	RLTP Availability and Continuity for Integrate.....	D-45
D.5.2.2.6.1	RLTP Availability for Integrate.....	D-46
D.5.2.2.6.2	RLTP Continuity for Integrate.....	D-46
D.5.3	Class G Airspace.....	D-46
D.5.3.1	Corrupted Cause	D-46
D.5.3.1.1	RLTP Integrity for Aviate.....	D-46
D.5.3.1.2	RLTP Integrity for Navigate.....	D-46
D.5.3.1.3	RLTP Integrity for Integrate	D-46
D.5.3.2	Interrupted Cause	D-47
D.5.3.2.1	Transaction Timelines.....	D-47
D.5.3.2.2	TET	D-47
D.5.3.2.2.1	DAA Initiated Maneuver for Separation Not Executed by RP/UA	D-47
D.5.3.2.2.2	RP Initiated Maneuver Not Executed by RP/UA in FGS Mode.....	D-47
D.5.3.2.2.3	RP Initiated Maneuver Not Executed by RP/UA in FMS Mode	D-47
D.5.3.2.3	RLTP Availability and Continuity for Aviate.....	D-48
D.5.3.2.3.1	RLTP Availability for Aviate	D-48
D.5.3.2.3.2	RLTP Continuity for Aviate	D-48
D.5.3.2.4	RLTP Availability and Continuity for Navigate.....	D-48
D.5.3.2.4.1	RLTP Availability for Navigate.....	D-48
D.5.3.2.4.2	RLTP Continuity for Navigate.....	D-48
D.5.3.2.5	RLTP Availability and Continuity for Integrate.....	D-48
D.5.3.2.5.1	RLTP Availability for Integrate.....	D-48
D.5.3.2.5.2	RLTP Continuity for Integrate.....	D-49
D.5.4	Oceanic A Airspace	D-49

D.5.4.1	Corrupted Cause	D-49
D.5.4.1.1	RLTP Integrity for Aviate.....	D-49
D.5.4.1.2	RLTP Integrity for Navigate.....	D-49
D.5.4.2	Interrupted Cause	D-49
D.5.4.2.1	Transaction Timelines.....	D-50
D.5.4.2.2	TET	D-50
D.5.4.2.2.1	RP initiated Maneuver Not Executed by UA in FGS Mode	D-50
D.5.4.2.2.2	RP Initiated Maneuver Not Executed by UA in FMS Mode	D-50
D.5.4.2.3	RLTP Availability and Continuity for Aviate.....	D-51
D.5.4.2.3.1	RLTP Availability for Aviate	D-51
D.5.4.2.3.2	RLTP Continuity for Aviate	D-51
D.5.4.2.4	RLTP Availability and Continuity for Navigate.....	D-51
D.5.4.2.4.1	RLTP Availability for Navigate.....	D-51
D.5.4.2.4.2	RLTP Continuity for Navigate.....	D-51
D.6	Opa For The Remote Pilot’s Manage C2 Link System Activity	D-51
D.6.1	Establish/Terminate	D-52
D.6.2	Switchover	D-55
D.6.2.1	Failed Switchovers.....	D-55
D.6.2.1.1	Allowable Quantitative Probability	D-55
D.6.2.1.2	Switchover Transaction Timeline and TET	D-56
D.6.2.1.2.1	Scheduled Make Before Break Switchover	D-56
D.6.2.1.2.2	Scheduled Break Before Make Switchover	D-56
D.6.2.1.2.3	Unscheduled Make Before Break Switchover	D-56
D.6.2.1.2.4	Unscheduled Break Before Make Switchover	D-56
D.6.2.2	Misdirected Switchover	D-57
D.6.2.3	Considerations on the C2 Link System’s Support of the Switchover Aspects of the Support of the Remote Pilot’s Manage C2 Link System Activity	D-57
D.6.3	Handover.....	D-58
D.6.3.1	Failed Handovers	D-58
D.6.3.1.1	Allowable Quantitative Probability	D-58
D.6.3.1.2	Handover Transaction Timeline and TET	D-58
D.6.3.1.2.1	Scheduled Make Before Break Handover.....	D-58
D.6.3.1.2.2	Unscheduled Make Before Break Handover	D-59
D.6.3.2	Misdirected Handover.....	D-59
D.6.4	Status Reporting.....	D-59
D.6.4.1	Latency of the C2 Link System Status Reporting.....	D-61
D.6.4.2	Missing C2 Link System Status Reports	D-61
D.6.4.3	Erroneous C2 Link System Status Reporting	D-62
D.6.4.4	Considerations on the C2 Link System’s Status Reporting Aspects of the Support of the Remote Pilots Manage C2 Link System Activity	D-62
D.6.5	External Changes to Operating Parameters	D-62
D.6.5.1	Failed Change to Operating Parameters	D-63
D.6.5.1.1	Allowable Quantitative Probability	D-63
D.6.5.1.2	Change to Operating Parameters Timeline and TET	D-63
D.6.5.2	Erroneous Operating Parameter Change.....	D-64
D.7	Summary of Results of THE Assessments	D-64
D.7.1.1	Transaction Expiration Times.....	D-65
D.7.2	Summary of the C2 Link System’s Performance when Supporting the Remote Pilot’s Aviate, Communicate, Navigate and Integrate Activities.....	D-68
D.7.3	Summary of the C2 Link System’s Performance when Supporting the Remote Pilot’s Manage C2 Link System Activity.....	D-68
D.7.4	Example of Availability, Continuity, and Use Time Considerations.....	D-71
D.7.5	Overall OPA Considerations.....	D-73
D.8	References.....	D-73

APPENDIX E C2 LINK SYSTEM USER DATA RATE CONSIDERATIONS..... E-1

E.1 Introduction..... E-1
E.2 Information Flows..... E-2
E.3 C2 Link System User Data Loading Estimates..... E-4
E.3.1 Aircraft Control..... E-4
E.3.2 Nav aids E-4
E.3.3 ATC Voice Relay..... E-4
E.3.4 ATS Data Relay E-5
E.3.5 Target Data E-5
E.3.6 Weather Radar E-5
E.3.7 Non-Payload Video..... E-6
E.4 C2 Link Management System Overhead And Throughput E-6
E.4.1 Addressing/Networking Protocol and Security Overhead E-6
E.4.1.1 Message Packing for Aircraft Control and Nav aids STANAG 4586 Messages..... E-8
E.4.1.2 Total Air/Ground RF Link Data Rates (Aircraft Control/Nav aids, ATC Voice Relay, Target Data) E-9
E.4.2 C2 Link System vs. Air/Ground RF Link User Data Throughput Requirements E-12
E.5 Notional C2 Link System Service Classes..... E-15
E.6 Air/Ground RF Link Delay (Latency) Simulation Results E-18
E.7 DO-362A Los Cn pc Radio System Data Modes Vs. C2 Link System Notional Service Classes E-27
E.8 Example C2 Link User Data Message Sizes And Content E-28
E.8.1 Aircraft Control Messages E-28
E.8.2 Nav aids Messages..... E-40
E.8.3 Target Data Message Encoding E-44
E.9 Required Total RF Link User Data Throughput E-52
E.10 References..... E-59

APPENDIX F RF LINK BUDGET CONSIDERATIONS FOR TERRESTRIAL AND SATELLITE-BASED C2 LINK SYSTEMS F-1

F.1 Introduction..... F-1
F.1.1 Causes of Variability in RF Transmission Loss with Time F-1
F.1.1.1 The Propagation Medium Itself F-1
F.1.1.2 The Boundaries of the Propagation Medium F-2
F.1.2 Additions to the Basic Free-Space Link Budget RF Transmission Loss F-2
F.1.3 Variability in the Basic Free-Space Link Budget RF Transmission Loss F-3
F.1.3.1 Fading F-3
F.1.3.2 Rain..... F-3
F.1.3.3 Scintillation..... F-4
F.1.4 The Interference-Free, Link Budget F-4
F.1.4.1 Effective Antenna Gains GETX and GERX..... F-4
F.1.4.2 Calculating the Es/No F-4
F.1.5 Interference Considerations F-5
F.1.6 Modeling and Simulation..... F-6
F.1.6.1 Propagation Modeling and Simulation F-6
F.1.6.2 Installed Antenna Modeling and Simulation F-8
F.1.6.3 Modeling and Simulation of Fade Duration and Number of Fades in the Time Frame of Interest F-11
F.2 Detailed Terrestrial-Based RF Link Budget Analysis F-11
F.2.1 Terrestrial-Based RF Links..... F-12
F.2.2 Time-Invariant Terrestrial Link Budget Elements..... F-13
F.2.2.1 EIRPSD and PFD Limitations F-13

F.2.2.2	Antenna Discrimination and Pointing Accuracy	F-13
F.2.2.3	GRS and ARS Performance.....	F-13
F.2.2.4	RF Transmission Loss	F-14
F.2.3	Time-Variant Terrestrial Link Budget Elements	F-14
F.2.3.1	Tropospheric Variability.....	F-14
F.2.3.2	Surface Reflection.....	F-15
F.2.3.3	Overall Fading Depths	F-15
F.2.4	Availability and Interruption Time Predictions	F-17
F.2.5	Other Terrestrial-Based RF Link Budget Considerations.....	F-17
F.2.5.1	Required Es/No.....	F-17
F.2.5.2	Interference	F-19
F.2.6	Terrestrial Link Budget Templates	F-19
F.2.6.1	C Band Link Forward Link.....	F-19
F.2.6.2	C Band Link Return Link	F-20
F.3	Detailed Satellite-Based RF Link Budget Analysis.....	F-20
F.3.1	Satellite-Based RF Links	F-21
F.3.2	Time-Invariant Satellite Link Budget Elements	F-23
F.3.2.1	Off-Axis EIRPSD and PFD Limitations.....	F-23
F.3.2.2	Earth Station Antenna Discrimination and Pointing Accuracy	F-24
F.3.2.3	Satellite Transponder and Earth Station Performance	F-24
F.3.2.4	RF Transmission Loss	F-26
F.3.3	Time-Variant Satellite Link Budget Elements.....	F-27
F.3.4	Availability and Interruption Time Predictions	F-28
F.3.5	Other Satellite Link Budget Considerations	F-30
F.3.5.1	Required Es/No.....	F-30
F.3.5.2	Interference	F-30
F.3.6	Satellite Link Budget Templates.....	F-30
F.3.6.1	Ku Band Link 1.....	F-31
F.3.6.2	Ku Band Link 2.....	F-32
F.3.6.3	Ku Band Link 3.....	F-33
F.3.6.4	Ku Band Link 4.....	F-34
F.3.6.5	Ka Band Link 1.....	F-35
F.3.6.6	Ka Band Link 2.....	F-36
F.3.6.7	Ka Band Link 3.....	F-37
F.3.6.8	Ka Band Link 4.....	F-37
F.4	References.....	F-38

APPENDIX G GROUND/GROUND LINK CONSIDERATIONSG-1

G.1	Introduction.....	G-1
G.2	Summary Of Air/Ground And Ground/Ground Links.....	G-2
G.3	Ground/ground Links.....	G-3
G.3.1	Direct Connections	G-3
G.3.2	Networked Connections.....	G-3
G.3.2.1.1	Public Networks.....	G-3
G.3.2.1.2	Virtual Private Network Connection Over The Internet.....	G-3
G.3.2.1.3	A Secure Wireless Network Connection	G-4
G.3.2.2	A Private Network Connection.....	G-4
G.4	Factors To Consider When Selecting A Ground/Ground Link Provider Or Developing A Ground/Ground Link	G-4
G.4.1	The Requirements in Section 3	G-4
G.4.2	Use of Service Level Agreements.....	G-5

APPENDIX H UNMANNED AIRCRAFT SYSTEMS (UAS) COMMAND AND CONTROL (C2) CONNECTIVITY USING SATCOM LINKS (L, C, KA, AND KU BAND)H-1

H.1	Introduction.....	H-1
H.2	Communication Satellites	H-2
H.3	L Band Satellite Communications	H-3
H.3.1	Introduction to L Band Satellites	H-3
H.3.2	L Band Services	H-3
H.3.2.1	AMSS and AMS(R)S Systems	H-3
H.3.2.2	FANS 1/A Data Link	H-4
H.3.2.3	Voice and Data Communications	H-4
H.3.3	Inmarsat System Description	H-5
H.3.3.1	Swift Broad Band Safety (SB-S)	H-5
H.3.3.2	L Band SATCOM Used for Iris Program Overview	H-8
H.3.4	Iridium System Description	H-9
H.3.4.1	Iridium System Architecture and Constellation.....	H-9
H.3.4.2	Iridium Terrestrial Segment.....	H-11
H.3.4.3	Iridium Aero User Terminal and Service.....	H-12
H.3.5	Ligado Networks System Description	H-12
H.4	C Band Satellite Communications	H-14
H.5	Ka And Ku Band Satellite Communications	H-14
H.5.1	Introduction to Ka and Ku Band Systems.....	H-14
H.5.2	Ka and Ku band Satellite Systems Overview	H-15
H.5.3	Fixed Satellite Service Geostationary Satellites (Resolution 155 Compliant).....	H-16
H.5.4	High Throughput Satellites (HTS).....	H-18
H.5.5	Non-GEO Satellites	H-20
H.6	Satcom Equipment Selection And Design Considerations	H-23
H.6.1	SATCOM Equipment Selection Drivers	H-23
H.6.1.1	CONOPS Drivers.....	H-23
H.6.1.2	Platform Constraints	H-25
H.6.2	Antenna Categories/Performance Characteristics.....	H-25
H.6.3	L Band Design Considerations and Equipment	H-26
H.6.4	Ka and Ku Design Considerations and Equipment.....	H-28
H.6.5	Summary/Recommendations	H-30
H.7	Bandwidth Management For Ua Satcom C2 Link With Demand-Assigned Multiple Access	H-30
H.7.1	DAMA Implementation Considerations	H-31
H.7.2	Experience With Satellite DAMA	H-31
H.8	References.....	H-32

APPENDIX I SERVICE LEVEL AGREEMENTS (TERRESTRIAL/SATCOM)..... I-1

I.1	Introduction.....	I-1
I.2	C2 Link Service Stakeholders And Associated Roles And Responsibilities.....	I-1
I.3	C2CSP Operational Considerations	I-2
I.3.1	QUALITY OF SERVICE REQUIRED (QoSR)	I-2
I.4	C2CSP Oversight.....	I-2
I.4.1	Monitoring and Interference Reporting Requirements	I-3
I.4.2	C2CSP Service Elements.....	I-3
I.4.3	Backhaul Network Extensions.....	I-6
I.4.4	Multiple Service Level Agreements	I-7
I.5	Service Level Agreements (SLAS) Content	I-8
I.5.1	Sample SLA Contents.....	I-9

APPENDIX J COMMAND AND CONTROL AND PAYLOAD ON SAME LINKJ-1

J.1 Introduction..... J-1
J.2 Applicability Of C2 And Payload Information On The Same Link J-1
J.3 Methods To Support C2 And Payload Data On The Same Link J-1
J.4 Prioritization And The C2 Link J-2
J.5 Prioritization And The C2csp J-3
J.6 Separation Of Protection Domains J-3
J.6.1 Description of C2CSP Encryption for End-to-End Domain Separation (C2 and Payload Data) J-3
J.6.2 Inner and Outer Tunnel Functionality..... J-3
J.6.3 C2 and Payload Data Separation Communications Security Considerations J-4

APPENDIX K INTERWORKING CONSIDERATIONS FOR C2 LINK SYSTEM CONNECTION, SWITCHOVER, AND CONTROL STATION HANDOVER....K-1

K.1 Introduction..... K-1
K.2 Definitions K-2
K.3 C2 Link System Operational Environment..... K-5
K.3.1 Example C2 Link System Switchover Scenarios..... K-5
K.3.2 Example Control Station Handover Scenarios K-5
K.3.3 Operational Considerations..... K-5
K.4 C2 Link System Components Overview..... K-8
K.4.1 Air/Ground Link Types K-8
K.4.2 Ground/Ground Link Interconnection Types..... K-9
K.5 C2 Link System Connections and Switchovers K-10
K.5.1 Connection Description K-10
K.5.1.1 Connections Over Point-to-Point Links Versus Over Networked Links K-11
K.5.2 C2 Link System Switchovers..... K-14
K.5.2.1 “DTSR Subsystem Connection” Switchover (Optional Procedure 1)..... K-14
K.5.2.2 “C2 Link System Route” Switchover (Optional Procedure 2)..... K-18
K.5.2.3 Multilink Operations..... K-20
K.5.3 Switchover Hand-Shake Sequence K-20
K.5.3.1 DTSR Subsystem Connection Switchover Hand-Shake Sequence K-20
K.5.3.2 C2 Link System Route Switchover Hand-Shake Sequence..... K-24
K.5.4 Control Station Handovers..... K-26
K.5.4.1 Control Station Handover Using Ground Link Connection..... K-27
K.5.4.2 Control Station Handover Using Simultaneous C2 Link System Connections K-30
K.5.5 Control Station Handover Hand-Shake Sequence K-31
K.5.5.1 Handshake Sequence for Handover over Point-to-Point Terrestrial LOS Link..... K-31
K.5.5.2 Handshake Sequence for Handover over Terrestrial or SATCOM Air/Ground Access Network K-32
K.5.5.3 Handshake Sequence for CS Handover using Ground Link Connection K-34
K.5.6 C2 Link Transmission Unit Size Selection..... K-36
K.6 Interworking Assessment..... K-37
K.6.1 CS C2 Link Management System..... K-38
K.6.1.1 CS C2 Link Management Support Functions K-38
K.6.1.2 CS C2 Data Multiplexing/Demultiplexing and Prioritization Functions K-40
K.6.1.3 CS C2 Link System Data Transfer, Security and Routing (DTSR) Subsystem..... K-41
K.6.2 UA C2 Link Management System..... K-41
K.6.2.1 UA C2 Link Management Support Functions K-41
K.6.2.2 UA C2 Data Multiplexing/Demultiplexing and Prioritization Functions K-42
K.6.2.3 UA C2 Link System Data Transfer, Security and Routing (DTSR) Subsystem..... K-42
K.7 C2 Link Switchover and Control Station Handover Safety Assessment K-43

K.8	C2 Link System Interworking Requirements	K-43
K.8.1	Minimum C2 Link System Connection Interworking Requirements	K-44
K.8.2	C2 Link System Switchover Interworking Requirements	K-48
K.8.2.1	DTSR Subsystem Connection Switchover Interworking Requirements (Optional Procedure 1).....	K-49
K.8.2.2	C2 Link System Route Switchover Interworking Requirements (Optional Procedure 2) K- 51	
K.8.3	Control Station Handover Interworking Requirements	K-52
K.8.4	C2 Link Switchover and Control Station Handover Related Recommendations	K-55
APPENDIX L C2 LINK SYSTEM SECURITY CONSIDERATIONS		L-1
L.1	Introduction.....	L-1
L.2	Definitions	L-1
L.3	C2 Link System Communications Security Context	L-1
L.3.1	Terrestrial and SATCOM Point-to-Point Links.....	L-2
L.3.2	Links over Terrestrial and SATCOM Air/Ground Access Networks.....	L-2
L.4	Security Requirements and Acceptable Means of Compliance (MOC)	L-3
L.5	Security Controls Overhead Mitigation	L-11
L.6	References.....	L-12
APPENDIX M ACRONYMS, TERMINOLOGY, AND DEFINITIONS.....		M-1

LIST OF TABLES

Table 3-1: Requirements Traceability.....	16
Table 3-2: Operational Requirement OR-1.....	28
Table 3-3: Operational Requirement OR-2.....	28
Table 3-4: Operational Requirement OR-3.....	29
Table 3-5: Operational Requirement OR-4.....	29
Table 3-6: Functional Requirement FR-1	30
Table 3-7: Functional Requirement FR-2	30
Table 3-8: Functional Requirement FR-3	31
Table 3-9: C2 Link System Connection Interworking Requirements.....	32
Table 3-10: C2 Link System Common Switchover Interworking Requirements	35
Table 3-11: Optional Procedure 1 DTSR Subsystem Connection Switchover Interworking Requirements	36
Table 3-12: Optional Procedure 2 C2 Link System Route Switchover Interworking Requirements	38
Table 3-13: Interworking Requirements for CS Handovers	39
Table 3-14: Operational Hazards for FR-1	42
Table 3-15: Safety Objectives for FR-1	46
Table 3-16: Operational Hazards for FR-2	51
Table 3-17: Safety Objectives for FR-2.....	53
Table 3-18: Operational Hazards for FR-3	55
Table 3-19: Safety Objectives for FR-3	56
Table 3-20: C2 Link System Performance Requirements Surface, Non-Towered.....	59
Table 3-21: C2 Link System Performance Requirements Surface, Towered.....	60
Table 3-22: C2 Link System Performance Requirements Departure and Arrival in Non-Towered Airspace.....	61
Table 3-23: C2 Link System Performance Requirements Departure and Arrival in Towered Airspace...	62
Table 3-24: C2 Link System Performance Requirements Transit/Extended Operations in Class A Airspace.....	63
Table 3-25: C2 Link System Performance Requirements Transit/Extended Operations in Class B, C, and E Airspace	64
Table 3-26: C2 Link System Performance Requirements Transit/Extended Operations in Class G Airspace.....	65
Table 3-27: C2 Link System Performance Requirements RLTP Transit/Extended Operations in Class Oceanic A Airspace.....	66
Table 3-28: Security Requirements for User Plane Traffic between Unmanned Aircraft and Control Station.....	67
Table 3-29: Security Requirements for Control Plane Traffic between Unmanned Aircraft and Control Station.....	68
Table 3-30: Security Requirements for User Plane Traffic over Connections between Unmanned Aircraft and Air/Ground Network Gateway and between Control Station and Air/Ground Network Gateway.....	69
Table 3-31: Security Requirements and Recommendations for Control Plane Traffic over Connections between Unmanned Aircraft and Air/Ground Network Gateway and between Control Station and Air/Ground Network Gateway	70
Table 3-32: Recommendations	71
Table 4-1: Identification and Definition of Test Actions.....	81
Table 4-2: Security Requirements VTM	101
Table 4-3: Internetworking Requirement VTM.....	124
Table A-1: CONOPS to be Studied	A-28
Table B-1: Descriptions of the Developed OV's and SV's [[B-3]and [B-4]]	B-3
Table B-2: C2 Information Exchanges Identified during Development of the OV-3 Matrices Occurring within Various Airspaces).....	B-106
Table C-1: Limitations to Scope	C-5

Table C-2: General Assumptions.....	C-7
Table C-3: Severity Definitions from FAA ATO SMS Manual [C-2]	C-18
Table C-4 Required Likelihood Matrix	C-20
Table C-5: Risk Assessment Matrix	C-21
Table C-6 Risk Acceptance Criteria	C-22
Table C-7: Standardized Lost C2 Link State Procedures.....	C-23
Table C-8: Most Stressful Use Case/Information Exchanges for Aviate Hazards	C-27
Table C-9: Most Stressful Use Case/Information Exchanges for Navigate Hazards.....	C-29
Table C-10: Most Stressful Use Case/Information Exchanges for Integrate Hazards.....	C-31
Table C-11: Most Stressful Use Case/Information Exchanges for Aviate Hazards	C-36
Table C-12: Most Stressful Use Case/Information Exchanges for Communicate Hazards Caused by Interrupted C2 Link.....	C-40
Table C-13: Most Stressful Use Case/Information Exchanges for Navigate Hazards.....	C-43
Table C-14: Most Stressful Use Case/Information Exchanges for Integrate Hazards.....	C-46
Table C-15: Use Case/Information Exchanges for Manage C2 Link Hazards Caused by Failed C2 Link Establishment	C-48
Table C-16: Use Case/Information Exchanges for Manage C2 Link Hazards Caused by Failed C2 Link Switchovers	C-49
Table C-17: Use Case/Information Exchanges for Manage C2 Link Hazards Caused by Failed C2 Link Handover	C-50
Table C-18: Most Stressful Use Case/Information Exchanges for Manage C2 Link Hazards Caused by Misdirected C2 Link during Establishment.....	C-51
Table C-19: Most Stressful Use Case/Information Exchanges for Manage C2 Link Hazards Caused by Misdirected C2 Link Switchovers.....	C-51
Table C-20: Most Stressful Use Case/Information Exchange for Manage C2 Link Hazards Caused by Misdirected C2 Link Handovers	C-52
Table C-21: Use Case/Information Exchanges for Manage C2 Link Hazards Caused by Missing Status Report.....	C-54
Table C-22: Most Stressful Use Case/Information Exchanges for Manage C2 Link Hazards Caused by Erroneous Status Report.....	C-55
Table C-23: Use Cases and Information Exchanges for Change to Operating Parameters of the C2 Link System Air/Ground Link – (FR-3.2) and Changes to Operating Parameters of the C2 Link System Ground/Ground Link – (FR-3.3)	C-56
Table C-24: Operational Hazards for FR-1.....	C-60
Table C-25: Residual Required Likelihoods for FR-1	C-65
Table C-26: Operational Hazards for FR-2.....	C-71
Table C-27: Residual Required Likelihoods for FR-2.....	C-73
Table C-28: Operational Hazards for FR-3.....	C-75
Table C-29: Residual Required Likelihoods for FR-3.....	C-76
Table C-30: Summary of CFR Concerning Pilot Responsibility for Traffic Avoidance.....	C-78
Table C-31: Summary of ATC Requirements	C-85
Table D-1: Overview of the Organization of Appendix D.3, D.4, and D.5	D-10
Table D-2: Corrupted Cause Use Cases Required Residual Likelihood by Phase of Flight Grouping, Airspace, and Remote Pilot Activity	D-12
Table D-3: Interrupted Cause Use Cases Required Residual Likelihood by Phase of Flight Grouping, Airspace, and Remote Pilot Activity	D-15
Table D-4: Latency Estimates - Networked Terrestrial C2 Link Systems.....	D-19
Table D-5: Latency Estimate – Networked Satellite C2 Link Systems	D-21
Table D-6: Latency Standards for Various NAS Voice Equipment	D-24
Table D-7: Manage C2 Link System Use Cases Organized by Phase of Flight Grouping, Airspace, and Remote Pilot Activity for FR-2.....	D-53
Table D-8: Manage C2 Link System Use Cases Organized by Phase of Flight Grouping, Airspace, and Remote Pilot Activity for FR-3	D-54
Table D-9: Summary of Transaction Expiration Times.....	D-66

Table D-10: Summary of OPA Results for the Remote Pilot’s, Aviate, Communicate, Navigate and Integrate Activity - FR-1	D-67
Table D-11: Summary of OPA Results for the Remote Pilot’s Manage C2 Link Activity - FR-2.....	D-69
Table D-12: Summary of OPA Results for the Remote Pilot’s Manage C2 Link Activity - FR-3.....	D-70
Table E-1: Total Air/Ground RF Link User Data Throughput for Descent/Landing Phase – Return Link Manual Mode	E-11
Table E-2: Estimated Non-Payload Throughput Requirements (bytes/sec) of a Single UA – Manual Mode.....	E-13
Table E-3: Estimated Non-Payload Throughput Requirements (bytes/sec) of a Single UA – Automatic Mode.....	E-14
Table E-4: C2 Link System Service Classes and Minimum Data Throughput – Manual Mode	E-16
Table E-5: C2 Link System Service Classes and Minimum Data Throughput – Automatic Mode.....	E-17
Table E-6: DO-362A LOS CNPC Radio Data Modes vs. C2 Link System Service Class Summary ...	E-27
Table E-7: STANAG 4586 Aircraft Control Message Lengths by Phase of Flight.....	E-29
Table E-8: Aircraft Control Messages, Takeoff/Climbout Phase: Forward.....	E-30
Table E-9: Aircraft Control Messages, Takeoff/Climbout Phase: Return	E-32
Table E-10: Aircraft Control Messages, En Route Phase: Forward	E-34
Table E-11: Aircraft Control Messages, En Route Phase: Return.....	E-35
Table E-12: Aircraft Control Messages, Descent/Landing Phase: Forward.....	E-36
Table E-13: Aircraft Control Messages, Descent/Landing Phase: Return.....	E-38
Table E-14: STANAG 4586 Navaids Message Lengths by Phase of Flight	E-40
Table E-15: Navaids Messages, Takeoff/Climbout Phase: Forward	E-41
Table E-16: Navaids Messages, Takeoff/Climbout Phase: Return	E-41
Table E-17: Navaids Messages, En Route Phase: Forward	E-42
Table E-18: Navaids Messages, En Route Phase: Return.....	E-42
Table E-19: Navaids Messages, Descent/Landing Phase: Forward.....	E-43
Table E-20: Navaids Messages, Descent/Landing Phase: Return.....	E-43
Table E-21: Single Target Data Block (Relative Position).....	E-44
Table E-22: Single Target Data Block (Absolute Position).....	E-48
Table E-23: Total RF Link User Data Throughput for Takeoff/Climbout Phase – Forward Manual Mode	E-53
Table E-24: Total RF Link User Data Throughput for Takeoff/Climbout Phase – Return Manual Mode	E-53
Table E-25: Total RF Link User Data Throughput for Takeoff/Climbout Phase – Forward Automatic Mode.....	E-54
Table E-26: Total RF Link User Data Throughput for Takeoff/Climbout Phase – Return Automatic Mode	E-54
Table E-27: Total RF Link User Data Throughput for En Route Phase – Forward Manual Mode	E-55
Table E-28: Total RF Link User Data Throughput for En Route Phase – Return Manual Mode.....	E-55
Table E-29: Total RF Link User Data Throughput for En Route Phase – Forward Automatic Mode..	E-56
Table E-30: Total RF Link User Data Throughput for En Route Phase – Return Automatic Mode....	E-56
Table E-31: Total RF Link User Data Throughput for Descent/Landing Phase – Forward Manual Mode	E-57
Table E-32: Total RF Link User Data Throughput for Descent/Landing Phase – Return Manual Mode .	E-57
Table E-33: Total RF Link User Data Throughput for Descent/Landing Phase – Forward Automatic Mode.....	E-58
Table E-34: Total RF Link User Data Throughput for Descent/Landing Phase – Return Automatic Mode	E-58
Table F-1: C Band Forward Link Budget	F-19
Table F-2: C Band Return Link Budget.....	F-20
Table F-3: Ku Band Satellite and GES Performance Characteristics	F-25
Table F-4: Ka Band Satellite and GES Performance Characteristics	F-25
Table F-5: Ku Band AES Performance Characteristics	F-26

Table F-6: Ka Band AES Performance Characteristics	F-26
Table F-7: Clear-Sky Additional RF Transmission Loss.....	F-26
Table F-8: Ku Band Link 1	F-31
Table F-9: Ku Band Link 2.....	F-32
Table F-10: Ku Band Link 3	F-33
Table F-11: Ku Band Link.....	F-34
Table F-12: Ka Band Link 1	F-35
Table F-13: Ka Band Link 2	F-36
Table F-14: Ka Band Link 3	F-37
Table F-15: Ka Band Link 4	F-37
Table H-1: LEO/ MEO Summary.....	H-22
Table H-32: Performance Characteristics for Various Antenna Types (L Band).....	H-27
Table K-1: Minimum C2 Link System Connection Interworking Requirements.....	K-44
Table K-2: Minimum C2 Link System Switchover Interworking Requirements	K-48
Table K-3: Optional Procedure 1 DTSR Subsystem Connection Switchover Interworking Requirements	K-50
Table K-4: Optional Procedure 2 Summary of C2 Link System Route Switchover Interworking Requirements.....	K-52
Table K-5: Summary of Interworking Requirements for CS Handovers.....	K-53
Table K-6: C2 Link System Connection and Switchover Recommendations	K-55
Table L-1: Summary of Security Requirements and MOCs for User Plane Traffic between Unmanned Aircraft (UA) and Control Station (CS).....	L-5
Table L-2: Summary of Security Requirements and MOCs for Control Plane Traffic between Unmanned Aircraft (UA) and Control station (CS).....	L-8
Table L-3: Summary of Security Requirements and MOCs for User Plane Traffic over Connections between Unmanned Aircraft (UA) and Air/Ground Network Gateway and between Control Station (CS) and Air/Ground Network Gateway.....	L-9
Table L-4: Summary of Security Requirements and MOCs for Control Plane Traffic over Connections between Unmanned Aircraft (UA) and Air/Ground Network Gateway and between Control Station (CS) and Air/Ground Network Gateway.....	L-10

LIST OF FIGURES

Figure 1-1: Systems Within and Beyond the C2 Link System Considered for UAS Operations within the U.S. Airspace.....	2
Figure 1-2: Document Sections and Appendices Relationships	3
Figure 3-1: Requirements Traceability	16
Figure 3-2 C2 Link System, Context, Scope and Boundaries.....	17
Figure 3-3 C2 Link System RLP in the Context of the C2 Link Specification and QoS.....	18
Figure 4-1: User Data and Command & Status Messages Interfaces, CS Test Driver, UA Test Driver, CS DTSR, and UA DTSR Super Imposed on Figure K-17 in Appendix K.....	75
Figure A-1: Phases of Flight	A-16
Figure A-2: Airspace Classification Descriptions	A-19
Figure A-3: Local Linear Sensing Operational View (OV-1)	A-29
Figure A-4: Local Aerial Survey Operational View (OV-1)	A-30
Figure A-5: Representative Extended Aerial Operations Operational View (OV-1)	A-31
Figure A-6: Representative Extended Aerial Operations Operational View (OV-1)	A-32
Figure B-1: Overview of Coordinated Requirements Determination	B-2
Figure B-2: Voice Communication Path Methods.....	B-15
Figure B-3: Power Line Inspection Scenario Flight Profile and Use Case Locations	B-23
Figure B-4: Flight Profile and Use Case Locations	B-30
Figure B-5: Local Cargo Delivery Flight Profile.....	B-35
Figure B-6: Alaska Pipeline Inspection Flight Sequence and Airspace Structure.....	B-41
Figure B-7: Alaska Pipeline Scenario Use Case Logical Sequential Order.....	B-43
Figure B-8: CONOPS 3 Scenario 2 Flight Profile	B-48
Figure B-9: Maritime Surveillance Scenario Use Case Logical Sequential Order	B-50
Figure B-10: CONOPS 3 Scenario 3 Flight Profile	B-55
Figure B-11: Coast to Coast Aerial Work Surveys Scenario Use Case Logical Sequential Order.....	B-57
Figure B-12: Regional Cargo Delivery Flight Profile.....	B-64
Figure B-13: HAPS Flight Profile	B-70
Figure B-14: High Altitude Relay System Flight Profile.....	B-76
Figure B-15: OV-1 of a Representative UAS Mission	B-83
Figure B-16: SV-1 – Possible C2 Link System Configurations	B-86
Figure B-17A: Operational View of Terrestrial-Based and High Altitude Relay (HAR)-Based Air/Ground Links and the Ground/Ground Links.....	B-88
Figure B-17B: Operational View of Satellite-Based Air/Ground Links and the Ground/Ground Links.....	B-90
Figure B-18: Needed Information Exchanges - OV-2	B-93
Figure B-19: OV-5: Operational Activity to Systems Function Traceability Matrix/ <i>System Mapping Function/System Traceability</i>	B-95
Figure B-20: SV-2: Systems Resource Flow Description/ <i>System Communication Description</i>	B-96
Figure B-21: SV-2: Systems Resource Flow Description Showing Two Control Station/ <i>System Communication Description</i>	B-100
Figure B-22: Revised Set of Phases of Flight Used in OV-3 Summary	B-105
Figure C-1: Phases of Flight	C-13
Figure D-1: Allowable Quantitative Probabilities for Qualitative Likelihoods from the ATO SMS Manual	D-7
Figure D-2: SV-2 for Voice Communications Relayed Through the UA.....	D-24
Figure D-3: Example Unavailability versus Fade Duration for Certain Additional Loss.....	D-72
Figure E-1: Basic Internal and External Non-Payload Information Flows of a UAS.....	E-3
Figure E-2: Information Exchanges Between CS and UA.....	E-3
Figure E-3: C2 Link System Block Diagram.....	E-6
Figure E-4: Example Illustration of the Overhead Added to the C2 Link User Data	E-7
Figure E-5: Combining Message Types.....	E-9
Figure E-6: C2 Link System Service Class 1 Automatic Mode Simulation Results	E-19
Figure E-7: C2 Link System Service Class 1 Manual Mode Simulation Results	E-20

Figure E-8: C2 Link System Service Class 2 Automatic Mode Simulation Results	E-21
Figure E-9: C2 Link System Service Class 2 Manual Mode Simulation Results	E-22
Figure E-10: C2 Link System Service Class 3 Automatic Mode Simulation Results	E-23
Figure E-11: C2 Link System Service Class 3 Manual Mode Simulation Results	E-24
Figure E-12: C2 Link System Service Class 4 for the Reverse Link and Service Class 3 for the Forward Link Automatic Mode Simulation Results	E-25
Figure E-13: C2 Link System Service Class 4 for the Reverse Link and Service Class 3 for the Forward Link Manual Mode Simulation Results.....	E-26
Figure F-1: Example Terrestrial-Based RF Link Modeling and Simulation	F-7
Figure F-2: Simulation of Antenna Installed on Aircraft.....	F-9
Figure F-3: Cumulative Distribution Function of Aircraft Antenna Gains.....	F-9
Figure F-4: Modeling of Installed Antenna Performance on a Generic Airframe	F-10
Figure F-5: Directional Antenna Apparent Gain Reduction with Airframe Obstruction	F-10
Figure F-6: Terrestrial-Based RF Link Architecture	F-12
Figure F-7: Terrestrial Link Fading	F-16
Figure F-8: Example Unavailability versus Fade Duration for Certain Additional Loss	F-18
Figure F-9: Satellite-Based RF Link Architecture	F-21
Figure F-10: Satellite link Coverage and Service Area	F-21
Figure F-11: Satellite Link EIRPSD Limitations.....	F-22
Figure F-12: Rain Rates, Percentages of Time, and Rain Regions	F-27
Figure F-13: Example Unavailability versus Fade Duration for Certain Additional Loss	F-29
Figure F-14: Example Unavailability versus Fade Duration for Certain Additional Loss	F-29
Figure G-1: Options for Connecting a CS through Terrestrial and/or High-Altitude Relay Air/Ground Links to Reach a UA Under Its Control	G-1
Figure G-2: Options for Connecting a CS through Satellite-Based Air/Ground Links to Reach a UA Under Its Control.....	G-2
Figure H-1: Inmarsat Constellation (Swift Broadband Services)	H-5
Figure H-2: Inmarsat Constellation (Swift Broadband Services)	H-6
Figure H-3: Inmarsat-4 Regional Beam Map Example	H-7
Figure H-4: Inmarsat-4 Narrow Spot Beam Example.....	H-7
Figure H-5: IRIS System View.....	H-9
Figure H-6: Key Elements of the Iridium AMS(R)S.....	H-10
Figure H-7: Iridium 66-Satellite Constellation	H-10
Figure H-8: Iridium Spot-Beam Configuration	H-11
Figure H-9: Ligado Networks (SkyTerra 1) Coverage Map.....	H-13
Figure H-10: Ligado Networks (Skyterra-1) Operating Frequencies	H-14
Figure H-11: Map of World ITU Regions	H-15
Figure H-12: Resolution 155 Frequency Allocation Summary	H-15
Figure H-13: Intelsat Galaxy 18 located at 123°W Longitude	H-16
Figure H-14: Inmarsat Global Xpress Ka Band Coverage.....	H-18
Figure H-15: ViaSat GEO Coverage Map (Ka Band)	H-19
Figure H-16: Jupiter-1 Coverage Map (Ka Band)	H-19
Figure H-17: Intelsat Flex Coverage Map (Ku Band)	H-20
Figure H-18: SES-15 Coverage Map (Ku Band)	H-20
Figure H-19: O3B Constellation and Coverage.....	H-23
Figure H-20: Antenna Types	H-25
Figure H-21: Representative L Band User Equipment Solutions	H-27
Figure H-22: Ka Band Equipment Solutions (Inmarsat GX Aviation).....	H-29
Figure H-23: Ka and Ku Aero Terminal Summary	H-29
Figure I-1: RLP, C2 Link Specification and QoS	I-2
Figure I-2: C2 Link System Overview – Example Operational View	I-4
Figure I-3: OV-1 with SLA Overlay.....	I-5
Figure I-4: SLA Overview with UAS Operator (Multiple SLAs)	I-6
Figure I-5: C2 Link System Overview – Example Operational View	I-7

Figure I-6: C2 Link System Overview – Example Operational View	I-8
Figure J-1: End-to-End Domain Separation Recommended Approach.....	J-3
Figure J-2: COMSEC Implementation	J-4
Figure K-1: C2 Link System Air/Ground Link and Ground Interconnection Types	K-1
Figure K-2: Required functionality of Point-to-Point Air/Ground Links vs. Links over Air/Ground Networks	K-11
Figure K-3: Switchover of the C2 Link System Connection Between Two Point-to-Point Links	K-15
Figure K-4: Switchover of the DTSR Subsystem Connection Between Two Networked Links.....	K-15
Figure K-5: Switchover of the DTSR Subsystem Connection Between a Point-to-Point Link and a Networked Link.....	K-15
Figure K-6: “C2 Link System Route” Switchover Context Diagram.....	K-18
Figure K-7: Make-Before-Break DTSR Subsystem Connection Switchover from a SATCOM Link to a Terrestrial Link.....	K-21
Figure K-8: Make-Before-Break DTSR Subsystem Connection Switchover from a Terrestrial Link to a SATCOM Link.....	K-22
Figure K-9: Break-Before-Make DTSR Subsystem Connection Switchover from a SATCOM Link to a Terrestrial Link.....	K-23
Figure K-10: Break-Before-Make DTSR Subsystem Connection Switchover from a Terrestrial Link to a SATCOM Link.....	K-24
Figure K-11: C2 Link System Route Switchover Sequence Diagram from Terrestrial to SATCOM....	K-25
Figure K-12: C2 Link System Route Switchover Sequence Diagram from SATCOM to Terrestrial....	K-26
Figure K-13: Control Station Handover Coordination: (a) via Ground Link; (b) via C2 Links.....	K-28
Figure K-14: Control Station Handover Sequence Diagram via Point-to-Point Terrestrial LOS Links with Overlapping Coverage.....	K-32
Figure K-15: Control Station Handover Sequence Diagram via Terrestrial or SATCOM Air/Ground Access Network when both CS can be Connected to UA.....	K-33
Figure K-16a: Control Station Handover Sequence Diagram via Terrestrial or SATCOM Air/Ground Access Network when both CS are Connected to UA and Collaboration Between CS1 and CS2 Performed on Ground Connection.....	K-35
Figure K-16b: Control Station Handover Sequence Diagram via Terrestrial or SATCOM Air/Ground Access Network when UA can Only Communicate with One CS at a Time and Collaboration Between CS1 and CS2 is Performed using Ground Connection.....	K-36
Figure K-17: C2 Link Management System View Diagram	K-38
Figure K-18: C2 Link Management System View Diagram with Two Control Stations and a Ground Link Between Them.....	K-39
Figure K-19: C2 Link Management System View Diagram with Two Control Stations with No Ground Link Between Them	K-40
Figure K-20: C2 Link System Interworking and Security Requirements Development Process Flow..	K-43
Figure L-1: C2 Link System Communications Security Context Diagram	L-2

1 PURPOSE AND SCOPE

1.1 INTRODUCTION AND PURPOSE OF DOCUMENT

1.1.1 INTRODUCTION

This document presents and justifies the Minimum Aviation System Performance Standards (MASPS) for a Command and Control Link System (C2 Link System) used to monitor and control an Unmanned Aircraft System (UAS). The C2 Link System carries the information exchanges between a Control Station (CS) and an Unmanned Aircraft (UA). This MASPS is not the only way to determine such standards but is one that was determined to be viable by the members of Special Committee SC-228.

1.1.2 PURPOSE

This MASPS specifies the C2 Link System standards that should be useful to designers, manufacturers, installers, service providers, and users of UAS to support approval of C2 Link Systems intended for operational use within the United States (U.S.) Airspace. The C2 Link may make use of dedicated (point-to-point) links set up by the UAS operator, or it may make use of the services provided by a C2 Link Communication Service Provider (C2CSP), e.g., Mobile Network Operators such as Inmarsat, Iridium, terrestrial 4G or 5G mobile network operators, or any entity that builds a terrestrial network for use as a C2 Link System (See Appendix A.2.9). It is up to the UAS operator and the UAS designer which types of links to select to ensure that C2 Link Service is appropriate for the intended scenarios and airspace. Each of the links selected by the UAS operator and/or UAS designer are represented by Links in Figure 1-1. The MASPS does not assume any specific design for the UA or the CS because of the wide variation found in current UAS designs. Consequently, this document is intended to provide information to support the determination of the specific performance requirements that will be applied to a UAS during the certification process.

The MASPS also explains the process the Special Committee used to create these standards, which enables each UAS certification applicant or C2 Link Service Provider to tailor that process to support approval of their specific design. Because there are a variety of possible UAS designs and possible C2 Link Systems that can be used in those designs, this MASPS establishes requirements based on the airspace where the UAS is operating and type of the messages flowing across the C2 Link Systems. The purpose of the MASPS is to define C2 Link System standards that will be applicable to all UA operating within the scope of the Concepts of Operations (CONOPS) defined in APPENDIX A. This is a different approach from other MASPS that started with requirements from the air navigation service provider and specific CONOPS for the use of communication systems (e.g., Controller Pilot Data Link Communications).

Compliance with these standards is recommended as one means of assuring that a C2 Link System and each of its subsystems will perform its intended function(s) satisfactorily under all conditions normally encountered in routine aeronautical operations for the environments intended. Additionally, the MASPS may be accepted as a means of compliance to regulations by one or more regulatory and/or advisory documents (e.g., advisory circulars, notices, etc.) and may be referenced in part or in total. Any regulatory application of this document is the sole responsibility of the appropriate certification authority