



UL 1561

**STANDARD FOR SAFETY**

Dry-Type General Purpose and Power Transformers

Currently in preview, click buy full version

Currently in preview, click buy full version

*UL COPYRIGHTED MATERIAL –  
NOT AUTHORIZED FOR FURTHER REPRODUCTION OR  
DISTRIBUTION WITHOUT PERMISSION FROM UL*

UL Standard for Safety for Dry-Type General Purpose and Power Transformers, UL 1561

Fourth Edition, Dated March 2, 2011

**Summary of Topics**

***This revision of ANSI/UL 1561 incorporates the following change:***

***Addition of Overload Test Requirements for Class 240 Insulation Systems***

The effective date for UL LLC will be announced through Industry File Review – Announcement Letter.

The new requirements are substantially in accordance with Proposal(s) on this subject dated March 20, 2015.

Text that has been changed in any manner or impacted by UL's electronic publishing system is marked with a vertical line in the margin.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form by any means, electronic, mechanical, photocopying, recording, or otherwise without prior permission of UL.

UL provides this Standard "as is" without warranty of any kind, either expressed or implied, including but not limited to, the implied warranties of merchantability or fitness for any purpose.

In no event will UL be liable for any special, incidental, consequential, indirect or similar damages, including loss of profits, lost savings, loss of data, or any other damages arising out of the use of or the inability to use this Standard, even if UL or an authorized UL representative has been advised of the possibility of such damage. In no event shall UL's liability for any damage ever exceed the price paid for this Standard, regardless of the form of the claim.

Users of the electronic versions of UL's Standards for Safety agree to defend, indemnify, and hold UL harmless from and against any loss, expense, liability, damage, claim, or judgment (including reasonable attorney's fees) resulting from any error or deviation introduced while purchaser is storing an electronic Standard on the purchaser's computer system.

No Text on This Page

Currently in preview, click buy full version

**UL COPYRIGHTED MATERIAL –  
NOT AUTHORIZED FOR FURTHER REPRODUCTION OR  
DISTRIBUTION WITHOUT PERMISSION FROM UL**

**MARCH 2, 2011**  
(Title Page Reprinted: June 16, 2015)



**ANSI/UL 1561-2015**

**1**

**UL 1561**

**Standard for Dry-Type General Purpose and Power Transformers**

Prior to the first edition, the requirements for the products covered by this standard were included in a supplement to the Standard for Specialty Transformers, UL 506.

Prior to March 27, 1987, the first edition was titled the Standard for Large General Purpose Transformers.

First Edition – January, 1986

Second Edition – April, 1994

Third Edition – March, 1999

**Fourth Edition**

**March 2, 2011**

This ANSI/UL Standard for Safety consists of the Fourth Edition including revisions through June 16, 2015.

The most recent designation of ANSI/UL 1561 as an American National Standard (ANSI) occurred on June 16, 2015. ANSI approval for a standard does not include the Cover Page, Transmittal Page, and Title Page.

Comments or proposals for revisions on any part of the Standard may be submitted to UL at any time. Proposals should be submitted via a Proposal Request in UL's On-Line Collaborative Standards Development System (CSDS) at <http://csds.ul.com>.

UL's Standards for Safety are copyrighted by UL. Neither a printed nor electronic copy of a Standard should be altered in any way. All of UL's Standards and all copyrights, ownerships, and rights regarding those Standards shall remain the sole and exclusive property of UL.

**COPYRIGHT © 2015 UNDERWRITERS LABORATORIES INC.**

**UL COPYRIGHTED MATERIAL –  
NOT AUTHORIZED FOR FURTHER REPRODUCTION OR  
DISTRIBUTION WITHOUT PERMISSION FROM UL**

No Text on This Page

Currently in preview, click buy full version

*UL COPYRIGHTED MATERIAL –  
NOT AUTHORIZED FOR FURTHER REPRODUCTION OR  
DISTRIBUTION WITHOUT PERMISSION FROM UL*

## CONTENTS

### INTRODUCTION

1 Scope .....	5
2 Components .....	5
3 Units of Measurement .....	6
4 Undated References .....	6
5 Glossary .....	6

### CONSTRUCTION

6 Mechanical Assembly .....	7
7 Enclosure .....	8
7.1 General .....	8
7.2 Sheet metal .....	8
7.3 Nonmetallic enclosures .....	9
7.4 Mounting .....	10
7.5 Covers .....	10
7.6 Ventilation .....	10
7.7 Specific environmental conditions .....	11
7.8 Corrosion protection .....	13
8 Corrosion Resistance .....	13
9 Supply and Load Connections .....	15
10 Field Wiring Connections .....	16
10.1 General .....	16
10.2 Leads .....	16
10.3 Pressure terminal connectors .....	17
11 Current-Carrying Parts .....	18
12 Electrical Insulation .....	20
13 Internal Wiring .....	20
14 Coil Insulation .....	21
15 Coil Details .....	21
16 Electrical Spacings .....	21
17 Insulating Barriers .....	25
18 Transient Voltage Surge Suppressors .....	26
19 Capacitors .....	26
20 Surge Arresters .....	26

### PERFORMANCE

21 General .....	26
22 Impedance Test .....	28
23 Temperature Test .....	28
23.1 General .....	28
23.2 Units for wall mounting .....	33
23.3 Units for floor mounting .....	34
23.4 Clamped bus joint .....	35
24 Dielectric Voltage-Withstand Test .....	35
24.1 Applied potential .....	35
24.2 Induced potential .....	36
25 Overload Test .....	37

UL COPYRIGHTED MATERIAL –

NOT AUTHORIZED FOR FURTHER REPRODUCTION OR  
DISTRIBUTION WITHOUT PERMISSION FROM UL

26 Dielectric Voltage-Withstand Test Repeated .....	37
27 Lifting or Mounting Means Test .....	38
28 Enclosure Strength Tests .....	39
28.1 Deflection test .....	39
28.2 Compression test .....	39
29 Clamped Insulating Joint and Insulating Barrier Tests .....	39
30 Water Spray Test .....	40
31 Drip Test .....	43
32 Icing Test .....	43
33 Rust Resistance Test .....	44
34 Corrosion Resistance Test .....	44
35 Metallic Coating Thickness Test .....	44
36 Production-Line Dielectric Voltage-Withstand Test .....	46

## RATINGS

37 General .....	47
------------------	----

## MARKINGS

38 Details .....	50
38.1 General .....	50
38.2 Nonsinusoidal load ratings .....	50
38.3 Insulation temperature class .....	51
38.4 Temperature rise .....	51
38.5 Temperature sensor .....	51
38.6 Ambient temperature .....	51
38.7 Autotransformer, elevated voltage (buck or boost) .....	51
38.8 Impedance .....	52
38.9 Environmental condition enclosures .....	52
38.10 Mounting .....	52
38.11 Weight .....	53
38.12 Field wiring .....	53
39 Permanence of Marking .....	54

## APPENDIX A

Standards for Components .....	A1
--------------------------------	----

## INTRODUCTION

### 1 Scope

1.1 These requirements cover:

a) General purpose and power transformers of the air-cooled, dry, ventilated, and nonventilated types to be used in accordance with the National Electrical Code, ANSI/NFPA 70. Constructions include step up, step down, insulating, and autotransformer type transformers as well as air-cooled and dry-type reactors or

b) General purpose and power transformers of the exposed core, air-cooled, dry, and compound-filled types rated more than 10 kVA to be used in accordance with the National Electrical Code, ANSI/NFPA 70. Constructions include step up, step down, insulating, and autotransformer type transformers as well as air-cooled, dry, and compound-filled core reactors.

1.2 These requirements do not cover ballasts for high intensity discharge (HID) lamps (metal halide, mercury vapor, and sodium types) or fluorescent lamps, exposed core transformers, compound-filled transformers, liquid-filled transformers, voltage regulators, general use or special types of transformers covered in requirements for other electrical equipment, autotransformers forming part of industrial control equipment, motor-starting autotransformers, variable voltage autotransformer, transformers having a nominal primary or secondary rating of more than 600 volts, or overvoltage taps rated greater than 660 volts.

1.3 These requirements do not cover transformers provided with waveshaping or rectifying circuitry. Waveshaping or rectifying circuits may include components such as diodes and transistors. Components such as capacitors, transient voltage surge suppressors, and surge arresters are not considered to be waveshaping or rectifying devices.

### 2 Components

2.1 Except as indicated in 2.2, a component of a product covered by this standard shall comply with the requirements for that component. See Appendix A for a list of standards covering components used in the products covered by this standard.

2.2 A component is not required to comply with a specific requirement that:

a) Involves a feature or characteristic not required in the application of the component in the product covered by this standard, or

b) Is superseded by a requirement in this standard.

2.3 A component shall be used in accordance with its rating established for the intended conditions of use.

2.4 Specific components are incomplete in construction features or restricted in performance capabilities. Such components are intended for use only under limited conditions, such as certain temperatures not exceeding specified limits, and shall be used only under those specific conditions.

### 3 Units of Measurement

3.1 Values stated without parentheses are the requirement. Values in parentheses are explanatory or approximate information.

3.2 Unless otherwise indicated, all voltages and current values mentioned in this standard are root-mean-square (rms).

### 4 Undated References

4.1 Any undated reference to a code or standard appearing in the requirements of this standard shall be interpreted as referring to the latest edition of that code or standard.

### 5 Glossary

5.1 For the purpose of this standard the following definitions apply.

5.2 COMPOUND-FILLED TRANSFORMER – A transformer in which the windings are enclosed with an insulating fluid which becomes solid, or remains plastic, at intended operating temperatures.

5.3 ENCAPSULATED COIL – A coil that

- a) Is enclosed with an insulating fluid that becomes solid and
- b) Can be used in either a ventilated or nonventilated transformer.

5.4 EXPOSED CORE TRANSFORMER – A transformer with exposed core laminations.

5.5 K-FACTOR – A rating optionally applied to a transformer indicating its suitability for use with loads that draw nonsinusoidal currents. The K-factor equals:

$$\sum_{h=1}^{\infty} I_h (pu)^2 h^2$$

in which:

$I_h(pu)$  is the rms current at harmonic "h" (per unit of rated rms load current) and

$h$  is the harmonic order.

K-factor rated transformers have not been evaluated for use with harmonic loads where the rms current of any singular harmonic greater than the tenth harmonic is greater than 1/h of the fundamental rms current.

5.6 NONVENTILATED DRY-TYPE TRANSFORMER – A dry-type transformer other than of the compound-filled or exposed core type that is constructed so as to provide no intentional circulation of ambient air through the transformer and is intended to operate at normal ambient air pressure.